

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 18/09/2017 Revision date: 04/05/2018 Supersedes: 18/09/2017 Version: 1.1

CLM-10204-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Product name : MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) 100 UG/ML

MTBE

Product code : CLM-10204-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225 Skin Irrit. 2 H315

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11 Xi; R38

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 H225 Skin Irrit. 2 H315

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02 GHS07

04/06/2018 EN (English US) 1/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment P264 - Wash hands, forearms and face thoroughly after handling

P280 - Wear eye protection, face protection, protective clothing, protective gloves

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower

GHS-US labeling

Hazard pictograms (GHS-US)





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P264 - Wash hands, forearms and face thoroughly after handling

P280 - Wear face protection, eye protection, protective clothing, protective gloves

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P321 - Specific treatment (see Hazardous component(s) for labeling on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry

extinguishing powder to extinguish

P403+P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
METHYL TERT-BUTYL ETHER UNLABELED	(CAS No) 1634-04-4 (EC No) 216-653-1 (EC Index No) 603-181-00-X (REACH-no) 01-2119452786-27	99.987	F; R11 Xi; R38
MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%)	(CAS No) 30833-53-5	0.013	N; R50/53 Repr.Cat.1; R60 Repr.Cat.1; R61

04/06/2018 EN (English US) 2/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
METHYL TERT-BUTYL ETHER UNLABELED	(CAS No) 1634-04-4 (EC No) 216-653-1 (EC Index No) 603-181-00-X (REACH-no) 01-2119452786-27	99.987	Flam. Liq. 2, H225 Skin Irrit. 2, H315
MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%)	(CAS No) 30833-53-5	0.013	Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
METHYL TERT-BUTYL ETHER UNLABELED	(CAS No) 1634-04-4	99.987	Flam. Liq. 2, H225 Skin Irrit. 2, H315
MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%)	(CAS No) 30833-53-5	0.013	Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation : When sy

- : If you feel unwell, seek medical advice (show the label where possible). Evacuate danger area.
- : When symptoms occur: go into open air and ventilate suspected area. If not breathing, give artificial respiration. Get medical advice/attention.

First-aid measures after skin contact : Rinse skin with water/shower. Remov

: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Gently wash with plenty of soap and water, Get immediate medical advice/attention. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).

First-aid measures after eye contact

: Rinse cautiously with water for several minutes.

First-aid measures after ingestion

: Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May be harmful if inhaled. May cause respiratory irritation.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : May cause eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Wear a self contained breathing

apparatus.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Use personal protective equipment as required. Avoid breathing vapors, mist, gas. Provide adequate ventilation to minimize dust and/or vapor concentrations. Avoid dust formation

adequate ventilation to minimize dust and/or vapor concentrations. Avoid dust formation. Evacuate area. Remove all sources of ignition. Special attention should be given to low areas/pits where flammable vapors can accumulate.

04/06/2018 EN (English US) 3/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and material for containment and cleaning up

: Collect spillage. This material and its container must be disposed of in a safe way, and as per For containment

local legislation.

Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into Methods for cleaning up

container for disposal.

Reference to other sections

No additional information available

SECTION 7: Handling and storage

Precautions for safe handling

: Handle empty containers with care because residual vapors are flammable. Additional hazards when processed

Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools. : Wash hands, forearms and face thoroughly after handling. Hygiene measures

Conditions for safe storage, including any incompatibilities

Technical measures Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Use explosion-proof Lighting equipment, ventilating

Store refrigerated (-5°C to 5°C). Protect from light. Storage conditions

Incompatible materials : Heat sources.

Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

Control parameters

o.i. Control parameters				
MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) 100 UG/ML MTBE				
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV) Remarks: Upper Respiratory Tract irritation. Kidney damage. Confirmed animal carcinogen with unknown relevance to humans.		
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	144 mg/m³ Basis: California permissible exposure limits for chemical contaminants. (Title 8, Article 107).		
USA OSHA	OSHA PEL (Ceiling) (ppm)	40 ppm Basis: California permissible exposure limits for chemical contaminants. (Title 8, Article 107).		
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)				
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50.00000000 ppm Basis: USA. ACGIH Threshold Limit		

METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)				
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV) Remarks: Upper Respiratory Tract irritation. Kidney damage. Confirmed animal carcinogen with unknown relevance to humans.		
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	144 mg/m³ Basis: California permissible exposure limits for chemical contaminants. (Title 8, Article 107).		
USA OSHA	OSHA PEL (Ceiling) (ppm)	40 ppm Basis: California permissible exposure limits for chemical contaminants. (Title 8, Article 107).		

Exposure controls

: Wash hands and other exposed areas with mild soap and water before eating, drinking or Appropriate engineering controls smoking and when leaving work.

Personal protective equipment Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing

: Wear suitable protective clothing and gloves. Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses.

04/06/2018 EN (English US) 4/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

Appearance : Liquid.

Molecular mass : 88.15 g/mol

Color : Colorless.

Odor : No data available.

Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : -108.6 °C (-163.5 °F)
Freezing point : No data available

Boiling point : 55 - 56 °C (131 - 133 °F) - lit. Flash point : -33 °C (- 27.4 °F) - closed cup

Auto-ignition temperature : 374 °C (705.2 °F)

Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapor

Vapor pressure : 1018.7 hPa (764.1 mmHg) at 55°C (131°F), 279.2 hPa (209.4 mmHg) at 20 °C (68°F)

Relative vapor density at 20 °C : No data available Relative density : No data available

Specific gravity / density : 0.74 g/ml at 25 °C (77 °F)

Solubility : Water: 42 g/l at 20 °C (68 °F) - OECD Test Guideline 105

Log Pow : 1.06

Log Kow : No data available

Viscosity, kinematic : 0.464 mm²/s at 20 °C (68 °F) - 0.409 mm2/s at 40 °C (104 °F)

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : 1.6 - 15.1 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

Oxidizing agent. Strong acids.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

04/06/2018 EN (English US) 5/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2012 / Itules and Regulations		
MONOISOBUTYL PHTHALATE (RING-1,2-1;	3C2	2, DICARBOXYL-13C2,99%) 100 UG/ML MTBE
LD50 oral rat		4000 mg/kg
LC50 inhalation rat (ppm)		23576 ppm/4h
METHYL TERT-BUTYL ETHER UNLABELED	D (1	634-04-4)
LD50 oral rat		4000 mg/kg
LC50 inhalation rat (ppm)		23576 ppm/4h
Skin corrosion/irritation	:	Causes skin irritation.
		Skin rabbit Causes skin irritation
Serious eye damage/irritation	:	Not classified
		Eyes rabbit No eye irritation
Respiratory or skin sensitization	:	Will not occur
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
Specific target organ toxicity – single exposure	:	Not classified
Specific target organ toxicity – repeated exposure	:	Not classified
Aspiration hazard	:	Not classified
Potential Adverse human health effects and symptoms	:	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. central nervous system. Dizziness. Nausea. Vomiting. IF INHALED: Risk of pneumonia.
IARC group	:	2B
Symptoms/injuries after inhalation	:	May be harmful if inhaled. May cause respiratory irritation.
Symptoms/injuries after skin contact	:	Causes skin irritation.
Symptoms/injuries after eye contact	:	May cause eye irritation.
Symptoms/injuries after ingestion	:	May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

LC30 IISH I	672 mg/i Pimephales prometas (tathead minhow) - 96 h	
EC50 Daphnia 1	472 mg/l Daphnia magna (Water flea) - 48 h	
EC50 other aquatic organisms 1	491 mg/l Pseudokirchneriella subcapitata (green algae) - 96 h	
LC50 fish 2	> 1000 mg/l other fish - 96 h	
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)		
LC50 fish 1	672 mg/l Pimephales promelas (fathead minnow) - 96 h	
EC50 Daphnia 1	472 mg/l Daphnia magna (Water flea) - 48 h	
EC50 other aquatic organisms 1	491 mg/l Pseudokirchneriella subcapitata (green algae) - 96 h	
LC50 fish 2	> 1000 mg/l other fish - 96 h	

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) 100 UG/ML MTBE

12.2. Persistence and degradability

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) 100 UG/ML MTBE		
Persistence and degradability	Not readily biodegradable. (OECD 301D method).	
Biodegradation	0 %	
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)		
Persistence and degradability	Not readily biodegradable. (OECD 301D method).	
Biodegradation	0 %	
MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) (30833-53-5)		
Persistence and degradability	Not available.	

04/06/2018 EN (English US) 6/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) 100 UG/ML MTBE

Log Pow 1.06

METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)

Log Pow 1.06

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) (30833-53-5)

Bioaccumulative potential Not available

12.4. Mobility in soil

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) (30833-53-5)

Ecology - soil Not available.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local

environmental control regulations.

Product/Packaging disposal recommendations: : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed

professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT) : 2398 DOT NA no. UN2398

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Methyl tert-butyl ether

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid

FLAMMABLE LIQUID

Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal............ 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Emergency Response Guide (ERG) Number : 127

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II

Class (ADR) : 3 - Flammable liquid

04/06/2018 EN (English US) 7/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard identification number (Kemler No.) : 33 Classification code (ADR) : F1

Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :

33 2398

Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) 11
Excepted quantities (ADR) : E2

Transport by sea

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

MFAG-No : 127

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) 100 UG/ML MTBE		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	

METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4) Subject to reporting requirements of United States SARA Section 313 SARA Section 302 Threshold Planning Quantity (TPQ) SARA Section 311/312 Hazard Classes Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) (30833-53-5)		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313	

04/06/2018 EN (English US) 8/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) 100 UG/ML MTBE

Listed on the Canadian DSL (Domestic Substances List)

METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) 100 UG/ML MTBE()			
U.S California - Proposition 65 - Carcinogens List	No		
U.S California - Proposition 65 - Developmental Toxicity	No		
U.S California - Proposition 65 - Reproductive Toxicity - Female	No		
U.S California - Proposition 65 - Reproductive Toxicity - Male	No		
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List		

METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) (30833-53-5)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		

METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)

State or local regulations

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

MONOISOBUTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2,99%) (30833-53-5)

State or local regulations

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

tox of tr, it and both princeso.				
	Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1		
	Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1		
	Flam. Liq. 2	Flammable liquids Category 2 Reproductive toxicity Category 1B		
	Repr. 1B			
	Skin Irrit. 2	Skin corrosion/irritation Category 2		

04/06/2018 EN (English US) 9/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H225	Highly flammable liquid and vapor	
H315	Causes skin irritation	
H360	May damage fertility or the unborn child	
H400	Very toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
R11	Highly flammable	
R38	Irritating to skin Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment May impair fertility May cause harm to the unborn child Highly flammable Dangerous for the environment	
R50/53		
R60		
R61		
F		
N		
Xi	Irritant	

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause

temporary incapacitation or residual injury.


NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended

solids) that can be ignited under almost all ambient

temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even

under fire conditions.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

04/06/2018 EN (English US) 10/10