

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /

Rules and Regulations

Date of issue: 04/05/2016 Revision date: : Version: 1

DLM-7708-C

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Product name. : 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML

IN ETHANOL

Product code : DLM-7708-C

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only.

Industrial.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 <u>cilsales@isotope.com</u> www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225 Skin Irrit. 2 H315 Eye Irrit. 2 H319 STOT SE 3 H335

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11 Xi; R36/37/38 N; R51/53

Full text of R-phrases: see section 16

Classification (GHS-US)

Flam. Liq. 2 H225 Skin Irrit. 2 H315 Eye Irrit. 2A H319 STOT SE 3 H335 Aquatic Acute 2 H401

Adverse physicochemical, human health and environmental effects

Nerves, Liver, Heart.

04/05/2016 EN (English US) 1/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P261 - Avoid breathing dust, fume, gas, mist, spray, vapors P264 - Wash Both hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective clothing, protective gloves

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation

H319 - Causes serious eye irritation H335 - May cause respiratory irritation

H401 - Toxic to aquatic life

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P261 - Avoid breathing dust, gas, mist, spray, vapors, fume

P264 - Wash Both hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective clothing, protective gloves

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P321 - Specific treatment (see Hazard pictograms (CLP) on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention P362 - Take off contaminated clothing and wash before reuse

P370+P378 - In case of fire: Use Carbon dioxide., Dry chemical., Alcohol resistant foam., Water spray for extinction

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to Comply with applicable regulations.

04/05/2016 EN (English US) 2/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Directive 67/548/EEC |
|--|--|--------|---|
| ETHANOL UNLABELED | (CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5 (REACH-no) 01-2119457610-43 | 99.987 | F; R11 Xi; R36 |
| 25-HYDROXYVITAMIN D3 MONOHYDRATE (26,26,26,27,27,27-D6, 98%) 97% CP | (CAS No) 63283-36-3 (Unlabeled) (EC no) 242-990-9 (Unlabeled) | 0.013 | T+; R26/27/28 R48 |
| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
| ETHANOL UNLABELED | (CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5 (REACH-no) 01-2119457610-43 | 99.987 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 |
| 25-HYDROXYVITAMIN D3 MONOHYDRATE (26,26,26,27,27,27-D6, 98%) 97% CP | (CAS No) 63283-36-3 (Unlabeled) (EC no) 242-990-9 (Unlabeled) | 0.013 | Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 Acute Tox. 2 (Inhalation:dust,mist), H330 STOT SE 1, H370 |
| Name | Product identifier | % | Classification (GHS-US) |
| ETHANOL UNLABELED | (CAS No) 64-17-5 | 99.987 | Flam. Liq. 3, H226 Eye Irrit. 2A, H319 Aquatic Acute 2, H401 |

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

| 4.1. | Description of first aid measures | |
|----------|-----------------------------------|---|
| First-ai | d measures general | : Move out of dangerous area. Consult a physician and show this safety data sheet. Never give |

anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. Remove to fresh air and keep at rest in a position comfortable for

breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

First-aid measures after skin contact

: Wash with soap and plenty of water. Consult a physician. Rinse skin with water/shower.

Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.

Wash contaminated clothing before reuse. If skin irritation occurs: Gently wash with plenty of

soap and water. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Flush eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention. Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. Rinse mouth. Do NOT induce vomiting. Obtain emergency

medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May be harmful if inhaled. Causes respiratory tract irritation. May cause respiratory irritation.

Symptoms/injuries after skin contact : May be harmful if absorbed through skin. Causes skin irritation. Causes skin irritation.

Symptoms/injuries after eye contact : Causes eye irritation. Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

04/05/2016 EN (English US) 3/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

suitable extinguishing media : Fo

For small fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water. Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.
Reactivity : Vapors may form explosive mixture with air.

5.3. Advice for firefighters

Firefighting instructions : Use water spray to cool unopened containers. Use water spray or fog for cooling exposed

containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to

enter environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain spillage, then collect with non-combustible absorbent material. Disposal should be in

accordance with applicable Federal, State and local regulations.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take

measures to prevent the build up of electrostatic charge. Handle empty containers with care because residual vapors are flammable.

because residual vapors are flammable

: Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated

area. Avoid breathing dust, mist or spray.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before

breaks and at the end of workday. Wash Both hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed in a cool, dry and well-ventilated place.

Storage conditions : Store in freezer (-20°C). Protect from light.

Incompatible products : Strong bases. strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Precautions for safe handling

No additional information available

04/05/2016 EN (English US) 4/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

3.1. Control parameters

| 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL | | |
|--|------------------------|--|
| Italy - Portugal - USA ACGIH | ACGIH TWA (ppm) | 1000.0000000000 ppm Upper Respiratory Tract irritation. Confirmed animal carcinogen. |
| USA OSHA | OSHA PEL (TWA) (mg/m3) | 1900.0000000000 mg/m³ |

| ETHANOL UNLABELED (64-17-5) | | |
|------------------------------|-------------------------|---|
| Italy - Portugal - USA ACGIH | ACGIH TWA (ppm) | 1000.0000000000 ppm Upper Respiratory Tract irritation. Confirmed animal carcinogen with unknown relevance to humans. |
| Italy - Portugal - USA ACGIH | ACGIH STEL (ppm) | 1000 ppm Upper Respiratory Tract irritation. Confirmed animal carcinogen with unknown relevance to humans. |
| USA NIOSH | NIOSH REL (TWA) (mg/m3) | 1900 mg/m³ Upper Respiratory Tract irritation. Confirmed animal carcinogen with unknown relevance to humans. |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 1000 ppm Upper Respiratory Tract irritation. Confirmed animal carcinogen with unknown relevance to humans. |
| USA OSHA | OSHA PEL (TWA) (mg/m3) | 1900.0000000000 mg/m³ The value in mg/m3 is approximate. |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| USA OSHA | Remark (US OSHA) | Upper Respiratory Tract irritation. Confirmed animal carcinogen with unknown relevance to humans. |

8.2. Exposure controls

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus. Avoid all









Hand protection : Wear suitable protective clothing and gloves. Wear protective gloves.

Eye protection : Wear safety glasses with side shields (or goggles) and a face shield. Chemical goggles or safety

glasses.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance

at the work place. Handle with gloves. Wear suitable protective clothing.

Respiratory protection : When appropriate, use NIOSH/CEN approved respirator. Wear approved mask.

Other information : When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

Appearance : Liquid, clear.

Molecular mass : 46.07 g/mol

Color : Colorless.

Odor : No data available

Odor threshold : No data available

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : -114 °C (-173 °F) Freezing point : No data available Boiling point : 78 °C (172 °F)

Flash point : 14 °C (57.2 °F) - closed cup

Self ignition temperature : 363 °C (685.4 °F)

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

04/05/2016 EN (English US) 5/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure : 59.5 hPa (44.6 mmHg) at 20 °C (68 °F)

Relative vapor density at 20 °C : No data available Relative density : No data available

: 0.789 g/ml at 25 °C (77 °F) Density Solubility : Water: completely soluble Log Pow : -0.349 at 24 °C (75 °F) Log Kow : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available : No data available Explosive properties Oxidizing properties : No data available Explosive limits : 3.3 - 19 %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

Three years after receipt of order if stored as above. Re-QC after three years.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Alkali metals, Ammonia, Oxidizing agents, Peroxides. strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - None known. fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL | |
|--|----------------------------|
| LD50 oral rat | 7060 mg/kg |
| LC50 inhalation rat (ppm) | 20000 ppm 10 h |
| ATE (oral) | 7060.000 mg/kg body weight |

| ETHANOL UNLABELED (64-17-5) | |
|-----------------------------|----------------------------|
| LD50 oral rat | 10470 mg/kg |
| LD50 dermal rat | 15800 mg/kg |
| LC50 inhalation rat (mg/l) | 30000 mg/l |
| ATE (oral) | 7060.000 mg/kg body weight |

| 25-HYDROXYVITAMIN D3 MONOHYDRATE (26,26,26,27,27,27-D6, 98%) 97% CP (63283-36-3 (Unlabeled)) | | |
|--|-------------------------|--|
| LC50 inhalation rat (ppm) | 130 - 380 ppm 4 h | |
| ATE (oral) | 5.000 mg/kg body weight | |
| ATE (dermal) | 5.000 mg/kg body weight | |
| ATE (dust, mist) | 0.050 mg/l/4h | |

Skin corrosion/irritation : Causes skin irritation.

Causes skin irritation

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

04/05/2016 EN (English US) 6/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Inhalation - May cause respiratory irritation.

May cause respiratory irritation

Specific target organ toxicity (repeated

exposure)

No data available

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

Symptoms/injuries after inhalation

symptoms

: Based on available data, the classification criteria are not met.

: May be harmful if inhaled. Causes respiratory tract irritation. May cause respiratory irritation.

Symptoms/injuries after skin contact : May be harmful if absorbed through skin. Causes skin irritation. Causes skin irritation.

Symptoms/injuries after eye contact : Causes eye irritation. Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life.

| 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL | |
|--|--|
| LC50 fish 1 | 13000.00 mg/l Oncorhynchus mykiss (rainbow trout) - 96 h |
| EC50 Daphnia 1 | 9.30 mg/l Daphnia magna (Water flea) - 48 h |

| ETHANOL UNLABELED (64-17-5) | |
|--------------------------------|--|
| LC50 fish 1 | 14200 mg/l Pimephales promelas (fathead minnow) - 96 h |
| EC50 Daphnia 1 | 5012 mg/l Ceriodaphnia dubia (water flea) - 48 h |
| EC50 other aquatic organisms 1 | 275 mg/l Chlorella vulgaris (Fresh water algae) - 72 h (OECD Test Guideline 201) |
| NOEC (acute) | 9.6 mg/l Daphnia magna (Water flea) - 9 d |

12.2. Persistence and degradability

| 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL | |
|--|---------------------------------|
| Persistence and degradability | Not available. Not established. |

| ETHANOL UNLABELED (64-17-5) | |
|-------------------------------|---------------------------------|
| Persistence and degradability | Not available. |
| BOD (% of ThOD) | 95 % ThOD Readily biodegradable |

25-HYDROXYVITAMIN D3 MONOHYDRATE (26,26,26,27,27,27-D6, 98%) 97% CP (63283-36-3 (Unlabeled)) Persistence and degradability Not available.

12.3. Bioaccumulative potential

| 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL | |
|--|---------------------------------|
| Log Pow | -0.349 at 24 °C (75 °F) |
| Bioaccumulative potential | Not available. Not established. |

| ETHANOL UNLABELED (64-17-5) | |
|-----------------------------|---|
| Log Pow | -0.349 at 24 °C (75 °F) |
| Bioaccumulative potential | Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected. |

25-HYDROXYVITAMIN D3 MONOHYDRATE (26,26,26,27,27,27-D6, 98%) 97% CP (63283-36-3 (Unlabeled)) Bioaccumulative potential Not available.

12.4. Mobility in soil

| 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL | |
|--|----------------|
| Ecology - soil | Not available. |

| l | ETHANOL | UNLABELED | (64-17-5) |
|---|---------|-----------|-----------|
| | | | |

Ecology - soil Not available.

| 25-HYDROXYVITAMIN D3 MONOHYDRATE (26,26,26,27,27,27-D6, 98%) 97% CP (63283-36-3 (Unlabeled)) | |
|--|----------------|
| Ecology - soil | Not available. |

12.5. Results of PBT and vPvB assessment

No additional information available

04/05/2016 EN (English US) 7/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.6. Other adverse effects

Other adverse effects : Not available.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local

environmental control regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to Comply with applicable regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

UN-No.(DOT) : 1170 DOT NA no. UN1170

14.2. UN proper shipping name

DOT Proper Shipping Name : Ethanol

Department of Transportation (DOT) Hazard : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Classes

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : 24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be

transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III.

Packing Group III.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

Marine pollutant : No



14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 33 Classification code (ADR) : F1

04/05/2016 EN (English US) 8/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Danger labels (ADR) : 3 - Flammable liquids

3

Orange plates :

33 1170

Tunnel restriction code : D/E
Limited quantities (ADR) 1L
EAC : •2YE
Excepted quantities (ADR) : E2

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

MFAG-No : 127

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Dangerous for the environment



Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

| 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL | |
|--|---|
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard |

| ETHANOL UNLABELED (64-17-5) | |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard |
| | Delayed (chronic) health hazard |

15.2. International regulations

CANADA

25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2.1. National regulations

No additional information available

04/05/2016 EN (English US) 9/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

| 25-HYDROXYVITAMIN D3 MONOHYDRATE 97% CP (26,26,26,27,27,27-D6, 98%) 100 UG/ML IN ETHANOL() | |
|--|---|
| State or local regulations | U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm. |

ETHANOL UNLABELED (64-17-5)

- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Other information

This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases::

| Acute Tox. 1 (Dermal) | Acute toxicity (dermal) Category 1 |
|-------------------------------------|--|
| Acute Tox. 2 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 2 |
| Acute Tox. 2 (Oral) | Acute toxicity (oral) Category 2 |
| Eye Irrit. 2 | Serious eye damage/eye irritation Category 2 |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Skin Irrit. 2 | skin corrosion/irritation Category 2 |
| STOT SE 1 | Specific target organ toxicity (single exposure) Category 1 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H225 | Highly flammable liquid and vapor |
| H300 | Fatal if swallowed |
| H310 | Fatal in contact with skin |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H330 | Fatal if inhaled |
| H335 | May cause respiratory irritation |
| H370 | Causes damage to organs |
| R11 | Highly flammable |
| R26/27/28 | Very toxic by inhalation, in contact with skin and if swallowed |
| R36 | Irritating to eyes |
| R36/37/38 | Irritating to eyes, respiratory system and skin |
| R48 | Danger of serious damage to health by prolonged exposure |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment |
| F | Highly flammable |
| N | Dangerous for the environment |
| T+ | Very toxic |
| Xi | Irritant |

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

04/05/2016 EN (English US) 10/11

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability : 3 Serious Hazard Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

04/05/2016 EN (English US) 11/11