

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 25/06/2015 Revision date: 19/08/2020 Supersedes: 12/09/2018 Version: 3.0 ULM-7451-S

	bstance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixtures
Product name	: PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED 50 UG/ML IN METHANOL
Product code	: ULM-7451-S
1.2. Relevant identified uses of the sul	ostance or mixture and uses advised against
1.2.1. Relevant identified uses	
Main use category	: Professional use
Industrial/Professional use spec	: For professional use only
1.2.2. Uses advised against	
No additional information available	
1.3. Details of the supplier of the safet	y data sheet
Cambridge Isotope Laboratories, Inc. 50 Frontage Road	
Andover, MA 01810	
USA	
USA: 1-800-322-1174 Int: 1-978-749-8000 cilsales@isotope.com www.isotope.com	
Emergency telephone number	
Emergency numbers:	
Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)	
· · · · · ·	
SECTION 2: Hazards identification	
2.1. Classification of the substance or	mixture
Classification according to Regulation (EC)	No. 1272/2008 [CLP]
Flam. Liq. 2 H225	
Acute Tox. 3 (Oral) H301	
Acute Tox. 3 (Dermal) H311	
Acute Tox. 3 (Inhalation:vapour) H331	
Skin Irrit. 2 H315	
Eye Irrit. 2 H319	
STOT SE 1 H370	
Full text of hazard classes and H-statements :	see section 16
Classification according to Directive 67/548	/EEC [DSD] or 1999/45/EC [DPD]
F; R11	
T; R39/23/24/25	
Xi; R36/38	
Full text of R-phrases: see section 16	

GHS-US classification

Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapour)	H331
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 1	H370

Full text of H statements : see section 16

METHANOL ULM-7451-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Eyes, Kidney, Liver, Heart, Central nervous system. Highly flammable liquid and vapor. Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (if inhaled, if swallowed, in contact with skin). Toxic in contact with skin. Toxic if inhaled. Toxic if swallowed. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements	
Labeling according to Regulation (EC)	lo. 1272/2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS08 GHS06
Signal word (CLP)	: Danger
Hazard statements (CLP)	 H225 - Highly flammable liquid and vapor H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, heart, kidneys, liver, central nervous system) (in contact with skin, if inhaled, if swallowed)
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment P260 - Do not breathe dust, mist, vapors, fume, gas, spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.
GHS-US labeling	
Hazard pictograms (GHS-US)	
Signal word (GHS-US)	GHS02 GHS08 GHS06 : Danger
Hazard statements (GHS-US)	 H225 - Highly flammable liquid and vapor H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal, Inhalation, oral)
Precautionary statements (GHS-US)	 P210 - Keep away from heat, open flames, sparks No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical, lighting, ventilating equipment P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust, fume, mist, gas, spray, vapors. P261 - Avoid breathing dust, fume, gas, spray, vapors, mist. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective clothing, protective gloves. P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER P302+P352 - If on skin: Wash with plenty of water P303+P361+P338 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed: Call a poison center/doctor
40/00/0000	
19/08/2020	EN (English US) 2/13

METHANOL ULM-7451-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P311 Call a doctor, a POISON CENTER P312 - Call a doctor, a POISON CENTER if you feel unwell P321 - Specific treatment (see Hazardous component(s) for labeling on this label)
- P322 Specific treatment (see Hazard pictograms (CLP) on this label)
- P330 Rinse mouth.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry

extinguishing powder to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

PBT: not relevant – no registration required

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC	
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.993679	F; R11 T; R39/23/24/25 Xi; R36/38	
PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED substance listed as REACH Candidate (Pentadecafluorooctanoic acid (PFOA))	(CAS-No.) 335-67-1 (EC-No.) 206-397-9	0.0063	T; R39/23/24/25 Xn; R22 C; R34 R52/53	
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.993679	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370	
PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED substance listed as REACH Candidate (Pentadecafluorooctanoic acid (PFOA))	(CAS-No.) 335-67-1 (EC-No.) 206-397-9	0.0063	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412	
Name	Product identifier	%	GHS-US classification	
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.993679	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370	
PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED	(CAS-No.) 335-67-1	0.0063	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402 Aquatic Chronic 3, H412	

Full text of R- and H- phrases: see section 16

METHANOL ULM-7451-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: Fir	st aid measures		
4.1. Description	on of first aid measures		
First-aid measures g	eneral :	If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.	
First-aid measures a	fter inhalation :	Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.	
First-aid measures a	fter skin contact :	Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.	
First-aid measures a	fter eye contact :	Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
First-aid measures a	fter ingestion :	Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth. Call a physician immediately.	
4.2. Most impo	ortant symptoms and effects	, both acute and delayed	
Symptoms/effects		Causes damage to organs (Eyes, heart, liver, kidneys, central nervous system, Skin) (in contact with skin, if inhaled, if swallowed).	
Symptoms/effects af	ter inhalation :	Toxic if inhaled.	
Symptoms/effects af	ter skin contact :	Toxic in contact with skin. Causes skin irritation.	
Symptoms/effects af	•	Causes serious eye irritation.	
Symptoms/effects af	ter ingestion :	Toxic if swallowed.	
4.3. Indication	of any immediate medical a	ttention and special treatment needed	
Treat symptomatical	ly.		
SECTION 5: Fir	efighting measures		
5.1. Extinguis	hing media		
Suitable extinguishin	g media :	Dry powder. Dry sand.	
Unsuitable extinguis	hing media :	Do not use a heavy water stream.	
5.2. Special hazards arising from the substance or mixture			
Fire hazard	:	Highly flammable liquid and vapor.	
Reactivity	:	Vapors may form flammable mixture with air. Highly flammable liquid and vapor.	
5.3. Advice for	r firefighters		
Firefighting instruction	ins :	Do not enter fire area without proper protective equipment, including respiratory protection.	
Protection during fire	fighting :	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.	
Other information	:	Use water spray to cool exposed surfaces.	
SECTION 6: Ac	cidental release measu	ires	
6.1. Personal	precautions, protective equi	pment and emergency procedures	
6.1.1. For non-e	mergency personnel		
Emergency procedu	res :	Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.	
6.1.2. For emerg	gency responders		
Protective equipmen	t :	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environm	ental precautions		
Prevent entry to sew	ers and public waters. Do not	allow to enter drains or water courses. Avoid release to the environment.	
6.3. Methods a	and material for containment	and cleaning up	
For containment	:	Dike and contain spill.	
Methods for cleaning	jup :	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.	
Other information	:	Dispose of materials or solid residues at an authorized site.	
6.4. Reference	e to other sections		

For further information refer to section 13.

METHANOL ULM-7451-S

Safety Data Sheet

SECTION 7: Handling and storage				
7.1. Precautions for safe				
Additional hazards when proces		ecause residual vapors are flammable.		
Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools.				
7.2. Conditions for safe s	storage, including any incompatibilities			
Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.				
Storage conditions	: Store at room temperature away fror	n light and moisture.		
Incompatible materials	: Heat sources.			
7.3. Specific end use(s)				
No additional information availal	ble			
SECTION 8: Exposure c	ontrols/personal protection			
8.1. Control parameters				
PERFLUORO-N-OCTANOIC	ACID (PFOA) UNLABELED 50 UG/ML IN METHANOL			
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)		
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)		
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.		
100% METHANOL UNLABEL	.ED (67-56-1)			
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)		
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)		
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits		
USA NIOSH	NIOSH REL (TWA) (ppm) 200 ppm Basis: NIOSH Recommended Expo Limits			
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits		
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits		
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.		
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.		
	1			

METHANOL ULM-7451-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED 50 UG/ML IN METHANOL			
DNEL/DMEL (Workers)			
Acute - systemic effects, dermal	40 mg/kg bodyweight/day		
Acute - systemic effects, inhalation	260 mg/m ³		
Acute - local effects, dermal	260 mg/cm ²		
Long-term - systemic effects, dermal	40 mg/kg bodyweight/day		
Long-term - local effects, dermal	260 mg/cm ²		
Long-term - local effects, inhalation	260 mg/m ³		
DNEL/DMEL (General population)			
Acute - systemic effects, dermal	8 mg/kg body weight		
Acute - systemic effects, inhalation	50 mg/m ³		
Acute - systemic effects, oral	8 mg/kg body weight		
Acute - local effects, inhalation	50 mg/m ³		
Long-term - systemic effects,oral	8 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	50 mg/m ³		
Long-term - systemic effects, dermal	8 mg/kg bodyweight/day		
Long-term - local effects, inhalation	50 mg/m ³		
PNEC (Water)			
PNEC aqua (freshwater)	154 mg/l		
PNEC aqua (marine water)	15.4 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	570.4 mg/kg dwt		
PNEC (Soil)			
PNEC soil	23.5 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	100 mg/kg		
3.2. Exposure controls			

Appropriate engineering controls

Appropriate engineering control

Personal protective equipment

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

: Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing	: Wear suitable protective clothing and gloves.
Hand protection	: Wear suitable protective clothing and gloves.
Eye protection	: Wear eye protection. Chemical goggles or face shield with safety glasses.
Skin and body protection	: Wear suitable protective clothing, gloves and eye/face protection.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	d chemical properties
The properties listed below are for the solvent, the main com	ponent of this mixture.
Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 32.04 g/mol
Color	: Colorless
Odor	: Pungent
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -98 °C (-144 °F)
Freezing point	: No data available
Boiling point	: 64.7 °C (148.5 °F)
Flash point	: 9.7 °C (49.5 °F) - closed cup

METHANOL ULM-7451-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

,	
Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)
Vapor pressure at 50 °C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)
Relative vapor density at 20 °C	: 1.11
Relative density	: No data available
Specific gravity / density	: 0.791 g/ml at 25 °C (77 °F)
Solubility	: Water: Completely miscible
Log Pow	: -0.77
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidizing properties	: Non oxidizing material according to EC criteria.
Explosion limits	: 6 - 36 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:vapour: Toxic if inhaled.		
PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED 50 UG/ML IN METHANOL			
LD50 oral rat	1187 - 2769 mg/kg		
LD50 dermal rabbit	17100 mg/kg		
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h		
ATE CLP (oral)	100.000 mg/kg body weight		
ATE CLP (dermal)	300.000 mg/kg body weight		
ATE CLP (vapors)	3.000 mg/l/4h		
ATE CLP (dust, mist)	128.200 mg/l/4h		
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED (335-67-1)			
ATE CLP (oral)	500.000 mg/kg body weight		
100% METHANOL UNLABELED (67-56-1)			
LD50 oral rat	1187 - 2769 mg/kg		
LD50 dermal rabbit	17100 mg/kg		
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h		
ATE CLP (oral)	100.000 mg/kg body weight		
ATE CLP (dermal)	300.000 mg/kg body weight		
ATE CLP (vapors)	3.000 mg/l/4h		
10/00/0000	51/5		

METHANOL ULM-7451-S

Safety Data Sheet

100% METHANOL UNLABELED (67-56-1)		
ATE CLP (dust, mist)		128.200 mg/l/4h
LDLO, oral, human		143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin corrosion/irritation	:	Skin - Rrabbit. Result: No skin irritation
Serious eye damage/irritation	:	Eyes - Rabbit. Result: No eye irritation
Respiratory or skin sensitization	:	Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)
Germ cell mutagenicity	:	AMES test : S. tymphimurium. Result: Negative. fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - male and female Result: Negative. Mouse - male and female. Result: Negative
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Damage to fetus not classifiable. Fertility classification not possible from current data.
Specific target organ toxicity – single exposure	:	Causes damage to organs through prolonged or repeated exposure
Specific target organ toxicity – repeated exposure	:	The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	:	Not classified
Potential Adverse human health effects and symptoms	:	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach.
Symptoms/effects after inhalation	:	Toxic if inhaled.
Symptoms/effects after skin contact	:	Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	:	Causes serious eye irritation.
Symptoms/effects after ingestion	:	Toxic if swallowed.

SECTION 12: Ecological in	nformation	
12.1. Toxicity		
Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.	
PERFLUORO-N-OCTANOIC AC	ID (PFOA) UNLABELED 50 UG/ML IN METHANOL	
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h	
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h	
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h	
100% METHANOL UNLABELED (67-56-1)		
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h	
EC50 Daphnia 1	> 10000 mg/l Danhnia magna (Water flea) - 48 h	

ECSU Daprinia 1	> 10000 mg/i Dapinia magia (water nea) - 48 m	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h	
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h	

12.2. Persistence and degradability		
PERFLUORO-N-OCTANOIC ACID (PFOA) UNL	ABELED 50 UG/ML IN METHANOL	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g	
Chemical oxygen demand (COD)	1420 mg/g	
ThOD	1500 mg/g	
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d	
100% METHANOL UNLABELED (67-56-1)		
Biochemical oxygen demand (BOD)	600 - 1200 mg/g	
Chemical oxygen demand (COD)	1420 mg/g	
ThOD	1500 mg/g	
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d	
12.3. Bioaccumulative potential		
PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED 50 UG/ML IN METHANOL		
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C	
19/08/2020	EN (English US) 8	8/13

METHANOL ULM-7451-S

Safety Data Sheet

6, 2012 / Rules and Regulations	
PERFLUORO-N-OCTANOIC ACID (PFOA) UN	ILABELED 50 UG/ML IN METHANOL
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77
100% METHANOL UNLABELED (67-56-1)	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77
12.4. Mobility in soil	
PERFLUORO-N-OCTANOIC ACID (PFOA) UN	ILABELED 50 UG/ML IN METHANOL
Ecology - soil	Not degradable in the soil.
100% METHANOL UNLABELED (67-56-1)	
Ecology - soil	Not degradable in the soil.
12.5. Results of PBT and vPvB assessme	
PERFLUORO-N-OCTANOIC ACID (PFOA) UN	
PBT: not relevant – no registration required	
PERFLUORO-N-OCTANOIC ACID (PFOA) UN This substance/mixture meets the PBT criteria	
This substance/mixture does not meet the vPvE	
100% METHANOL UNLABELED (67-56-1)	
PBT: not relevant – no registration required	
12.6. Other adverse effects	
Other adverse effects	: Avoid release to the environment.
Other information	: Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water. Hydrolyses readily.
SECTION 12, Dispession envideration	
SECTION 13: Disposal consideration	15
13.1. Waste treatment methods	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
13.1. Waste treatment methods Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local
13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed
13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number UN-No.(DOT)	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
 13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number UN-No.(DOT) DOT NA no. 	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
 13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number UN-No.(DOT) DOT NA no. 14.2. UN proper shipping name 	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
 13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number UN-No.(DOT) DOT NA no. 14.2. UN proper shipping name Proper Shipping Name (DOT) 	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number UN-No.(DOT) DOT NA no. 14.2. UN proper shipping name Proper Shipping Name (DOT) Class (DOT)	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
 13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number UN-No.(DOT) DOT NA no. 14.2. UN proper shipping name Proper Shipping Name (DOT) Class (DOT) 	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.
 13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number UN-No.(DOT) DOT NA no. 14.2. UN proper shipping name Proper Shipping Name (DOT) Class (DOT) Hazard labels (DOT) 	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product. 20N 1230 UN1230 Wethanol 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 3 - Flammable liquid 6.1 - Poison <i>interview of the poison of the</i>
 13.1. Waste treatment methods Regional legislation (waste) Product/Packaging disposal recommendations Ecology - waste materials SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / AI 14.1. UN number UN-No.(DOT) DOT NA no. 14.2. UN proper shipping name Proper Shipping Name (DOT) 	 Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of as unused product.

METHANOL ULM-7451-S

Safety Data Sheet

26, 2012 / Rules and Regulations	
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
14.3. Additional information	
Emergency Response Guide (ERG) Number	: 131
Other information	: No supplementary information available.
Overland transport	
Packing group (ADR)	: II
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 336
Classification code (ADR)	: FT1
Hazard labels (ADR)	: 3 - Flammable liquids
Orange plates	
e range parte	336 1230
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
Excepted quantities (ADR)	: E2
Transport by sea	
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living guarters"
MFAG-No	: 131
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
Civil Aeronautics Law	: Flammable liquids
14.4. Environmental hazards	
Other information	: No supplementary information available.

METHANOL ULM-7451-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information	1	
15.1. US Federal regulations		
PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED 50 UG/ML IN METHANOL		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	
PERFLUORO-N-OCTANOIC ACID (PFOA) U	NLABELED (335-67-1)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313	
100% METHANOL UNLABELED (67-56-1)		
Listed on the United States TSCA (Toxic Subs	tances Control Act) inventory	
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	
15.2. International regulations		

CANADA

PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED 50 UG/ML IN METHANOL
Listed on the Canadian DSL (Domestic Substances List)
100% METHANOL UNLABELED (67-56-1)
Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED 50 UG/ML IN METHANOL()				
U.S California - Proposition 65 - Carcinogens List		No		
U.S California - Proposition 65 - Developmental Toxicity		Yes		
U.S California - Proposition 65 - Reproductive Toxicity - Female		No		
U.S California - Proposition 65 - Reproductive Toxicity - Male		No		
State or local regulations		U.S Idaho - Non-Carcinoge U.S Massachusetts - Right U.S Pennsylvania - RTK (F U.S New Jersey - Right to		able Ambient Concentrations
PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED (335-67-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)

METHANOL ULM-7451-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PERFLUORO-N-OCTANOIC ACID (PFOA) UNLABELED (335-67-1)				
No	No	No	No	
100% METHANOL UNLABE	100% METHANOL UNLABELED (67-56-1)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	
PERFLUORO-N-OCTANOIO	C ACID (PFOA) UNLABELED	(335-67-1)		
State or local regulations				
U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List				
100% METHANOL UNLABELED (67-56-1)				
State or local regulations				
U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances				

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

text of R-, H- and EUH-phrases:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H370	Causes damage to organs
H412	Harmful to aquatic life with long lasting effects
R11	Highly flammable
R22	Harmful if swallowed
R34	Causes burns
R36/38	Irritating to eyes and skin
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
С	Corrosive
F	Highly flammable
Т	Toxic
Xi	Irritant
Xn	Harmful

METHANOL ULM-7451-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	 : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product