

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 24/05/2016 Revision date: 31/07/2018 Supersedes: 24/05/2016 Version: 1.1 ULM-9886-S

SECTION 1: Identifie	cation of the substance/mixture and of the company/undertaking	
1.1. Product identif		
Product form	: Mixtures	
Product name	: 2-PROPYL PHOSPHONIC ACID UNLABELED 1000 UG/ML IN METHANOL	
Product code	: ULM-9886-S	
1.2. Relevant identi	fied uses of the substance or mixture and uses advised against	
1.2.1. Relevant identi	fied uses	
Industrial/Professional use	e spec : For professional use only	
1.2.2. Uses advised a	gainst	
No additional information a	available	
1.3. Details of the s	upplier of the safety data sheet	
Cambridge Isotope Labora 50 Frontage Road Andover, MA 01810 USA	atories, Inc.	
USA: 1-800-322-1174 In cilsales@isotope.com w	it: 1-978-749-8000 /ww.isotope.com	
Emergency tele	ephone number	
Emergency numbers:		
Chemtrec: 1-800-424-930 International: 1-703-741-5		
SECTION 2: Hazard	s identification	
2.1. Classification of	of the substance or mixture	
Classification according	to Regulation (EC) No. 1272/2008 [CLP]	
-	H225	
Acute Tox. 3 (Oral)	H301	
Acute Tox. 3 (Dermal)	H311	
Acute Tox. 3 (Inhalation)	H331	
Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
STOT SE 1	H370	
Full text of hazard classes	and H-statements : see section 16	
Classification according	to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]	
F; R11 T; R23/24/25 T; R39/23/24/25 Xi; R36/37/38		
Full text of R-phrases: see	e section 16	
GHS-US classification		
	H225	
Acute Tox. 3 (Oral)	H301	
· · · · · ·	H311 H331	
	H315	
	H319	

Eye Irrit. 2AH319STOT SE 1H370

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

METHANOL ULM-9886-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements

2.2. Label elements	
Labeling according to Regulation (EC) No	. 1272/2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS08 GHS06
Signal word (CLP)	: Danger
	: 2-PROPYL PHOSPHONIC ACID UNLABELED
Hazardous ingredients	
Hazard statements (CLP)	 H225 - Highly flammable liquid and vapour H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
	H315 - Causes skin irritation
	H319 - Causes serious eye irritation
	H370 - Causes damage to organs (brain, eyes, heart, liver, kidneys) (in contact with skin, if inhaled, if swallowed)
Propositionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
Precautionary statements (CLP)	smoking.
	P233 - Keep container tightly closed.
	P240 - Ground/bond container and receiving equipment.
	P241 - Use explosion-proof electrical, lighting, ventilating equipment P260 - Do not breathe dust, gas, fume, mist, spray, vapors.
	P264 - Wash Both hands thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area. P308+P313 - IF exposed or concerned: Get medical advice/attention.
GHS-US labeling	
Hazard pictograms (GHS-US)	
	GHS02 GHS08 GHS06
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H225 - Highly flammable liquid and vapour
, , , , , , , , , , , , , , , , , , ,	H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
	H315 - Causes skin irritation
	H319 - Causes serious eye irritation H370 - Causes damage to organs (brain, eyes, heart, kidneys, liver) (Dermal, Inhalation, oral)
Precautionary statements (GHS-US)	: P210 - Keep away from heat, hot surfaces, open flames, sparks No smoking.
r recationary statements (0113-03)	P233 - Keep container tightly closed.
	P240 - Ground/Bond container and receiving equipment
	P241 - Use explosion-proof electrical, lighting, ventilating equipment
	P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge.
	P260 - Do not breathe dust, fume, gas, mist, spray, vapors.
	P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.
	P264 - Wash Both hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area.
	P280 - Wear eye protection, face protection, protective clothing, protective gloves.
	P301+P310 - If swallowed: Immediately call a poison center or doctor
	P302+P352 - If on skin: Wash with plenty of water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse
	skin with water/shower
	P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
	P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
	P311 - Call a poison center or doctor
	P312 - Call a poison center or doctor if you feel unwell
	P321 - Specific treatment (see Hazard pictograms (CLP) on this label)
	P330 - Rinse mouth.

METHANOL ULM-9886-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P361 - Take off immediately all contaminated clothing.

P362 - Take off contaminated clothing and wash before reuse.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to Both hands

2.3. Other hazards

PBT: not relevant - no registration required

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable 3.2. Mixtures

5.2. MIXtures			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.873737	F; R11 T; R39/23/24/25 Xi; R36/38
2-PROPYL PHOSPHONIC ACID UNLABELED	(CAS-No.) 4721-37-3	0.13	C; R35 Xi; R41
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.873737	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
2-PROPYL PHOSPHONIC ACID UNLABELED	(CAS-No.) 4721-37-3	0.13	Skin Corr. 1B, H314 Eye Dam. 1, H318
Name	Product identifier	%	GHS-US classification
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.873737	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures			
4.1. Description of first aid measures			
First-aid measures general	 If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area. 		
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.		
First-aid measures after skin contact	: Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.		
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, i present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention		
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth Call a physician immediately.		
4.2. Most important symptoms and eff	ects, both acute and delayed		
Symptoms/effects after inhalation : Toxic if inhaled.			
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.		

METHANOL ULM-9886-S

Safety Data Sheet

26, 2012 / Rules and Regulations				
Symptoms/effects after eye contact : Causes serious eye irritation.				
Symptoms/effects after ingestion	: Toxic if swallowed.			
4.3. Indication of any immediate medic	cal attention and special treatment needed			
Treat symptomatically.				
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media	: Dry powder. Dry sand.			
Unsuitable extinguishing media	: Do not use a heavy water stream.			
5.2. Special hazards arising from the s	ubstance or mixture			
Fire hazard	: Highly flammable liquid and vapour.			
Reactivity	: Vapors may form flammable mixture with air. Highly flammable liquid and vapour.			
5.3. Advice for firefighters				
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.			
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.			
Other information	: Use water spray to cool exposed surfaces.			
SECTION 6: Accidental release me	asures			
6.1. Personal precautions, protective e	equipment and emergency procedures			
6.1.1. For non-emergency personnel				
Emergency procedures	: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.			
6.1.2. For emergency responders				
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".			
6.2. Environmental precautions				
	not allow to enter drains or water courses. Avoid release to the environment.			
6.3. Methods and material for contain	nent and cleaning up			
For containment	: Dike and contain spill.			
Methods for cleaning up	 Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation. 			
Other information	: Dispose of materials or solid residues at an authorized site.			
6.4. Reference to other sections				
For further information refer to section 13.				
SECTION 7: Handling and storage				
7.1. Precautions for safe handling Additional hazards when processed	· Handle empty containers with care because residual venera are flormable			
•	: Handle empty containers with care because residual vapors are flammable.			
Precautions for safe handling Hygiene measures	 No open flames. No smoking. Use only non-sparking tools. Avoid breathing dust, mist or spray. Do not eat, drink or smoke when using this product. Wash Both hands thoroughly after 			
rigicile measures	handling.			
7.2. Conditions for safe storage, include	ding any incompatibilities			
Technical measures	 Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment. 			
Storage conditions	: Store at room temperature away from light and moisture.			
Incompatible materials : Heat sources.				
No additional information available				

METHANOL ULM-9886-S

Safety Data Sheet

SECTION 8: Exposure c	ontrols/personal protection	
.1. Control parameters		
2-PROPYL PHOSPHONIC AC	DID UNLABELED 1000 UG/ML IN METHAN	IOL
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Ily - Portugal - USA ACGIH Remark (ACGIH) Headache. Nausea. Dizziness. E Substances for which there is a B Index or Indices (see BEI section cutaneous absorption.	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.
100% METHANOL UNLABEL	ED (67-56-1)	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.

METHANOL ULM-9886-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL UNLABELED (67-56-1)				
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.		

2-PROPYL PHOSPHONIC ACID UNLABELED 1000 UG/ML IN METHANOL			
DNEL/DMEL (Workers)			
Acute - systemic effects, dermal	40 mg/kg bodyweight/day		
Acute - systemic effects, inhalation	260 mg/m ³		
Acute - local effects, dermal	260 mg/cm ²		
Long-term - systemic effects, dermal	40 mg/kg bodyweight/day		
Long-term - local effects, dermal	260 mg/cm ²		
Long-term - local effects, inhalation	260 mg/m ³		
DNEL/DMEL (General population)			
Acute - systemic effects, dermal	8 mg/kg body weight		
Acute - systemic effects, inhalation	50 mg/m ³		
Acute - systemic effects, oral	8 mg/kg body weight		
Acute - local effects, inhalation	50 mg/m ³		
Long-term - systemic effects,oral	8 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	50 mg/m ³		
Long-term - systemic effects, dermal	8 mg/kg bodyweight/day		
Long-term - local effects, inhalation	50 mg/m³		
PNEC (Water)			
PNEC aqua (freshwater)	154 mg/l		
PNEC aqua (marine water)	15.4 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	570.4 mg/kg dwt		
PNEC (Soil)			
PNEC soil	23.5 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant 100 mg/kg			
8.2. Exposure controls			

Appropriate engineering controls

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.

Personal protective equipment



Wear eye protection. Chemical goggles or face shield with safety glasses.Wear suitable protective clothing, gloves and eye/face protection.

Wear suitable protective clothing and gloves.

Materials for protective clothing Hand protection Eye protection Skin and body protection

EN (English US)

METHANOL ULM-9886-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: In	a case of inadequate ventilation wear respiratory protection.	Approved supplied air respirator
Environmental exposure controls	: A\	void release to the environment.	

SECTION 9: Physical and chemical properties

The properties listed below are for the solvent, the main component of this inditro. Physical state : Liquid Appearance : Liquid Molecular mass : 32.04 g/mol Color : Colorless Odor : No data available PH : No data available Pd : No data available Relative evaporation rate (butyl acetate=1) : No data available Pfreezing point : No data available Boiling point : e98 °C (-144 °F) Freezing point : No data available Boiling point : e95 °C (49.5 °F) - closed cup Auto-ignition temperature : 455 °C (851 °F) at 1,013 hPa (750 mmHg) Decomposition temperature : No data available Vapor pressure : No data available Vapor pressure at 50 °C : 546.6 hPa (410 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F) Relative vapor density at 20 °C : No data available Supecific gravity / density : No data available Supecific gravity / density : No data available Supecific gravity / density : No data available Viscosity, kin	9.1. Information on basic physical and chemical properties		
Appearance: LiquidMolecular mass: 32.04 g/molColor: ColoriessOdor: ColoriessOdor: No data availablepH: No data availableRelative evaporation rate (butyl acetate=1): No data availableRelative evaporation rate (butyl acetate=1): No data availableBolling point: 64.7 °C (144.°F)Freezing point: 64.7 °C (144.85.°F)Flash point: 64.7 °C (144.85.°F)Paramability (solid, gas): 8.7 °C (49.5 °F) - closed cupAuto-ignition temperature: 9.7 °C (49.5 °F) - closed cupVapor pressure: 130.3 hPa (76.0 mmHg)Vapor pressure: 130.3 hPa (77.7 mmHg) at 20 °C (68.°F); 169.27 hPa (126.96 mmHg) at 25 °C (77.°F)Vapor pressure at 50 °C: 1.11Relative density at 20 °C: 1.11Relative density: 0.791 g/m1 at 25 °C (77.°F)Solubility: Water: Completely miscibleLog Pow: 0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, kinematic: No data availableViscosity, kinematic: No data availableViscosity, kinematic: No data availableViscosity, kinem	The properties listed below are for the solvent, the main component of this mixture.		
Molecular mass: 32.04 g/molColor: ColorlessOdor: PungentOdor threshold: No data availablePH: No data availableRelative evaporation rate (butyl acetate=1): No data availableMelting point: -98 °C (-144 °F)Freezing point: No data availableBoiling point: 64.7 °C (148.5 °F)Fraezing point: 9.7 °C (49.5 °F) - closed cupAuto-ignition temperature: No data availableDecomposition temperature: No data availableFlammability (solid, gas): No data availableVapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSolubility: No data availableLog Pow: 0.791 g/ml at 25 °C (77 °F)Solubility: No data availableLog Pow: 0.771Log Kow: No data availableViscosity, kinematic: No data availableViscosity, kinematic: No data availableViscosity, kinematic: No data availableLog Pow: 0.771Log Kow: No data availableViscosity, kinematic: No	Physical state	: Liquid	
Color: ColorlesOdor: PungentOdor threshold: No data availablePH: No data availableRelative evaporation rate (butyl acetate=1): No data availableMetting point: -98 °C (144 °F)Freezing point: No data availableBoiling point: 64.7 °C (148.5 °F)Flash point: 9.7 °C (49.5 °F) - closed cupAuto-ignition temperature: 455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature: No data availableVapor pressure: No data availableVapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 1.11Relative vapor density at 20 °C: 1.11Relative vapor density at 20 °C: 0.791 g/ml at 25 °C (77 °F)Solubility: 0.791 g/ml at 25 °C (77 °F)Solubility: 0.791 g/ml at 25 °C (77 °F)Log Pow: No data availableViscosity, kinematic:	Appearance	: Liquid	
Odor: PungentOdor threshold: No data availablepH: No data availableRelative evaporation rate (butyl acetate=1): No data availableRelative evaporation rate (butyl acetate=1): No data availableTreezing point: -98 °C (144 °F)Freezing point: No data availableBoiling point: 64.7 °C (148.5 °F)Flash point: 97 °C (148.5 °F) - closed cupAuto-ignition temperature: 455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature: No data availableParmability (solid, gas): No data availableVapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 340.6 hPa (410 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Relative vapor density at 20 °C: 1.11Relative vapor density at 20 °C: 1.01Solubility: No data availableSolubility: No data availableLog Pow: No data availableViscosity, kinematic: No data availableViscos	Molecular mass	: 32.04 g/mol	
Odor threshold: No data availablepH: No data availableRelative evaporation rate (butyl acetate=1): No data availableMetting point: 98 °C (-144 °F)Freezing point: No data availableBoiling point: 64.7 °C (148.5 °F)Flash point: 9.7 °C (48.5 °F) - closed cupAuto-ignition temperature: 455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature: No data availableFlash point: No data availableFlash point: No data availableParomposition temperature: No data availableFlash point: No data availableParomposition temperature: No data availableVapor pressure at 50 °C: S46.6 hPa (410 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: 0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableViscosity, dynamic: No data availableViscosity, dynamic: No data availableViscosity, dynamic: No data availableViscosity, properties: No data availableViscosity, properties: No data availableViscosity, properties: No data available <td< td=""><td>Color</td><td>: Colorless</td></td<>	Color	: Colorless	
pH: No data availableRelative evaporation rate (butyl acetate=1): No data availableMelting point: -98 °C (-144 °F)Freezing point: No data availableBoiling point: 64.7 °C (148.5 °F)Flash point: 9.7 °C (49.5 °F) - closed cupAuto-ignition temperature: 455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature: No data availableFlasmability (solid, gas): No data availableVapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSolubility: Vater: Completely miscibleLog Pow: 0.791 g/ml at 25 °C (77 °F)Solubility: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data available </td <td>Odor</td> <td>: Pungent</td>	Odor	: Pungent	
Relative evaporation rate (butyl acetate=1):No data availableMelting point:-98 °C (-144 °F)Freezing point:No data availableBoiling point:64.7 °C (148.5 °F)Flash point:9.7 °C (49.5 °F) - closed cupAuto-ignition temperature:455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature:No data availableFlasm ability (solid, gas):No data availableVapor pressure at 50 °C:546.6 hPa (410 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C:546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C:1.11Relative density:No data availableSolubility:0.791 g/ml at 25 °C (77 °F)Solubility:0.791 g/ml at 25 °C (77 °F)Solubility:No data availableLog Pow:-0.77Log Kow:No data availableViscosity, kinematic:No data availableViscosity, dynamic:No da	Odor threshold	: No data available	
Melting point: -98 °C (-144 °F)Freezing point: No data availableBoiling point: 64.7 °C (148.5 °F)Flash point: 9.7 °C (49.5 °F) - closed cupAuto-ignition temperature: 455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature: No data availableFlammability (solid, gas): No data availableVapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: No data availableViscosity groperties: No data availableViscosity groperties: No data available	рН	: No data available	
Freezing point: No data availableBoiling point: 64.7 °C (148.5 °F)Flash point: 9.7 °C (49.5 °F) - closed cupAuto-ignition temperature: 455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature: No data availableFlammability (solid, gas): No data availableVapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: 0.791 g/ml at 25 °C (77 °F)Solubility: No data availableViscosity, kinematic: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Relative evaporation rate (butyl acetate=1)	: No data available	
Boiling point:64.7 °C (148.5 °F)Flash point:9.7 °C (49.5 °F) - closed cupAuto-ignition temperature:455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature:No data availableFlammability (solid, gas):No data availableVapor pressure:130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C:546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C:1.11Relative density:No data availableSpecific gravity / density:0.791 g/ml at 25 °C (77 °F)Solubility:Water: Completely miscibleLog Pow:-0.77Log Kow:No data availableViscosity, kinematic:No data availableViscosity, dynamic:No data availableExplosive properties:Product is not explosive.Oxidizing properties:No oxidizing material according to EC criteria.	Melting point	: -98 °C (-144 °F)	
Flash point: 9.7 °C (49.5 °F) - closed cupAuto-ignition temperature: 455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature: No data availableFlammability (solid, gas): No data availableVapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Freezing point	: No data available	
Auto-ignition temperature: 455 °C (851 °F) at 1,013 hPa (760 mmHg)Decomposition temperature: No data availableFlammability (solid, gas): No data availableVapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Boiling point	: 64.7 °C (148.5 °F)	
Decomposition temperature: No data availableFlammability (solid, gas): No data availableVapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Vater: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Flash point	: 9.7 °C (49.5 °F) - closed cup	
Flammability (solid, gas): No data availableVapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)	
Vapor pressure: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Decomposition temperature	: No data available	
Vapor pressure at 50 °C: 546.6 hPa (410 mmHg) at 50 °C (122 °F)Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Flammability (solid, gas)	: No data available	
Relative vapor density at 20 °C: 1.11Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Vapor pressure	: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)	
Relative density: No data availableSpecific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Vapor pressure at 50 °C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)	
Specific gravity / density: 0.791 g/ml at 25 °C (77 °F)Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Relative vapor density at 20 °C	: 1.11	
Solubility: Water: Completely miscibleLog Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: No data availableOxidizing properties: Non oxidizing material according to EC criteria.	Relative density	: No data available	
Log Pow: -0.77Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Specific gravity / density	: 0.791 g/ml at 25 °C (77 °F)	
Log Kow: No data availableViscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Solubility	: Water: Completely miscible	
Viscosity, kinematic: No data availableViscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Log Pow	: -0.77	
Viscosity, dynamic: No data availableExplosive properties: Product is not explosive.Oxidizing properties: Non oxidizing material according to EC criteria.	Log Kow	: No data available	
Explosive properties : Product is not explosive. Oxidizing properties : Non oxidizing material according to EC criteria.	Viscosity, kinematic	: No data available	
Oxidizing properties : Non oxidizing material according to EC criteria.	Viscosity, dynamic	: No data available	
	Explosive properties	: Product is not explosive.	
Explosion limits : 6 - 36 % (V)	Oxidizing properties	: Non oxidizing material according to EC criteria.	
	Explosion limits	: 6 - 36 % (V)	

9.2. Other information

No additional information available

NU auun			
SECTI	10: Stability and reactivity		
10.1.	eactivity		
Vapors r	/ form flammable mixture with air. Highly flammable liquid and vapour.		
10.2.	hemical stability		
See stor	e and expiration date on CoA.		
10.3.	ossibility of hazardous reactions		
No dang	ous reactions known under normal conditions of use.		
10.4.	onditions to avoid		
Avoid co	ct with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.		
10.5.	acompatible materials		
Acid anh	rides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.		
10.6.	azardous decomposition products		
	des (CO, CO2).		
SECTI	11: Toxicological information		
11.1.	Iformation on toxicological effects		
Acute to	ty : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: Toxic if inhaled.		

METHANOL ULM-9886-S

Safety Data Sheet

2-PROPYL PHOSPHONIC ACID UNLABELED	1000 UG/ML IN METHANOL
LD50 oral rat	1187 - 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	128.200 mg/l/4h
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
100% METHANOL UNLABELED (67-56-1)	
LD50 oral rat	1187 - 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	128.200 mg/l/4h
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin corrosion/irritation	: Skin - Rabbit. Result: No skin irritation
Serious eye damage/irritation	: Eyes - Rabbit. Result: No eye irritation
Respiratory or skin sensitization	: Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)
Germ cell mutagenicity	: AMES test : S. tymphimurium. Result: negative. fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - male and female Result: negative. Mouse - male and female. Result: Negative
Carcinogenicity	: Not classified
Reproductive toxicity	: Damage to fetus not classifiable. Fertility classification not possible from current data.
Specific target organ toxicity – single exposure	: Causes damage to organs through prolonged or repeated exposure
· · · · · · · · · · · · · · · · · · ·	Causes damage to organs
Specific target organ toxicity – repeated xposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure No data available
Aspiration hazard	: No aspiration toxicity classification.
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product fo the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach.
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.

SECTION 12: Ecological information			
12.1. Toxicity			
Ecology - general	The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.		
2-PROPYL PHOSPHONIC ACID UNLABELED	1000 UG/ML IN METHANOL		
LC50 fish 1			
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h		
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h		
NOEC (acute) 7900 mg/l Oryzias latipes - 200 h			
100% METHANOL UNLABELED (67-56-1)			
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h		
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h		
31/07/2018 EN (English US)			

METHANOL ULM-9886-S

Safety Data Sheet

100% METHANOL UNLABELED (67-56-1)	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h
2.2. Persistence and degradability	
2-PROPYL PHOSPHONIC ACID UNLABELE	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD Riedegradetien	1500 mg/g 72 % - rapidly biodegradable aerobic - Exposure time 5 d
Biodegradation	72 % - Tapidiy biodegradable aerobic - Exposure time 5 d
100% METHANOL UNLABELED (67-56-1)	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d
2.3. Bioaccumulative potential	
2-PROPYL PHOSPHONIC ACID UNLABELE	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77
100% METHANOL UNLABELED (67-56-1)	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77
2.4. Mobility in soil	
2-PROPYL PHOSPHONIC ACID UNLABELE	D 1000 LIG/ML IN METHANOL
Ecology - soil	Not degradable in the soil.
••	
100% METHANOL UNLABELED (67-56-1) Ecology - soil	Not degradable in the soil.
2.5. Results of PBT and vPvB assessme	
2-PROPYL PHOSPHONIC ACID UNLABELE	D 1000 UG/ML IN METHANOL
PBT: not relevant – no registration required	
100% METHANOL UNLABELED (67-56-1)	
PBT: not relevant – no registration required	
2.6. Other adverse effects	
Other adverse effects	: Avoid release to the environment.
Other information	: Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water.
	Hydrolyses readily.
SECTION 13: Disposal consideratio	ns
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Hazardous waste due to toxicity.
SECTION 14: Transport information	
n accordance with ADR / RID / IMDG / IATA / A	
4.1. UN number	
	: 1230
JN-No.(DOT) DOT NA no.	UN1230
4.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Methanol

Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

METHANOL ULM-9886-S

Safety Data Sheet

26, 2012 / Rules and Regulations	
Hazard labels (DOT)	: 3 - Flammable liquid 6.1 - Poison
	FLAMMABLE LIQUD POISON
	3 6
DOT Symbols	: + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper shipping name appropriate for international and domestic transportation
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
14.3. Additional information	All some land of the state of the second state in
Other information	: No supplementary information available.
Overland transport	
Packing group (ADR)	: II
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 336
Classification code (ADR)	: FT1
Hazard labels (ADR)	: 3 - Flammable liquids 6.1 - Toxic substances
Orange plates	336 1230
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
EAC	: •2WE
APP	: A(fl)
Excepted quantities (ADR)	: E2
Transport by sea	
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a
	passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
MFAG-No	: 131

METHANOL ULM-9886-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport		
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	60 L
Civil Aeronautics Law	:	Flammable liquids

14.4.	Environmental hazards		
Other in	formation	: No supplementary information available.	
14.5.	Special precautions for user		
14.6.	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		

Not applicable

SECTION 15: Regulatory information		
15.1. US Federal regulations		
2-PROPYL PHOSPHONIC ACID UNLABELED	1000 UG/ML IN METHANOL	
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory	
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting Subject to reporting requirements of United States SARA Section 313		
100% METHANOL UNLABELED (67-56-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ 5000 lb		
SARA Section 302 Threshold Planning Quantity (TPQ) Not subject to reporting requirements of the United States SARA Section 302.		
SARA Section 311/312 Hazard Classes Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard		
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	
15.2. International regulations		

CANADA

2-PROPYL PHOSPHONIC ACID UNLABELED 1000 UG/ML IN METHANOL
Listed on the Canadian DSL (Domestic Substances List)
100% METHANOL UNLABELED (67-56-1)

15.2.1. National regulations

No additional information available

15.3. US State regulations

2-PROPYL PHOSPHONIC ACID UNLABELED 1000	JG/ML IN METHANOL
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	Yes
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances

METHANOL ULM-9886-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL UNLABELED (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	
100% METHANOL UNLABELED (67-56-1)				
State or local regulations				
U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances				

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:


Acute toxicity (dermal) Category 3	
Acute toxicity (inhalation) Category 3	
Acute toxicity (inhalation:vapour) Category 3	
, , , , , , , , , , , , , , , , , , , ,	
Acute toxicity (oral) Category 3	
Serious eye damage/eye irritation Category 1	
Serious eye damage/eye irritation Category 2	
Flammable liquids Category 2	
Skin corrosion/irritation Category 1B	
Skin corrosion/irritation Category 2	
Specific target organ toxicity (single exposure) Category 1	
Highly flammable liquid and vapour	
Toxic if swallowed	
Toxic in contact with skin	
Causes severe skin burns and eye damage	
Causes skin irritation	
Causes serious eye damage	
Causes serious eye irritation	
Toxic if inhaled	
Causes damage to organs	
Highly flammable	
Toxic by inhalation, in contact with skin and if swallowed	
Causes severe burns	
Irritating to eyes, respiratory system and skin	
Irritating to eyes and skin	
Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed	
Risk of serious damage to eyes	
Corrosive	
Highly flammable	
Toxic	
Irritant	

NFPA health hazard	:
NFPA fire hazard	:
NFPA reactivity	:

2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

0 - Material that in themselves are normally stable, even under fire conditions.



METHANOL ULM-9886-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

hazara nating		
Health	:	2 Moderate Hazard - Temporary or minor injury may occur
Flammability	:	3 Serious Hazard
Physical	:	0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product