

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/04/2015 Revision date: : Version: 1.0

CLM-4668-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Product name : DI-N-PENTYL PHTHALATE (100 UG/ML IN NONANE) (RING-1,2-13C2, DICARBOXYL-

13C2, 99%)

Product code : CLM-4668-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 <u>cilsales@isotope.com</u> www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226
Acute Tox. 4 (Inhalation:dust,mist) H332
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT SE 3 H336
Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R20 Xn; R65 R10

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 3 H226
Acute Tox. 4 (Inhalation:dust,mist) H332
Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 3 H336
Asp. Tox. 1 H304
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Central Nervous System. Flammable liquid and vapor. May cause drowsiness or dizziness. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.

22/09/2021 EN (English US) 1/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. **Label elements**

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

Signal word (CLP)

: N-NONANE UNLABELED Hazardous ingredients

: H226 - Flammable liquid and vapor Hazard statements (CLP)

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation H319 - Causes serious eve irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof ventilating, lighting, electrical equipment P261 - Avoid breathing vapors, spray, mist, gas, fume, dust. P264 - Wash Both hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, face protection, eye protection.

GHS-US labeling

Hazard pictograms (GHS-US)







Signal word (GHS-US) : Danger

H226 - Flammable liquid and vapor Hazard statements (GHS-US)

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) P210 - Keep away from sparks, open flames, hot surfaces, heat. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof ventilating, lighting, electrical equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P261 - Avoid breathing vapors, spray, mist, gas, fume, dust. P264 - Wash Both hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, protective clothing, face protection, eye protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P312 - Call a poison center or doctor if you feel unwell

P321 - Specific treatment (see Hazard pictograms (CLP) on this label)

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.

22/09/2021 EN (English US) 2/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to Comply with applicable regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

3.2. WIXIUIES			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.9861	R10 Xn; R20 Xn; R65 Xi; R36/38 R67
DI-N-PENTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL-13C2, 99%) substance listed as REACH Candidate	(CAS-No.) 131-18-0 (unlabeled) (EC-No.) 205-017-9 (EC Index-No.) 607-426-00-1	0.0139	N; R50/53 R33
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.9861	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
DI-N-PENTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL- 13C2, 99%) substance listed as REACH Candidate	(CAS-No.) 131-18-0 (unlabeled) (EC-No.) 205-017-9 (EC Index-No.) 607-426-00-1	0.0139	Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS-No.) 111-84-2	99.9861	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

4.1. E	Description	of first aid	d measures
--------	-------------	--------------	------------

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash

with plenty of soap and water. Wash contaminated clothing before reuse.

Asp. Tox. 1, H304

First-aid measures after eye contact : Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

First-aid measures after ingestion : Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

inhaled. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

22/09/2021 EN (English US) 3/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

: Flammable liquid and vapor. Vapors may form flammable mixture with air. Reactivity

Advice for firefighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection. Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No

smoking.

6.1.1. For non-emergency personnel

: Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and **Emergency procedures**

no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

: Dike and contain spill. Dispose as hazardous waste. Comply with local regulations for disposal. For containment

Methods for cleaning up Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

Other information : Dispose of materials or solid residues at an authorized site.

Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

No open flames. No smoking. Take precautionary measures against static discharge. Use only Precautions for safe handling

non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust, mist or

Hygiene measures

Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Use explosion-proof electrical equipment.

Store at room temperature away from light and moisture. Storage conditions

Incompatible materials : Heat sources.

Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

Control parameters

N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1050 mg/m³ USA. NIOSH Recommended Exposure Limits

22/09/2021 EN (English US) 4/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-NONANE UNLABELED (111-84-2)		
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m³)	1050 mg/m³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.

8.2. Exposure controls

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.









Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.

Skin and body protection : Wear suitable protective clothing

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

Appearance : Liquid

Molecular mass : 128.3 g/mol

Color : Colorless

Odor : No data available
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : Not applicable
Freezing point : -53 °C (- 63 °F) - lit
Boiling point : 151 °C (304 °F) - lit
Flash point : 31 °C (87.8 °F) - closed cup

Auto-ignition temperature : 205 °C (401 °F)

Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapor

Vapor pressure : 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)

Relative vapor density at 20 °C : No data available Relative density : No data available

Specific gravity / density : 0.718 g/ml at 25 °C (77 °F)

Solubility : Water: 0.0002 % at 25 °C (77 °F) - slightly soluble

Log Pow : 5.65

Log Kow : No data available

Viscosity, kinematic : <= 1.008 mm²/s at 20 °C (68 °F)

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : 0.87 - 2.9 % (V)

22/09/2021 EN (English US) 5/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor. Vapors may form flammable mixture with air.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

DI-N-PENTYL PHTHALATE (100 UG/ML IN NONANE) (RING-1,2-13C2, DICARBOXYL- 13C2, 99%)	
LC50 inhalation rat (mg/l)	23760 mg/m³ male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative

N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m³ male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Potential Adverse human health effects and

symptoms

: Harmful if inhaled.

Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

inhaled. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

22/09/2021 EN (English US) 6/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

DI-N-PENTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL- 13C2, 99%) (131-18-0 (unlabeled))	
Persistence and degradability	Not available.

12.3. Bioaccumulative potential

DI-N-PENTYL PHTHALATE (100 UG/ML IN NONANE) (RING-1,2-13C2, DICARBOXYL- 13C2, 99%)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
N NONANE UNI APELED (444 04 0)	

DI NI DENTALI DI TUAL ATE (DINO 4 0 4000 DI	10ARROVVI 4000 000/ /404 40 0 /
Bioaccumulative potential	Indication of bioaccumulation.
Log Pow	5.65
N-NONANE UNLABELED (111-84-2)	

DI-N-PENTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL- 13C2, 99%) (131-18-0 (unlabeled))	
Log Pow	4.85
Bioaccumulative potential	Not available.

12.4. Mobility in soil

DI-N-PENTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL- 13C2, 99%) (131-18-0 (unlabeled))	
Ecology - soil	Not available.

12.5. Results of PBT and vPvB assessment

DI-N-PENTYL PHTHALATE (RING-1,2-13C2, DICARBOXYL- 13C2, 99%) (131-18-0 (unlabele	ed))
This substance/mixture does not meet the PBT criteria of REACH, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH annex XIII	

12.6. Other adverse effects

Other adverse effects : Disposal must be done according to official regulations.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local

environmental control regulations.

Product/Packaging disposal recommendations : Dispose of contents/container to Comply with applicable regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT) : 1920 DOT NA no. UN1920

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Nonanes

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid

FLAMMABLE LIQUID

Packing group (DOT) : III - Minor Danger

22/09/2021 EN (English US) 7/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : III

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 30
Classification code (ADR) : F1

Hazard labels (ADR) : 3 - Flammable liquids



Orange plates

30 1920

Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) 5I
EAC : 3Y
Excepted quantities (ADR) : E1

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

MFAG-No : 128

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

22/09/2021 EN (English US) 8/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

DI-N-PENTYL PHTHALATE (100 UG/ML IN NONANE) (RING-1,2-13C2, DICARBOXYL- 13C2, 99%)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard			
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.			

	, , , ,			
N-NONANE UNLABELED (111-84-2)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard			
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.			

15.2. International regulations

CANADA

DI-N-PENTYL PHTHALATE (100 UG/ML IN NONANE) (RING-1,2-13C2, DICARBOXYL- 13C2, 99%)

Listed on the Canadian DSL (Domestic Substances List)

N-NONANE UNLABELED (111-84-2)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

DI-N-PENTYL PHTHALATE (100 UG/ML IN NONANE) (RING-1,2-13C2, DICARBOXYL- 13C2, 99%)()			
U.S California - Proposition 65 - Carcinogens List	No		
U.S California - Proposition 65 - Developmental Toxicity	No		
U.S California - Proposition 65 - Reproductive Toxicity - Female	No		
U.S California - Proposition 65 - Reproductive Toxicity - Male	No		
State or local regulations	U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S New Jersey - Right to Know Hazardous Substance List U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances		

N-NONANE UNLABELED (111-84-2)

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

N-NONANE UNLABELED (111-84-2)

State or local regulations

- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances

22/09/2021 EN (English US) 9/10

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

tokt of it , if and Eoff phiaooo.		
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1	
Asp. Tox. 1	Aspiration hazard Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation Category 2	
Flam. Liq. 3	Flammable liquids Category 3	
Repr. 1B	Reproductive toxicity Category 1B	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H226	Flammable liquid and vapor	
H304	May be fatal if swallowed and enters airways	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H332	Harmful if inhaled	
H336	May cause drowsiness or dizziness	
H360	May damage fertility or the unborn child	
H400	Very toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
R10	Flammable	
R20	Harmful by inhalation	
R33	Danger of cumulative effects	
R36/38	Irritating to eyes and skin	
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment	
R65	Harmful: may cause lung damage if swallowed	
R67	Vapors may cause drowsiness and dizziness	
N	Dangerous for the environment	
Xi	Irritant	
Xn	Harmful	

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

22/09/2021 EN (English US) 10/10