

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 27/03/2017 Revision date: 27/09/2018 Supersedes: 27/03/2017 Version: 1.1

ULM-10256-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Product name : URACIL UNLABELED 1000 UG/ML IN 1:1 METHANOL:WATER

Product code : ULM-10256-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 <u>cilsales@isotope.com</u> www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation) H331
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT RE 2 H373

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11 T; R23/24/25 Xi; R36/38 Xi; R39

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 H225
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation) H331
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT RE 2 H373

Full text of H statements : see section 16

27/09/2018 EN (English US) 1/11

ULM-10256-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS08

GHS06

Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H373 - May cause damage to organs (central nervous system, eyes, heart, kidneys, liver) through prolonged or repeated exposure (in contact with skin, if inhaled, if swallowed)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Precautionary statements (CLP)

smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment P260 - Do not breathe dust, fume, gas, mist, spray, vapors. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

GHS-US labeling

Hazard pictograms (GHS-US)

Precautionary statements (GHS-US)







GHS08

GHS06

Signal word (GHS-US) : Danger

: H225 - Highly flammable liquid and vapour Hazard statements (GHS-US)

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H373 - May cause damage to organs (central nervous system, eyes, heart, kidneys, liver)

through prolonged or repeated exposure (Dermal, Inhalation, oral)

: P210 - Keep away from heat, open flames, sparks. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust, fume, mist, gas, spray, vapors. P261 - Avoid breathing dust, fume, gas, spray, vapors, mist. P264 - Wash Both hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective clothing, protective gloves.

P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P311 - Call a doctor, a POISON CENTER

P312 - Call a doctor, a POISON CENTER if you feel unwell P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see Suitable first-aid treatment should be immediately available. on

this label)

EN (English US) 27/09/2018 2/11

ULM-10256-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P322 - Specific treatment (see Hazard pictograms (CLP) on this label)

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use Dry chemical, Alcohol resistant foam, Carbon dioxide. to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to Dispose in a safe manner in accordance with

local/national regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
WATER UNLABELED	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	55.77	Not classified
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	44.116007	F; R11 T; R39/23/24/25 Xi; R36/38
URACIL UNLABELED	(CAS-No.) 66-22-8 (EC-No.) 200-621-9	0.11	Not classified

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
WATER UNLABELED	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	55.77	Not classified
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	44.116007	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
URACIL UNLABELED	(CAS-No.) 66-22-8 (EC-No.) 200-621-9	0.11	Not classified

Name	Product identifier	%	GHS-US classification
WATER UNLABELED	(CAS-No.) 7732-18-5	55.77	Not classified
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	44.116007	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370
URACIL UNLABELED	(CAS-No.) 66-22-8	0.11	Not classified

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If medical advice is needed, have product container or label at hand. Call a physician

immediately. Evacuate danger area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Call a doctor.

27/09/2018 EN (English US) 3/11

ULM-10256-9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact

Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water. Specific measures (see Hazard pictograms (CLP) on this label). Wash contaminated clothing before reuse. If skin irritation occurs: Wash with plenty of soap and water, Get immediate medical advice/attention. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

: Rinse mouth. Obtain emergency medical attention. Immediately call a poison center or doctor/physician. Specific treatment (see Hazard pictograms (CLP) on this label).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: Toxic if inhaled.

Symptoms/effects after skin contact

: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.

Symptoms/effects after eye contact

Causes serious eye irritation.

Symptoms/effects after ingestion

 $: \ \, \text{Toxic if swallowed. Swallowing a small quantity of this material will result in serious health} \\$

hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Dry sand.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Highly flammable liquid and vapour.

Explosion hazard

: May form flammable/explosive vapor-air mixture.

Reactivity

: Vapors may form flammable mixture with air. Highly flammable liquid and vapour.

5.3. Advice for firefighters

Firefighting instructions

: Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures

: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not allow to enter drains or water courses. Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Dike and contain spill.

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: No open flames. No smoking. Use only non-sparking tools. Avoid breathing dust, fume, gas, mist, spray, vapors.

27/09/2018 EN (English US) 4/11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures

: Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly

ULM-10256-S

after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Lighting equipment, ventilating

Storage conditions Store at room temperature away from light and moisture.

Incompatible materials : Heat sources.

Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

Control parameters

Italy - Portugal - USA ACGIH ACGIH TWA (ppm) 200.00000000 ppm Basis: USA, ACGIH Threshold Limit Values (TLV) Italy - Portugal - USA ACGIH ACGIH STEL (ppm) 250 ppm Basis: USA, ACGIH Threshold Limit Values (TLV) Italy - Portugal - USA ACGIH Remark (ACGIH) Headache, Nausea, Dizziness, Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section), Danger of cutaneous absorption. USA NIOSH NIOSH REL (TWA) (mg/m³) 260 mg/m³ Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (STEL) (mg/m³) 200 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (STEL) (mg/m³) 250 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH Remark (NIOSH) Potential for dermal absorption. USA OSHA OSHA PEL (TWA) (mg/m³) 260 mg/m³ Basis: USA, Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) 220 mg/m³ Basis: USA, OCCUPATIONAL Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) 325 mg/m³ Basis: USA, OSHA - Table Z-1 Limits for Air Contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA, OSHA	100% METHANOL UNLABEL	.ED (67-56-1)	
Italy - Portugal - USA ACGIH Remark (ACGIH)	Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	
Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption. USA NIOSH NIOSH REL (TWA) (mg/m³) 260 mg/m³ Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (TWA) (ppm) 200 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (STEL) (mg/m³) 325 mg/m³ Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (STEL) (ppm) 250 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (STEL) (ppm) Potential for dermal absorption. USA OSHA OSHA PEL (TWA) (mg/m³) 260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table 2-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) 325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 6, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) 325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	
USA NIOSH NIOSH REL (TWA) (ppm) 200 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (STEL) (mg/m³) 325 mg/m³ Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (STEL) (ppm) 250 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH Remark (NIOSH) Potential for dermal absorption. USA OSHA OSHA PEL (TWA) (mg/m³) 260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (TWA) (ppm) OSHA PEL (STEL) (mg/m³) 325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (Ceiling) (ppm) 1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	Italy - Portugal - USA ACGIH	Remark (ACGIH)	Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of
USA NIOSH NIOSH REL (STEL) (mg/m³) 250 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH NIOSH REL (STEL) (ppm) 250 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH Remark (NIOSH) Potential for dermal absorption. USA OSHA OSHA PEL (TWA) (mg/m³) 260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) USA OSHA OSHA PEL (STEL) (mg/m³) OSHA PEL (STEL) (ppm) OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (Ceiling) (ppm) 1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	USA NIOSH	NIOSH REL (TWA) (mg/m³)	
Limits USA NIOSH NIOSH REL (STEL) (ppm) 250 ppm Basis: NIOSH Recommended Exposure Limits USA NIOSH Remark (NIOSH) Potential for dermal absorption. 260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (TWA) (ppm) 200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) 325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (Ceiling) (ppm) 1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	USA NIOSH	NIOSH REL (TWA) (ppm)	
Limits USA NIOSH Remark (NIOSH) Potential for dermal absorption. 260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (TWA) (ppm) OSHA PEL (TWA) (ppm) 200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (Ceiling) (ppm) 1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	USA NIOSH	NIOSH REL (STEL) (mg/m³)	
USA OSHA OSHA PEL (TWA) (mg/m³) 260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (TWA) (ppm) 200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) 325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (Ceiling) (ppm) 1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	USA NIOSH	NIOSH REL (STEL) (ppm)	l ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
(OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (TWA) (ppm) 200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (mg/m³) 325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (Ceiling) (ppm) 1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA OSHA PEL (STEL) (mg/m³) USA OSHA OSHA PEL (STEL) (mg/m³) USA OSHA OSHA PEL (STEL) (ppm)	USA OSHA	OSHA PEL (TWA) (mg/m³)	(OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for
Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (STEL) (ppm) 250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (Ceiling) (ppm) 1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	USA OSHA	OSHA PEL (TWA) (ppm)	(OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for
Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107) USA OSHA OSHA PEL (Ceiling) (ppm) 1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	USA OSHA	OSHA PEL (STEL) (mg/m³)	Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8,
chemical contaminants (Title 8, Article 107)	USA OSHA	OSHA PEL (STEL) (ppm)	Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8,
USA OSHA Remark (OSHA) The value in mg/m3 is approximate. Skin notation.	USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
	USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.

Exposure controls

Skin and body protection : Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Liquid Appearance : Liquid Color : Colorless Odor : No data available Odor threshold : No data available : No data available рΗ

27/09/2018 EN (English US) 5/11

ULM-10256-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapour

Vapor pressure No data available Relative vapor density at 20 °C No data available : No data available Relative density Solubility : No data available : No data available Log Pow Log Kow : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive properties No data available : No data available Oxidizing properties **Explosion limits** : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapour.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

May form flammable/explosive vapor-air mixture.

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

LD50 dermal rabbit

ATE CLP (oral)

ATE CLP (dermal)

ATE CLP (vapors)

LC50 inhalation rat (mg/l)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: Toxic if inhaled.

URACIL UNLABELED 1000 UG/ML IN 1:1 METHANOL:WATER		
ATE CLP (oral)	226.655 mg/kg body weight	
ATE CLP (dermal)	300.000 mg/kg body weight	
ATE CLP (gases)	700.000 ppmV/4h	
ATE CLP (vapors)	3.000 mg/l/4h	
ATE CLP (dust, mist)	0.500 mg/l/4h	
WATER UNLABELED (7732-18-5)		
LD50 oral rat	> 90000 mg/kg	
URACIL UNLABELED (66-22-8)		
LD50, oral, rat	> mg/kg	
100% METHANOL UNLABELED (67-56-1)		
LD50 oral rat	1187 - 2769 mg/kg	

27/09/2018 EN (English US) 6/11

128.2 mg/l/4h; 87.6 mg/l - 6 h

100.000 mg/kg body weight

300.000 mg/kg body weight

17100 mg/kg

3.000 mg/l/4h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL UNLABELED (67-56-1)	
ATE CLP (dust, mist)	128.200 mg/l/4h
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: May cause damage to organs (central nervous system, eyes, heart, kidneys, liver) through prolonged or repeated exposure (in contact with skin, if inhaled, if swallowed).
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. **Toxicity**

100% METHANOL UNLABELED (67-56-1)	
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h

12.2. Persistence and degradability

100% METHANOL UNLABELED (67-56-1)	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d

12.3. **Bioaccumulative potential**

100% METHANOL UNLABELED (67-56-1)	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77

12.4. **Mobility in soil**

100% METHANOL UNLABELED (67-56-1)	
Ecology - soil	Not degradable in the soil.

12.5. Results of PBT and vPvB assessment

100% METHANOL UNLABELED (67-56-1)
PBT: not relevant – no registration required

Other adverse effects 12.6.

No additional information available

SECTION 13: Disposal considerations

40.4	Address to the attendant or attendant	
13.1.	Waste treatment methods	

13.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.

27/09/2018 7/11 EN (English US)

ULM-10256-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT) : 1230 DOT NA no. UN1230

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Methanol

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid

6.1 - Poison





DOT Symbols

: + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper

shipping name appropriate for international and domestic transportation

Packing group (DOT)

: II - Medium Danger

DOT Special Provisions (49 CFR 172.102)

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Emergency Response Guide (ERG) Number : 131

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 336 Classification code (ADR) : FT1

Hazard labels (ADR) : 3 - Flammable liquids

6.1 - Toxic substances



Orange plates

336 1230

Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) 11
Excepted quantities (ADR) : E2

27/09/2018 EN (English US) 8/11

ULM-10256-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

MFAG-No : 131

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

URACIL UNLABELED 1000 UG/ML IN 1:1 METHANOL:WATER		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of the United States SARA Section 313	
WATER UNLABELED (7732-18-5)		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.	
URACIL UNLABELED (66-22-8)		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302	
SARA Section 313 - Emission Reporting	Not subject to reporing requirements of the United States SARA Section 313	
100% METHANOL UNLABELED (67-56-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	

15.2. International regulations

CANADA

100% METHANOL UNLABELED (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

27/09/2018 EN (English US) 9/11

ULM-10256-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

URACIL UNLABELED 1000 UG/ML IN 1:1 METHANOL:WATER	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	Yes
U.S California - Proposition 65 - Reproductive Toxicity - Female	Yes
U.S California - Proposition 65 - Reproductive Toxicity - Male	Yes
State or local regulations	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances

WATER UNLABELED (7732-18-5)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

URACIL UNLABELED (66-22-8)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

100% METHANOL UNLABELED (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

WATER UNLABELED (7732-18-5)

State or local regulations

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

URACIL UNLABELED (66-22-8)

State or local regulations

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

100% METHANOL UNLABELED (67-56-1)

State or local regulations

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3

27/09/2018 EN (English US) 10/11

ULM-10256-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
R11	Highly flammable
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed
R36/38	Irritating to eyes and skin
R39	Danger of very serious irreversible effects
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
F	Highly flammable
Т	Toxic
Xi	Irritant

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause

temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended

solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even

under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard Physical : 0 Minimal Hazard

CIL Multi-Solvent Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

27/09/2018 EN (English US) 11/11