

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 11/12/2019 Date of issue: 09/03/2011 Supersedes: 24/10/2019 Version: 3.1 CLM-1337

SECTION 1: Identification of the subs	tance/mixture and of the company/undertaking	
1.1. Product identifier		
Product form	: Substance	
Substance name	: ANISOLE (RING-13C6, 99%)	
EC-No.	: 202-876-1 (Unlabeled)	
CAS-No.	: 152571-52-3	
Product code	: CLM-1337	
Formula	: *C6H5OCH3	
Synonyms	: Methoxybenzene / Methyl phenyl ether	
1.2. Relevant identified uses of the substa	ance or mixture and uses advised against	
1.2.1. Relevant identified uses		
Main use category	: Professional use	
Industrial/Professional use spec	: For professional use only	
1.2.2. Uses advised against		
1.2.2. Uses advised against No additional information available		
1.3. Details of the supplier of the safety da	ata sheet	
Cambridge Isotope Laboratories, Inc. 50 Frontage Road		
Andover, MA 01810		
USA		
USA: 1-800-322-1174 Int: 1-978-749-8000		
<u>cilsales@isotope.com</u> www.isotope.com		
Emergency telephone number		
Emergency numbers:		
Chemtrec: 1-800-424-9300 (24 hours)		
International: 1-703-741-5970 (24 hours)		
SECTION 2: Hazards identification		
2.1. Classification of the substance or mixture		
Classification according to Regulation (EC) No. 1272/2008 [CLP]		
Flam. Liq. 3 H226		
Full text of hazard classes and H-statements : see section 16		
Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]		
N; R51		
R10		
Full text of R-phrases: see section 16		

GHS-US classification


Flam. Liq. 3 H226 Aquatic Acute 2 H401 Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



SECTION 3: Composition/Information on ingredients

3.1. Substances			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
ANISOLE (RING-13C6, 99%)	(CAS-No.) 152571-52-3 (EC-No.) 202-876-1 (Unlabeled) (EC Index-No.)	100	N; R51 R10
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]

Full text of R- and H- phrases: see section 16

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
ANISOLE (RING-13C6, 99%) (Main constituent)	(CAS-No.) 152571-52-3	100	Flam. Liq. 3, H226 Aquatic Acute 2, H401

Full text of H-phrases: see section 16

3.2. **Mixtures**

Neterrieshi	
Not applicable	
SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). Evacuate danger area.
First-aid measures after inhalation	: When symptoms occur: go into open air and ventilate suspected area. If not breathing give artificial respiration. Get medical advice/attention.
First-aid measures after skin contact	: Wash with plenty of soap and water. and soap. Get immediate medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
4.2. Most important symptoms and effect	s, both acute and delayed
Symptoms/effects after inhalation	: May be harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
4.3. Indication of any immediate medical	attention and special treatment needed
No additional information available	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: For small fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.
5.2. Special hazards arising from the sub	stance or mixture
No additional information available	
5.3. Advice for firefighters	
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Wear a self contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear recommended personal protective equipment.
Other information	: Use water spray to cool unopened containers.
SECTION 6: Accidental release meas	
6.1. Personal precautions, protective equ	
	ipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Avoid breathing vapors, mist, gas. Avoid dust formation.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Prevent entry to sewers and public waters. Do no	t allow to enter drains or water courses. Avoid release to the environment.
6.3. Methods and material for containment	nt and cleaning up
For containment	: Contain spillage, then collect with non-combustible absorbent material. Disposal should be in accordance with applicable Federal, State and local regulations.
Methods for cleaning up	: This material and its container must be disposed of in a safe way, and as per local legislation.

For further information refer to section 13.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage	9
7.1. Precautions for safe handling	
Additional hazards when processed	: Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. Avoid all eye and skin contact and do not breathe vapor and mist.
Precautions for safe handling	: Provide adequate ventilation to minimize dust and/or vapor concentrations.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle in accordance with good industrial hygiene and safety practice.
7.2. Conditions for safe storage, incl	uding any incompatibilities
Technical measures	: Store in a well-ventilated place. Keep container tightly closed.
Storage conditions	: Store at room temperature away from light and moisture.
7.3. Specific end use(s)	
No additional information available	
SECTION 8: Exposure controls/po	proceed protection
8.1. Control parameters	
No additional information available	
8.2. Exposure controls	
Appropriate engineering controls	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Personal protective equipment	: Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.
Materials for protective clothing	: Wear suitable protective clothing and gloves.
Hand protection	: Wear suitable protective clothing and gloves.
Eye protection	: Wear eye protection. Chemical goggles or face shield with safety glasses.
Skin and body protection	: Wear suitable protective clothing, gloves and eye/face protection.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
Environmental exposure controls	: Avoid release to the environment.
SECTION 9: Physical and chemic	al properties

9.1. Information on basic physical and	I chemical properties
Physical state	: Liquid
Appearance	: Clear, Liquid
Molecular mass	: 114.09 g/mol (Labeled)
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -37 °C (-35 °F)
Freezing point	: No data available
Boiling point	: 154 °C (309 °F)
Flash point	: 51.7 °C (125.1 °F) - closed cup
Auto-ignition temperature	: 475 °C (887 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 13 hPa (10 mmHg) at 42.20 °C (107.96 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 3.73 - (Air = 1.0)
Solubility	: Insoluble.
Log Pow	: 2.1
Log Kow	: No data available
Viscosity, kinematic	: No data available
11/12/2019	EN (English US)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

26, 2012 / Rules and Regulations	
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available
9.2. Other information	
No additional information available	
SECTION 10: Stability and reactivity	
10.1. Reactivity	
No additional information available	
10.2. Chemical stability	
Stable if stored under recommended conditions.	
10.3. Possibility of hazardous reactions	
Vapors may form explosive mixture with air.	
10.4. Conditions to avoid	
Avoid Heat, Flames and Sparks.	
10.5. Incompatible materials	
Strong oxidizing agents.	
10.6. Hazardous decomposition products Carbon oxides (CO, CO2).	
SECTION 11: Toxicological informati	on
11.1. Information on toxicological effects	
Acute toxicity	: Not classified
ANISOLE (RING-13C6, 99%) (152571-52-3)	2700 maller
LD50 oral LC50 inhalation rat (mg/l)	3700 mg/kg > 5000 g/m ³
	·
Skin corrosion/irritation Serious eye damage/irritation	: Skin - Rabbit - Result: Mid skin irritation : Eyes - Rabbit - Result: No eye irritation
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	 Laboratory experiments have shown mutagenic effects - Genotoxicity in vivo - Human sister chromatid exchange
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	 This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: May be harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause skin irritation.

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general	: Very toxic to aquatic life.	
ANISOLE (RING-13C6, 99%) (152571-52-3)		
LC50 fish 1	> 1 mg/l Danio rerio (zebra fish) - 96 h	
EC50 Daphnia 1	11.05 mg/l 24 h	

No additional information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ANISOLE (RING-13C6, 99%) (152571-52-3)	Operational and the factor (Managerita first). Odd
BCF fish 1	Gambusia affnis (Mosquito fist) - 24 h
Bioconcentration factor (BCF REACH)	22
Log Pow	2.1
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessme	nt
No additional information available	
12.6. Other adverse effects	
No additional information available	
SECTION 13: Disposal consideration	IS
I3.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and loca environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a license professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.
SECTION 14. Transport information	
SECTION 14: Transport information	
n accordance with ADR / RID / IMDG / IATA / AI	ON
I4.1. UN number	
JN-No.(DOT)	: 2222
DOT NA no.	UN2222
4.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Anisole
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
	FLAMMABLE LIQUID
Dealing group (DOT)	
Packing group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	 III - Minor Danger B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composit (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tai 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only lique with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) HA.3. Additional information Emergency Response Guide (ERG) Number	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) HA.3. Additional information Emergency Response Guide (ERG) Number	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) H4.3. Additional information Emergency Response Guide (ERG) Number Dther information	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) H4.3. Additional information Emergency Response Guide (ERG) Number Dther information	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Compositi (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqu with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Ta 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard identification number (Kemler No.)	: 30
Classification code (ADR)	: F1
Hazard labels (ADR)	: 3 - Flammable liquids
	3
Orange plates	30 2222
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	51
EAC	: 3Y
Excepted quantities (ADR)	: E1
Transport by sea	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
MFAG-No	: 128
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
Civil Aeronautics Law	: Flammable liquids
14.4. Environmental hazards	
Other information	: No supplementary information available.
14.5. Special precautions for user	
14.6. Transport in bulk according to Anne	ex II of MARPOL 73/78 and the IBC Code
Net and 'sakle	

Not applicable

SECTION 15: Regulatory information	
15.1. US Federal regulations	
ANISOLE (RING-13C6, 99%) (152571-52-3)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.

15.2. International regulations

CANADA

ANISOLE (RING-13C6, 99%) (152571-52-3)		
Listed on the Canadian DSL (Domestic Substances List)		

15.2.1. National regulations

No additional information available

15.3. US State regulations

ANISOLE (RING-13C6, 99%)(152571-52-3)		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ANISOLE (RING-13C6, 99%)(152571-52-3)	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:


Flam. Liq. 3	Flammable liquids Category 3	
H226	Flammable liquid and vapor	
R10	Flammable	
R51	Toxic to aquatic organisms	
N	Dangerous for the environment	

NFPA	health	hazard

NFPA fire hazard

NFPA reactivity

- : 0 Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
- : 2 Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
- : 0 Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health	: 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability	: 2 Moderate Hazard
Physical	: 0 Minimal Hazard

CIL Substance SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product