

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 2/20/2015 Revision date: 9/21/2023 Supersedes: 8/21/2018 Version: 2.0

SECTION 1: Identification	
1.1. Identification	
Product form Product name	: Mixture : METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL
Product code	: CLM-8249-S
1.2. Recommended use and restrictions or	n use
No additional information available	
1.3. Supplier	
Cambridge Isotope Laboratories, Inc. 50 Frontage Rd 01810 ANDOVER, MA, 01810 USA T 1-800-322-1174 <u>cilsales@isotope.com</u> - <u>www.isotope.com</u>	
1.4. Emergency telephone number	
Emergency number	: 1-703-741-5970 Chemtrec 1-800-424-9300 24 hours

SECTION 2: Hazard(s) identification

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Acute toxicity (oral) Category 3	H301	Toxic if swallowed
Acute toxicity (dermal) Category 3	H311	Toxic in contact with skin
Acute toxicity (inhalation:vapor) Category 3	H331	Toxic if inhaled
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity (single exposure) Category 1	H370	Causes damage to organs (eyes, kidneys, liver, heart, central
		nervous system) (Dermal, Inhalation, oral)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)

Signal word (GHS US) Hazard statements (GHS US) : Danger

:

·

H225 - Highly flammable liquid and vapor H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Processitionery statements (CHS US)	H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal, Inhalation, oral)
Precautionary statements (GHS US) :	Innaiation, oral) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, open flames, sparks P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust, fume, mist, gas, spray, vapors. P261 - Avoid breathing dust, fume, gas, spray, vapors, mist. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective clothing, protective gloves. P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER. P303+P352 - If on skin: Wash with plenty of water. P303+P351 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P307+P311 - If exposed: Call a poison center/doctor. P311 - Call a doctor, a POISON CENTER. P312 - Call a doctor, a POISON CENTER P312 - Call a doctor, a POISON CENTER P313 - Specific treatment (see Hazardous component(s) for labeling on this label). P322 - Specific treatment (see Hazard pictograms (CLP) on this label) P330 - Rinse mouth. P337+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If skin irritation persists: Get medical advice/attention. P337+P313 - If skin iri
	 P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	GHS US classification
100% METHANOL UNLABELED	CAS-No.: 67-56-1	99.873737	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%)	CAS-No.: 99-76-3 (unlabeled)	0.1264	Aquatic Acute 3, H402 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures 4.1. Description of first aid measures If medical advice is needed, have product container or label at hand. Call a physician First-aid measures general immediately. Evacuate danger area. First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial · respiration. Call a doctor. First-aid measures after skin contact Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. First-aid measures after eye contact Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. First-aid measures after ingestion Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth. Call a physician immediately. 4.2. Most important symptoms and effects (acute and delayed) Potential Adverse human health effects and : This information is based on our current knowledge and is intended to describe the product for symptoms the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach. Symptoms/effects Causes damage to organs (Eyes, heart, liver, kidneys, central nervous system, Skin) (in contact with skin, if inhaled, if swallowed). Symptoms/effects after inhalation Toxic if inhaled. Symptoms/effects after skin contact Toxic in contact with skin. Causes skin irritation. Symptoms/effects after eye contact Causes serious eye irritation. Symptoms/effects after ingestion : Toxic if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	media
Suitable extinguishing media Unsuitable extinguishing media	Dry powder. Dry sand.Do not use a heavy water stream.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical		
	Highly flammable liquid and vapor. Toxic fumes may be released.	
5.3. Special protective equipment and precautions for fire-fighters		
	Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.	
Other information :	Use water spray to cool exposed surfaces.	

SECTION 6: Accidental release n	neasures
6.1. Personal precautions, protective	equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up	
For containment	: Dike and contain spill. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	

For further information refer to section 13.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed Precautions for safe handling	 Handle empty containers with care because residual vapors are flammable. No open flames. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. 	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.	
Storage conditions Incompatible materials	Store at room temperature away from light and moisture.Heat sources.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

METHYL PARABEN (METHYL 4-HYDROXYB	ENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	200 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)	
ACGIH OEL STEL [ppm]	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)	
Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.	
ACGIH chemical category	No component of this product present at levels greater than or equal to 0.1% is identifiable as a carcinogen or potential carcinogen by ACGIH.	
USA - ACGIH - Biological Exposure Indices		
BEI	15 mg/l Urine Basis: ACGIH - Biological Exposure Indices (BEI)	
Remark	End of shift (As soon as possible after exposure ceases)	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
OSHA PEL TWA [2]	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
OSHA PEL STEL [1]	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
OSHA PEL STEL [2]	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
OSHA PEL C [ppm]	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits	
NIOSH REL TWA [ppm]	200 ppm Basis: NIOSH Recommended Exposure Limits	
NIOSH REL STEL	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits	
NIOSH REL STEL [ppm]	250 ppm Basis: NIOSH Recommended Exposure Limits	
Remark (NIOSH)	Potential for dermal absorption.	
100% METHANOL UNLABELED (67-56-1)		
USA - ACGIH - Occupational Exposure Limits	-	
ACGIH OEL TWA [ppm]	200 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)	
ACGIH OEL STEL [ppm]	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)	
Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL UNLABELED (67-56-1)	
ACGIH chemical category	No component of this product present at levels greater than or equal to 0.1% is identifiable as a carcinogen or potential carcinogen by ACGIH.
USA - ACGIH - Biological Exposure Indices	
BEI	15 mg/l Urine Basis: ACGIH - Biological Exposure Indices (BEI)
Remark	End of shift (As soon as possible after exposure ceases)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA PEL TWA [2]	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA PEL STEL [1]	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA PEL STEL [2]	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA PEL C [ppm]	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107
Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
NIOSH REL TWA [ppm]	200 ppm Basis: NIOSH Recommended Exposure Limits
NIOSH REL STEL	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
NIOSH REL STEL [ppm]	250 ppm Basis: NIOSH Recommended Exposure Limits
Remark (NIOSH)	Potential for dermal absorption.
METHYL PARABEN (METHYL 4-HYDROXY	/ /BENZOATE) (RING-13C6, 99%) (99-76-3 (unlabeled))
USA - ACGIH - Occupational Exposure Limits	
ACGIH chemical category	No component of this product present at levels greater than or equal to 0.1% is identifiable as a carcinogen or potential carcinogen by ACGIH.
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Wash hands and other exposed areas with mild soap and water before eating, drinking or
Environmental exposure controls	smoking and when leaving work. : Avoid release to the environment.
8.3. Individual protection measures/Person	al protective equipment
Personal protective equipment: Gloves. Protective clothing. Protective goggles. Self	-contained breathing apparatus.
Materials for protective clothing:	
Maar auitable protective elething and gloves	

Wear suitable protective clothing and gloves

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection:

Wear suitable protective clothing and gloves

Eye protection:

Wear eye protection. Chemical goggles or face shield with safety glasses

Skin and body protection:

Wear suitable protective clothing, gloves and eye/face protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	. 1:
Physical state	: Liquid
Appearance	: Liquid.
Color	: Colorless
Odor	: Pungent
Odor threshold	: No data available
рН	: No data available
Melting point	: -98 °C (-144 °F)
Freezing point	: No data available
Boiling point	: 64.7 °C (148.5 °F)
Flash point	: 9.7 °C (49.5 °F) - closed cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)
Vapor pressure at 50°C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)
Relative vapor density at 20°C	: 1.11
Relative density	: No data available
Density	: 0.791 g/ml at 25 °C (77 °F)
Molecular mass	: 32.04 g/mol
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: -0.77
Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: 6 – 36 % (V)
Explosive properties	: Product is not explosive.
Oxidizing properties	: Non oxidizing material according to EC criteria.

9.2. Other information

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

SECTION 11: Toxicological informa	tion
11.1. Information on toxicological effect	ts
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	 Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.
METHYL PARABEN (METHYL 4-HYDR	OXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL
LD50 oral rat	1187 – 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 Inhalation - Rat	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (vapors)	3 mg/l/4h
Additional data	LDLO, oral, human: 143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
100% METHANOL UNLABELED (67-56-	1)
LD50 oral rat	1187 – 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 Inhalation - Rat	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight

ATE US (vapors)

3 mg/l/4h

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL UNLABELED (67-56-1				
ATE US (dust, mist)	128.2 mg/l/4h			
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.			
METHYL PARABEN (METHYL 4-HYDRO	XYBENZOATE) (RING-13C6, 99%) (99-76-3 (unlabeled))			
LD50 oral rat	2100 mg/kg (OCED Test Guideline 401)			
ATE US (oral)	2100 mg/kg body weight			
Skin corrosion/irritation	: Causes skin irritation.			
Serious eye damage/irritation	: Causes serious eye irritation.			
Respiratory or skin sensitization	: Not classified			
Germ cell mutagenicity	: Not classified			
Carcinogenicity	: Not classified			
100% METHANOL UNLABELED (67-56-1)			
National Toxicology Program (NTP) Status	No component of this product present at levels greater than or equal to 0.1% is identifiable as probable, possible, or confirmed human carcinogen by IARC.			
Reproductive toxicity	: Not classified			
STOT-single exposure	: Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal, Inhalation, oral).			
100% METHANOL UNLABELED (67-56-1)			
STOT-single exposure	Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal, Inhalation, oral).			
STOT-repeated exposure	: Not classified			
Aspiration hazard	: Not classified			
Viscosity, kinematic	: No data available			
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach.			
Symptoms/effects	: Causes damage to organs (Eyes, heart, liver, kidneys, central nervous system, Skin) (in contac with skin, if inhaled, if swallowed).			
Symptoms/effects after inhalation	: Toxic if inhaled.			
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.			
Symptoms/effects after eye contact	: Causes serious eye irritation.			
Symptoms/effects after ingestion	: Toxic if swallowed.			

SECTION 12: Ecological information

12.1. Toxicity			
Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.			
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL			
LC50 - Fish [1]	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h		
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna (Water flea) - 48 h		
EC50 - Crustacea [2]	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL				
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h			
100% METHANOL UNLABELED (67-56-1)				
LC50 - Fish [1]	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h			
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna (Water flea) - 48 h			
EC50 - Crustacea [2]	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h			
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h			
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) (99-76-3 (unlabeled))				
LC50 - Fish [1]	59.5 mg/l Oryzias latipes - 96 h			
EC50 - Crustacea [1]	41.1 mg/l Daphnia magna (water flea) - 48 h			

12.2. Persistence and degradability

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL				
Biochemical oxygen demand (BOD)	600 – 1200 mg/g			
Chemical oxygen demand (COD)	1420 mg/g			
ThOD	1500 mg/g			
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d			
100% METHANOL UNLABELED (67-56-1)				
Biochemical oxygen demand (BOD)	600 – 1200 mg/g			
Chemical oxygen demand (COD)	1420 mg/g			
ThOD	1500 mg/g			
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d			
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) (99-76-3 (unlabeled))				
Persistence and degradability	Biodegradability: Result: 89 % - Readily biodegradable. Aerobic - exposure time: 28 d.			

12.3. Bioaccumulative potential

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL				
BCF - Fish [1]	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C			
Bioconcentration factor (BCF REACH)	1			
Partition coefficient n-octanol/water (Log Pow)	efficient n-octanol/water (Log Pow) -0.77			
100% METHANOL UNLABELED (67-56-1)				
BCF - Fish [1]	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C			
Bioconcentration factor (BCF REACH)	1			
Partition coefficient n-octanol/water (Log Pow)	-0.77			
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) (99-76-3 (unlabeled))				
Partition coefficient n-octanol/water (Log Pow)	1.98			
Bioaccumulative potential	No data available.			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL					
Ecology - soil	Not degradable in the soil.				
100% METHANOL UNLABELED (67-56-1)					
Ecology - soil	Not degradable in the soil.				
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) (99-76-3 (unlabeled))					
Ecology - soil	No data available.				
12.5. Other adverse effects					
Other adverse effects :	Avoid release to the environment.				
Other information :	Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water. Hydrolyses readily.				

SECTION 13: Disposal considerations	3
13.1. Disposal methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.


SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number	
DOT NA No UN-No. (TDG) UN-No. (IMDG) UN-No. (IATA)	: UN1230 : UN1230 : 1230 : 1230
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	: Methanol : METHANOL : METHANOL : Methanol
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 3 (6.1) : 3, 6.1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L		
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 2 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of t section is exceeded.		
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"		
TDG			
UN-No. (TDG)	: UN1230		
TDG Special Provisions	: 43 - Despite section 2.1 of Part 2 (Classification), these dangerous goods are assigned to this classification based on human experience.		
Explosive Limit and Limited Quantity Index	: 1L		
Excepted quantities (TDG)	: E2		
Passenger Carrying Road Vehicle or Passenger	: 1L		
Carrying Railway Vehicle Index			
Emergency Response Guide (ERG) Number	: 131		
IMDG			
Special provision (IMDG)	: 279		
Limited quantities (IMDG)	: 1L		
Excepted quantities (IMDG)	: E2		
Packing instructions (IMDG)	: P001		
IBC packing instructions (IMDG)	: IBC02		
Tank instructions (IMDG)	: T7		
Tank special provisions (IMDG)	: TP2		
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS		
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS		
Stowage category (IMDG)	: В		
Stowage and handling (IMDG)	: SW2		
Flash point (IMDG)	: 12°C c.c.		
Properties and observations (IMDG)	: Colourless, volatile liquid. Flashpoint: 12°C c.c. Explosive limits: 6% to 36.5% Miscible with water. Toxic if swallowed; may cause blindness. Avoid skin contact.		
MFAG-No	: 131		
ΙΑΤΑ			
PCA Excepted quantities (IATA)	: E2		
PCA Limited quantities (IATA)	: Y341		
PCA limited quantity max net quantity (IATA)	: 1L		
PCA packing instructions (IATA)	: 352		
PCA max net quantity (IATA)	: 1L		
CAO packing instructions (IATA)	: 364		
CAO max net quantity (IATA)	: 60L		
Special provision (IATA)	: A113		
ERG code (IATA)	: 3L		

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL						
CERCLA RQ	5000 lb	5000 lb				
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.					
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard					
Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):						
Name	CAS-No.	Listing	Commercial	Flags		

Name	CAS-NO.	Listing	status	Flays
100% METHANOL UNLABELED	67-56-1	Present	Active	
METHYL PARABEN (METHYL 4- HYDROXYBENZOATE) (RING-13C6, 99%)	99-76-3 (unlabeled)	Not present	-	

100% METHANOL UNLABELED (67-56-1)	
CERCLA RQ	5000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) (99-76-3 (unlabeled))			
SARA Section 302 Threshold Planning Quantity (TPQ)			

15.2. International regulations

CANADA

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL

Listed on the Canadian DSL (Domestic Substances List)

100% METHANOL UNLABELED (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (RING-13C6, 99%) 1 MG/ML IN METHANOL		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	Yes	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	
State or local regulations	U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List	

100% METHANOL UNLABELED (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	Proposition 65 -	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		

Component	State or local regulations
	U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) List; U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

Other information

 : 09/21/2023
 : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of H-phrases	
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H370	Causes damage to organs
H402	Harmful to aquatic life

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases			
H412	Harmful to aquatic life with long lasting effects		
NFPA health haza	rd : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.		
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.		
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.		
Hazard Rating			
Health	: 2 Moderate Hazard - Temporary or minor injury may occur		
Flammability	 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC) 		
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.		

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.