

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 17/12/2015 Revision date: 24/03/2020 Supersedes: 17/12/2015 Version: 2.0

CLM-8588-T-S

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product form : Mixtures

Product name : DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE

Product code : CLM-8588-T-S

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 <u>cilsales@isotope.com</u> www.isotope.com

#### **Emergency telephone number**

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225 Skin Irrit. 2 H315 Repr. 2 H361 STOT SE 3 H336 STOT RE 2 H373 Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.1; R60 Repr.Cat.1; R61 F; R11 Xn; R65 Xi; R38

R67 R48 N; R51

Full text of R-phrases: see section 16

## **GHS-US** classification

Flam. Liq. 2 H225 Skin Irrit. 2 H315 Repr. 2 H361 STOT SE 3 H336 STOT RE 2 H373 Asp. Tox. 1 H304 Aquatic Acute 2 H401

Full text of H statements : see section 16

24/03/2020 EN (English US) 1/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Adverse physicochemical, human health and environmental effects

Bladder, Liver, Kidney, Brain.

#### 2.2. Label elements

Signal word (CLP)

#### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







: Danger

Hazardous ingredients : TOLUENE UNLABELED

Hazard statements (CLP) : H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

#### **GHS-US** labeling

Hazard pictograms (GHS-US)







· Danger

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H401 - Toxic to aquatic life

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P308+P313 - If exposed or concerned: Get medical advice/attention.

24/03/2020 EN (English US) 2/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P312 - Call a poison center or doctor if you feel unwell

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label)

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

PBT: not relevant - no registration required

### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 2.2 Mixtures

3.2. Mixtures			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
TOLUENE UNLABELED	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	99.988	F; R11 Xi; R38 Xn; R65 Repr.Cat.3; R62 Repr.Cat.3; R63 R67 N; R51/53 Xn; R48/20
DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%)	(CAS-No.) 135821-74-8 (Unlabeled)	0.012	Xn; R20 N; R51/53
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
TOLUENE UNLABELED	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	99.988	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%)	(CAS-No.) 135821-74-8 (Unlabeled)	0.012	Acute Tox. 3 (Inhalation), H331
Name	Product identifier	%	GHS-US classification
TOLUENE UNLABELED	(CAS-No.) 108-88-3	99.988	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%)	(CAS-No.) 135821-74-8 (Unlabeled)	0.012	Acute Tox. 3 (Inhalation), H331

Full text of R- and H- phrases: see section 16

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general

- : IF exposed or concerned: Get medical advice/attention.
- : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact

First-aid measures after inhalation

: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Wash with plenty of soap and water, Get immediate medical advice/attention. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).

24/03/2020 EN (English US) 3/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

Immediately call a poison center or doctor/physician.

#### Most important symptoms and effects, both acute and delayed

Symptoms/effects

: Suspected of damaging fertility. Suspected of damaging the unborn child. (in contact with skin, if inhaled, if swallowed). Causes damage to organs (brain, kidneys, liver, urinary bladder) (in contact with skin, if inhaled, if swallowed).

Symptoms/effects after inhalation

: Harmful if inhaled. May cause drowsiness or dizziness.

Symptoms/effects after skin contact

: Harmful in contact with skin. Causes skin irritation. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

Symptoms/effects after eye contact

: May cause eye irritation.

Symptoms/effects after ingestion

: May be fatal if swallowed and enters airways. Risk of lung edema.

#### Indication of any immediate medical attention and special treatment needed 4.3.

Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### **Extinguishing media**

: Dry powder. Dry sand. Dry chemical. Foam. Carbon dioxide. Suitable extinguishing media

Unsuitable extinguishing media

: Do not use a heavy water stream.

#### Special hazards arising from the substance or mixture

Fire hazard

: Highly flammable liquid and vapor.

Explosion hazard

: May form flammable/explosive vapor-air mixture.

Reactivity

: Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

#### **Advice for firefighters** 5.3.

Firefighting instructions

: Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.

: Use water spray to cool exposed surfaces.

## **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

General measures

Other information

: Flammable liquids. No open flames. No smoking. Eliminate every possible source of ignition.

Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Use personal protective equipment as required. Ensure adequate air ventilation. Avoid breathing vapors, mist, gas. Eliminate all ignition sources if safe to do so. Evacuate unnecessary personnel. Special attention should be given to low areas/pits where flammable vapors can accumulate.

#### For emergency responders 6.1.2.

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### **Environmental precautions**

Prevent liquid from entering sewers, watercourses, underground or low areas. Do not allow to enter drains or water courses. Do not discharge the product into the environment.

### Methods and material for containment and cleaning up

For containment

: Dike and contain spill.

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local

Other information : Dispose of materials or solid residues at an authorized site.

## Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

## Precautions for safe handling

Additional hazards when processed

: Avoid all eye and skin contact and do not breathe vapor and mist. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Handle empty containers with care because residual vapors are flammable.

24/03/2020 EN (English US) 4/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust, fume, gas, spray, vapors, mist. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. No open flames. No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust, fume, gas, mist, spray, vapors.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. Wash hands, forearms and face thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof Lighting equipment, ventilating equipment.

Storage conditions

: Store at room temperature away from light and moisture.

Incompatible materials : Heat sources.
Storage area : Under inert gas.

#### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE			
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)	
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Visual impairment. Female reproductive. Pregnancy loss. 2015 Adoption. Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen.; Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0300 mg/l Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0200 mg/l Biological specimen: In blood Remarks: Prior to last shift of workweek Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: o-Cresol Value: 0.3000 mg/g Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	375 mg/m³ USA. NIOSH Recommended Exposure Limits	
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm USA. NIOSH Recommended Exposure Limits	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	560 mg/m³ USA. NIOSH Recommended Exposure Limits	
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm USA. NIOSH Recommended Exposure Limits	
USA OSHA	OSHA PEL (TWA) (mg/m³)	375 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000	
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000	
USA OSHA	OSHA PEL (STEL) (mg/m³)	560 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000	
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000	
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-2	
USA OSHA	Remark (OSHA)	OSHA PEL (TWA) - 200 ppm - USA. Occupational Exposure Limits (OSHA) - Table Z-2. Remarks: Z37.12-1967	

24/03/2020 EN (English US) 5/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE UNLABELED (108-88-3)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Visual impairment. Female reproductive. Pregnancy loss. 2015 Adoption. Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen.; Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0300 mg/l Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0200 mg/l Biological specimen: In blood Remarks: Prior to last shift of workweek Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: o-Cresol Value: 0.3000 mg/g Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	375 mg/m³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m³)	560 mg/m³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm USA. NIOSH Recommended Exposure Limits
USA OSHA	OSHA PEL (TWA) (mg/m³)	375 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (mg/m³)	560 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-2
USA OSHA	Remark (OSHA)	OSHA PEL (TWA) - 200 ppm - USA. Occupational Exposure Limits (OSHA) - Table Z-2. Remarks: Z37.12-1967

#### 8.2. Exposure controls

Appropriate engineering controls

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing

Hand protection

Eye protection

Skin and body protection

Respiratory protection

: Wear suitable protective clothing and gloves.

: Wear suitable protective clothing and gloves.

recommended. Wear respiratory protection.

: Wear eye protection. Chemical goggles or face shield with safety glasses.

Wear suitable protective clothing, gloves and eye/face protection. Wear suitable protective clothing.

: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator. Where exposure through inhalation may occur from use, respiratory protection equipment is

Environmental exposure controls : Avoid release to the environment.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

24/03/2020 EN (English US) 6/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Physical state : Liquid

Appearance : Liquid

Molecular mass : 92.14 g/mol

Color : Colorless

Odor : Aromatic

Odor threshold : No data available

pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : -93 °C (-135 °F)
Freezing point : No data available

Boiling point :  $110 - 111 \,^{\circ}\text{C} \, (230 - 232 \,^{\circ}\text{F})$ Flash point :  $4 \,^{\circ}\text{C} \, (39.2 \,^{\circ}\text{F}) - \text{closed cup}$ 

Auto-ignition temperature : 535 °C (995 °F)

Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapor

Vapor pressure : 29.1 hPa (21.8 mmHg) at 20.0 °C (68.0 °F)

Relative vapor density at 20 °C : No data available Relative density : No data available

Specific gravity / density : 0.865 g/ml at 25 °C (77 °F)
Solubility : Water: 0.5 g/l at 15 °C (59 °F)

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : 1.2 - 7 % (V)

## 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

#### 10.2. Chemical stability

See storage and expiration date on CoA.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Heat. Open flame. Sparks. Direct sunlight. Extremely high or low temperatures.

## 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE	
LD50 oral rat	> 5580 mg/kg
LD50 dermal rabbit	12196 mg/kg
LC50 inhalation rat (mg/l)	12,500 - 28,800 mg/m3 - 4 h
ATE CLP (dermal)	12196.000 mg/kg body weight
ATE CLP (vapors)	12.500 mg/l/4h
ATE CLP (dust, mist)	12.500 mg/l/4h

24/03/2020 EN (English US) 7/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

-, - · · · · · · · · · · · · · · · · · ·	
DECHLORANE PLUS ANTI (BIS-CYCLOPEN	TENE-13C10, 99%) (135821-74-8 (Unlabeled))
ATE CLP (gases)	700.000 ppmV/4h
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	0.500 mg/l/4h
TOLUENE UNLABELED (108-88-3)	
LD50 oral rat	> 5580 mg/kg
LD50 dermal rabbit	12196 mg/kg
LC50 inhalation rat (mg/l)	12,500 - 28,800 mg/m3 - 4 h
ATE CLP (dermal)	12196.000 mg/kg body weight
ATE CLP (vapors)	12.500 mg/l/4h
ATE CLP (dust, mist)	12.500 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
	Skin - Rabbit - Causes skin irritation - 24 Hours
Serious eye damage/irritation	: Not classified
	Eyes - Rabbit - No eye irritation - (OECD 405 method)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Rat - Liver - DNA Damage
Carcinogenicity	: Not classified
Reproductive toxicity	: Damage to fetus possible. Suspected human reproductive toxicant - Reproductive toxicity - Rat - Inhalation. Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count) - Experiments have shown reproductive toxicity effects in male and female laboratory animals - Developmental Toxicity - Rat - Oral - Effects on Embryo or Fetus: Fetotoxicity (except death, e.g, stunted fetus).
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Symptoms/effects. IF INHALED: lungs. Pulmonary irritation. Pulmonary edema. Chest pain. central nervous system. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Stomach - Irregularities - Based on Human Evidence. Lung irritation, chest pain, pulmonay edema, Inhalation sudies have shown the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotom in animals.
IARC group	: 3
Symptoms/effects after inhalation	: Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Harmful in contact with skin. Causes skin irritation. Repeated exposure to this material can result in absorption through skin causing significant health hazard.
0	

## **SECTION 12: Ecological information**

Symptoms/effects after eye contact

Symptoms/effects after ingestion

12.1. Toxicity
----------------

Ecology - general : Toxic to bees.

Ecology - water : Toxic to aquatic life.

DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE		
EC50 Daphnia 1	8 mg/l Daphnia magna (Water flea) - 24h	
LC50 fish 2	7.63 mg/l Oncorhynchus mykiss (Rainbow trout) - 96 h	
EC50 Daphnia 2	6 mg/l Daphnia magna (Water flea) - Immobilization - 48 h	
ErC50 (algae)	245 mg/l Chlorella vulgaris (Fresh water algae) - 24 h	
ErC50 (other aquatic plants)	10 mg/l Pseudokirchneriella subcapitata (Green algae) - 24 h	
NOEC (chronic)	5.44 mg/l Pimephales promelas (fathead minnow) - 7 d	
TOLUENE UNLABELED (108-88-3)		
EC50 Daphnia 1	8 mg/l Daphnia magna (Water flea) - 24h	
LC50 fish 2	7.63 mg/l Oncorhynchus mykiss (Rainbow trout) - 96 h	
EC50 Daphnia 2	6 mg/l Daphnia magna (Water flea) - Immobilization - 48 h	
ErC50 (algae)	245 mg/l Chlorella vulgaris (Fresh water algae) - 24 h	

: May be fatal if swallowed and enters airways. Risk of lung edema.

: May cause eye irritation.

24/03/2020 EN (English US) 8/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE UNLABELED (108-88-3)	
ErC50 (other aquatic plants)	10 mg/l Pseudokirchneriella subcapitata (Green algae) - 24 h
NOEC (chronic)	5.44 mg/l Pimephales promelas (fathead minnow) - 7 d

## 12.2. Persistence and degradability

DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE	
Persistence and degradability	Readily biodegradable.
TOLUENE UNLABELED (108-88-3)	
TOLUENE UNLABELED (108-88-3)	

#### 12.3 Rioaccumulative notential

12.3. Bioaccumulative potential		
DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE		
BCF fish 1	0.05 mg/l Leuciscus idus (Golden orfe) - 3 d	
Bioconcentration factor (BCF REACH)	90	
TOLUENE UNLABELED (108-88-3)		
BCF fish 1	0.05 mg/l Leuciscus idus (Golden orfe) - 3 d	
Bioconcentration factor (BCF REACH)	90	

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

PBT: not relevant - no registration required

### **TOLUENE UNLABELED (108-88-3)**

PBT: not relevant - no registration required

### 12.6. Other adverse effects

Other adverse effects : Toxic to aquatic life with long lasting effects. Disposal must be done according to official regulations. Avoid release to the environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local

environmental control regulations.

Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed

professional waste disposal service to dispose of this material. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or

international regulation.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Dispose of as unused product. Hazardous waste due to toxicity.

## **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No.(DOT) : 1294 DOT NA no. UN1294

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Toluene

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

24/03/2020 EN (English US) 9/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

#### 14.3. Additional information

Other information : No supplementary information available.

#### **Overland transport**

Packing group (ADR) : II

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 33 Classification code (ADR) : F1

Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :

33 1294

Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) 11
EAC : 3YE
Excepted quantities (ADR) : E2

### Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

MFAG-No : 130

## Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

## 14.4. Environmental hazards

Other information : No supplementary information available.

#### 14.5. Special precautions for user

## 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

24/03/2020 EN (English US) 10/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 15: Regulatory information 15.1. US Federal regulations

DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313

	<u> </u>	
DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) (135821-74-8 (Unlabeled))		
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313	

TOLUENE UNLABELED (108-88-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ 1000 lb		
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	

## 15.2. International regulations

#### **CANADA**

## DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE

Listed on the Canadian DSL (Domestic Substances List)

## **TOLUENE UNLABELED (108-88-3)**

Listed on the Canadian DSL (Domestic Substances List)

### 15.2.1. National regulations

No additional information available

## 15.3. US State regulations

DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) 100 UG/ML IN TOLUENE()		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	Yes	
U.S California - Proposition 65 - Reproductive Toxicity - Female	Yes	
U.S California - Proposition 65 - Reproductive Toxicity - Male	Yes	
State or local regulations	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S Pennsylvania - RTK (Right to Know) List U.S Massachusetts - Right To Know List	

DE	DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) (135821-74-8 (Unlabeled))				
Pro	S California - oposition 65 - rcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	S	No	No	No	

24/03/2020 EN (English US) 11/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE UNLABELED (108-88-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

#### DECHLORANE PLUS ANTI (BIS-CYCLOPENTENE-13C10, 99%) (135821-74-8 (Unlabeled))

#### State or local regulations

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

#### **TOLUENE UNLABELED (108-88-3)**

#### State or local regulations

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

## **SECTION 16: Other information**

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

### Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
R11	Highly flammable
R20	Harmful by inhalation
R38	Irritating to skin
R48	Danger of serious damage to health by prolonged exposure
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R51	Toxic to aquatic organisms
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R60	May impair fertility
R61	May cause harm to the unborn child
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

24/03/2020 EN (English US) 12/13

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause


temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient

temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even

under fire conditions.



### **Hazard Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

#### **CIL Mixture SDS**

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

24/03/2020 EN (English US) 13/13