

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 27/09/2018 Date of issue: 11/09/2015 Supersedes: 11/09/2015 Version: 1.1 CLM-9652-S

SECTION 1: Identificatio	n of the substance/mixture and of the company/undertaking	
1.1. Product identifier		
Product form	: Mixtures	
Product name	: THIACLOPRID (PYRIDYLMETHYL-13C6, 99%) 100 UG/ML IN METHANOL	
Product code	: CLM-9652-S	
1.2. Relevant identified u	ses of the substance or mixture and uses advised against	
1.2.1. Relevant identified u	Ses	
Industrial/Professional use spec	: For professional use only	
1.2.2. Uses advised agains	t	
No additional information availab	ble	
1.3. Details of the supplie	er of the safety data sheet	
Cambridge Isotope Laboratories	, Inc.	
50 Frontage Road		
Andover, MA 01810 USA		
USA: 1-800-322-1174 Int: 1-9	78-749-8000	
cilsales@isotope.com www.is	otope.com	
Emergency telephon	e number	
Emergency numbers:		
Chemtrec: 1-800-424-9300 (24 International: 1-703-741-5970 (
SECTION 2: Hazards ide	ntification	
	substance or mixture	
Classification according to Re	gulation (EC) No. 1272/2008 [CLP]	
Flam. Liq. 2	H225	
Acute Tox. 3 (Oral)	H301	
Acute Tox. 3 (Dermal)	H311	
Acute Tox. 3 (Inhalation:vapour)	H331	
Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
STOT SE 1	H370	
Full text of hazard classes and H-statements : see section 16		
Classification according to Di	rective 67/548/EEC [DSD] or 1999/45/EC [DPD]	
F; R11 T; R39/23/24/25 Xi; R36/38		
	on 16	
Full text of R-phrases: see section		
GHS-US classification		
·	H225	
GHS-US classification Flam. Liq. 2 Acute Tox. 3 (Oral)	H301	
GHS-US classification Flam. Liq. 2	H301 H311	

Eye Irrit. 2A H319 STOT SE 1 H370 Full text of H statements : see section 16

METHANOL CLM-9652-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Eyes, Kidney, Liver, Heart, Central nervous system. Highly flammable liquid and vapour. Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (if inhaled, if swallowed, in contact with skin). Toxic in contact with skin. Toxic if inhaled. Toxic if swallowed. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements	
Labeling according to Regulation (EC) N	lo. 1272/2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS08 GHS06
Signal word (CLP)	: Danger
Hazard statements (CLP)	 H225 - Highly flammable liquid and vapour H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, heart, kidneys, liver, central nervous system) (in contact with skin, if inhaled, if swallowed)
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment P260 - Do not breathe dust, mist, vapors, fume, gas, spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.
GHS-US labeling	
Hazard pictograms (GHS-US)	GHS02 GHS08 GHS06
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	 H225 - Highly flammable liquid and vapour H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal, Inhalation, oral)
Precautionary statements (GHS-US)	 P210 - Keep away from heat, open flames, sparks No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical, lighting, ventilating equipment P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust, fume, mist, gas, spray, vapors. P261 - Avoid breathing dust, fume, gas, spray, vapors, mist. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective clothing, protective gloves. P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER P303+P351 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P330 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
	P307+P311 - If exposed: Call a poison center/doctor
27/09/2018	EN (English US) 2/13

METHANOL CLM-9652-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P311 Call a doctor, a POISON CENTER P312 - Call a doctor, a POISON CENTER if you feel unwell P321 - Specific treatment (see Hazardous component(s) for labeling on this label) P322 - Specific treatment (see Hazard pictograms (CLP) on this label) P330 - Rinse mouth. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P361+P364 - Take off immediately all contaminated clothing and wash it before reuse. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry
- extinguishing powder to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. **Other hazards**

PBT: not relevant - no registration required

SECTION 3: Composition/Information on ingredients

3.1. **Substances**

Not applicable

32 Mixturos

3.2. Mixtures			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.987359	F; R11 T; R39/23/24/25 Xi; R36/38
THIACLOPRID (PYRIDYLMETHYL-13C6, 99%)	(CAS-No.) 111988-49-9	0.0126	Xn; R20/22 R52/53
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.987359	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
THIACLOPRID (PYRIDYLMETHYL-13C6, 99%)	(CAS-No.) 111988-49-9	0.0126	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 3, H412
Name	Product identifier	%	GHS-US classification
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.987359	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370

Full text of R- and H- phrases: see section 16

oduct container or label at hand. Call a physician
oduct container or label at hand. Call a physician
o comfortable for breathing. If not breathing, give artificial
mmediately victim to hospital. Remove/Take off g. If skin irritation occurs: Get medical advice/attention.
m

METHANOL CLM-9652-S

Safety Data Sheet

o, 2012 / Rules and Regulations	
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth Call a physician immediately.
4.2. Most important symptoms and	effects, both acute and delayed
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.
4.3. Indication of any immediate me	edical attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measure	es
5.1. Extinguishing media	
Suitable extinguishing media	: Dry powder. Dry sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the	e substance or mixture
Fire hazard	: Highly flammable liquid and vapour.
Reactivity	: Vapors may form flammable mixture with air. Highly flammable liquid and vapour.
5.3. Advice for firefighters	
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.
Other information	: Use water spray to cool exposed surfaces.
SECTION 6: Accidental release n	neasures
6.1. Personal precautions, protectiv	ve equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contac with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions Prevent entry to sewers and public waters. I	refer to section 8: "Exposure controls/personal protection".
 6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta 	refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. ainment and cleaning up : Dike and contain spill.
 6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment Methods for cleaning up 	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. ainment and cleaning up : Dike and contain spill. : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local
 6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment Methods for cleaning up Other information 	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. imment and cleaning up : Dike and contain spill. : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment Wethods for cleaning up Other information 6.4. Reference to other sections	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. imment and cleaning up : Dike and contain spill. : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment Methods for cleaning up Other information 6.4. Reference to other sections For further information refer to section 13.	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. ainment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation. Dispose of materials or solid residues at an authorized site.
6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment Wethods for cleaning up Other information 6.4. Reference to other sections For further information refer to section 13. SECTION 7: Handling and storage	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. ainment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation. Dispose of materials or solid residues at an authorized site.
6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment Wethods for cleaning up Other information 6.4. Reference to other sections For further information refer to section 13. SECTION 7: Handling and storage 7.1. Precautions for safe handling	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. ainment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation. Dispose of materials or solid residues at an authorized site.
6.2. Environmental precautions Prevent entry to sewers and public waters. It 6.3. Methods and material for conta For containment Methods for cleaning up Other information 6.4. Reference to other sections For further information refer to section 13. SECTION 7: Handling and storag 7.1. Precautions for safe handling Additional hazards when processed	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. Simment and cleaning up : Dike and contain spill. : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation. : Dispose of materials or solid residues at an authorized site.
 6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment Wethods for cleaning up Other information 6.4. Reference to other sections For further information refer to section 13. SECTION 7: Handling and storag 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling 	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. imment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation. Dispose of materials or solid residues at an authorized site. Handle empty containers with care because residual vapors are flammable. No open flames. No smoking. Use only non-sparking tools.
6.2. Environmental precautions Prevent entry to sewers and public waters. It 6.3. Methods and material for conta For containment Methods for cleaning up Other information 6.4. Reference to other sections For further information refer to section 13. SECTION 7: Handling and storage 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe storage, income	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. imment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation. Dispose of materials or solid residues at an authorized site. Handle empty containers with care because residual vapors are flammable. No open flames. No smoking. Use only non-sparking tools.
 6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for conta For containment Methods for cleaning up Other information 6.4. Reference to other sections For further information refer to section 13. SECTION 7: Handling and storag 7.1. Precautions for safe handling Additional hazards when processed Precautions for safe handling 	refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. imment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation. Dispose of materials or solid residues at an authorized site. Handle empty containers with care because residual vapors are flammable. No open flames. No smoking. Use only non-sparking tools. Cluding any incompatibilities Proper grounding procedures to avoid static electricity should be followed. Ground/bond

METHANOL CLM-9652-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure c	ontrols/personal protection	
.1. Control parameters		
	[HYL-13C6, 99%) 100 UG/ML IN METHANC	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.
100% METHANOL UNLABEL	ED (67-56-1)	·
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.

METHANOL CLM-9652-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL U	NLABELED (67-56-1)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.

THIACLOPRID (FTRIDTLMETHTL-13CO, 99%) 100 UG/MIL IN METHANOL		
DNEL/DMEL (Workers)		
Acute - systemic effects, dermal	40 mg/kg bodyweight/day	
Acute - systemic effects, inhalation	260 mg/m ³	
Acute - local effects, dermal	260 mg/cm ²	
Long-term - systemic effects, dermal	40 mg/kg bodyweight/day	
Long-term - local effects, dermal	260 mg/cm ²	
Long-term - local effects, inhalation	260 mg/m ³	
DNEL/DMEL (General population)		
Acute - systemic effects, dermal	8 mg/kg body weight	
Acute - systemic effects, inhalation	50 mg/m³	
Acute - systemic effects, oral	8 mg/kg body weight	
Acute - local effects, inhalation	50 mg/m³	
Long-term - systemic effects,oral	8 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	50 mg/m³	
Long-term - systemic effects, dermal	8 mg/kg bodyweight/day	
Long-term - local effects, inhalation	50 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	154 mg/l	
PNEC aqua (marine water)	15.4 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	570.4 mg/kg dwt	
PNEC (Soil)		
PNEC soil	23.5 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/kg	
8.2. Exposure controls		

Appropriate engineering controls

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.

Wear eye protection. Chemical goggles or face shield with safety glasses.Wear suitable protective clothing, gloves and eye/face protection.

Personal protective equipment



: Wear suitable protective clothing and gloves.

Wear suitable protective clothing and gloves.

Materials for protective clothing Hand protection Eye protection Skin and body protection

EN (English US)

METHANOL CLM-9652-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties
The properties listed below are for the solvent, the main compo	onent of this mixture.
Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 32.04 g/mol
Color	: Colorless
Odor	: Pungent
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -98 °C (-144 °F)
Freezing point	: No data available
Boiling point	: 64.7 °C (148.5 °F)
Flash point	: 9.7 °C (49.5 °F) - closed cup
Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)
Vapor pressure at 50 °C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)
Relative vapor density at 20 °C	: 1.11
Relative density	: No data available
Specific gravity / density	: 0.791 g/ml at 25 °C (77 °F)
Solubility	: Water: Completely miscible
Log Pow	: -0.77
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidizing properties	: Non oxidizing material according to EC criteria.
Explosion limits	: 6 - 36 % (V)

9.2. Other information

No additional information available

NU auun	
SECTI	N 10: Stability and reactivity
10.1.	Reactivity
Vapors n	ay form flammable mixture with air. Highly flammable liquid and vapour.
10.2.	Chemical stability
See stor	ge and expiration date on CoA.
10.3.	Possibility of hazardous reactions
No dang	rous reactions known under normal conditions of use.
10.4.	Conditions to avoid
Avoid co	tact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
10.5.	Incompatible materials
Acid anh	drides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.
10.6.	Hazardous decomposition products
	ides (CO, CO2).
SECTI	N 11: Toxicological information
11.1.	Information on toxicological effects
Acute to:	city : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:vapour: Toxic if inhaled.

METHANOL CLM-9652-S

Safety Data Sheet

6) 100 UG/ML IN METHANOL
1187 - 2769 mg/kg
17100 mg/kg
128.2 mg/l/4h ; 87.6 mg/l - 6 h
100.000 mg/kg body weight
300.000 mg/kg body weight
3.000 mg/l/4h
128.200 mg/l/4h
143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
6) (111988-49-9)
444 mg/kg
> 2000 mg/kg
1223 mg/m ³ 4 h
444.000 mg/kg body weight
1.223 mg/l/4h
1.223 mg/l/4h
1187 - 2769 mg/kg
17100 mg/kg
128.2 mg/l/4h ; 87.6 mg/l - 6 h
100.000 mg/kg body weight 300.000 mg/kg body weight
3.000 mg/l/4h
128.200 mg/l/4h 143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause
gastrointestinal irritation, nausea, vomiting and diarrhea.
: Skin. Rabbit. Result: No skin irritation
: Eyes. Rabbit. Result: No eye irritation
: Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)
: AMES test : S. tymphimurium. Result: negative. fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - male and female Result: negative. Mouse - male and female. Result: Negative
: Not classified
: Damage to fetus not classifiable. Fertility classification not possible from current data.
: Causes damage to organs through prolonged or repeated exposure Causes damage to organs
: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
No data available
: No aspiration toxicity classification.
: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans.
stomach.
stomach.
stomach. : Toxic if inhaled.

SECTION 12: E	logical information
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

METHANOL CLM-9652-S

Safety Data Sheet

THIACLOPRID (PYRIDYLMETHYL-13C6, 99%) 100 UG/ML IN METHANOL		
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h	
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h	
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h	
THIACLOPRID (PYRIDYLMETHYL-13C6, 99%) (111988-49-9)		
LC50 fish 1	30.5 mg/l Oncorhynchus mykiss (rainbow trout) - 96 h	
EC50 Daphnia 1	> 85.1 mg/l 48 h	
ErC50 (algae)	60.6 mg/l Pseudokirchneriella subcapita (green algae) - 72 h	
100% METHANOL UNLABELED (67-56-1)		
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h	
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h	
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h	

12.2. Persistence and degradability		
THIACLOPRID (PYRIDYLMETHYL-13C6, 99%)	100 UG/ML IN METHANOL	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g	
Chemical oxygen demand (COD)	1420 mg/g	
ThOD	1500 mg/g	
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d	
100% METHANOL UNLABELED (67-56-1)		
Biochemical oxygen demand (BOD)	600 - 1200 mg/g	
Chemical oxygen demand (COD)	1420 mg/g	
ThOD	1500 mg/g	
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d	
12.3. Bioaccumulative potential		
THIACLOPRID (PYRIDYLMETHYL-13C6, 99%)	100 UG/ML IN METHANOL	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C	
Bioconcentration factor (BCF REACH)	1	
Log Pow	-0.77	
100% METHANOL UNLABELED (67-56-1)		
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C	
Bioconcentration factor (BCF REACH)	1	
Log Pow	-0.77	
12.4. Mobility in soil		
THIACLOPRID (PYRIDYLMETHYL-13C6, 99%)	100 UG/ML IN METHANOL	
Ecology - soil	Not degradable in the soil.	
100% METHANOL UNLABELED (67-56-1)		
Ecology - soil	Not degradable in the soil.	
12.5. Results of PBT and vPvB assessment		
THIACLOPRID (PYRIDYLMETHYL-13C6, 99%)	100 UG/ML IN METHANOL	
PBT: not relevant – no registration required		
100% METHANOL UNLABELED (67-56-1)		
PBT: not relevant – no registration required		
12.6. Other adverse effects		
	: Avoid release to the environment.	
Other information	: Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water.	
	Hydrolyses readily.	
SECTION 13: Disposal considerations		

13.1. Waste treatment methods		
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.	
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.	
27/09/2018	EN (English US) 9/13	

METHANOL CLM-9652-S

Safety Data Sheet

26, 2012 / Rules and Regulations	· Dispass of as unused product
Ecology - waste materials	: Dispose of as unused product.
SECTION 14: Transport information	
In accordance with ADR / RID / IMDG / IATA / A 14.1. UN number	ADN
UN-No.(DOT)	: 1230
DOT NA no.	UN1230
14.0 UN menor chiming neme	
14.2.UN proper shipping nameProper Shipping Name (DOT)	: Methanol
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
	6.1 - Poison
	3 6
DOT Symbols	: + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper shipping name appropriate for international and domestic transportation
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
14.3. Additional information	
Emergency Response Guide (ERG) Number	: 131
Other information	: No supplementary information available.
Overland transport	
Packing group (ADR)	: 11
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 336
Classification code (ADR)	: FT1
Hazard labels (ADR)	: 3 - Flammable liquids 6.1 - Toxic substances
Orange plates	336 1230
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
Excepted quantities (ADR)	: E2

METHANOL CLM-9652-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea	
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
MFAG-No	: 131
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
Civil Aeronautics Law	: Flammable liquids
14.4. Environmental hazards	
Other information	: No supplementary information available.

14.5. Special precautions for user
14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information		
15.1. US Federal regulations		
THIACLOPRID (PYRIDYLMETHYL-13C6, 99%) 100 UG/ML IN METHANOL		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	
100% METHANOL UNLABELED (67-56-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	

15.2. International regulations

CANADA

THIACLOPRID (PYRIDYLMETHYL-13C6, 99%) 100 UG/ML IN METHANOL		
Listed on the Canadian DSL (Domestic Substances List)		
100% METHANOL UNLABELED (67-56-1)		
Listed on the Canadian DSL (Domestic Substances List)		

15.2.1. National regulations

No additional information available

METHANOL CLM-9652-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulati	ons			
THIACLOPRID (PYRID	YLMETHYL-13C6, 99%) 100 U	IG/ML IN METHANOL		
U.S California - Proposition 65 - Carcinogens List		No		
U.S California - Proposition 65 - Developmental Toxicity		Yes		
U.S California - Proposition 65 - Reproductive Toxicity - Female		No		
U.S California - Proposition 65 - Reproductive Toxicity - Male		No		
State or local regulations		U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances		
100% METHANOL UNL	ABELED (67-56-1)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	
100% METHANOL UNL	ABELED (67-56-1)			
State or local regulation	ons			

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations

U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

SECTION 16: Other information

This product is not radioactive. The data given for this product are those of the corresponding : unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Other information

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H370	Causes damage to organs
H412	Harmful to aquatic life with long lasting effects
R11	Highly flammable
R20/22	Harmful by inhalation and if swallowed
R36/38	Irritating to eyes and skin
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed

METHANOL CLM-9652-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	R52/53 F T Xi	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment Highly flammable Toxic Irritant
	Xn	Harmful
NFP	A health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFP	A fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFP	A reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Haza	ard Rating	
Hea	lth	: 2 Moderate Hazard - Temporary or minor injury may occur
Flam	nmability	: 3 Serious Hazard
Phys	sical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product