



PROPANE (1,1,1,3,3,3-D6, 98%)

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 20/12/2010

Revision date: 20/10/2016

Supersedes: 12/11/2014

Version: 5.0

DLM-3476

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Substance name : PROPANE (1,1,1,3,3,3-D6, 98%)
EC index no : 601-003-00-5 (Unlabeled)
EC no : 200-827-9 (Unlabeled)
CAS No : 2875-96-9
Product code : DLM-3476
Formula : CD₃CH₂CD₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA
USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Gas 1 H220
Liquefied gas H280

Full text of H-statements: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F+; R12
Full text of R-phrases: see section 16

GHS-US classification

Flam. Gas 1 H220
Compressed gas H280

Adverse physicochemical, human health and environmental effects

No additional information available

PROPANE (1,1,1,3,3,3-D6, 98%) DLM-3476

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H220 - Extremely flammable gas
H280 - Contains gas under pressure; may explode if heated

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
P381 - Eliminate all ignition sources if safe to do so
P403 - Store in a well-ventilated place
P410+P403 - Protect from sunlight. Store in a well-ventilated place

GHS-US labelling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H220 - Extremely flammable gas
H280 - Contains gas under pressure; may explode if heated

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
P381 - Eliminate all ignition sources if safe to do so
P403 - Store in a well-ventilated place
P410+P403 - Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name	Product identifier	%	Classification according to Directive 67/548/EEC
PROPANE (1,1,1,3,3,3-D6, 98%) (Main constituent)	(CAS No) 2875-96-9 (EC no) 200-827-9 (Unlabeled) (EC index no) 601-003-00-5 (Unlabeled)	100	F+; R12
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
PROPANE (1,1,1,3,3,3-D6, 98%) (Main constituent)	(CAS No) 2875-96-9 (EC no) 200-827-9 (Unlabeled) (EC index no) 601-003-00-5 (Unlabeled)	100	Flam. Gas 1, H220 Liquefied gas, H280

Full text of R- and H-statements: see section 16

Name	Product identifier	%	GHS-US classification
PROPANE (1,1,1,3,3,3-D6, 98%) (Main constituent)	(CAS No) 2875-96-9	100	Flam. Gas 1, H220 Compressed gas, H280

Full text of H-statements: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

PROPANE (1,1,1,3,3,3-D6, 98%) DLM-3476

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: If breathed in, move person to fresh air. If not breathing, give artificial respiration. Consult a physician.
First-aid measures after skin contact	: Wash off with soap and plenty of water. Consult a physician.
First-aid measures after eye contact	: Flush eyes with water as a precaution.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May be harmful if inhaled. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May be harmful if absorbed through skin. May cause skin irritation.
Symptoms/injuries after eye contact	: Contact may cause eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.
------------------------------	---

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Use water spray to cool unopened containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
----------------------	---

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For containment	: Contain spillage, then collect with non-combustible absorbent material. Disposal should be in accordance with applicable Federal, State and local regulations.
-----------------	--

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent build up of electrostatic charge.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep container tightly closed in a dry and well-ventilated place.
Storage conditions	: Store at room temperature away from light and moisture.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PROPANE (1,1,1,3,3,3-D6, 98%) (2875-96-9)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	1000.0000000000 ppm Central Nervous System impairment. Cardiac sensitization.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1800 mg/m³ USA. NIOSH Recommended Exposure Limits See Appendix F: Minimal Oxygen Content Asphyxia 2015 Adoption

PROPANE (1,1,1,3,3,3-D6, 98%) DLM-3476

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PROPANE (1,1,1,3,3,3-D6, 98%) (2875-96-9)		
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm USA. NIOSH Recommended Exposure Limits See Appendix F: Minimal Oxygen Content Asphyxia 2015 Adoption
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1800.0000000000 mg/m ³ USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	1,800 mg/m ³ California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2. Exposure controls

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : When appropriate, use NIOSH/CEN approved respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquefied gas.
Molecular mass	: 50.13 g/mol (Labeled)
Colour	: Colourless.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -188 °C (-306 °F) - lit
Freezing point	: No data available
Boiling point	: -42.1 °C (-43.8 °F) - lit
Flash point	: -104 °C (-155 °F) - closed cup
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 13096 hPa (9,823mmHg) @ 37.7°C(99.9°F)
Relative vapour density at 20 °C	: 1.52 - (Air = 1.0)
Relative density	: No data available
Density	: 0.564 g/ml at 20 °C (68 °F)
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 2.1 - 9.5 % (V)

9.2. Other information

No additional information available

PROPANE (1,1,1,3,3,3-D6, 98%) DLM-3476

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Avoid Heat, Flames and Sparks. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified No data available
Serious eye damage/irritation	: Not classified No data available
Respiratory or skin sensitisation	: Not available No data available
Germ cell mutagenicity	: Not available
Carcinogenicity	: Not classified
Reproductive toxicity	: Not available
Specific target organ toxicity (single exposure)	: Not classified No data available
Specific target organ toxicity (repeated exposure)	: Not classified No data available
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Dizziness. Drowsiness. Unconsciousness. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Symptoms/injuries after inhalation	: May be harmful if inhaled. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May be harmful if absorbed through skin. May cause skin irritation.
Symptoms/injuries after eye contact	: Contact may cause eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

PROPANE (1,1,1,3,3,3-D6, 98%) (2875-96-9)

Persistence and degradability	Not available.
-------------------------------	----------------

12.3. Bioaccumulative potential

PROPANE (1,1,1,3,3,3-D6, 98%) (2875-96-9)

Bioaccumulative potential	Not available.
---------------------------	----------------

12.4. Mobility in soil

PROPANE (1,1,1,3,3,3-D6, 98%) (2875-96-9)

Ecology - soil	Not available.
----------------	----------------

12.5. Results of PBT and vPvB assessment

No additional information available

PROPANE (1,1,1,3,3,3-D6, 98%) DLM-3476

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.6. Other adverse effects

Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.

Waste disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT) : 1978

DOT NA no. UN1978

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Propane
see also Petroleum gases, liquefied

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : 19 - For domestic transportation only, the identification number UN1075 may be used in place of the identification number specified in column (4) of the 172.101 table. The identification number used must be consistent on package markings, shipping papers and emergency response information.
T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 304

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

Marine pollutant : No

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : IATA/DOT: Not permitted on passenger aircraft.

Overland transport

Class (ADR) : 2 - Gases

Hazard identification number (Kemler No.) : 23

Classification code (ADR) : 2F

Danger labels (ADR) : 2.1 - Flammable gases



Orange plates : An orange rectangular plate with a black border. The top half contains the number '23' and the bottom half contains the number '1978' in black.

Tunnel restriction code : B/D

Limited quantities (ADR) : 0

EAC code : 2YE

Excepted quantities (ADR) : E0

PROPANE (1,1,1,3,3,3-D6, 98%) DLM-3476

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

MFAG-No : 115

Air transport

DOT Quantity Limitations Passenger aircraft/rail : Forbidden
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

Civil Aeronautics Law : Gases under pressure/Gases flammable under pressure(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

Special transport precautions : IATA/DOT: Not permitted on passenger aircraft.

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

PROPANE (1,1,1,3,3,3-D6, 98%) (2875-96-9)

SARA Section 311/312 Hazard Classes	Fire hazard Sudden release of pressure hazard
-------------------------------------	--

15.2. International regulations

CANADA

PROPANE (1,1,1,3,3,3-D6, 98%) (2875-96-9)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

PROPANE (1,1,1,3,3,3-D6, 98%)(2875-96-9)

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.
----------------------------	---

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-statements:


Flam. Gas 1	Flammable gases, Category 1
Liquefied gas	Gases under pressure : Liquefied gas
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
R12	Extremely flammable
F+	Extremely flammable

PROPANE (1,1,1,3,3,3-D6, 98%) DLM-3476

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.
NFPA fire hazard	: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health	: 0 Minimal Hazard - No significant risk to health
Flammability	: 4 Severe Hazard
Physical	: 3 Serious Hazard

CIL Multi-Solvent Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product