

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 11/30/2010 Revision date: 6/21/2023 Supersedes: 10/23/2018 Version: 3.4

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : TOLUENE-D8 (D, 99.5%)
Chemical name : TOLUENE-D8 (D, 99.5%)

 CAS-No.
 : 108-88-3

 Product code
 : DLM-5

 Formula
 : C7H8

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Cambridge Isotope Laboratories, Inc.

50 Frontage Rd

01810

ANDOVER, MA, 01810

USA

T 1-800-322-1174

cilsales@isotope.com - www.isotope.com

1.4. Emergency telephone number

Emergency number : 1-703-741-5970

Chemtrec 1-800-424-9300 24 hours

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
------------------------------	------	-----------------------------------

Skin corrosion/irritation Category 2 H315 Causes skin irritation
Reproductive toxicity Category 2 H361 (Dermal, Inhalation, oral)

Specific target organ toxicity – Single exposure, Category 3, Narcosis H336 May cause drowsiness or dizziness

Specific target organ toxicity (repeated exposure) Category 2 H373 May cause damage to organs (kidneys, liver, urinary bladder,

brain) through prolonged or repeated exposure (Dermal,

Inhalation, oral)

Aspiration hazard Category 1 H304 May be fatal if swallowed and enters airways

Hazardous to the aquatic environment – Acute Hazard Category 2 H401 Toxic to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

Safety Data Sheet

Precautionary statements (GHS US)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361 - (Dermal, Inhalation, oral)

H373 - May cause damage to organs (kidneys, liver, urinary bladder, brain) through prolonged or repeated exposure (Dermal, Inhalation, oral)

H401 - Toxic to aquatic life

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking, heat, hot surfaces, open flames, sparks

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe fume, mist, spray, vapors.

P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.

P264 - Wash Both hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear eye protection, face protection, protective clothing, protective gloves.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a poison center or doctor if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see Hazard pictograms (CLP) on this label).

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to Comply with applicable regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

6/21/2023 (Revision date) US - en 2/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Product identifier	%	GHS US classification
TOLUENE-D8 (D, 99.5%) (Main constituent)	CAS-No.: 108-88-3	100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of hazard classes and H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of

dangerous area.
First-aid measures after inhalation : If breathed in, me

nalation : If breathed in, move person to fresh air. If not breathing, give artificial respiration. Consult a

physician.

First-aid measures after skin contact : Wash off with soap and plenty of water. Consult a physician.

First-aid measures after eye contact : Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Lung irritation, chest pain, pulmonay edema, Inhalation sudies have shown the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotom in animals. To the best of

our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Symptoms/effects after inhalation : May be har

: May be harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.

Symptoms/effects after skin contact

: May be harmful if absorbed through the skin. Causes skin irritation.

Symptoms/effects after eye contact

: Contact may cause eye irritation.

Symptoms/effects after ingestion

: May be fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

5.2. Specific hazards arising from the chemical

No additional information available

6/21/2023 (Revision date) US - en 3/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: Use water spray to cool unopened containers.

Protection during firefighting

: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Flammable in presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures

: Use personal protective equipment, and ensure adequate ventilation. Avoid breathing vapors, mist, gas. Remove ignition sources, and move personnel to safe area. Vapors accumulate especially in low areas to form explosive concentrations.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

For containment

: Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of

ignition - No smoking. Take measures to prevent build up of electrostatic charge.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Keep container tightly closed in a cool, dry and well-ventilated place.

Storage conditions

Store at room temperature away from light and moisture.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

TOLUENE-D8 (D, 99.5%) (108-88-3)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Toluene	
ACGIH OEL TWA [ppm]	20 ppm Visual impairment, Female reproductive, Pregnancy loss	

6/21/2023 (Revision date) US - en 4/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE-D8 (D, 99.5%) (108-88-3)	
Remark (ACGIH)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2022
USA - ACGIH - Biological Exposure Indices	
Local name	TOLUENE
BEI	0.3 mg/g Kreatinin Parameter: o-Cresol (with hydrolysis) - Medium: urine - Sampling time: End of shift - Notations: B 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [2]	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
OSHA PEL STEL [2]	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.

Hand protection:

Wear suitable protective clothing and gloves

Eye protection:

Wear safety glasses with side shields (or goggles) and a face shield.

Skin and body protection:

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection:

Wear appropriate NIOSH/MSHA approved respirator.

Personal protective equipment symbol(s):









SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : Colorless
Odor : No data available
Odor threshold : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH : No data available
Melting point : -93 °C (-135 °F)
Freezing point : No data available

Boiling point : 110 – 111 °C (230 - 232 °F) Flash point : 4 °C (39.2 °F) - closed cup

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available

Vapor pressure : 29.1 hPa (21.8 mmHg) at 20.0 °C (68.0 °F)

Relative vapor density at 20°C : No data available Relative density : No data available

Density : 0.865 g/ml at 25 °C (77 °F) Molecular mass : 100.19 g/mol (Labeled) Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : 535 °C (995 °F) Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** 1.2 - 7% (V)Explosive properties : No data available Oxidizing properties No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Avoid Heat, Flames and Sparks. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Formed under fire conditions. - Carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE-D8 (D, 99.5%) (108-88-3)	
LD50 oral rat	> 5580 mg/kg
LD50 dermal rabbit	12196 mg/kg
LC50 Inhalation - Rat	12500 – 28800 mg/m³ 4 h
ATE US (dermal)	12196 mg/kg body weight
ATE US (vapors)	12.5 mg/l/4h
ATE US (dust, mist)	12.5 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
TOLUENE-D8 (D, 99.5%) (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: (Dermal, Inhalation, oral).
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (kidneys, liver, urinary bladder, brain) through prolonged or repeated exposure (Dermal, Inhalation, oral).
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: No data available
Potential Adverse human health effects and	: Lung irritation, chest pain, pulmonay edema, Inhalation sudies have shown the development of
symptoms	inflammatory and ulcerous lesions of the penis, prepuce, and scrotom in animals. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Symptoms/effects after inhalation	: May be harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	: May be harmful if absorbed through the skin. Causes skin irritation.
Symptoms/effects after eye contact	: Contact may cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.

SECTION 12: Ecological information

12.1. Toxicity

TOLUENE-D8 (D, 99.5%) (108-88-3)		
LC50 - Fish [1]	74 – 340 mg/l Lepomis macrochirus (Bluegill) - 96h	
LC50 - Other aquatic organisms [1]	10 mg/l Pseudokirchneriella subcapitata (Green algae) - 24 h	
EC50 - Crustacea [1]	3.78 mg/l	
LC50 - Fish [2]	7.63 mg/l Oncorhynchus mykiss (Rainbow trout) - 96 h	
EC50 - Crustacea [2]	6 mg/l Daphnia magna (Water flea) - Immobilization - 48 h	
ErC50 algae	245 mg/l Chlorella vulgaris (Fresh water algae) - 24 h	
LOEC (chronic)	8.04 mg/l Pimephales promelas (Fathead minnow) - 7 d	
NOEC (chronic)	5.44 mg/l Pimephales promelas (fathead minnow) - 7 d	
NOEC chronic crustacea	0.74 mg/l	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)

: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.

Product/Packaging disposal recommendations

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed

professional waste disposal service to dispose of this material.

Ecology - waste materials

: Dispose of as unused product.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No : UN1294 UN-No. (TDG) : UN1294 UN-No. (IMDG) : 1294 UN-No. (IATA) : 1294

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Toluene
Proper Shipping Name (TDG) : TOLUENE
Proper Shipping Name (IMDG) : TOLUENE
Proper Shipping Name (IATA) : Toluene

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3 Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : 3 Hazard labels (TDG) : 3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1294

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

TDG

UN-No. (TDG) : UN1294

6/21/2023 (Revision date) US - en 9/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger : 5 L
Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 130

IMDG

Limited quantities (IMDG) : 1 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

IBC packing instructions (IMDG) : IBC02

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

Stowage category (IMDG) : B
Flash point (IMDG) : 7°C c.c.

Properties and observations (IMDG) : Colourless liquid with a benzene-like odour. Flashpoint: 7°C c.c. Explosive limits: 1.27% to

7% Immiscible with water.

MFAG-No : 130

IATA

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) 353 PCA max net quantity (IATA) 5L CAO packing instructions (IATA) 364 CAO max net quantity (IATA) 60L ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

TOLUENE-D8 (D, 99.5%) (108-88-3)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
TOLUENE-D8 (D, 99.5%)	108-88-3	Present	Active	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

TOLUENE-D8 (D, 99.5%) (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

TOLUENE-D8 (D, 99.5%) (108-88-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on TECI (Thailand Existing Chemicals Inventory)

15.3. US State regulations

TOLUENE-D8 (D, 99.5%) (108-88-3)	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	Yes
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
No significant risk level (NSRL)	7000 μg/day μg/day
Maximum allowable dose level (MADL)	7000 μg/day
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/21/2023

Other information : This product is not radioactive. The data given for this product are those of the corresponding

unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the

corresponding unlabeled compound.

Full text of I	Full text of H-phrases	
H225	Highly flammable liquid and vapor	
H304	May be fatal if swallowed and enters airways	
H315	Causes skin irritation	
H336	May cause drowsiness or dizziness	
H361	Suspected of damaging fertility or the unborn child	
H373	May cause damage to organs through prolonged or repeated exposure	
H401	Toxic to aquatic life	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary


incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can

be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions.

Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well

as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.