

TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 12/09/2017 Revision date: 23/07/2018 Supersedes: 04/05/2018 Version: 1.2 DLM-9567-C

SECTION 1: Identification of the substance/mixture and of the company/undertaking **Product identifier** 1.1. Product form : Mixtures Product name TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL : DLM-9567-C Product code 1.2. Relevant identified uses of the substance or mixture and uses advised against **Relevant identified uses** 1.2.1. Main use category : Professional use Industrial/Professional use spec : For professional use only 1.2.2. Uses advised against No additional information available Details of the supplier of the safety data sheet 1.3. Cambridge Isotope Laboratories, Inc. 50 Frontage Road Andover, MA 01810 USA USA: 1-800-322-1174 Int: 1-978-749-8000 www.isotope.com cilsales@isotope.com **Emergency telephone number** Emergency numbers: Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours) **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No. 1272/2008 [CLP] H225 Flam. Liq. 2 Acute Tox. 3 (Oral) H301 Acute Tox. 3 (Dermal) H311 Acute Tox. 3 (Inhalation) H331 Skin Irrit, 2 H315 Eye Irrit. 2 H319 STOT SE 1 H370 Full text of hazard classes and H-statements : see section 16 Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD] F; R11 T: R39/23/24/25 Xi; R36/38 Full text of R-phrases: see section 16

GHS-US classification

 Flam. Liq. 2
 H225

 Acute Tox. 3 (Oral)
 H301

 Acute Tox. 3 (Dermal)
 H311

 Acute Tox. 3 (Inhalation)
 H331

 Skin Irrit. 2
 H315

 Eye Irrit. 2
 H319

 STOT SE 1
 H370

Full text of H statements : see section 16

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Eyes, Kidney, Liver, Heart, Central nervous system. Highly flammable liquid and vapour. Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (if inhaled, if swallowed, in contact with skin). Toxic in contact with skin. Toxic if inhaled. Toxic if swallowed. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements	
Labeling according to Regulation (EC) N	lo. 1272/2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS08 GHS06
Signal word (CLP)	: Danger
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation
	H370 - Causes damage to organs (eyes, heart, kidneys, liver, central nervous system) (in contact with skin, if inhaled, if swallowed)
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment P260 - Do not breathe dust, mist, vapors, fume, gas, spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.
GHS-US labeling	
Hazard pictograms (GHS-US)	HS02 GHS08 GHS06
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	 H225 - Highly flammable liquid and vapour H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (central nervous system, eyes, heart, kidneys, liver) (Dermal, Inhalation, oral)
Precautionary statements (GHS-US)	 P210 - Keep away from heat, hot surfaces, open flames, sparks No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical, lighting, ventilating equipment P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust, fume, gas, mist, spray, vapors. P261 - Avoid breathing dust, fume, gas, mist, spray, vapors. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective clothing, protective gloves. P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed: Call a poison center/doctor
23/07/2018	EN (English US) 2/13

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P311 Call a doctor, a POISON CENTER
- P312 Call a doctor, a POISON CENTER if you feel unwell
- P321 Specific treatment (see Hazardous component(s) for labeling on this label)
- P322 Specific treatment (see Hazard pictograms (CLP) on this label)
- P330 Rinse mouth.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P361+P364 Take off immediately all contaminated clothing and wash it before reuse.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry
- extinguishing powder to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. **Other hazards**

PBT: not relevant - no registration required

SECTION 3: Composition/Information on ingredients

3.1. **Substances**

Not applicable

2.2 Mixt

3.2. Mixtures			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.987359	F; R11 T; R39/23/24/25 Xi; R36/38
TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11- D6, 98%)	(CAS-No.) 1180-95-6 (Unlabeled) (EC-No.) (EC Index-No.)	0.013	Xi; R36/37/38
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.987359	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11- D6, 98%)	(CAS-No.) 1180-95-6 (Unlabeled) (EC-No.) (EC Index-No.)	0.013	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Name	Product identifier	%	GHS-US classification
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.987359	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370
TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11- D6, 98%)	(CAS-No.) 1180-95-6 (Unlabeled)	0.013	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

First-aid measures after eye contact	 Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth Call a physician immediately.
4.2. Most important symptom	and effects, both acute and delayed
Symptoms/effects	: Causes damage to organs (Eyes, heart, liver, kidneys, central nervous system) (in contact with skin, if inhaled, if swallowed).
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.
4.3. Indication of any immedia	te medical attention and special treatment needed
Treat symptomatically.	

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Dry powder. Dry sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the su	ibstance or mixture
Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Vapors may form flammable mixture with air. Highly flammable liquid and vapour.
5.3. Advice for firefighters	
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.
Other information	: Use water spray to cool exposed surfaces.
SECTION 6: Accidental release mea	sures
	uipment and emergency procedures
General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
6.1.1. For non-emergency personnel	
Emergency procedures	: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Do not allow to enter drains or water courses. A	void release to the environment. Prevent entry to sewers and public waters.
6.3. Methods and material for containm	ent and cleaning up
For containment	: Dike and contain spill.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13.	
SECTION 7: Handling and storage	

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust, fume, gas, spray, vapors, mist. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includ	ing any incompatibilities
Technical measures	 Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Lighting equipment, ventilating equipment.
Storage conditions	: Store in freezer (-20 C). Protect from light.
Incompatible materials	: Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters		
TAURODEOXYCHOLIC ACID	, SODIUM SALT (2,2,4,4,11,11-D6, 98%) 100	UG/ML IN METHANOL
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.
100% METHANOL UNLABEL	ED (67-56-1)	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL UNLABEL	ED (67-56-1)	
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.

- 8.2. Exposure controls
- Appropriate engineering controls

Personal protective equipment

 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
 Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.

- Materials for protective clothing
 : Wear suitable protective clothing and gloves.

 Hand protection
 : Wear suitable protective clothing and gloves.

 Eye protection
 : Wear eye protection. Chemical goggles or face shield with safety glasses.

 Skin and body protection
 : Wear suitable protective clothing, gloves and eye/face protection. Wear suitable protective clothing.

 Respiratory protection
 : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

 Environmental exposure controls
 : Avoid release to the environment.

3EC	ION 9: Physical and chemical properties
9.1	Information on basic physical and chemical properties

The properties listed below are for the so	lvent, the main component of this mixture.
Physical state	: Liquid
Appearance	: Liquid

Molecular mass

: 32.04 g/mol

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

20, 2012 / 11000 and 110 galations	
Color	: Colorless
Odor	: Pungent
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -98 °C (-144 °F)
Freezing point	: No data available
Boiling point	: 64.7 °C (148.5 °F)
Flash point	: 9.7 °C (49.5 °F) - closed cup
Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapor pressure	: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)
Vapor pressure at 50 °C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)
Relative vapor density at 20 °C	: 1.11
Relative density	: No data available
Specific gravity / density	: 0.791 g/ml at 25 °C (77 °F)
Solubility	: Water: Completely miscible
Log Pow	: -0.77
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidizing properties	: Non oxidizing material according to EC criteria.
Explosion limits	: 6 - 36 % (V)
9.2. Other information	

No additional information available

SECTION 10: Stability and reactivity		
10.1. Reactivity		
Vapors may form flammable mixture with air. Highly flammable liquid and vapour.		
10.2. Chemical stability		
See storage and expiration date on CoA.		
10.3. Possibility of hazardous reactions		
No dangerous reactions known under normal conditions of use.		
10.4. Conditions to avoid		
Avoid contact with hot surfaces. Heat. Open flame. Direct sunlight. Sparks.		
10.5. Incompatible materials		
Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.		
10.6. Hazardous decomposition products		
Carbon oxides (CO, CO2).		
SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: Toxic if inhaled.		
TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL		
LD50 oral rat 1187 - 2769 mg/kg		

2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL
1187 - 2769 mg/kg
17100 mg/kg
128.2 mg/l/4h ; 87.6 mg/l - 6 h
100.000 mg/kg body weight
17.100 mg/kg body weight
700.000 ppmV/4h
3.000 mg/l/4h
0.500 mg/l/4h

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause
	gastrointestinal irritation, nausea, vomiting and diarrhea.
100% METHANOL UNLABELED (67-56-1)	
LD50 oral rat	1187 - 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	128.200 mg/l/4h
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin corrosion/irritation	: Skin - Rabbit. Result: No skin irritation
Serious eye damage/irritation	: Eyes - Rabbit. Result: No eye irritation
Respiratory or skin sensitization	: Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)
Germ cell mutagenicity	: AMES test : S. tymphimurium. Result: negative. fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - male and female Result: negative. Mouse - male and female. Result: Negative
Carcinogenicity	: Not classified
Reproductive toxicity	: Damage to fetus not classifiable. Fertility classification not possible from current data.
Specific target organ toxicity – single exposure	: Causes damage to organs through prolonged or repeated exposure
	Causes damage to organs
Specific target organ toxicity – repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure No data available
Aspiration hazard	: No aspiration toxicity classification.
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach. Toxic if swallowed. Toxic in contact with skin.
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general	The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.	
TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL	
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h	
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h	
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h	
100% METHANOL UNLABELED (67-56-1)		
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h	
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h	
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h	

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

12.2. Persistence and degradability	12.2 Bareistance and degradability		
TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL			
· · · · · · · · · · · · · · · · · · ·			
Biochemical oxygen demand (BOD)	600 - 1200 mg/g		
Chemical oxygen demand (COD)	1420 mg/g		
ThOD Diadegradation	1500 mg/g		
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d		
100% METHANOL UNLABELED (67-56-1)			
Biochemical oxygen demand (BOD)	600 - 1200 mg/g		
Chemical oxygen demand (COD)	1420 mg/g		
ThOD	1500 mg/g		
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d		
12.3. Bioaccumulative potential			
TAURODEOXYCHOLIC ACID, SODIUM SALT	(2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL		
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C		
Bioconcentration factor (BCF REACH)	1		
Log Pow	-0.77		
100% METHANOL UNLABELED (67-56-1)			
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C		
Bioconcentration factor (BCF REACH)	1		
Log Pow	-0.77		
12.4. Mobility in soil			
	(2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL		
Ecology - soil	Not degradable in the soil.		
100% METHANOL UNLABELED (67-56-1)			
Ecology - soil	Not degradable in the soil.		
12.5. Results of PBT and vPvB assessmen	nt		
TAURODEOXYCHOLIC ACID, SODIUM SALT	(2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL		
PBT: not relevant – no registration required			
100% METHANOL UNLABELED (67-56-1)			
PBT: not relevant – no registration required			
12.6. Other adverse effects			
Other adverse effects	: Avoid release to the environment.		
Other information	: Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water.		
	Hydrolyses readily.		
SECTION 13: Disposal consideration	S		
13.1. Waste treatment methods			
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.		
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.		
Ecology - waste materials	: Dispose of as unused product.		
SECTION 14: Transport information	SECTION 14: Transport information		
In accordance with ADR / RID / IMDG / IATA / AD	DN		
14.1. UN number			
UN-No.(DOT)	: 1230		
DOT NA no.	UN1230		
14.2. UN proper shipping name			
Proper Shipping Name (DOT)	: Methanol		
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120		

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

26, 2012 / Rules and Regulations	
Hazard labels (DOT)	: 3 - Flammable liquid 6.1 - Poison
	FLAMMABLE LIQUID POISON
	3 6
DOT Symbols	: + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group, I - Proper shipping name appropriate for international and domestic transportation
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite
	(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal
	TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image)
	Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
14.3. Additional information	
Emergency Response Guide (ERG) Number	: 131
Other information	: No supplementary information available.
Overland transport	
Packing group (ADR)	: 11
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 336
Classification code (ADR)	: FT1
Hazard labels (ADR)	: 3 - Flammable liquids 6.1 - Toxic substances
Orange plates	336 1230
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
Excepted quantities (ADR)	: E2
Transport by sea	
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
MFAG-No	: 131

100 UG/ML IN METHANOL DLM-9567-C

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

26, 2012 / Rules and Regulations	· · · · · · · · · · · · · · · · · · ·	
Air transport		
DOT Quantity Limitations Passenger aircraft/rai (49 CFR 173.27)	I : 1L	
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	9 : 60 L	
Civil Aeronautics Law	: Flammable liquids	
14.4. Environmental hazards		
Other information	: No supplementary information available.	
14.5. Special precautions for user		
14.6. Transport in bulk according to Ann	nex II of MARPOL 73/78 and the IBC Code	
Not applicable		
SECTION 15: Regulatory informatio	n	
15.1. US Federal regulations		
TAURODEOXYCHOLIC ACID, SODIUM SAL	T (2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL	
Listed on the United States TSCA (Toxic Subs	stances Control Act) inventory	
Subject to reporting requirements of United St	ates SARA Section 313	
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
TAURODEOXYCHOLIC ACID, SODIUM SAL	_T (2,2,4,4,11,11-D6, 98%) (1180-95-6 (Unlabeled))	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313	
100% METHANOL UNLABELED (67-56-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	

15.2. International regulations

SARA Section 313 - Emission Reporting

CANADA

TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11-D6, 98%) 100 UG/ML IN METHANOL
Listed on the Canadian DSL (Domestic Substances List)
100% METHANOL UNLABELED (67-56-1)

Subject to reporting requirements of United States SARA Section 313

15.2.1. **National regulations**

No additional information available

15.3. US State regulations

TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4	,11,11-D6, 98%) 100 UG/ML IN METHANOL
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	Yes
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TAURODEOXYCHOLIC AC	ID, SODIUM SALT (2,2,4,4,1	1,11-D6, 98%) 100 UG/ML IN N	IETHANOL	
State or local regulations		U.S Delaware - Pollutant Disc U.S Idaho - Non-Carcinogenic U.S Massachusetts - Right To U.S Pennsylvania - RTK (Righ U.S New Jersey - Right to Knr U.S New York - Reporting of F	c Toxic Air Pollutants - Accepta b Know List ht to Know) List ow Hazardous Substance List	ble Ambient Concentrations
TAURODEOXYCHOLIC AC	ID, SODIUM SALT (2,2,4,4,1	1,11-D6, 98%) (1180-95-6 (Unla	abeled))	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
100% METHANOL UNLAB	ELED (67-56-1)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	
TAURODEOXYCHOLIC AC	TAURODEOXYCHOLIC ACID, SODIUM SALT (2,2,4,4,11,11-D6, 98%) (1180-95-6 (Unlabeled))			
State or local regulations				
U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List				
100% METHANOL UNLAB	ELED (67-56-1)			
State or local regulations				
U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances				

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H370	Causes damage to organs
R11	Highly flammable
R36/37/38	Irritating to eyes, respiratory system and skin
R36/38	Irritating to eyes and skin
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed

100 UG/ML IN METHANOL DLM-9567-C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

F	Highly flammable
Т	Toxic
Xi	Irritant
NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product