



NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 25/01/2016

Revision date:

Version: 1.0

EC-5412

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name. : NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE
Product code : EC-5412

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Skin Irrit. 2 H315
STOT SE 3 H336
Asp. Tox. 1 H304
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11
Xi; R38
N; R50/53
R67

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 H225
Skin Irrit. 2 H315
STOT SE 3 H336
Asp. Tox. 1 H304
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Adverse physicochemical, human health and environmental effects

Liver, Kidney.

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE EC-5412


Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H410 - Very toxic to aquatic life with long lasting effects
H400 - Very toxic to aquatic life

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P261 - Avoid breathing dust, fume, gas, mist, spray, vapours
P264 - Wash Both hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust, fume, gas, mist, spray, vapours
P264 - Wash Both hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective clothing, protective gloves
P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P321 - Specific treatment (see Hazard pictograms (CLP) on this label)
P331 - If swallowed, do NOT induce vomiting
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use personal protective equipment as required for extinction
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to Comply with applicable regulations.

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE EC-5412

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC no) 208-759-1 (EC index no) 601-009-00-8	99.99624	Xi; R38 N; R50/53 R67 F; R11
DECACB UNLABELED	(CAS No) 2051-24-3	0.00029	N; R50/53
2,2',3,4,4',5,5'-HEPTACB UNLABELED	(CAS No) 35065-29-3	0.00029	R33
2,2',3,3',4,4',5,5'-OCTACB UNLABELED	(CAS No) 35694-08-7	0.00029	Xn; R48/20 N; R50/53
2,2',3,3',4,4',5,5',6-NONACB UNLABELED	(CAS No) 40186-72-9	0.00029	R33
2,2',4,4',5,5'-HEXACB UNLABELED	(CAS No) 35065-27-1	0.00029	R33
2,2',5,5'-TETRACB UNLABELED	(CAS No) 35693-99-3	0.00029	Xn; R22 N; R50/53
2,3,4,4',5-PENTACB UNLABELED	(CAS No) 74472-37-0 (EC index no) 602-039-00-4	0.00029	Xn; R22 N; R50/53
2,3',4,4',5-PENTACB UNLABELED	(EC no) 215-648-1 (EC index no) 602-039-00-4	0.00029	Xn; R22
2,4,4'-TRICB UNLABELED	(CAS No) 7012-37-5 (EC no) 230-293-2	0.00029	Xi; R36/37/38 N; R50/53
4-MONOCB UNLABELED	(CAS No) 2051-62-9 (EC no) 218-127-7	0.00029	Xn; R48/20
2,2',4,5,5'-PENTACB UNLABELED	(CAS No) 37680-73-2	0.00029	R33
2,2',3,4,4',5'-HEXACB UNLABELED	(CAS No) 35065-28-2	0.00029	N; R50/53 R33
2,4'-DICB UNLABELED	(EC index no) 602-039-00-4	0.00029	Xn; R48/20/21/22 N; R50/53 R33

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC no) 208-759-1 (EC index no) 601-009-00-8	99.99624	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
DECACB UNLABELED	(CAS No) 2051-24-3	0.00029	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,4',5,5'-HEPTACB UNLABELED	(CAS No) 35065-29-3	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,3',4,4',5,5'-OCTACB UNLABELED	(CAS No) 35694-08-7	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,3',4,4',5,5',6-NONACB UNLABELED	(CAS No) 40186-72-9	0.00029	Carc. 1B, H350 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',4,4',5,5'-HEXACB UNLABELED	(CAS No) 35065-27-1	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE EC-5412

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2,2',5,5'-TETRACB UNLABELED	(CAS No) 35693-99-3	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4,4',5-PENTACB UNLABELED	(CAS No) 74472-37-0 (EC index no) 602-039-00-4	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4,4',5-PENTACB UNLABELED	(EC no) 215-648-1 (EC index no) 602-039-00-4	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,4,4'-TRICB UNLABELED	(CAS No) 7012-37-5 (EC no) 230-293-2	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
4-MONOCB UNLABELED	(CAS No) 2051-62-9 (EC no) 218-127-7	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',4,5,5'-PENTACB UNLABELED	(CAS No) 37680-73-2	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,4',5'-HEXACB UNLABELED	(CAS No) 35065-28-2	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,4'-DICB UNLABELED	(EC index no) 602-039-00-4	0.00029	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
ISOOCTANE UNLABELED	(CAS No) 540-84-1	99.99624	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash off with soap and plenty of water. Consult a physician.
- First-aid measures after eye contact : Flush eyes with water as a precaution.
- First-aid measures after ingestion : Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : May be harmful if absorbed through skin. May cause skin irritation.
- Symptoms/injuries after eye contact : May cause eye irritation.
- Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : For small fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.
- Reactivity : Vapors may form explosive mixture with air.

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE EC-5412

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

- Firefighting instructions : Use water spray to cool unopened containers.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Use personal protective equipment, and ensure adequate ventilation. Avoid breathing vapors, mist, gas. Remove ignition sources, and move personnel to safe area. Vapors accumulate especially in low areas to form explosive concentrations.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

- For containment : Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store at room temperature away from light and moisture.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2,2',5,5'-TETRACB UNLABELED (35693-99-3)

USA OSHA	OSHA PEL (TWA) (mg/m ³)	0.5000000000 mg/m ³
----------	-------------------------------------	--------------------------------

8.2. Exposure controls

- Personal protective equipment : Gloves. Safety glasses. Protective clothing. Respiratory protection of the dependent type.



- Hand protection : protective gloves.
Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

- Physical state : Liquid
Appearance : Liquid.
Molecular mass : 114.23 g/mol
Colour : Colourless.

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE EC-5412

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -107 °C (- 161 °F)
Freezing point	: No data available
Boiling point	: 99 °C (210 °F)
Flash point	: -12 °C (10 °F) - closed cup
Self ignition temperature	: 396 °C (745 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapour pressure	: 55 hPa (41 mmHg) at 21 °C (70 °F)
Relative vapour density at 20 °C	: 3.94 - (Air = 1.0)
Relative density	: No data available
Density	: 0.692 g/ml
Solubility	: Water: 0 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1 - 6 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation. No data available
Serious eye damage/irritation	: Not classified No data available
Respiratory or skin sensitisation	: Not available No data available
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not available
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE EC-5412

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: Not classified No data available
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: The chemical, physical, and toxicological properties have not been thoroughly investigated.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May be harmful if absorbed through skin. May cause skin irritation.
Symptoms/injuries after eye contact	: May cause eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Very toxic to aquatic life with long lasting effects.

2,2',4,4',5,5'-HEXACB UNLABELED (35065-27-1)

LC50 fishes 1	Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	Daphnia magna (Water flea) - 48 h

2,2',5,5'-TETRACB UNLABELED (35693-99-3)

LC50 fishes 1	Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	Daphnia magna (Water flea) - 48 h
NOEC (chronic)	0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 7 d

2,4,4'-TRICB UNLABELED (7012-37-5)

LC50 fishes 1	> 0.16 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 Daphnia 1	> 0.16 mg/l Daphnia magna (Water flea) - 48h

4-MONOCB UNLABELED (2051-62-9)

LC50 fishes 1	0.72 mg/l Oncorhynchus mykiss (rainbow trout) - 96 h
EC50 Daphnia 1	0.42 mg/l Daphnia magna (Water flea) - 48 h

12.2. Persistence and degradability

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

12.3. Bioaccumulative potential

2,3',4,4',5-PENTACB UNLABELED

Log Pow	7.12
---------	------

4-MONOCB UNLABELED (2051-62-9)

BCF fish 1	>= 0.5 mg/l Oryzias latipes - 20 d
Bioconcentration factor (BCF REACH)	>= 54

2,4'-DICB UNLABELED

Log Pow	5.242
---------	-------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
Waste disposal recommendations	: Dispose of contents/container to ...
Additional information	: Handle empty containers with care because residual vapours are flammable.

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE EC-5412

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ecology - waste materials : Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

UN-No.(DOT) : 1262
DOT NA no. UN1262

14.2. UN proper shipping name

DOT Proper Shipping Name : Octanes
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
Marine pollutant : No



14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II
Class (ADR) : 3 - Flammable liquids
Hazard identification number (Kemler No.) : 33
Classification code (ADR) : F1
Danger labels (ADR) : 3 - Flammable liquids



Orange plates : An orange rectangular plate with a black border. The number '33' is printed in black in the upper half, and the number '1262' is printed in black in the lower half.

Tunnel restriction code : D/E
Limited quantities (ADR) : 1L
EAC code : 3YE
Excepted quantities (ADR) : E2

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOCTANE EC-5412

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

MFAG-No : 128

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

Civil Aeronautics Law : Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)

14.4. Environmental hazards

Dangerous for the environment :



Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOCTANE

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

ISOCTANE UNLABELED (540-84-1)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

15.2. International regulations

CANADA

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOCTANE

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2.1. National regulations

No additional information available

15.3. US State regulations

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOCTANE()

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.
----------------------------	---

ISOCTANE UNLABELED (540-84-1)

U.S. - Massachusetts - Right To Know List

NATIVE PREDOMINANT MONO-DECA PCBS UNLABELED 2000 NG/ML IN ISOOCTANE EC-5412

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ISOOCTANE UNLABELED (540-84-1)

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases::

Aquatic Acute 1	Hazardous to the aquatic environment — AcuteHazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R11	Highly flammable
R22	Harmful if swallowed
R33	Danger of cumulative effects
R36/37/38	Irritating to eyes, respiratory system and skin
R38	Irritating to skin
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product