



LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/01/2016

Revision date:

Version: 1.0

EM-4173-2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name. : LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2
Product code : EM-4173-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Eye Irrit. 2 H319
STOT SE 3 H336

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11
Xi; R36
R66
R67

Full text of R-phrases: see section 16

Classification (GHS-US)

Flam. Liq. 2 H225
Eye Irrit. 2A H319
STOT SE 3 H336

Adverse physicochemical, human health and environmental effects

Liver, Kidney.

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653

REV A - VIAL 2 EM-4173-2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors
P264 - Wash Both hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective clothing, protective gloves

EUH phrases

: EUH066 - Repeated exposure may cause skin dryness or cracking

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors
P264 - Wash Both hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective clothing, protective gloves
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P337+P313 - If eye irritation persists: Get medical advice/attention
P370+P378 - In case of fire: Use Hazard pictograms (CLP) for extinction
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to Comply with applicable regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653

REV A - VIAL 2 EM-4173-2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ACETONE UNLABELED	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8	99.968	F; R11 Xi; R36 R67 R66
5-CHLOROVANILLIN (RING-13C6, 99%)	(CAS No) 19463-48-0 (Unlabeled)	0.032	Xi; R36/37/38

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETONE UNLABELED	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8	99.968	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
5-CHLOROVANILLIN (RING-13C6, 99%)	(CAS No) 19463-48-0 (Unlabeled)	0.032	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Name	Product identifier	%	Classification (GHS-US)
ACETONE UNLABELED	(CAS No) 67-64-1	99.968	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Move out of dangerous area. Consult a physician and show this safety data sheet.
First-aid measures after inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Gently wash with plenty of soap and water.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Harmful if swallowed, inhaled or absorbed through skin.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Harmful if absorbed through skin. Prolonged or repeated contact can result in drying of the skin which may result in skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Vapors may form explosive mixture with air.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray to cool unopened containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653

REV A - VIAL 2 EM-4173-2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required. In case of leaking gas fire, eliminate all ignition sources if safe to do so. Evacuate the danger area. Avoid breathing dust, mist or spray.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For containment : Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Hygiene measures : Wash hands before eating and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store at room temperature away from light and moisture.

Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	500 ppm Eye & Upper Respiratory irritation, Central Nervous System impairment.
Italy - Portugal - USA ACGIH	ACGIH STEL (mg/m ³)	Eye & Upper Respiratory irritation, Central Nervous System impairment.
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	750 ppm
ACETONE UNLABELED (67-64-1)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	500 ppm Eye & Upper Respiratory irritation, Central Nervous System impairment.
Italy - Portugal - USA ACGIH	ACGIH STEL (mg/m ³)	Eye & Upper Respiratory irritation, Central Nervous System impairment.
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	750 ppm The acetone STEL does not apply to the cellulose acetate fiber industry.
USA OSHA	OSHA PEL (STEL) (ppm)	100 ppm The acetone STEL does not apply to the cellulose acetate fiber industry.

8.2. Exposure controls

Personal protective equipment : Gloves. Safety glasses. Protective clothing. Respiratory protection of the dependent type.



Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.

Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653

REV A - VIAL 2 EM-4173-2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appearance	: Liquid, Clear.
Molecular mass	: 58.08 g/mol
Color	: Colorless.
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -94 °C (-137 °F)
Freezing point	: No data available
Boiling point	: 56 °C (133 °F) at 1,013 hPa (760 mmHg)
Flash point	: -16.99 °C (1.42 °F) - closed cup
Self ignition temperature	: 465 °C (869.0 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: 533.3 hPa (400.0 mmHg) at 39.5 °C (103.1 °F)
Critical pressure	: 245.3 hPa (184.0 mmHg) at 20.0°C (68.0 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.791 g/ml at 25 °C (68.0 °F)
Solubility	: Water: Completely miscible
Log Pow	: -0.24
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 2 - 13 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

Bases, Oxidizing agents, Reducing agents.

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2	
LD50 oral rat	5800 mg/kg
LC50 inhalation rat (mg/l)	50100 mg/m ³ 8 h
ATE (oral)	5800.000 mg/kg body weight
ATE (vapors)	50.100 mg/l/4h
ATE (dust, mist)	50.100 mg/l/4h

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653

REV A - VIAL 2 EM-4173-2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACETONE UNLABELED (67-64-1)	
LD50 oral rat	5800 mg/kg
LC50 inhalation rat (mg/l)	50100 mg/m ³ 8 h
ATE (oral)	5800.000 mg/kg body weight
ATE (vapors)	50.100 mg/l/4h
ATE (dust, mist)	50.100 mg/l/4h

Skin corrosion/irritation	: Skin - rabbit - Mild skin irritation - 24 h
Serious eye damage/irritation	: Result: Severe eye irritation - 24 h
Respiratory or skin sensitization	: Chronic exposure may cause dermatitis.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: This product is or contains a component that is not classifiable as to its carcinogenicity on its IARC, ACGIH, NTP, or EPA classification.
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause drowsiness or dizziness May cause damage to organs.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Harmful if absorbed through skin. Prolonged or repeated contact can result in drying of the skin which may result in skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2	
LC50 fish 1	5540 mg/l Oncorhynchus mykiss (rainbow trout) -96h
EC50 Daphnia 1	13500 mg/l Daphnia magna (Water flea) - 48h

ACETONE UNLABELED (67-64-1)	
LC50 fish 1	5540 mg/l Oncorhynchus mykiss (rainbow trout) -96h
EC50 Daphnia 1	13500 mg/l Daphnia magna (Water flea) - 48h

12.2. Persistence and degradability

5-CHLOROVANILLIN (RING-13C6, 99%) (19463-48-0 (Unlabeled))	
Persistence and degradability	Not available.

12.3. Bioaccumulative potential

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2	
Log Pow	-0.24

ACETONE UNLABELED (67-64-1)	
Log Pow	-0.24

5-CHLOROVANILLIN (RING-13C6, 99%) (19463-48-0 (Unlabeled))	
Bioaccumulative potential	Not available.

12.4. Mobility in soil

5-CHLOROVANILLIN (RING-13C6, 99%) (19463-48-0 (Unlabeled))	
Ecology - soil	Not available.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653

REV A - VIAL 2 EM-4173-2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
- Waste disposal recommendations : Dispose of contents/container to ...
- Additional information : Handle empty containers with care because residual vapors are flammable.

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

- UN-No.(DOT) : 1090
- DOT NA no. UN1090

14.2. UN proper shipping name

- DOT Proper Shipping Name : Acetone
- Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
- DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

- Other information : No supplementary information available.

Overland transport

- Packing group (ADR) : II
- Class (ADR) : 3 - Flammable liquid
- Hazard identification number (Kemler No.) : 33
- Classification code (ADR) : F1
- Danger labels (ADR) : 3 - Flammable liquids



- Orange plates : An orange rectangular label with a black border. It is divided into two horizontal sections. The top section contains the number '33' and the bottom section contains the number '1090'.

- Tunnel restriction code : D/E
- Limited quantities (ADR) : 1L
- EAC : •2YE
- Excepted quantities (ADR) : E2

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2 EM-4173-2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

MFAG-No : 127

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard
-------------------------------------	---

ACETONE UNLABELED (67-64-1)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard
-------------------------------------	---

15.2. International regulations

CANADA

No additional information available

15.2.1. National regulations

No additional information available

15.3. US State regulations

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653 REV A - VIAL 2()

State or local regulations	This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm. U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
----------------------------	---

ACETONE UNLABELED (67-64-1)

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

LABELED CHLOROPHENOLIC DERIVATIVES MIX FOR METHOD 1653

REV A - VIAL 2 EM-4173-2

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases::

Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
R11	Highly flammable
R36	Irritating to eyes
R36/37/38	Irritating to eyes, respiratory system and skin
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapors may cause drowsiness and dizziness
F	Highly flammable
Xi	Irritant

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product