

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 1/31/2019 Revision date: 12/12/2023 Supersedes: 1/31/2019 Version: 2.0

## **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture

Product name : 1,2,3,4-TETRACDF UNLABELED ~25 NG/ML IN NONANE

Product code : JR-F01-25

#### 1.2. Recommended use and restrictions on use

No additional information available

## 1.3. Supplier

Cambridge Isotope Laboratories, Inc.

50 Frontage Rd

01810

ANDOVER, MA, 01810

USA

T 1-800-322-1174

cilsales@isotope.com - www.isotope.com

## 1.4. Emergency telephone number

: 1-703-741-5970 **Emergency number** 

Chemtrec 1-800-424-9300 24 hours

## **SECTION 2: Hazard(s) identification**

## 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (inhalation:vapor) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airwa

Full text of H statements: see section 16

## 2.2. GHS Label elements, including precautionary statements

## **GHS US labeling**

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing fume, mist, spray, vapors.

P264 - Wash Both hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, face protection, protective clothing, protective gloves.

P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a doctor, a POISON CENTER if you feel unwell.

P321 - Specific treatment (see Hazard pictograms (CLP) on this label).

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to Comply with applicable regulations.

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

#### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
N-NONANE UNLABELED	CAS-No.: 111-84-2	99.9999965	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
1,2,3,4-TETRACDF UNLABELED	CAS-No.: 24478-72-6	0.0000035	Not classified

Full text of hazard classes and H-statements : see section 16

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice. Evacuate danger area. First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms

: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Harmful if inhaled. May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation. May be harmful in contact with skin.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Risk of lung edema.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Alcohol resistant foam.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions
Protection during firefighting

 $: \ \, \text{Do not enter fire area without proper protective equipment, including respiratory protection.}$ 

: Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

Emergency procedures : Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

12/12/2023 (Revision date) US - en 3/12

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill. For large spills, confine the spill in a dike and charge it with wet sand or

earth for subsequent safe disposal. Dispose as hazardous waste. Comply with local regulations for disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and

shovel into container for disposal.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

Nonane

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a well-ventilated place. Keep container tightly closed. Keep dry. Ground/bond container

and receiving equipment.

Storage conditions : Store at room temperature away from light and moisture.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Local name

## 1,2,3,4-TETRACDF UNLABELED ~25 NG/ML IN NONANE

No additional information available

#### **N-NONANE UNLABELED (111-84-2)**

<b>USA - ACGIH -</b>	<ul> <li>Occupationa</li> </ul>	al Exposure Limits
----------------------	---------------------------------	--------------------

ACGIH OEL TWA [ppm]	200 ppm USA. ACGIH Threshold Limit Values (TLV)
Remark (ACGIH)	CNS impair
9 ,	No component of this product present at levels greater than or equal to 0.1% is identifiable as a carcinogen or potential carcinogen by ACGIH.

#### **USA - OSHA - Occupational Exposure Limits**

OSHA PEL C [ppm]	200 ppm California permissible exposure limits for chemical contaminants.
OSHA PEL C	1050 California permissible exposure limits for chemical contaminants.
OSHA PEL TWA [2]	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
OSHA PEL TWA [1]	1050 mg/m³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000

#### **USA - NIOSH - Occupational Exposure Limits**

NIOSH REL TWA	1050 mg/m³ USA. NIOSH Recommended Exposure Limits	
NIOSH REL TWA [ppm]	200 ppm USA. NIOSH Recommended Exposure Limits	

12/12/2023 (Revision date) US - en 4/12

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **N-NONANE UNLABELED (111-84-2)**

Remark (NIOSH) Central Nervous System impairment

#### 1,2,3,4-TETRACDF UNLABELED (24478-72-6)

No additional information available

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.

#### Materials for protective clothing:

Wear suitable protective clothing and gloves

#### Hand protection:

protective gloves

#### Eye protection:

Chemical goggles or face shield. Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing, gloves and eye/face protection

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator

#### Personal protective equipment symbol(s):











## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : Colorless
Odor : No data available

Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : -53 °C (-63 °F) - lit
Boiling point : 151 °C (304 °F) - lit
Flash point : 31 °C (87.8 °F) - closed cup

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas)

: Not applicable.

Vapor pressure : 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)

Relative vapor density at 20°C : No data available

12/12/2023 (Revision date) US - en 5/12

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density : No data available

Density : 0.718 g/ml at 25 °C (77 °F)

Molecular mass : 128.3 g/mol Solubility : Water: 0.0002 %

Partition coefficient n-octanol/water (Log Pow) : 5.65

Auto-ignition temperature : 205 °C (401 °F)

Decomposition temperature : No data available

Viscosity, kinematic : ≤ 1.008 mm²/s at 20 °C (68 °F)

#### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Flammable liquid and vapor. Vapors may form flammable mixture with air.

### 10.2. Chemical stability

Stable if stored under recommended conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Overheating. Open flame. Sparks.

## 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO2). May release flammable gases.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

1,2,3,4-TETRACDF UNLABELED ~25 NG/ML IN NONANE		
LC50 Inhalation - Rat 23760 mg/m³ male - 4 h		
Additional data  Skin corrosion/irritation, Dermal, rat: Result: Skin Irritation (Draize Test)  S. Typhimurium Result negative		
N-NONANE UNLABELED (111-84-2)		
LC50 Inhalation - Rat 23760 mg/m³ male - 4 h		
ATE US (gases)	4500 ppmV/4h	

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-NONANE UNLABELED (111-84-2)	
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
N-NONANE UNLABELED (111-84-2)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: ≤ 1.008 mm²/s at 20 °C (68 °F)
N-NONANE UNLABELED (111-84-2)	
Viscosity, kinematic	≤ 1.008 mm²/s at 20 °C (68 °F)
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.
Symptoms/effects after ingestion	. May be fatal if Swallowed and enters allways. Risk of fung edema.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

## 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

1,2,3,4-TETRACDF UNLABELED ~25 NG/ML IN NONANE		
Partition coefficient n-octanol/water (Log Pow) 5.65		
Bioaccumulative potential	Indication of bioaccumulation.	
N-NONANE UNLABELED (111-84-2)		
Partition coefficient n-octanol/water (Log Pow)	5.65	
Bioaccumulative potential	Indication of bioaccumulation.	

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other adverse effects : Disposal must be done according to official regulations.

### **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local

environmental control regulations.

Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed

professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

## **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

DOT NA No : UN1920 UN-No. (TDG) : UN1920 UN-No. (IMDG) : 1920 UN-No. (IATA) : 1920

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Nonanes
Proper Shipping Name (TDG) : NONANES
Proper Shipping Name (IMDG) : NONANES
Proper Shipping Name (IATA) : Nonanes

## 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 3 Hazard labels (DOT) : 3



#### **TDG**

Transport hazard class(es) (TDG) : 3 Hazard labels (TDG) : 3



## IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



#### IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



#### 14.4. Packing group

Packing group (DOT) : III
Packing group (TDG) : III
Packing group (IMDG) : III
Packing group (IATA) : III

#### 14.5. Environmental hazards

Marine pollutant : Yes (IMDG only)



Other information : No supplementary information available.

## 14.6. Special precautions for user

### **DOT**

UN-No.(DOT) : UN1920

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

12/12/2023 (Revision date) US - en 9/12

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

**TDG** 

UN-No. (TDG) : UN1920
Explosive Limit and Limited Quantity Index : 5 L
Excepted quantities (TDG) : E1
Passenger Carrying Road Vehicle or Passenger : 60 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 128

**IMDG** 

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T2

Tank special provisions (IMDG) : 12

Tank special provisions (IMDG) : TP1

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : A Flash point (IMDG) : '

Properties and observations (IMDG) : Colourless liquids. Explosive limits: 0.8% to 2.9% normal-NONANE: flashpoint 31°C c.c.

Immiscible with water. Irritating to skin, eyes and mucous membranes.

MFAG-No : 128

**IATA** 

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) : 10L PCA packing instructions (IATA) 355 PCA max net quantity (IATA) 60L CAO packing instructions (IATA) 366 : 220L CAO max net quantity (IATA) ERG code (IATA) : 3L

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

1,2,3,4-TETRACDF UNLABELED ~25 NG/ML IN NONANE		
SARA Section 302 Threshold Planning Quantity (TPQ)  Not subject to reporting requirements of the United States SARA Section 302.		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	<b>3</b>	Commercial status	Flags
N-NONANE UNLABELED	111-84-2	Present	Active	Т
1,2,3,4-TETRACDF UNLABELED	24478-72-6	Not present	-	

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-NONANE UNLABELED (111-84-2)	
SARA Section 302 Threshold Planning Quantity (TPQ)  Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard

#### 15.2. International regulations

#### **CANADA**

## 1,2,3,4-TETRACDF UNLABELED ~25 NG/ML IN NONANE

Listed on the Canadian DSL (Domestic Substances List)

## **N-NONANE UNLABELED (111-84-2)**

Listed on the Canadian DSL (Domestic Substances List)

#### 1,2,3,4-TETRACDF UNLABELED (24478-72-6)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

#### **EU-Regulations**

No additional information available

#### **National regulations**

No additional information available

## 15.3. US State regulations

Component	State or local regulations
	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) List

## **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 12/12/2023

Other information : This product is not radioactive. The data given for this product are those of the corresponding

unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the

corresponding unlabeled compound.

Full text of H-phrases	
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

Safety Data Sheet (SDS), USA

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.