

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 1/28/2019 Revision date: 12/22/2023 Supersedes: 1/28/2019 Version: 2.0

SECTION 1: Identification	
1.1. Identification	
Product form Product name Product code	 Mixture 1,2,3,4,9-PENTACDF UNLABELED ~25 NG/ML IN NONANE JR-F42-25
1.2. Recommended use and restrictions on	use
No additional information available	
1.3. Supplier	
Cambridge Isotope Laboratories, Inc. 50 Frontage Rd 01810 ANDOVER, MA, 01810 USA T 1-800-322-1174 <u>cilsales@isotope.com</u> - <u>www.isotope.com</u>	
1.4. Emergency telephone number	
Emergency number	: 1-703-741-5970 Chemtrec 1-800-424-9300 24 hours

ISECTION 2	Hazard(s) identification
	i luzui u (S	

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (inhalation) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)

Signal word (GHS US) Hazard statements (GHS US)



- : Danger
- : H226 Flammable liquid and vapor
 - H304 May be fatal if swallowed and enters airways
 - H315 Causes skin irritation
 - H319 Causes serious eye irritation
 - H332 Harmful if inhaled
 - H336 May cause drowsiness or dizziness

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear eye protection, face protection, protective clothing, protective gloves. P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER. P302+P352 - If on skin: Wash with plenty of water. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P312 - Call a doctor, a POISON CENTER if you feel unwell. P312 - Call a doctor, a POISON CENTER if you feel unwell. P312 - Specific treatment (see Hazardous component(s) for labeling on this label). P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: Get medical advice/attention. P362+P354 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry extinguishing powder to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool.
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
N-NONANE UNLABELED	CAS-No.: 111-84-2	99.9999965	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
1,2,3,4,9-PENTACDF UNLABELED	CAS-No.: 83704-49-8	0.0000035	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 4, H413

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures 4.1. Description of first aid measures First-aid measures general : Call a physician immediately. First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. Give oxygen or artificial respiration if necessary. First-aid measures after skin contact Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin : irritation occurs: Get medical advice/attention. First-aid measures after eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to · do. Continue rinsing. If eye irritation persists: Get medical advice/attention. First-aid measures after ingestion Do not induce vomiting. Call a physician immediately. : 4.2. Most important symptoms and effects (acute and delayed) Potential Adverse human health effects and : This information is based on our current knowledge and is intended to describe the product for symptoms the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. May cause drowsiness or dizziness. Symptoms/effects : Symptoms/effects after inhalation Harmful if inhaled. May cause respiratory irritation. : Symptoms/effects after skin contact Causes skin irritation. May be harmful in contact with skin. :

Causes serious eye irritation.

May be fatal if swallowed and enters airways. Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

·

Treat symptomatically.

Symptoms/effects after eye contact

Symptoms/effects after ingestion

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. Alcohol resistant foam.	
5.2. Specific hazards arising from the chemical		
Fire hazard Hazardous decomposition products in case of fire	Flammable liquid and vapor.Toxic fumes may be released.	
5.3. Special protective equipment and precautions for fire-fighters		
Firefighting instructions Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.Do not attempt to take action without suitable protective equipment. Self-contained breathing	

apparatus. Complete protective clothing.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equip	ment and emergency procedures		
6.1.1. For non-emergency personnel			
Emergency procedures	: Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
6.2. Environmental precautions			
Prevent entry to sewers and public waters. Avoid rel	ease to the environment.		
6.3. Methods and material for containment	and cleaning up		
For containment	: Dike and contain spill. Dispose as hazardous waste. Comply with local regulations for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.		
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.		
Other information	: Dispose of materials or solid residues at an authorized site.		

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Avoid all contact with skin, eyes, or clothing. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the manufacturer). Take precautionary measures against static discharges.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including	g any incompatibilities
Technical measures Storage conditions	Store in a well-ventilated place. Keep container tightly closed.Store at room temperature away from light and moisture.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,3,4,9-PENTACDF UNLABELED ~2 USA - ACGIH - Occupational Exposure Lin		
Local name	Nonane	
ACGIH OEL TWA [ppm]	200 ppm USA. ACGIH Threshold Limit Values (TLV)	
Remark (ACGIH)	CNS impair	
ACGIH chemical category	No component of this product present at levels greater than or equal to 0.1% is identifiable as a carcinogen or potential carcinogen by ACGIH.	
USA - OSHA - Occupational Exposure Lim	its	
OSHA PEL TWA [1]	1050 mg/m ³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000	
OSHA PEL TWA [2]	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000	
OSHA PEL C	1050 California permissible exposure limits for chemical contaminants.	
OSHA PEL C [ppm]	200 ppm California permissible exposure limits for chemical contaminants.	
USA - NIOSH - Occupational Exposure Lim	its	
NIOSH REL TWA	1050 mg/m ³ USA. NIOSH Recommended Exposure Limits	
NIOSH REL TWA [ppm]	200 ppm USA. NIOSH Recommended Exposure Limits	
Remark (NIOSH)	Central Nervous System impairment	
N-NONANE UNLABELED (111-84-2)		
USA - ACGIH - Occupational Exposure Lin	nits	
Local name	Nonane	
ACGIH OEL TWA [ppm]	200 ppm USA. ACGIH Threshold Limit Values (TLV)	
Remark (ACGIH)	CNS impair	
ACGIH chemical category	No component of this product present at levels greater than or equal to 0.1% is identifiable as a carcinogen or potential carcinogen by ACGIH.	
USA - OSHA - Occupational Exposure Lim	its	
OSHA PEL TWA [1]	1050 mg/m ³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000	
OSHA PEL TWA [2]	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000	
OSHA PEL C	1050 California permissible exposure limits for chemical contaminants.	
OSHA PEL C [ppm]	200 ppm California permissible exposure limits for chemical contaminants.	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	1050 mg/m ³ USA. NIOSH Recommended Exposure Limits	
NIOSH REL TWA [ppm]	200 ppm USA. NIOSH Recommended Exposure Limits	
Remark (NIOSH)	Central Nervous System impairment	
1,2,3,4,9-PENTACDF UNLABELED (83704-49-8)		
No additional information available		
8.2. Appropriate engineering controls		
Appropriate engineering controls	: Ensure good ventilation of the work station.	

Appropriate engineering controls Environmental exposure controls

: Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.

Materials for protective clothing:

Wear suitable protective clothing and gloves

Hand protection:

protective gloves

Eye protection:

Chemical goggles or face shield. Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing, gloves and eye/face protection

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: Not applicable
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31 °C (87.8 °F) - closed cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.718 g/ml at 25 °C (77 °F)
Molecular mass	: 128.3 g/mol
Solubility	: Water: 0.0002 %
Partition coefficient n-octanol/water (Log Pow)	: 5.65
Auto-ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Viscosity, kinematic	: ≤ 1.008 mm²/s at 20 °C (68 °F)
Viscosity, dynamic	: No data available
Explosion limits	: 0.87 – 2.9 % (V)
Explosive properties	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties

: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor. Vapors may form flammable mixture with air.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2). May release flammable gases.

SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Acute toxicity (dermal) : Acute toxicity (inhalation) :	Not classified Not classified Harmful if inhaled.		
1,2,3,4,9-PENTACDF UNLABELED ~25 NG/ML	IN NONANE		
LC50 Inhalation - Rat	23760 mg/m³ male - 4 h		
Additional data	Skin corrosion/irritation, Dermal, rat: Result: Skin Irritation (Draize Test) S. Typhimurium Result negative		
N-NONANE UNLABELED (111-84-2)	N-NONANE UNLABELED (111-84-2)		
LC50 Inhalation - Rat	23760 mg/m³ male - 4 h		
ATE US (gases)	4500 ppmV/4h		
ATE US (vapors)	11 mg/l/4h		
ATE US (dust, mist)	1.5 mg/l/4h		
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)		
Additional information	: S. Typhimurium Result: negative		
1,2,3,4,9-PENTACDF UNLABELED (83704-49-8)			
ATE US (oral)	0.1 mg/kg body weight		
ATE US (dermal)	5 mg/kg body weight		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
N-NONANE UNLABELED (111-84-2)	
STOT-single exposure	May cause drowsiness or dizziness.
1,2,3,4,9-PENTACDF UNLABELED (83	704-49-8)
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: ≤ 1.008 mm²/s at 20 °C (68 °F)
N-NONANE UNLABELED (111-84-2)	
Viscosity, kinematic	≤ 1.008 mm²/s at 20 °C (68 °F)
Potential Adverse human health effects and	: This information is based on our current knowledge and is intended to describe the product for
symptoms	the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation : Harmful if inhaled. May cause respiratory irritation.	
mptoms/effects after skin contact : Causes skin irritation. May be harmful in contact with skin.	
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

SECTION 12: Ecological information			
12.1. Toxicity			
Ecology - general :	The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.		
12.2. Persistence and degradability			
No additional information available			
12.3. Bioaccumulative potential			
1,2,3,4,9-PENTACDF UNLABELED ~25 NG/ML IN NONANE			
Partition coefficient n-octanol/water (Log Pow)	5.65		
Bioaccumulative potential	Indication of bioaccumulation.		
N-NONANE UNLABELED (111-84-2)			
Partition coefficient n-octanol/water (Log Pow)	5.65		
Bioaccumulative potential	Indication of bioaccumulation.		
12.4. Mobility in soil			
No additional information available			
12.5. Other adverse effects			
Other adverse effects :	Disposal must be done according to official regulations.		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.
SECTION 14: Transport information	
In accordance with DOT / TDG / IMDG / IATA	
14.1. UN number	
DOT NA No UN-No. (TDG) UN-No. (IMDG) UN-No. (IATA)	: UN1920 : UN1920 : 1920 : 1920
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	: Nonanes : NONANES : NONANES : Nonanes
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 3 : 3
TDG Transport hazard class(es) (TDG) Hazard labels (TDG)	: 3 : 3
IMDG Transport hazard class(es) (IMDG) Hazard labels (IMDG)	
IATA Transport hazard class(es) (IATA)	: 3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (IATA)	: 3
	3
14.4. Packing group	
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	: III : III : III : III
14.5. Environmental hazards	
Marine pollutant	: Yes (IMDG only)
Other information	: No supplementary information available.
14.6. Special precautions for user	
DOT UN-No.(DOT) DOT Special Provisions (49 CFR 172.102)	 UN1920 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) DOT Vessel Stowage Location	: 150 : 203 : 242
TDG UN-No. (TDG) Explosive Limit and Limited Quantity Index Excepted quantities (TDG)	: UN1920 : 5 L : E1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Passenger Carrying Road Vehicle or Passenger	: 60 L
Carrying Railway Vehicle Index	400
Emergency Response Guide (ERG) Number	: 128
IMDG	
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001. LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
	. 12 : TP1
Tank special provisions (IMDG) EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: A
Flash point (IMDG)	: '
Properties and observations (IMDG)	: Colourless liquids. Explosive limits: 0.8% to 2.9% normal-NONANE: flashpoint 31°C c.c. Immiscible with water. Irritating to skin, eyes and mucous membranes.
MFAG-No	: 128
ΙΑΤΑ	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

1,2,3,4,9-PENTACDF UNLABELED ~25 NG/ML IN NONANE				
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.			
Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):			trol Act (TSCA):	
Name	CAS-No.	Listing	Commercial status	Flags
N-NONANE UNLABELED	111-84-2	Present	Active	т
1,2,3,4,9-PENTACDF UNLABELED	83704-49-8	Not present	-	

N-NONANE UNLABELED (111-84-2)		
SARA Section 302 Threshold Planning Quantity (TPQ)	d Planning Quantity Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,3,4,9-PENTACDF UNLABELED (83704-49-8)		
SARA Section 302 Threshold Planning Quantity (TPQ)Not subject to reporting requirements of the United States SARA Section 302.		
15.2. International regulations		
CANADA		

CANADA

1,2,3,4,9-PENTACDF UNLABELED ~25 NG/ML IN NONANE

Listed on the Canadian DSL (Domestic Substances List)

N-NONANE UNLABELED (111-84-2)

Listed on the Canadian DSL (Domestic Substances List)

1,2,3,4,9-PENTACDF UNLABELED (83704-49-8)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

1,2,3,4,9-PENTACDF UNLABELED ~25 NG/ML IN NONANE		
State or local regulations	U.S New Jersey - Right to Know Hazardous Substance List	
	U.S Massachusetts - Right To Know List	
	U.S Pennsylvania - RTK (Right to Know) List	

1,2,3,4,9-PENTACDF UNLABELED (83704-49-8)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female		No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
N-NONANE UNLABELED(111-84-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) List
1,2,3,4,9-PENTACDF UNLABELED(83704-49-8)	U.S Pennsylvania - RTK (Right to Know) List; U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 12/22/2023

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of H-phrases	
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.