

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 26/04/2018 Revision date: 23/07/2018 Supersedes: 26/04/2018 Version: 1.1 ULM-10529-S

<b>SECTION 1: Identificatio</b>	on of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixtures
Product name	: N-METHYLETHANOLAMINE UNLABELED 5 MG/ML IN METHANOL
Product code	: ULM-10529-S
1.2. Relevant identified u	ses of the substance or mixture and uses advised against
1.2.1. Relevant identified u	
Main use category	: Professional use
Industrial/Professional use spec	: For professional use only
1.2.2. Uses advised agains	t
No additional information availab	ble
1.3. Details of the supplie	er of the safety data sheet
Cambridge Isotope Laboratories 50 Frontage Road	
Andover, MA 01810 USA	
USA: 1-800-322-1174 Int: 1-9 cilsales@isotope.com www.is	78-749-8000 otope.com
Emergency telephon	e number
Emergency numbers:	
Chemtrec: 1-800-424-9300 (24 International: 1-703-741-5970 (	
SECTION 2: Hazards ide	entification
	substance or mixture
	egulation (EC) No. 1272/2008 [CLP]
Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapour)	
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 1	H370
Full text of hazard classes and H	H-statements : see section 16
Classification according to Di	rective 67/548/EEC [DSD] or 1999/45/EC [DPD]
F; R11 T; R39/23/24/25 Xi; R36/38	
Full text of R-phrases: see section	on 16
GHS-US classification	

Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapour)	H331
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 1	H370

Full text of H statements : see section 16

### ULM-10529-S

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Adverse physicochemical, human health and environmental effects

Eyes, Kidney, Liver, Heart, Central nervous system. Highly flammable liquid and vapour. Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (if inhaled, if swallowed, in contact with skin). Toxic in contact with skin. Toxic if inhaled. Toxic if swallowed. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements	
Labeling according to Regulation (EC) No Hazard pictograms (CLP)	5. 1272/2008 [CLP]
	$\langle \langle \langle \langle \rangle \rangle \rangle \langle \langle \langle \rangle \rangle \rangle \langle \langle \rangle \rangle \rangle \rangle = \langle \langle \rangle \rangle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \rangle \rangle \langle \rangle \rangle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \rangle \rangle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \rangle \rangle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \rangle \rangle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \rangle \rangle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \rangle \rangle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \rangle \rangle \langle \rangle \rangle \langle \langle \rangle \langle \langle \rangle \rangle \langle \langle \rangle \rangle \langle \langle \rangle \langle \rangle \langle \langle \rangle \rangle \langle \langle \rangle \langle \rangle \langle \langle \rangle \langle \rangle \langle \rangle \rangle \langle \langle \rangle \langle \langle \rangle \langle \rangle \langle \rangle \langle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \rangle \langle \langle \rangle \langle \langle \rangle \langle \langle \rangle $
	GHS02 GHS08 GHS06
Signal word (CLP)	: Danger
Hazard statements (CLP)	<ul> <li>H225 - Highly flammable liquid and vapour H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, heart, kidneys, liver, central nervous system) (in contact with skin, if inhaled, if swallowed)</li> </ul>
Precautionary statements (CLP)	<ul> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P233 - Keep container tightly closed.</li> <li>P240 - Ground/bond container and receiving equipment.</li> <li>P241 - Use explosion-proof electrical, lighting, ventilating equipment</li> <li>P260 - Do not breathe dust, mist, vapors, fume, gas, spray.</li> <li>P264 - Wash hands, forearms and face thoroughly after handling.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> </ul>
GHS-US labeling	
Hazard pictograms (GHS-US)	
Signal word (GHS-US)	GHS02 GHS08 GHS06 : Danger
Hazard statements (GHS-US)	<ul> <li>H225 - Highly flammable liquid and vapour</li> <li>H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled</li> <li>H315 - Causes skin irritation</li> <li>H319 - Causes serious eye irritation</li> <li>H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal Inhalation, oral)</li> </ul>
Precautionary statements (GHS-US)	<ul> <li>P210 - Keep away from heat, open flames, sparks No smoking.</li> <li>P233 - Keep container tightly closed.</li> <li>P240 - Ground/Bond container and receiving equipment</li> <li>P241 - Use explosion-proof electrical, lighting, ventilating equipment</li> <li>P242 - Use only non-sparking tools.</li> <li>P243 - Take precautionary measures against static discharge.</li> <li>P260 - Do not breathe dust, fume, mist, gas, spray, vapors.</li> <li>P261 - Avoid breathing dust, fume, gas, spray, vapors, mist.</li> <li>P264 - Wash hands, forearms and face thoroughly after handling.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P280 - Wear protective clothing, protective gloves.</li> <li>P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER</li> <li>P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower</li> <li>P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing</li> <li>P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contac lenses, if present and easy to do. Continue rinsing</li> <li>P307+P311 - If exposed: Call a poison center/doctor</li> </ul>
23/07/2018	P311 - Call a doctor, a POISON CENTER EN (English US) 2/14

#### ULM-10529-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P312 - Call a doctor, a POISON CENTER if you feel unwell
P321 - Specific treatment (see Hazardous component(s) for labeling on this label)
P322 - Specific treatment (see Hazard pictograms (CLP) on this label)
P330 - Rinse mouth.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry extinguishing powder to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

PBT: not relevant - no registration required

#### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

3.2. Mixtures			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.37	F; R11 T; R39/23/24/25 Xi; R36/38
N-METHYLETHANOLAMINE UNLABELED	(CAS-No.) 109-83-1 (EC-No.) 203-710-0	0.63	C; R35 Xn; R48/21/22 Xi; R41 Xi; R37 Xi; R36
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.37	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
N-METHYLETHANOLAMINE UNLABELED	(CAS-No.) 109-83-1 (EC-No.) 203-710-0	0.63	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373
Name	Product identifier	%	GHS-US classification
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.37	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370
N-METHYLETHANOLAMINE UNLABELED	(CAS-No.) 109-83-1	0.63	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 3, H402

Full text of R- and H- phrases: see section 16

## ULM-10529-S

5, 2012 / Rules and Regulations SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	<ul> <li>If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.</li> </ul>
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.
First-aid measures after skin contact	<ul> <li>Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.</li> </ul>
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mout Call a physician immediately.
4.2. Most important symptoms and eff	ects, both acute and delayed
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.
4.3. Indication of any immediate medio	cal attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	Dry pourder Dry cond
Suitable extinguishing media	: Dry powder. Dry sand.
Jnsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the s	
Fire hazard	: Highly flammable liquid and vapour.
Reactivity	: Vapors may form flammable mixture with air. Highly flammable liquid and vapour.
5.3. Advice for firefighters	
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.
Other information	: Use water spray to cool exposed surfaces.
SECTION 6: Accidental release me	asures
	equipment and emergency procedures
6.1.1. For non-emergency personnel Emergency procedures	: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
	not allow to enter drains or water courses. Avoid release to the environment.
6.3. Methods and material for contain	nent and cleaning up
For containment	: Dike and contain spill.
Methods for cleaning up	<ul> <li>Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.</li> </ul>
	: Dispose of materials or solid residues at an authorized site.
Other information	

## ULM-10529-S

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust, fume, gas, spray, vapors, mist. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including	ng any incompatibilities
Technical measures	: Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep

Storage conditions

container tightly closed. Store locked up.Store at room temperature away from light and moisture.

7.3. Specific end use(s)

No additional information available

3.1. Control parameters	ontrols/personal protection	
	UNLABELED 5 MG/ML IN METHANOL	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup> Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup> Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m <sup>3</sup> Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m <sup>3</sup> Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.
100% METHANOL UNLABEL	ED (67-56-1)	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)

## ULM-10529-S

100% METHANOL UNLABEL	ED (67-56-1)		
Italy - Portugal - USA ACGIH	Remark (ACGI	4)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (T)	VA) (mg/m³)	260 mg/m <sup>3</sup> Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (T\	VA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (S	ΓEL) (mg/m³)	325 mg/m <sup>3</sup> Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (S	FEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSI	1)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TW	/A) (mg/m³)	260 mg/m <sup>3</sup> Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TW	/A) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (ST	EL) (mg/m³)	325 mg/m <sup>3</sup> Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (ST	EL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ce	iling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA	)	The value in mg/m3 is approximate. Skin notation.
N-METHYLETHANOLAMINE			1
DNEL/DMEL (Workers)			
Acute - systemic effects, derm	al	40 mg/kg bodyweight/day	
Acute - systemic effects, inhal		260 mg/m <sup>3</sup>	
Acute - local effects, dermal		260 mg/cm <sup>2</sup>	
Long-term - systemic effects, o	dermal	40 mg/kg bodyweight/day	
Long-term - local effects, derm		260 mg/cm <sup>2</sup>	
Long-term - local effects, inhal		260 mg/m <sup>3</sup>	
DNEL/DMEL (General populat		200 mg/m	
Acute - systemic effects, derm		8 mg/kg body weight	
Acute - systemic effects, inhala		50 mg/m <sup>3</sup>	
Acute - systemic effects, mila	allon	8 mg/kg body weight	
Acute - local effects, inhalation	<b>)</b>	50 mg/m <sup>3</sup>	
Long-term - systemic effects, o		8 mg/kg bodyweight/day	
<b>č</b> ,		50 mg/m <sup>3</sup>	
Long-term - systemic effects, i		8 mg/kg bodyweight/day	
Long-term - systemic effects, dermal Long-term - local effects, inhalation			
0		50 mg/m³	
PNEC (Water)		154 mg/l	
PNEC aqua (freshwater)		154 mg/l	
PNEC aqua (marine water)		15.4 mg/l	
PNEC (Sediment)			
PNEC sediment (freshwater)		570.4 mg/kg dwt	
PNEC (Soil)			
PNEC soil		23.5 mg/kg dwt	
		23.5 mg/kg dwt 100 mg/kg	

### ULM-10529-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls	
Appropriate engineering controls	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Personal protective equipment	: Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.
Materials for protective clothing	: Wear suitable protective clothing and gloves.
Hand protection	: Wear suitable protective clothing and gloves.
Eye protection	: Wear eye protection. Chemical goggles or face shield with safety glasses.
Skin and body protection	: Wear suitable protective clothing, gloves and eye/face protection.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
Environmental exposure controls	: Avoid release to the environment.
SECTION 9: Physical and chen	nical properties
9.1. Information on basic physica	I and chemical properties
The properties listed below are for the solvent, the main	n component of this mixture.
Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 32.04 g/mol
Color	: Colorless
Odor	: Pungent

Appearance	: Liquid
Molecular mass	: 32.04 g/mol
Color	: Colorless
Odor	: Pungent
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -98 °C (-144 °F)
Freezing point	: No data available
Boiling point	: 64.7 °C (148.5 °F)
Flash point	: 9.7 °C (49.5 °F) - closed cup
Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)
Vapor pressure at 50 °C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)
Relative vapor density at 20 °C	: 1.11
Relative density	: No data available
Specific gravity / density	: 0.791 g/ml at 25 °C (77 °F)
Solubility	: Water: Completely miscible
Log Pow	: -0.77
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidizing properties	: Non oxidizing material according to EC criteria.
Explosion limits	: 6 - 36 % (V)

#### 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapour.

#### 10.2. Chemical stability

See storage and expiration date on CoA.

No dangerous reactions known under normal conditions of use.

### ULM-10529-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

### SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:vapour: Toxic if inhaled.

N-METHYLETHANOLAMINE UNLABELED 5 MG/ML IN METHANOL			
LD50 oral rat	1187 - 2769 mg/kg		
LD50 dermal rabbit	17100 mg/kg		
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h		
ATE CLP (oral)	100.000 mg/kg body weight		
ATE CLP (dermal)	17.100 mg/kg body weight		
ATE CLP (vapors)	3.000 mg/l/4h		
ATE CLP (dust, mist)	128.200 mg/l/4h		
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
N-METHYLETHANOLAMINE UNLABELED (10	09-83-1)		
LD50 oral rat	1391 mg/kg - female (OECD Test Guideline 401)		
LD50 dermal rabbit	1006 mg/kg - female (OECD Test Guideline 402)		
ATE CLP (oral)	1391.000 mg/kg body weight		
ATE CLP (dermal)	1006.000 mg/kg body weight		
100% METHANOL UNLABELED (67-56-1)			
LD50 oral rat	1187 - 2769 mg/kg		
LD50 dermal rabbit	17100 mg/kg		
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h		
ATE CLP (oral)	100.000 mg/kg body weight		
ATE CLP (dermal)	300.000 mg/kg body weight		
ATE CLP (vapors)	3.000 mg/l/4h		
ATE CLP (dust, mist)	128.200 mg/l/4h		
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
Skin corrosion/irritation	: Skin - Rabbit. Result: No skin irritation		
Serious eye damage/irritation	: Eyes - Rabbit. Result: No eye irritation		
Respiratory or skin sensitization	: Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)		
Germ cell mutagenicity	: AMES test : S. tymphimurium. Result: negative. fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - male and female Result: negative. Mouse - male and female. Result: Negative		
Carcinogenicity	: Not classified		
Reproductive toxicity	: Damage to fetus not classifiable. Fertility classification not possible from current data.		
Specific target organ toxicity – single exposure	: Causes damage to organs through prolonged or repeated exposure		
	Causes damage to organs		

N-METHYLETHANOLAMINE UNLABELED (109	-83-1)	
NOAEL (oral,rat)	50 mg/kg body weight male and female	
Specific target organ toxicity – repeated : exposure	The substance or mixture is not classified as specific target organ toxicant, repeated expose No data available	sure.
Aspiration hazard :	No aspiration toxicity classification.	
Potential Adverse human health effects and symptoms	This information is based on our current knowledge and is intended to describe the product the purposes of health, safety and environmental requirements only. It should not therefore construed as guaranteeing any specific property of the product. Effects due to Ingestion main include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans stomach.	e be ay
Symptoms/effects after inhalation :	Toxic if inhaled.	
23/07/2018	EN (English US)	8/14

### ULM-10529-S

Symptoms/effects after skin contact	:	Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	:	Causes serious eye irritation.
Symptoms/effects after ingestion	:	Toxic if swallowed.

SECTION 12: Ecological information	1		
12.1. Toxicity			
Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.		
N-METHYLETHANOLAMINE UNLABELED 5 MG/ML IN METHANOL			
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h		
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h		
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h		
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h		
N-METHYLETHANOLAMINE UNLABELED (109-83-1)			
LC50 fish 1	> 100 mg/l Danio rerio (zebra fish) - 96 h		
EC50 Daphnia 1	33 mg/l Daphnia magna (Water flea) - 48 h - (Directive 67/548/EEC, Annex V, C.2.)		
EC50 Daphnia 2	28.1 mg/l Desmodesmus subspicatus (green algae) - 72 h - (Directive 67/548/EEC, Annex V, C.3.)		
100% METHANOL UNLABELED (67-56-1)			
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h		
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h		
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h		
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h		
· · ·			

12.2. Persistence and degradability	12.2. Persistence and degradability			
N-METHYLETHANOLAMINE UNLABELED 5 M	N-METHYLETHANOLAMINE UNLABELED 5 MG/ML IN METHANOL			
Biochemical oxygen demand (BOD)	600 - 1200 mg/g			
Chemical oxygen demand (COD)	1420 mg/g			
ThOD	1500 mg/g			
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d			
N-METHYLETHANOLAMINE UNLABELED (109	9-83-1)			
Biodegradation	92 - 93 % - aerobic - Readily biodegradable - Exposure time 21 d - (OECD Test Guideline 301A)			
100% METHANOL UNLABELED (67-56-1)				
Biochemical oxygen demand (BOD)	600 - 1200 mg/g			
Chemical oxygen demand (COD)	1420 mg/g			
ThOD	1500 mg/g			
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d			
12.3. Bioaccumulative potential				
N-METHYLETHANOLAMINE UNLABELED 5 M	G/ML IN METHANOL			
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C			
Bioconcentration factor (BCF REACH)	1			
Log Pow	-0.77			
N-METHYLETHANOLAMINE UNLABELED (109	9-83-1)			
Log Pow	-0.91			
100% METHANOL UNLABELED (67-56-1)				
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C			
Bioconcentration factor (BCF REACH)	1			
Log Pow	-0.77			
12.4. Mobility in soil				
N-METHYLETHANOLAMINE UNLABELED 5 MG/ML IN METHANOL				
Ecology - soil	Not degradable in the soil.			
100% METHANOL UNLABELED (67-56-1)				
Ecology - soil	Not degradable in the soil.			

### ULM-10529-S

12.5. Results of PBT and vPvB assessme	12.5. Results of PBT and vPvB assessment			
N-METHYLETHANOLAMINE UNLABELED 5 MG/ML IN METHANOL				
PBT: not relevant – no registration required				
100% METHANOL UNLABELED (67-56-1)				
PBT: not relevant – no registration required				
12.6. Other adverse effects				
Other adverse effects	: Avoid release to the environment.			
Other information	: Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water.			
	Hydrolyses readily.			
SECTION 13: Disposal consideration	ns			
13.1. Waste treatment methods				
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.			
Product/Packaging disposal recommendations	<ul> <li>Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.</li> </ul>			
Ecology - waste materials	: Dispose of as unused product.			
SECTION 14: Transport information				
In accordance with ADR / RID / IMDG / IATA / A	 DN			
14.1. UN number				
UN-No.(DOT)	: 1230			
DOT NA no.	UN1230			
14.2. UN proper shipping name				
Proper Shipping Name (DOT)	: Methanol			
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120			
Hazard labels (DOT)	: 3 - Flammable liquid 6.1 - Poison			
	FLAMMABLE LIQUID 3 6			
DOT Symbols	: + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper shipping name appropriate for international and domestic transportation			
Packing group (DOT)	: II - Medium Danger			
DOT Special Provisions (49 CFR 172.102)	<ul> <li>IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.</li> <li>T7 - 4 178.274(d)(2) Normal</li></ul>			
	Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.			
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150			
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202			
DOT Packaging Bulk (49 CFR 173.xxx)	: 242			
DOT RQ	: 5000 lbs			
Marine pollutant	: No			
14.3. Additional information				
Emergency Response Guide (ERG) Number	: 131			

ULM-10529-S

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Overland transport	
Packing group (ADR)	: 11
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 336
Classification code (ADR)	: FT1
Hazard labels (ADR)	: 3 - Flammable liquids 6.1 - Toxic substances
Orange plates	<b>336</b> <b>1230</b>
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
Excepted quantities (ADR)	: E2
Transport by sea	
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a
	passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
MFAG-No	: 131
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
Civil Aeronautics Law	: Flammable liquids
14.4. Environmental hazards	
Other information	: No supplementary information available.
14.5. Special precautions for user	
14.6. Transport in bulk according to Anne	x II of MARPOL 73/78 and the IBC Code
Not applicable	
SECTION 15: Regulatory information	
15.1. US Federal regulations	
N-METHYLETHANOLAMINE UNLABELED 5 I	MG/ML IN METHANOL
Listed on the United States TSCA (Toxic Substa	ances Control Act) inventory
CERCLA RQ	5000 lb

	5000 D		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard		
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313		
N-METHYLETHANOLAMINE UNLABELED (109-83-1)			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard		

## ULM-10529-S

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-METHYLETHANOLAMINE UNLABELED (109-83-1)			
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313		
100% METHANOL UNLABELED (67-56-1)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
CERCLA RQ	5000 lb		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard		
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313		

### 15.2. International regulations

### CANADA

N-METHYLETHANOLAMINE UNLABELED 5 MG/ML IN METHANOL		
Listed on the Canadian DSL (Domestic Substances List)		
100% METHANOL UNLABELED (67-56-1)		
Listed on the Canadian DSL (Domestic Substances List)		

### 15.2.1. National regulations

No additional information available

15.3. US State regulations						
N-METHYLETHANOLAMINE UNLABELED 5 MG/ML IN METHANOL						
U.S California - Proposition 65 - Carcinogens List		Ν	lo			
U.S California - Proposition 65 - Developmental Toxicity		Y	/es			
U.S California - Proposition Toxicity - Female	n 65 - Reproductive	Ν	No			
U.S California - Proposition Toxicity - Male	n 65 - Reproductive	No				
State or local regulations		U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances				
N-METHYLETHANOLAMIN	E UNLABELED (109-83-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity		U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No		No	No		
100% METHANOL UNLAB	ELED (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity		U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	Yes		No	No		
N-METHYLETHANOLAMIN	E UNLABELED (109-83-1)					
State or local regulations						
U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List						
100% METHANOL UNLABELED (67-56-1)						
State or local regulations						
U.S Delaware - Pollutant E	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities					

#### ULM-10529-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 100% METHANOL UNLABELED (67-56-1)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations

U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

#### **SECTION 16: Other information**

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

#### Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3		
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3		
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4		
Eye Dam. 1	Serious eye damage/eye irritation Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation Category 2		
Flam. Liq. 2	Flammable liquids Category 2		
Skin Corr. 1	Skin corrosion/irritation Category 1		
Skin Irrit. 2	Skin corrosion/irritation Category 2		
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2		
STOT SE 1	Specific target organ toxicity (single exposure) Category 1		
STOT SE 3	Specific target organ toxicity (single exposure) Category 3		
H225	Highly flammable liquid and vapour		
H301	Toxic if swallowed		
H302	Harmful if swallowed		
H311	Toxic in contact with skin		
H312	Harmful in contact with skin		
H314	Causes severe skin burns and eye damage		
H315	Causes skin irritation		
H318	Causes serious eye damage		
H319	Causes serious eye irritation		
H331	Toxic if inhaled		
H335	May cause respiratory irritation		
H370	Causes damage to organs		
H373	May cause damage to organs through prolonged or repeated exposure		
R11	Highly flammable		
R35	Causes severe burns		
R36	Irritating to eyes		
R36/38	Irritating to eyes and skin		
R37	Irritating to respiratory system		
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed		
R41	Risk of serious damage to eyes		
R48/21/22	Harmful: danger of serious damage to health by prolonged exposure in contact with skin and if swallowed		
С	Corrosive		
F	Highly flammable		
Т	Toxic		
Xi	Irritant		
Xn	Harmful		
L	1		

NFPA health hazard

NFPA fire hazard

NFPA reactivity

: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

3 - Liquids and solids (including finely divided suspended ÷ solids) that can be ignited under almost all ambient temperature conditions.

: 0 - Material that in themselves are normally stable, even under fire conditions.



0

ULM-10529-S

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **Hazard Rating**

- : 2 Moderate Hazard Temporary or minor injury may occur Health Flammability : 3 Serious Hazard Physical
  - : 0 Minimal Hazard

#### CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product