

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 11/08/2020 Revision date: : Version: 1.0 ULM-11111-S

<b>SECTION 1: Identifica</b>	tion of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixtures
Product name	: 5-HYDROXYINDOLE-3-ACETIC ACID UNLABELED 100 UG/ML IN METHANOL
Product code	: ULM-11111-S
1.2. Relevant identified	d uses of the substance or mixture and uses advised against
1.2.1. Relevant identified	d uses
Main use category	: Professional use
Industrial/Professional use sp	bec : For professional use only
1.2.2. Uses advised aga	inst
No additional information ava	
	plier of the safety data sheet
Cambridge Isotope Laborator 50 Frontage Road Andover, MA 01810 USA	
USA: 1-800-322-1174 Int: cilsales@isotope.com www	1-978-749-8000 w.isotope.com
Emergency teleph	none number
Emergency numbers:	
Chemtrec: 1-800-424-9300 International: 1-703-741-597	
<b>SECTION 2: Hazards i</b>	identification
2.1. Classification of t	he substance or mixture
Classification according to	Regulation (EC) No. 1272/2008 [CLP]
Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapo	pur) H331
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 1	H370
Full text of hazard classes an	nd H-statements : see section 16
Classification according to	Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]
F; R11 T; R39/23/24/25 Xi; R36/38	
Full text of R-phrases: see se	action 16
GHS-US classification	

#### **GHS-US classification**

Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapour)	H331
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 1	H370

Full text of H statements : see section 16

METHANOL ULM-11111-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Adverse physicochemical, human health and environmental effects

Eyes, Kidney, Liver, Heart, Central nervous system. Highly flammable liquid and vapor. Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (if inhaled, if swallowed, in contact with skin). Toxic in contact with skin. Toxic if inhaled. Toxic if swallowed. Causes skin irritation. Causes serious eye irritation.

Labeling according to Regulation (EC) N	lo. 1272/2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS08 GHS06
Signal word (CLP)	: Danger
Hazard statements (CLP)	<ul> <li>H225 - Highly flammable liquid and vapor H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, heart, kidneys, liver, central nervous system) (in contact with skin, if inhaled, if swallowed)</li> </ul>
Precautionary statements (CLP)	<ul> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P233 - Keep container tightly closed.</li> <li>P240 - Ground/bond container and receiving equipment.</li> <li>P241 - Use explosion-proof electrical, lighting, ventilating equipment</li> <li>P260 - Do not breathe dust, mist, vapors, fume, gas, spray.</li> <li>P264 - Wash hands, forearms and face thoroughly after handling.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> </ul>
GHS-US labeling	
Hazard pictograms (GHS-US)	HS02 GHS08 GHS06
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	<ul> <li>H225 - Highly flammable liquid and vapor H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal Inhalation, oral)</li> </ul>
Precautionary statements (GHS-US)	<ul> <li>P210 - Keep away from heat, open flames, sparks No smoking.</li> <li>P233 - Keep container tightly closed.</li> <li>P240 - Ground/Bond container and receiving equipment</li> <li>P241 - Use explosion-proof electrical, lighting, ventilating equipment</li> <li>P242 - Use only non-sparking tools.</li> <li>P243 - Take precautionary measures against static discharge.</li> <li>P260 - Do not breathe dust, fume, mist, gas, spray, vapors.</li> <li>P261 - Avoid breathing dust, fume, gas, spray, vapors, mist.</li> <li>P264 - Wash hands, forearms and face thoroughly after handling.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P280 - Wear protective clothing, protective gloves.</li> <li>P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER</li> <li>P302+P352 - If on skin: Wash with plenty of water</li> <li>P303+P361+P338 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower</li> <li>P304+P340 - If in eyes: Rinse cautiously with water for several minutes. Remove contac lenses, if present and easy to do. Continue rinsing</li> <li>P307+P311 - If exposed: Call a poison center/doctor</li> </ul>

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P311 -	Call a	doctor,	a POISON CENTER	

- P312 Call a doctor, a POISON CENTER if you feel unwell
- P321 Specific treatment (see Hazardous component(s) for labeling on this label)
- P322 Specific treatment (see Hazard pictograms (CLP) on this label)
- P330 Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry

extinguishing powder to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

PBT: not relevant – no registration required

#### SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

••			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.987	F; R11 T; R39/23/24/25 Xi; R36/38
5-HYDROXYINDOLE-3-ACETIC ACID UNLABELED	(CAS-No.) 54-16-0 (EC-No.) 200-195-4 (EC Index-No.)	0.013	Not classified
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.987	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
5-HYDROXYINDOLE-3-ACETIC ACID UNLABELED	(CAS-No.) 54-16-0 (EC-No.) 200-195-4 (EC Index-No.)	0.013	Not classified
Name	Product identifier	%	GHS-US classification
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.987	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370
	(CAS-No.) 54-16-0	0.013	Not classified

#### Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	<ul> <li>If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.</li> </ul>
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

20, 2012 / Rules and Regulations	
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, i present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth Call a physician immediately.
4.2. Most important symptoms and ef	fects, both acute and delayed
Symptoms/effects	: Causes damage to organs (Eyes, heart, liver, kidneys, central nervous system, Skin) (in contact with skin, if inhaled, if swallowed).
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.
4.3. Indication of any immediate medi	cal attention and special treatment needed
Treat symptomatically.	
<b>SECTION 5: Firefighting measures</b>	
5.1. Extinguishing media	
Suitable extinguishing media	: Dry powder. Dry sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the	substance or mixture
Fire hazard	: Highly flammable liquid and vapor.
Reactivity	: Vapors may form flammable mixture with air. Highly flammable liquid and vapor.
5.3. Advice for firefighters	
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	<ul> <li>Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.</li> </ul>
Other information	: Use water spray to cool exposed surfaces.
SECTION 6: Accidental release me	easures
6.1. Personal precautions, protective	equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Prevent entry to sewers and public waters. Do	o not allow to enter drains or water courses. Avoid release to the environment.
6.3. Methods and material for contain	ment and cleaning up
For containment	: Dike and contain spill.
Methods for cleaning up	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13.	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust, fume, gas, spray, vapors, mist. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area.

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene	measures	:	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2.	Conditions for safe storage, includir	ŋg	any incompatibilities
Technica	al measures	:	Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Storage	conditions	:	Store in freezer (-20°C). Protect from light, air and moisture.
7.3.	Specific end use(s)		

No additional information available

### **SECTION 8: Exposure controls/personal protection**

3.1. Control parameters		
5-HYDROXYINDOLE-3-ACET	IC ACID UNLABELED 100 UG/ML IN METHANC	)L
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m <sup>3</sup> Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup> Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m <sup>3</sup> Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m <sup>3</sup> Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.
100% METHANOL UNLABEL	ED (67-56-1)	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m <sup>3</sup> Basis: NIOSH Recommended Exposure Limits

METHANOL ULM-11111-S

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL UNLAB	ELED (67-56-1)			
USA NIOSH	NIOSH REL (TWA) (ppm)		200 ppm Basis: NIOSH Recommended Exposure Limits	
USA NIOSH	NIOSH REL (S	STEL) (mg/m³)	325 mg/m <sup>3</sup> Basis: NIOSH Recommended Exposure Limits	
USA NIOSH	NIOSH REL (S	STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits	
USA NIOSH	Remark (NIOS	iH)	Potential for dermal absorption.	
USA OSHA	OSHA PEL (T)	NA) (mg/m³)	260 mg/m <sup>3</sup> Basis: USA. Occupational Exposure Limit (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	OSHA PEL (T)	NA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	OSHA PEL (S	TEL) (mg/m³)	325 mg/m <sup>3</sup> Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	OSHA PEL (S	TEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Ai Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	OSHA PEL (C	eiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	Remark (OSH/	A)	The value in mg/m3 is approximate. Skin notation.	
5-HYDROXYINDOLE-3-AC	ETIC ACID UNLA	BELED 100 UG/ML IN METHANOL		
DNEL/DMEL (Workers)				
Acute - systemic effects, der	mal	40 mg/kg bodyweight/day		
Acute - systemic effects, inh	alation	260 mg/m <sup>3</sup>		
Acute - local effects, dermal		260 mg/cm <sup>2</sup>		
Long-term - systemic effects	, dermal	40 mg/kg bodyweight/day		
Long-term - local effects, der		260 mg/cm <sup>2</sup>		
Long-term - local effects, inh		260 mg/m <sup>3</sup>		
DNEL/DMEL (General popul				
Acute - systemic effects, der		8 mg/kg body weight		
Acute - systemic effects, inh		50 mg/m <sup>3</sup>		
Acute - systemic effects, ora		8 mg/kg body weight		
Acute - local effects, inhalati		50 mg/m <sup>3</sup>		
Long-term - systemic effects, oral			8 mg/kg bodyweight/day	
Long-term - systemic effects		50 mg/m <sup>3</sup>		
Long-term - systemic effects, dermal		8 mg/kg bodyweight/day		
Long-term - local effects, inhalation		50 mg/m <sup>3</sup>		
PNEC (Water)		154 mg/l		
PNEC aqua (freshwater) PNEC aqua (marine water)		15.4 mg/l		
PNEC (Sediment)				
PNEC (Sediment) PNEC sediment (freshwater)	)	570.4 mg/kg dwt		
PNEC (Soil)	/			
PNEC (Soll)		23.5 mg/kg dwt		
PNEC (STP)				
	int	100 mg/kg		
PNEC sewage treatment pla				
PNEC sewage treatment pla .2. Exposure controls				

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment	: Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing	: Wear suitable protective clothing and gloves.
Hand protection	: Wear suitable protective clothing and gloves.
Eye protection	: Wear eye protection. Chemical goggles or face shield with safety glasses.
Skin and body protection	: Wear suitable protective clothing, gloves and eye/face protection.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
Environmental exposure controls	: Avoid release to the environment.

### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties The properties listed below are for the solvent, the main component of this mixture.

The properties listed below are for the solvent, the main compo	nent of this mixture.
Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 32.04 g/mol
Color	: Colorless
Odor	: Pungent
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -98 °C (-144 °F)
Freezing point	: No data available
Boiling point	: 64.7 °C (148.5 °F)
Flash point	: 9.7 °C (49.5 °F) - closed cup
Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	<ul> <li>130.3 hPa (97.7 mmHg) at 20 °C (68 °F);</li> <li>169.27 hPa (126.96 mmHg) at 25 °C (77 °F)</li> </ul>
Vapor pressure at 50 °C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)
Relative vapor density at 20 °C	: 1.11
Relative density	: No data available
Specific gravity / density	: 0.791 g/ml at 25 °C (77 °F)
Solubility	: Water: Completely miscible
Log Pow	: -0.77
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidizing properties	: Non oxidizing material according to EC criteria.
Explosion limits	: 6 - 36 % (V)
9.2 Other information	

9.2. Other information

No additi	onal information available
SECTIO	ON 10: Stability and reactivity
10.1.	Reactivity
Vapors m	nay form flammable mixture with air. Highly flammable liquid and vapor.
10.2.	Chemical stability
See stora	age and expiration date on CoA.
10.3.	Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:vapour: Toxic if inhaled.

5-HYDROXYINDOLE-3-ACETIC ACID UNLABELED 100 UG/ML IN METHANOL				
LD50 oral rat	1187 - 2769 mg/kg			
LD50 dermal rabbit	17100 mg/kg			
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h			
ATE CLP (oral)	100.000 mg/kg body weight			
ATE CLP (dermal)	300.000 mg/kg body weight			
ATE CLP (vapors)	3.000 mg/l/4h			
ATE CLP (dust, mist)	128.200 mg/l/4h			
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.			
100% METHANOL UNLABELED (67-56-1)				
LD50 oral rat	1187 - 2769 mg/kg			
LD50 dermal rabbit	17100 mg/kg			
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h			
ATE CLP (oral)	100.000 mg/kg body weight			
ATE CLP (dermal)	300.000 mg/kg body weight			
ATE CLP (vapors)	3.000 mg/l/4h			
ATE CLP (dust, mist)	128.200 mg/l/4h			
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.			
5-HYDROXYINDOLE-3-ACETIC ACID UNLAB	BELED (54-16-0)			
LD50, intraperitoneal, mouse	1,125 mg/kg Remarks: Behavioral: Somnolence (general depressed activity).			
Skin corrosion/irritation	: Skin - Rabbit - Result: No skin irritation			
Serious eye damage/irritation	: Eyes - Rabbit - Result: No eye irritation			
Respiratory or skin sensitization	: Maximisation Test - Guinea pig - Did not cause sensitization - (OECD 406 method)			
Germ cell mutagenicity	: AMES test : S. tymphimurium. Result: Negative - Fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - Male and female - Result: negative. Mouse - Male and female. Result: Negative			
Carcinogenicity	: Not classified			
5-HYDROXYINDOLE-3-ACETIC ACID UNLAB	BELED (54-16-0)			
Carcinogenicity, mouse	Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Tumorigenic: Tumor types after systemic administration not seen spontaneously.			
Reproductive toxicity	: Damage to fetus not classifiable. Fertility classification not possible from current data.			
Specific target organ toxicity – single exposure	: Causes damage to organs through prolonged or repeated exposure			
Specific target organ toxicity – repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.			
Aspiration hazard	: Not classified			
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach.			
	Stoffiach.			
Symptoms/effects after inhalation	: Toxic if inhaled.			
Symptoms/effects after inhalation Symptoms/effects after skin contact				

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion

: Toxic if swallowed.

SECTION 12: Ecological information	on
2.1. Toxicity	
cology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
5-HYDROXYINDOLE-3-ACETIC ACID UNL	ABELED 100 UG/ML IN METHANOL
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h
100% METHANOL UNLABELED (67-56-1)	
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h
2.2. Persistence and degradability	
5-HYDROXYINDOLE-3-ACETIC ACID UNL	ABELED 100 UG/ML IN METHANOL
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d
100% METHANOL UNLABELED (67-56-1)	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d
2.3. Bioaccumulative potential	
5-HYDROXYINDOLE-3-ACETIC ACID UNL	ABELED 100 UG/ML IN METHANOL
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77
100% METHANOL UNLABELED (67-56-1)	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	
Log Pow	-0.77
2.4. Mobility in soil	
·	
5-HYDROXYINDOLE-3-ACETIC ACID UNL	
Ecology - soil	Not degradable in the soil.
100% METHANOL UNLABELED (67-56-1)	
Ecology - soil	Not degradable in the soil.
2.5. Results of PBT and vPvB assess	ment
5-HYDROXYINDOLE-3-ACETIC ACID UNL	ABELED 100 UG/ML IN METHANOL
PBT: not relevant – no registration required	
100% METHANOL UNLABELED (67-56-1)	
PBT: not relevant – no registration required	
2.6. Other adverse effects	
Other adverse effects	: Avoid release to the environment.
Other information	: Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water.
	Hydrolyses readily.

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Diapaged consideration	
SECTION 13: Disposal consideration	
13.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.
SECTION 14: Transport information	
In accordance with ADR / RID / IMDG / IATA / AI	2N
14.1. UN number	
UN-No.(DOT)	: 1230
DOT NA no.	UN1230
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Methanol
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid 6.1 - Poison
	FLAMMABLE LIQUID 3 6
DOT Symbols	: + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper shipping name appropriate for international and domestic transportation
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
14.3. Additional information	
Emergency Response Guide (ERG) Number	: 131
Other information	: No supplementary information available.
Overland transport Hazard identification number (Kemler No.) Orange plates	336 336 1230
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
Excepted quantities (ADR)	: E2

METHANOL ULM-11111-S

### Safety Data Sheet

DOT Vessel Stowage Other

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 Transport by sea

 DOT Vessel Stowage Location
 :

B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
40 - Stow "clear of living quarters"

# MFAG-No

Air transport		
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	60 L
Civil Aeronautics Law	:	Flammable liquids

: 131

14.4.	Environmental hazards	
Other in	formation	: No supplementary information available.
14.5.	Special precautions for user	
14.6.	Transport in bulk according to	Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information 15.1. US Federal regulations

5-HYDROXYINDOLE-3-ACETIC ACID UNLAB	ELED 100 UG/ML IN METHANOL			
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
CERCLA RQ 5000 lb				
SARA Section 302 Threshold Planning Quantity (TPQ)				
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	SARA Section 313 - Emission Reporting Subject to reporting requirements of United States SARA Section 313			
100% METHANOL UNLABELED (67-56-1)				
Listed on the United States TSCA (Toxic Substa	Listed on the United States TSCA (Toxic Substances Control Act) inventory			
CERCLA RQ	5000 lb			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313			
5-HYDROXYINDOLE-3-ACETIC ACID UNLABELED (54-16-0)				
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302.			
SARA Section 313 - Emission Reporting	Not subject to reporing requirements of the United States SARA Section 313.			

#### 15.2. International regulations

#### CANADA

5-HYDROXYINDOLE-3-ACETIC ACID UNLABELED 100 UG/ML IN METHANOL	
Listed on the Canadian DSL (Domestic Substances List)	
100% METHANOL UNLABELED (67-56-1)	
Listed on the Canadian DSL (Domestic Substances List)	

#### 15.2.1. National regulations

No additional information available

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations	;				
5-HYDROXYINDOLE-3-AC	ETIC ACID UNLABELED 1	00 UG/ML IN METHANOL()			
U.S California - Proposition 65 - Carcinogens List		No			
U.S California - Propositio Toxicity	on 65 - Developmental	Yes			
U.S California - Propositio Toxicity - Female	on 65 - Reproductive	No			
U.S California - Propositio Toxicity - Male	on 65 - Reproductive	No			
State or local regulations		U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances			
100% METHANOL UNLAB	ELED (67-56-1)	•			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	Yes	No	No		
5-HYDROXYINDOLE-3-AC	ETIC ACID UNLABELED (5	54-16-0)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
100% METHANOL UNLAB	ELED (67-56-1)				
State or local regulations	. ,				
U.S Idaho - Non-Carcinog U.S Massachusetts - Righ U.S Pennsylvania - RTK ( U.S New Jersey - Right to	nt To Know List	cceptable Ambient Concentration	ons		
5-HYDROXYINDOLE-3-AC	ETIC ACID UNLABELED (5	54-16-0)			
State or local regulations					
U.S Pennsylvania - RTK ( U.S New Jersey - Right to	(Right to Know) List S Know Hazardous Substanc	e List			

### **SECTION 16: Other information**

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

### Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation

METHANOL ULM-11111-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H331	Toxic if inhaled
H370	Causes damage to organs
R11	Highly flammable
R36/38	Irritating to eyes and skin
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
F	Highly flammable
Т	Toxic
Xi	Irritant

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	<ul> <li>3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.</li> </ul>
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

#### CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product