

### Safety Data Sheet

 according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 Date of issue: 26/08/2020
 Revision date:
 :
 Version: 1.0

 ULM-11147-S

SECTION 1: Identificati	ion of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixtures
Product name	: P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED 100 UG/ML IN NONANE
Product code	: ULM-11147-S
1.2. Relevant identified	uses of the substance or mixture and uses advised against
1.2.1. Relevant identified	uses
Main use category	: Professional use
Industrial/Professional use spe	ec : For professional use only
1.2.2. Uses advised again	nst
No additional information available	able
	lier of the safety data sheet
Cambridge Isotope Laboratorie 50 Frontage Road Andover, MA 01810 USA	es, Inc.
USA: 1-800-322-1174 Int: 1- cilsales@isotope.com www.	-978-749-8000 isotope.com
Emergency telepho	one number
Emergency numbers:	
Chemtrec: 1-800-424-9300 (2 International: 1-703-741-5970	
<b>SECTION 2: Hazards id</b>	lentification
2.1. Classification of the	e substance or mixture
Classification according to F	Regulation (EC) No. 1272/2008 [CLP]
Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:vapou	r) H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Full text of hazard classes and	H-statements : see section 16
Classification according to E	Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]
R10	
Xn; R20	
Xn; R65 Xi; R36/38	
R67	
Full text of R-phrases: see sec	tion 16
GHS-US classification	
Flom Lig 2 H22	

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of H statements : see section 16

### NONANE ULM-11147-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Adverse physicochemical, human health and environmental effects

Central Nervous System. Flammable liquid and vapor. May cause drowsiness or dizziness. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.



### NONANE ULM-11147-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry
extinguishing powder to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in
accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Not applicable

3.2. Mixtures			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.986	R10 Xn; R20 Xn; R65 Xi; R36/38 R67
P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED	(CAS-No.) 27176-95-0	0.014	Xi; R36/37/38
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED	(CAS-No.) 27176-95-0	0.014	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS-No.) 111-84-2	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED	(CAS-No.) 27176-95-0	0.014	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

#### Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
4.2. Most important symptoms and effec	ts, both acute and delayed
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.

## NONANE ULM-11147-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.
4.3. Indication of any immediate me	edical attention and special treatment needed
Treat symptomatically.	
<b>SECTION 5: Firefighting measur</b>	es
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. Alcohol resistant foam.
5.2. Special hazards arising from the	ne substance or mixture
Fire hazard	: Flammable liquid and vapor.
Reactivity	: Flammable liquid and vapor. Vapors may form flammable mixture with air.
5.3. Advice for firefighters	
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release I	neasures
6.1. Personal precautions, protection	ve equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	Avoid release to the environment.
6.3. Methods and material for conta	ainment and cleaning up
For containment	: Dike and contain spill. Dispose as hazardous waste. Comply with local regulations for disposal.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13.	
SECTION 7: Handling and storage	ge
7.1. Precautions for safe handling	
Additional hazards when processed	: Avoid all contact with skin, eyes, or clothing. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the manufacturer). Take precautionary measures against static discharges.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Technical measures	: Store in a well-ventilated place. Keep container tightly closed. Keep dry. Ground/bond containe and receiving equipment.
	and receiving equipment.

#### 7.3. Specific end use(s)

No additional information available

### NONANE ULM-11147-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure c	ontrols/personal protection	
.1. Control parameters		
P-N-NONYLPHENOL TRIETH	OXYLATE UNLABELED 100 UG/ML IN NO	NANE
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.
N-NONANE UNLABELED (11	1-84-2)	1
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.

#### 8.2. **Exposure controls**

Appropriate engineering controls

Personal protective equipment

: Ensure good ventilation of the work station.

: Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.



Materials for protective clothing : Wear suitable protective clothing and gloves. Hand protection : protective gloves. Chemical goggles or face shield. Chemical goggles or safety glasses. Eve protection • Wear suitable protective clothing, gloves and eye/face protection. Skin and body protection · Where exposure through inhalation may occur from use, respiratory protection equipment is Respiratory protection recommended. Approved respirator. : Avoid release to the environment. Environmental exposure controls

### **SECTION 9: Physical and chemical properties**

9.1. Information on basic ph	sical and chemical properties	
The properties listed below are for the solvent, the main component of this mixture.		
Physical state	: Liquid	
Appearance	: Liquid	

## NONANE ULM-11147-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

· · · · · · · · · · · · · · · · · · ·	
Molecular mass	: 128.3 g/mol
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31 °C (87.8 °F) - closed cup
Auto-ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.718 g/ml at 25 °C (77 °F)
Solubility	: Water: 0.0002 % at 25 °C (77 °F) - slightly soluble
Log Pow	: 5.65
Log Kow	: No data available
Viscosity, kinematic	: <= 1.008 mm <sup>2</sup> /s at 20 °C (68 °F)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 0.87 - 2.9 % (V)

#### 9.2. Other information

No additional information available

SECTION 10: Stability and reactivity	SECTION 10: Stability and reactivity		
10.1. Reactivity			
Flammable liquid and vapor. Vapors may form flan	nmable mixture with air.		
10.2. Chemical stability			
See storage and expiration date on CoA.			
10.3. Possibility of hazardous reactions			
No dangerous reactions known under normal conc	litions of use.		
10.4. Conditions to avoid			
Avoid contact with hot surfaces. Heat. No flames, r	no sparks. Eliminate all sources of ignition.		
10.5. Incompatible materials			
No additional information available			
10.6. Hazardous decomposition products			
Carbon oxides (CO, CO2).			
SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Acute toxicity	Inhalation:vapour: Harmful if inhaled.		
P-N-NONYLPHENOL TRIETHOXYLATE UNLA	BELED 100 UG/ML IN NONANE		
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h		
ATE CLP (vapors)	11.000 mg/l/4h		
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)		
Additional information : S. Typhimurium Result: negative			
N-NONANE UNLABELED (111-84-2)			
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h		
ATE CLP (vapors)	11.000 mg/l/4h		

### NONANE ULM-11147-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-NONANE UNLABELED (111-84-2)	
Additional information	: S. Typhimurium Result: negative
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity - single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

<b>SECTION 12: Ecological information</b>	
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

#### 12.2. Persistence and degradability

### No additional information available

12.3. Bioaccumulative potential		
P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED 100 UG/ML IN NONANE		
Log Pow	5.65	
Bioaccumulative potential	Indication of bioaccumulation.	
N-NONANE UNLABELED (111-84-2)		
Log Pow	5.65	
Bioaccumulative potential	Indication of bioaccumulation.	
12.4. Mobility in soil		
No additional information available		
12.5. Results of PBT and vPvB assessment		
No additional information available		

12.6. Other adverse effects

Other adverse effects

: Disposal must be done according to official regulations.

SECTION 13: Disposal consideration	1S
13.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.
<b>SECTION 14: Transport information</b>	
In accordance with ADR / RID / IMDG / IATA / A	DN
14.1. UN number	

## NONANE ULM-11147-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Nonanes
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
	FLAMMABLE LIQUID
Packing group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	<ul> <li>B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.</li> <li>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).</li> <li>T2 - 1.5 178.274(d)(2) Normal</li></ul>
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
Marine pollutant	: No
14.3.         Additional information           Emergency Response Guide (ERG) Number           Other information	: 128
Other information	: No supplementary information available.
Overland transport	
Packing group (ADR)	: III
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 30
Classification code (ADR)	: F1
Hazard labels (ADR)	: 3 - Flammable liquids
Orange plates	30 1920
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	51
EAC	: 3Y
Excepted quantities (ADR)	: E1
Transport by sea	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
MFAG-No	: 128

## NONANE ULM-11147-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport		
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	220 L
Civil Aeronautics Law	:	Flammable liquids

14.4.	Environmental hazards	
Other in	formation	: No supplementary information available.
14.5.	Special precautions for user	
14.6.	6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	

Not applicable

<b>SECTION 15: Regulatory information</b>		
15.1. US Federal regulations		
P-N-NONYLPHENOL TRIETHOXYLATE UNLA	BELED 100 UG/ML IN NONANE	
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.	
N-NONANE UNLABELED (111-84-2)		
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.	
P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED (27176-95-0)		
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313	

#### 15.2. International regulations

#### CANADA

P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED 100 UG/ML IN NONANE
Listed on the Canadian DSL (Domestic Substances List)
N-NONANE UNLABELED (111-84-2)
Listed on the Canadian DSL (Domestic Substances List)

#### 15.2.1. National regulations

No additional information available

15.3. US State regulations

P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED 100 UG/ML IN NONANE()		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	
State or local regulations	U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S New Jersey - Right to Know Hazardous Substance List U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List	

### NONANE ULM-11147-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P-N-NONYLPHENOL TRIE	THOXYLATE UNLABELED 1	Ŭ		
		U.S New York - Reporting of	Releases Part 597 - List of Ha	azardous Substances
N-NONANE UNLABELED (	111-84-2)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
P-N-NONYLPHENOL TRIE	THOXYLATE UNLABELED (	27176-95-0)		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
N-NONANE UNLABELED (	111-84-2)			
State or local regulations	-			
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S New Jersey - Right to Know Hazardous Substance List U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances				
P-N-NONYLPHENOL TRIETHOXYLATE UNLABELED (27176-95-0)				
State or local regulations				
U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List				

### **SECTION 16: Other information**

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

#### Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
R10	Flammable
R20	Harmful by inhalation
R36/37/38	Irritating to eyes, respiratory system and skin
R36/38	Irritating to eyes and skin
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
Xi	Irritant
Xn	Harmful

### NONANE ULM-11147-S

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product