

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 19/01/2021 Revision date: : Version: 1.0

ULM-11175-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Product name : 1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN

METHANOL

Product code : ULM-11175-

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation) H331
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT SE 1 H370

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11 T; R23/24/25 Xi; R36/38

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 H225
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation:vapour) H331
Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 1 H370
Full text of H statements : see section 16

19/01/2021 EN (English US) 1/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. **Label elements**

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







Signal word (CLP) : Danger

H225 - Highly flammable liquid and vapor Hazard statements (CLP)

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H315 - Causes skin irritation H319 - Causes serious eye irritation

H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (in

contact with skin, if inhaled, if swallowed)

Precautionary statements (CLP) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P260 - Do not breathe fume, mist, spray, vapors. P264 - Wash both hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

GHS-US labeling

Hazard pictograms (GHS-US)







GHS06

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H225 - Highly flammable liquid and vapor

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H315 - Causes skin irritation H319 - Causes serious eye irritation

H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal,

Inhalation, oral)

Precautionary statements (GHS-US) P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe fume, mist, spray, vapors. P261 - Avoid breathing fume, mist, spray, vapors. P264 - Wash Both hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, face protection, protective clothing, protective gloves.

P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P311 - Call a doctor, a POISON CENTER

P312 - Call a doctor, a POISON CENTER if you feel unwell

P321 - Specific treatment (see Hazard pictograms (CLP) on this label)

EN (English US) 19/01/2021 2/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361 - Take off immediately all contaminated clothing.

P362 - Take off contaminated clothing and wash before reuse.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to Comply with applicable regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.9937	F; R11 T; R39/23/24/25 Xi; R36/38
1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED	(CAS-No.) 865-86-1 (EC Index-No.)	0.0063	Xi; R36/37/38
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]

Name	Product identifier	%	Regulation (EC) No. 1272/2008 [CLP]
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.9937	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED	(CAS-No.) 865-86-1 (EC Index-No.)	0.0063	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Name	Product identifier	%	GHS-US classification
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.9937	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370
1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED	(CAS-No.) 865-86-1	0.0063	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.

First-aid measures after skin contact

: Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

19/01/2021 EN (English US) 3/13

Safety Data Sheet

First-aid measures after ingestion

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Call a physician immediately.

Most important symptoms and effects, both acute and delayed : Causes damage to organs (Eyes, heart, liver, kidneys, central nervous system, Skin) (in

contact with skin, if inhaled, if swallowed).

Symptoms/effects after inhalation

Symptoms/effects after skin contact Toxic in contact with skin. Causes skin irritation.

Symptoms/effects after eye contact Causes serious eye irritation.

Symptoms/effects after ingestion Toxic if swallowed.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Symptoms/effects

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Dry powder. Dry sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

: Vapors may form flammable mixture with air. Highly flammable liquid and vapor. Reactivity

5.3. Advice for firefighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing. Wear recommended personal protective equipment.

Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth.

Other information Use water spray to cool exposed surfaces.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Avoid release to the environment.

Methods and material for containment and cleaning up 6.3.

For containment

Methods for cleaning up

Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation

Other information : Dispose of materials or solid residues at an authorized site.

Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust, fume, gas, spray, vapors, mist. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area.

Hygiene measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

EN (English US) 19/01/2021 4/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep

container tightly closed. Store locked up.

Storage conditions : Store at room temperature away from light and moisture.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

USA NIOSH

1H 1H 2H 2H-PERFI LIORO-1	-DODECANOL (10:2 FTOH) UNLABELED 5	50 LIG/MLIN METHANOL
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold
· ·	W. 1 /	Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.
100% METHANOL UNLABEL	.ED (67-56-1)	
Italy - Portugal - USA ACGIH		200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³ Basis: NIOSH Recommended Exposure Limits

19/01/2021 EN (English US) 5/13

200 ppm Basis: NIOSH Recommended Exposure

Limits

NIOSH REL (TWA) (ppm)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% METHANOL UNLABELED (67-56-1)		
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	40 mg/kg bodyweight/day
Acute - systemic effects, inhalation	260 mg/m³
Acute - local effects, dermal	260 mg/cm ²
Long-term - systemic effects, dermal	40 mg/kg bodyweight/day
Long-term - local effects, dermal	260 mg/cm ²
Long-term - local effects, inhalation	260 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	8 mg/kg body weight
Acute - systemic effects, inhalation	50 mg/m³
Acute - systemic effects, oral	8 mg/kg body weight
Acute - local effects, inhalation	50 mg/m³
Long-term - systemic effects,oral	8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	50 mg/m³
Long-term - systemic effects, dermal	8 mg/kg bodyweight/day
Long-term - local effects, inhalation	50 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	154 mg/l
PNEC aqua (marine water)	15.4 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	570.4 mg/kg dwt
PNEC (Soil)	
PNEC soil	23.5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/kg

8.2. Exposure controls

Appropriate engineering controls

19/01/2021 EN (English US) 6/13

[:] Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.









Materials for protective clothing : Wear suitable protective clothing and gloves. Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses.

Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

Appearance : Liquid

Molecular mass : 32.04 g/mol

Color : Colorless

Odor : Pungent

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : -98 °C (-144 °F) Freezing point : No data available Boiling point : 64.7 °C (148.5 °F)

Flash point : 9.7 °C (49.5 °F) - closed cup

Auto-ignition temperature : $455 \, ^{\circ}\text{C} \, (851 \, ^{\circ}\text{F})$ at 1,013 hPa (760 mmHg)

Decomposition temperature : No data available Flammability (solid, gas) : No data available

Vapor pressure : 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)

Vapor pressure at 50 °C : 546.6 hPa (410 mmHg) at 50 °C (122 °F)

Relative vapor density at 20 °C : 1.11

Relative density : No data available

Specific gravity / density : 0.791 g/ml at 25 °C (77 °F)
Solubility : Water: Completely miscible

Log Pow : -0.77

Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : Product is not explosive.

Oxidizing properties : Non oxidizing material according to EC criteria.

Explosion limits : 6 - 36 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

19/01/2021 EN (English US) 7/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

Incompatible materials

Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.

Hazardous decomposition products

Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects		
Acute toxicity	Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: Toxic if inhaled.	
1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL		
LD50 oral rat	1187 - 2769 mg/kg	
LD50 dermal rabbit	17100 mg/kg	
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h	
ATE CLP (oral)	100.000 mg/kg body weight	
ATE CLP (dermal)	300.000 mg/kg body weight	
ATE CLP (vapors)	3.000 mg/l/4h	
ATE CLP (dust, mist)	128.200 mg/l/4h	
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
100% METHANOL UNLABELED (67-56-1)		
LD50 oral rat	1187 - 2769 mg/kg	
LD50 dermal rabbit	17100 mg/kg	
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h	
ATE CLP (oral)	100.000 mg/kg body weight	
ATE CLP (dermal)	300.000 mg/kg body weight	
ATE CLP (vapors)	3.000 mg/l/4h	
ATE CLP (dust, mist)	128.200 mg/l/4h	
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.	

Skin corrosion/irritation	: Skin - Rabbit. Result: No skin irritation
Serious eve damage/irritation	: Eves - Rabbit, Result: No eve irritation

Respiratory or skin sensitization : Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)

AMES test: S. tymphimurium. Result: Negative. Fibroblast. Result: Negative. Mutation in Germ cell mutagenicity mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test,

chromosomal analysis) - Mouse - male and female Result: Negative. Mouse - Male and female. Result: Negative

Carcinogenicity : Not classified

Reproductive toxicity Damage to fetus not classifiable. Fertility classification not possible from current data.

Specific target organ toxicity - single exposure Causes damage to organs through prolonged or repeated exposure

Specific target organ toxicity - repeated exposure

: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach.

Symptoms/effects after inhalation Toxic if inhaled.

Symptoms/effects after skin contact : Toxic in contact with skin. Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Toxic if swallowed.

19/01/2021 EN (English US) 8/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

ALLALI QUI DEDELLIODO A DODECANOL (40-2 FTOLVINI ADELED EQUICINI IN METHANOL		
1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL		
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h	
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h	
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h	
100% METHANOL UNLABELED (67-56-1)		
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h	
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h	
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h	
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h	

12.2. Persistence and degradability

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL	
600 - 1200 mg/g	
1420 mg/g	
1500 mg/g	

100% METHANOL UNLABELED (67-56-1)	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d

12.3. Bioaccumulative potential

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77

100% METHANOL UNLABELED (67-56-1)	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77

12.4. Mobility in soil

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL		
Ecology - soil	Not degradable in the soil.	
100% METHANOL UNLABELED (67-56-1)		
Fcology - soil Not degradable in the soil		

12.5. Results of PBT and vPvB assessment

100% METHANOL UNLABELED (67-56-1)	
	PBT: not relevant – no registration required

12.6. Other adverse effects

Other adverse effects : Avoid release to the environment.

Other information : Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water. Hydrolyses readily.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.

Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed

professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

19/01/2021 EN (English US) 9/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

UN number

UN-No.(DOT) : 1230 DOT NA no. UN1230

14.2 **UN** proper shipping name

Proper Shipping Name (DOT) : Methanol

3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 Class (DOT)

3 - Flammable liquid Hazard labels (DOT)

6.1 - Poison





DOT Symbols

+ - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper shipping name appropriate for international and domestic transportation

Packing group (DOT)

: II - Medium Danger

DOT Special Provisions (49 CFR 172.102)

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal...... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

Additional information

Emergency Response Guide (ERG) Number : 131

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 336 Classification code (ADR)

Hazard labels (ADR) 3 - Flammable liquids

6.1 - Toxic substances



Orange plates

336 230

Tunnel restriction code (ADR) : D/E Limited quantities (ADR) 11 Excepted quantities (ADR) : E2

19/01/2021 EN (English US) 10/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

MFAG-No : 131

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	

100% METHANOL UNLABELED (67-56-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
CERCLA RQ	5000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED (865-86-1)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.

15.2. International regulations

CANADA

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL

Listed on the Canadian DSL (Domestic Substances List)

100% METHANOL UNLABELED (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

19/01/2021 EN (English US) 11/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED 50 UG/ML IN METHANOL()		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	Yes	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	
State or local regulations	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances	
100% METHANOL UNI ABELED (67-56-1)		

100% METHANOL UNLABELED (67-56-1)

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED (865-86-1)

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

100% METHANOL UNLABELED (67-56-1)

State or local regulations

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances

1H,1H,2H,2H-PERFLUORO-1-DODECANOL (10:2 FTOH) UNLABELED (865-86-1)

State or local regulations

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3	
Acute Tox. 3 (Inhalation)	e Tox. 3 (Inhalation) Acute toxicity (inhalation) Category 3	
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3	
Eye Irrit. 2	Serious eye damage/eye irritation Category 2	
Flam. Liq. 2	Flammable liquids Category 2	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
STOT SE 1	Specific target organ toxicity (single exposure) Category 1	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H225	Highly flammable liquid and vapor	
H301	Toxic if swallowed	
H311	Toxic in contact with skin	
H315	Causes skin irritation	
H319	Causes serious eye irritation	

19/01/2021 EN (English US) 12/13

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H331	Toxic if inhaled
H335	May cause respiratory irritation
H370	Causes damage to organs
R11	Highly flammable
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed
R36/37/38	Irritating to eyes, respiratory system and skin
R36/38	Irritating to eyes and skin
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
F	Highly flammable
Т	Toxic
Xi	Irritant

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause


temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient

temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even

under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

19/01/2021 EN (English US) 13/13