

PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED 50 UG/ML IN METHANOL

Safety Data Sheet

 according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 Date of issue: 09/09/2021
 Revision date:
 Version: 1.0

 ULM-12322-S

SECTION 4. Identi	ination of the cubet	oncolmisture and of the company/undertaking
		ance/mixture and of the company/undertaking
1.1. Product ident		1Patrone
Product form		
Product name		PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED 50 UG/ML IN METHANOL
Product code	:	ULM-12322-S
1.2. Relevant iden	tified uses of the substar	nce or mixture and uses advised against
1.2.1. Relevant iden	tified uses	
Main use category	:	Professional use
Industrial/Professional us	se spec :	For professional use only
1.2.2. Uses advised	against	
No additional information	•	
	supplier of the safety dat	ta chaot
Cambridge Isotope Labo		נמ הווכדו
50 Frontage Road		
Andover, MA 01810		
USA		
USA: 1-800-322-1174		
cilsales@isotope.com	www.isotope.com	
	lephone number	
Emergency numbers:		
Chemtrec: 1-800-424-93 International: 1-703-741		
SECTION 2: Hazar	ds identification	
2.1. Classification	of the substance or mixt	ture
Classification accordin	g to Regulation (EC) No.	1272/2008 [CLP]
Flam. Liq. 2	H225	
Acute Tox. 3 (Oral)	H301	
Acute Tox. 3 (Dermal)	H311	
Acute Tox. 3 (Inhalation:		
Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
STOT SE 1	H370	
Full text of hazard classe	es and H-statements : see s	section 16
Classification accordin	a to Directive 67/548/EEC	C [DSD] or 1999/45/EC [DPD]
F; R11	•	
T; R39/23/24/25		
Xi; R36/38		

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 Acute Tox. 3 (Oral) Acute Tox. 3 (Dermal) Acute Tox. 3 (Inhalation:vapour) Skin Irrit. 2 Eye Irrit. 2A	H225 H301 H311 H331 H315 H319
STOT SE 1	H370

Full text of H statements : see section 16

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Eyes, Kidney, Liver, Heart, Central nervous system. Highly flammable liquid and vapor. Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (if inhaled, if swallowed, in contact with skin). Toxic in contact with skin. Toxic if inhaled. Toxic if swallowed. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements	
Labeling according to Regulation (EC) N	lo. 1272/2008 [CLP]
Hazard pictograms (CLP)	
Signal word (CLD)	GHS02 GHS08 GHS06
Signal word (CLP) Hazard statements (CLP)	: Danger : H225 - Highly flammable liquid and vapor
	 H225 - Highly harmable liquid and vapor H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, heart, kidneys, liver, central nervous system) (in contact with skin, if inhaled, if swallowed)
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment P260 - Do not breathe dust, mist, vapors, fume, gas, spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.
GHS-US labeling	
Hazard pictograms (GHS-US)	HS02 GHS08 GHS06
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	 H225 - Highly flammable liquid and vapor H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal, Inhalation, oral)
Precautionary statements (GHS-US)	 P210 - Keep away from heat, open flames, sparks No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical, lighting, ventilating equipment P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust, fume, mist, gas, spray, vapors. P261 - Avoid breathing dust, fume, gas, spray, vapors, mist. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective clothing, protective gloves. P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
	P307+P311 - If exposed: Call a poison center/doctor
09/09/2021	EN (English US) 2/13

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P311 Call a doctor, a POISON CENTER
- P312 Call a doctor, a POISON CENTER if you feel unwell
- P321 Specific treatment (see Hazardous component(s) for labeling on this label)
- P322 Specific treatment (see Hazard pictograms (CLP) on this label)
- P330 Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry
- extinguishing powder to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. **Other hazards**

PBT: not relevant - no registration required

SECTION 3: Composition/Information on ingredients

3.1. **Substances**

Not applicable

32 **Mixtures**

Name	Product identifier	%	Classification according to
			Directive 67/548/EEC
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.9937	F; R11 T; R39/23/24/25 Xi; R36/38
PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED	(CAS-No.) 2806-16-8	0.0063	T; R25 Xn; R20 N; R51/53
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.9937	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED	(CAS-No.) 2806-16-8	0.0063	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 2, H411
Name	Product identifier	%	GHS-US classification
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.9937	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370
PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED	(CAS-No.) 2806-16-8	0.0063	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Inhalation), H332 Aquatic Chronic 2, H411

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures			
4.1. Description of first aid measures			
First-aid measures general	: If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.		

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.
First-aid measures after skin contact	 Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, i present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth Call a physician immediately.
4.2. Most important symptoms and	effects, both acute and delayed
Symptoms/effects	: Causes damage to organs (Eyes, heart, liver, kidneys, central nervous system, Skin) (in contact with skin, if inhaled, if swallowed).
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.
4.3. Indication of any immediate me	dical attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measure	9S
5.1. Extinguishing media	
Suitable extinguishing media	: Dry powder. Dry sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the	e substance or mixture
Fire hazard	: Highly flammable liquid and vapor.
Reactivity	: Vapors may form flammable mixture with air. Highly flammable liquid and vapor.
5.3. Advice for firefighters	
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.
Other information	: Use water spray to cool exposed surfaces.
SECTION 6: Accidental release n	neasures
	e equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.
	with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should
Emergency procedures	with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should
Emergency procedures 6.1.2. For emergency responders	 with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate. Do not attempt to take action without suitable protective equipment. For further information
Emergency procedures 6.1.2. For emergency responders Protective equipment 6.2. Environmental precautions	 with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate. Do not attempt to take action without suitable protective equipment. For further information
Emergency procedures 6.1.2. For emergency responders Protective equipment 6.2. Environmental precautions Prevent entry to sewers and public waters. I	 with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures 6.1.2. For emergency responders Protective equipment 6.2. Environmental precautions Prevent entry to sewers and public waters. I	 with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures 6.1.2. For emergency responders Protective equipment 6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for contains	 with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. inment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local
 Emergency procedures 6.1.2. For emergency responders Protective equipment 6.2. Environmental precautions Prevent entry to sewers and public waters. If 6.3. Methods and material for containment 	 with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. inment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public
Emergency procedures 6.1.2. For emergency responders Protective equipment 6.2. Environmental precautions Prevent entry to sewers and public waters. I 6.3. Methods and material for contal For containment Methods for cleaning up	 with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Do not allow to enter drains or water courses. Avoid release to the environment. inment and cleaning up Dike and contain spill. Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling ar	d storage			
7.1. Precautions for safe				
Precautions for safe handling		smoking. Ground/bond container and precautionary measures against static container. Use explosion-proof equipr	parks, open flames and other ignition sources. No receiving equipment. Use only non-sparking tools. Take c discharge. Flammable vapors may accumulate in the nent. Wear personal protective equipment. Do not s, mist. Do not get in eyes, on skin, or on clothing. Use rea.	
Hygiene measures :		Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe s	storage, including	any incompatibilities		
Technical measures	:	Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep container tightly closed. Store locked up.		
Storage conditions	:	Store at room temperature away from	light and moisture.	
7.3. Specific end use(s)				
No additional information availab	ble			
SECTION 8: Exposure c	ontrols/person	al protection		
8.1. Control parameters	•	•		
PERFLUORODECANESULFO	ONATE, POTASSIU	IM SALT UNLABELED 50 UG/ML IN	METHANOL	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppn	n)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)	
Italy - Portugal - USA ACGIH	ACGIH STEL (pp	m)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)	
Italy - Portugal - USA ACGIH	Remark (ACGIH)		Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.	
USA NIOSH	NIOSH REL (TWA	A) (mg/m³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits	
USA NIOSH	NIOSH REL (TWA) (ppm)		200 ppm Basis: NIOSH Recommended Exposure Limits	
USA NIOSH	NIOSH REL (STE	EL) (mg/m³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits	
USA NIOSH	NIOSH REL (STE	L) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits	
USA NIOSH	Remark (NIOSH)		Potential for dermal absorption.	
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	OSHA PEL (STEL	_) (mg/m³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	OSHA PEL (STEL	_) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	OSHA PEL (Ceilir	ng) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
USA OSHA	Remark (OSHA)		The value in mg/m3 is approximate. Skin notation.	
100% METHANOL UNLABEL	ED (67-56-1)			
Italy - Portugal - USA ACGIH		n)	200.00000000 ppm Basis: USA. ACGIH Threshold	

Limit Values (TLV)

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

100% METHANOL UNLABEL		
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³ Basis: USA. Occupational Exposure Limi (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m ³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for A Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.

Acute - systemic effects, dermal	40 mg/kg bodyweight/day	
Acute - systemic effects, inhalation	260 mg/m ³	
Acute - local effects, dermal	260 mg/cm ²	
Long-term - systemic effects, dermal	40 mg/kg bodyweight/day	
Long-term - local effects, dermal	260 mg/cm ²	
Long-term - local effects, inhalation	260 mg/m ³	
DNEL/DMEL (General population)		
Acute - systemic effects, dermal	8 mg/kg body weight	
Acute - systemic effects, inhalation	50 mg/m ³	
Acute - systemic effects, oral	8 mg/kg body weight	
Acute - local effects, inhalation	50 mg/m³	
Long-term - systemic effects,oral	8 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	50 mg/m³	
Long-term - systemic effects, dermal	8 mg/kg bodyweight/day	
Long-term - local effects, inhalation	50 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	154 mg/l	
PNEC aqua (marine water)	15.4 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	570.4 mg/kg dwt	
PNEC (Soil)		
PNEC soil	23.5 mg/kg dwt	

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED 50 UG/ML IN METHANOL				
PNEC (STP)				
PNEC sewage treatment plant	100 mg/kg			
8.2. Exposure controls				
Appropriate engineering controls	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.			
Personal protective equipment	Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.			
Materials for protective clothing	: Wear suitable protective clothing and gloves.			
Hand protection	: Wear suitable protective clothing and gloves.			
Eye protection	: Wear eye protection. Chemical goggles or face shield with safety glasses.			
Skin and body protection	: Wear suitable protective clothing, gloves and eye/face protection.			
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.			
Environmental exposure controls	: Avoid release to the environment.			

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.		
Physical state	: Liquid	
Appearance	: Liquid	
Molecular mass	: 32.04 g/mol	
Color	: Colorless	
Odor	: Pungent	
Odor threshold	: No data available	
рН	: No data available	
Relative evaporation rate (butyl acetate=1)	: No data available	
Melting point	: -98 °C (-144 °F)	
Freezing point	: No data available	
Boiling point	: 64.7 °C (148.5 °F)	
Flash point	: 9.7 °C (49.5 °F) - closed cup	
Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapor pressure	: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)	
Vapor pressure at 50 °C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)	
Relative vapor density at 20 °C	: 1.11	
Relative density	: No data available	
Specific gravity / density	: 0.791 g/ml at 25 °C (77 °F)	
Solubility	: Water: Completely miscible	
Log Pow	: -0.77	
Log Kow	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
Explosive properties	: Product is not explosive.	
Oxidizing properties	: Non oxidizing material according to EC criteria.	
Explosion limits	: 6 - 36 % (V)	
0.2 Other information		

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

10.2. Chemical stability	
See storage and expiration date on CoA.	
10.3. Possibility of hazardous reactions	
No dangerous reactions known under normal co	nditions of use
ç	
10.4. Conditions to avoid	
Avoid contact with hot surfaces. Heat. No flames	s, no sparks. Eliminate all sources of ignition.
10.5. Incompatible materials	
Acid anhydrides. Acid chlorides. Oxidizing agent	. Alkali Metal Amides. Reducing agents. Acids.
10.6. Hazardous decomposition products	
Carbon oxides (CO, CO2).	
· · ·	
SECTION 11: Toxicological informat	
11.1. Information on toxicological effects	
Acute toxicity	: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:vapour: Toxic if inhaled.
PERFLUORODECANESULFONATE, POTAS	SIUM SALT UNLABELED 50 UG/ML IN METHANOL
LD50 oral rat	1187 - 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	128.200 mg/l/4h
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
100% METHANOL UNLABELED (67-56-1)	
LD50 oral rat	1187 - 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	128.200 mg/l/4h
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
PERFLUORODECANESULFONATE, POTAS	SIUM SALT UNLABELED (2806-16-8)
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h
Skin corrosion/irritation	: Skin – Rabbit - Result: No skin irritation
Serious eye damage/irritation	: Eyes – Rabbit - Result: No eye irritation
Respiratory or skin sensitization	: Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)
Germ cell mutagenicity	: AMES test : S. tymphimurium. Result: Negative. fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - Male and female Result: Negative. Mouse - Male and female. Result: Negative
Carcinogenicity	: Not classified
Reproductive toxicity	: Damage to fetus not classifiable. Fertility classification not possible from current data.
Specific target organ toxicity – single exposure	: Causes damage to organs through prolonged or repeated exposure
Specific target organ toxicity – repeated	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
exposure	Net desc'ford
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach.

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

skin irritation.

Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.

: Toxic if swallowed.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
PERFLUORODECANESULFONATE, POTASSI	IUM SALT UNLABELED 50 UG/ML IN METHANOL
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h
100% METHANOL UNLABELED (67-56-1)	
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h

12.2. Persistence and degradability

PERFLUORODECANESULFONATE, POTASS	IUM SALT UNLABELED 50 UG/ML IN METHANOL
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d
100% METHANOL UNLABELED (67-56-1)	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d
12.3. Bioaccumulative potential	
PERFLUORODECANESULFONATE, POTASS	IUM SALT UNLABELED 50 UG/ML IN METHANOL
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77
100% METHANOL UNLABELED (67-56-1)	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77
12.4. Mobility in soil	
PERFLUORODECANESULFONATE, POTASS	IUM SALT UNLABELED 50 UG/ML IN METHANOL
Ecology - soil	Not degradable in the soil.
100% METHANOL UNLABELED (67-56-1)	
Ecology - soil	Not degradable in the soil.
12.5. Results of PBT and vPvB assessmen	t
PERFLUORODECANESULFONATE, POTASS	IUM SALT UNLABELED 50 UG/ML IN METHANOL
PBT: not relevant – no registration required	
100% METHANOL UNLABELED (67-56-1)	
PBT: not relevant – no registration required	
12.6. Other adverse effects	
Other adverse effects	: Avoid release to the environment.
Other information	: Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water. Hydrolyses readily.

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

26, 2012 / Rules and Regulations	
SECTION 13: Disposal consideration	15
13.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.
SECTION 14: Transport information	
In accordance with ADR / RID / IMDG / IATA / A	DN
14.1. UN number	
UN-No.(DOT)	: 1230
DOT NA no.	UN1230
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Methanol
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid 6.1 - Poison
	PLANMABLE LIQUID 3 6
DOT Symbols	: + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper shipping name appropriate for international and domestic transportation
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	 : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
14.3. Additional information	
Emergency Response Guide (ERG) Number	: 131
Other information	: No supplementary information available.
Overland transport	
Hazard identification number (Kemler No.)	: 336
Orange plates	336 1230
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
Excepted quantities (ADR)	: E2

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea	
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
MFAG-No	: 131
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
Civil Aeronautics Law	: Flammable liquids

14.4.Environmental hazardsOther information

: No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

13.1. 05 rederal regulations				
PERFLUORODECANESULFONATE, POTASSI	UM SALT UNLABELED 50 UG/ML IN METHANOL			
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
CERCLA RQ	5000 lb			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313			
100% METHANOL UNLABELED (67-56-1)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
CERCLA RQ	5000 lb			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313			
PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED (2806-16-8)				
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302			
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard			
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313			

15.2. International regulations

CANADA

PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED 50 UG/ML IN METHANOL
Listed on the Canadian DSL (Domestic Substances List)
100% METHANOL UNLABELED (67-56-1)
Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations					
PERFLUORODECANESUL	FONATE, POTASSIUM SA	LT UNL	ABELED 50 UG/ML IN M	IETHANOL ()	
U.S California - Proposition 65 - Carcinogens List		No			
U.S California - Proposition Toxicity	n 65 - Developmental	Yes			
U.S California - Proposition Toxicity - Female	n 65 - Reproductive	No			
U.S California - Proposition Toxicity - Male	n 65 - Reproductive	No			
State or local regulations		U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances			
100% METHANOL UNLAB	ELED (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	Pro	California - position 65 - roductive Toxicity - nale	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No		No	
PERFLUORODECANESUL	FONATE, POTASSIUM SA	LT UNL	ABELED (2806-16-8)		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	Pro	California - position 65 - roductive Toxicity - nale	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No		No	
100% METHANOL UNLAB	ELED (67-56-1)				
State or local regulations					
U.S Delaware - Pollutant E U.S Idaho - Non-Carcinog U.S Massachusetts - Righ U.S Pennsylvania - RTK (f U.S New Jersey - Right to U.S New York - Reporting	enic Toxic Air Pollutants - A t To Know List Right to Know) List Know Hazardous Substanc	cceptabl e List	e Ambient Concentrations	5	
PERFLUORODECANESULFONATE, POTASSIUM SALT UNLABELED (2806-16-8)					
State or local regulations					
U.S Pennsylvania - RTK (F U.S New Jersey - Right to	Right to Know) List Know Hazardous Substanc	e List			

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed

50 UG/ML IN METHANOL ULM-12322-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H311	Toxic in contact with skin	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H331	Toxic if inhaled	
H332	Harmful if inhaled	
H370	Causes damage to organs	
H411	Toxic to aquatic life with long lasting effects	
R11	Highly flammable	
R20	Harmful by inhalation	
R25	Toxic if swallowed	
R36/38	Irritating to eyes and skin	
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed	
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment	
F	Highly flammable	
Ν	Dangerous for the environment	
Ţ	Тохіс	
Xi	Irritant	
Xn	Harmful	

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product