



1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 16/03/2015

Revision date:

Version: 1.0

ULM-7375-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name : 1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE
Product code : ULM-7375-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Carc. 2	H351
Repr. 2	H361
STOT SE 2	H371
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Acute 1	H400

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

Carc.Cat.3; R40
Repr.Cat.3; R62
Repr.Cat.3; R63
F; R11
Xn; R20
Xn; R65
Xi; R36/38

Full text of R-phrases: see section 16

Classification (GHS-US)

Flam. Liq. 2	H225
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Carc. 2	H351

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Repr. 2	H361
STOT SE 2	H371
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Acute 1	H400

Adverse physicochemical, human health and environmental effects

Bladder, Liver, Kidney, Brain.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: TOLUENE UNLABELED

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H351 - Suspected of causing cancer
H361 - Suspected of damaging the unborn child
H371 - May cause damage to organs (brain, blood, kidneys, liver, urinary bladder)
H373 - May cause damage to organs (blood, brain, kidneys, liver, urinary bladder) through prolonged or repeated exposure
H400 - Very toxic to aquatic life

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P260 - Do not breathe fume, mist, spray, vapors
P264 - Wash both hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H351 - Suspected of causing cancer (Dermal, Inhalation, oral)
H361 - Suspected of damaging fertility or the unborn child (Dermal, Inhalation, oral)
H371 - May cause damage to organs (blood, brain, kidneys, liver, urinary bladder) (Dermal, Inhalation, oral)
H373 - May cause damage to organs (blood, brain, kidneys, liver, urinary bladder) through prolonged or repeated exposure (Dermal, Inhalation, oral)
H400 - Very toxic to aquatic life

Precautionary statements (GHS-US)

: P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe fume, mist, spray, vapors
P261 - Avoid breathing fume, mist, spray, vapors
P264 - Wash Both hands thoroughly after handling
P270 - Do no eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear eye protection, face protection, protective clothing, protective gloves
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P314 - Get medical advice and attention if you feel unwell
P331 - If swallowed, do NOT induce vomiting
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use Alcohol resistant foam., Carbon dioxide., Dry chemical., Water spray for extinction
P391 - Collect spillage
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to Comply with applicable regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
TOLUENE UNLABELED	(CAS No) 108-88-3 (EC no) 203-625-9 (EC index no) 601-021-00-3	99.9971	Repr.Cat.3; R62 Repr.Cat.3; R63 F; R11 Xi; R36/38 Carc.Cat.3; R40 N; R51 Xn; R20 R67 Xn; R65
1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED	(CAS No) 84852-53-9 (EC no) 284-366-9	0.0029	Carc.Cat.3; R40 Xn; R22 Xi; R41 N; R51/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
TOLUENE UNLABELED	(CAS No) 108-88-3 (EC no) 203-625-9 (EC index no) 601-021-00-3	99.9971	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 Repr. 2, H361d STOT SE 3, H336 STOT SE 2, H371 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400
1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED	(CAS No) 84852-53-9 (EC no) 284-366-9	0.0029	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Carc. 2, H351 Aquatic Chronic 2, H411

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
TOLUENE UNLABELED	(CAS No) 108-88-3	99.9971	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 Repr. 2, H361 STOT SE 3, H336 STOT SE 2, H371 Asp. Tox. 1, H304 Aquatic Acute 1, H400

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.
- First-aid measures after ingestion : Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes eye irritation.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Reactivity : Vapors may form explosive mixture with air.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray to cool unopened containers.
- Protection during firefighting : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Use personal protective equipment, and ensure adequate ventilation. Avoid breathing vapors, mist, gas. Remove ignition sources, and move personnel to safe area. Vapors accumulate especially in low areas to form explosive concentrations.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : No naked lights. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions : Store at room temperature away from light and moisture.
Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available


SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.0000000000 ppm Visual impairment, Female reproductive, Pregnancy loss
TOLUENE UNLABELED (108-88-3)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.0000000000 ppm Visual impairment, Female reproductive, Pregnancy loss
USA OSHA	OSHA PEL (TWA) (ppm)	100.0000000000 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (ppm)	150.0000000000 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED (84852-53-9)		
Italy - Portugal - USA ACGIH	ACGIH TWA (mg/m ³)	10.0000000000 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15.0000000000 mg/m ³

8.2. Exposure controls

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Hand protection : Wear suitable protective clothing and gloves.
Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid
Appearance : Liquid.
Color : Colourless.
Odor : No data available.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : -93 °C (-135 °F)

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point	: No data available
Boiling point	: 110 - 111 °C (230 - 232 °F)
Flash point	: 4.0 °C (39.2 °F) - closed cup
Self ignition temperature	: 535 °C (995 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: 29.1 hPa (21.8 mmHg) at 20.0 °C (68.0 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.865 g/ml at 25 °C (77 °F)
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 1.2 - 7 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE	
LD50 oral rat	> 5580 mg/kg
LD50 dermal rabbit	12196 mg/kg
LC50 inhalation rat (mg/l)	12500 - 28800 mg/m ³ 4 h
ATE (dermal)	12196.000 mg/kg body weight
ATE (gases)	4500.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
ATE (dust, mist)	1.500 mg/l/4h

TOLUENE UNLABELED (108-88-3)	
LD50 oral rat	> 5580 mg/kg
LD50 dermal rabbit	12196 mg/kg
LC50 inhalation rat (mg/l)	12500 - 28800 mg/m ³ 4 h
ATE (dermal)	12196.000 mg/kg body weight
ATE (gases)	4500.000 ppmV/4h
ATE (vapors)	12.500 mg/l/4h
ATE (dust, mist)	1.500 mg/l/4h

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED (84852-53-9)	
LD50 oral rat	2000 mg/kg
LD50 oral	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
ATE (oral)	2000.000 mg/kg body weight

Skin corrosion/irritation	: Causes skin irritation. Skin - rabbit - Skin irritation - 24 h
Serious eye damage/irritation	: Causes serious eye irritation. No data available
Respiratory or skin sensitization	: Not available No data available
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Experiments have shown reproductive toxicity effects in male and female laboratory animals.
Specific target organ toxicity (single exposure)	: May cause damage to organs (brain, blood, kidneys, liver, urinary bladder). No data available
Specific target organ toxicity (repeated exposure)	: May cause damage to organs (blood, brain, kidneys, liver, urinary bladder) through prolonged or repeated exposure. No data available
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Lung irritation, chest pain, pulmonary edema, Inhalation studies have shown the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals.
IARC group	: 3
Symptoms/injuries after inhalation	: Harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Very toxic to aquatic life.

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE	
LC50 fish 1	74 - 340 mg/l <i>Lepomis macrochirus</i> (Bluegill) - 96h
LC50 other aquatic organisms 1	10 mg/l <i>Pseudokirchneriella subcapitata</i> (Green algae) - 24 h
EC50 Daphnia 1	8 mg/l <i>Daphnia magna</i> (Water flea) - 24h
LC50 fish 2	7.63 mg/l <i>Oncorhynchus mykiss</i> (Rainbow trout) - 96 h
EC50 Daphnia 2	6 mg/l <i>Daphnia magna</i> (Water flea) - Immobilization - 48 h
ErC50 (algae)	245 mg/l <i>Chlorella vulgaris</i> (Fresh water algae) - 24 h
LOEC (chronic)	8.04 mg/l <i>Pimephales promelas</i> (Fathead minnow) - 7 d
NOEC (chronic)	5.44 mg/l <i>Pimephales promelas</i> (fathead minnow) - 7 d

TOLUENE UNLABELED (108-88-3)	
LC50 fish 1	74 - 340 mg/l <i>Lepomis macrochirus</i> (Bluegill) - 96h
LC50 other aquatic organisms 1	10 mg/l <i>Pseudokirchneriella subcapitata</i> (Green algae) - 24 h
EC50 Daphnia 1	8 mg/l <i>Daphnia magna</i> (Water flea) - 24h
LC50 fish 2	7.63 mg/l <i>Oncorhynchus mykiss</i> (Rainbow trout) - 96 h
EC50 Daphnia 2	6 mg/l <i>Daphnia magna</i> (Water flea) - Immobilization - 48 h
ErC50 (algae)	245 mg/l <i>Chlorella vulgaris</i> (Fresh water algae) - 24 h
LOEC (chronic)	8.04 mg/l <i>Pimephales promelas</i> (Fathead minnow) - 7 d
NOEC (chronic)	5.44 mg/l <i>Pimephales promelas</i> (fathead minnow) - 7 d

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED (84852-53-9)	
LC50 fish 1	>10,000 mg/l - 96h
ErC50 (algae)	> 10,000 mg/l - <i>Daphnia magna</i> (Waterflea)- 48h

12.2. Persistence and degradability

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED (84852-53-9)	
Persistence and degradability	Not available.

12.3. Bioaccumulative potential

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE	
Bioaccumulative potential	Not available.

TOLUENE UNLABELED (108-88-3)	
Bioaccumulative potential	Not available.

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED (84852-53-9)	
Bioaccumulative potential	Bioaccumulation is unlikely.

12.4. Mobility in soil

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE	
Ecology - soil	Not available.

TOLUENE UNLABELED (108-88-3)	
Ecology - soil	Not available.

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED (84852-53-9)	
Ecology - soil	Not available.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

UN-No.(DOT) : 1294
DOT NA no. UN1294

14.2. UN proper shipping name

DOT Proper Shipping Name : Toluene
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II
Class (ADR) : 3 - Flammable liquid
Hazard identification number (Kemler No.) : 33
Classification code (ADR) : F1
Danger labels (ADR) : 3 - Flammable liquids



Orange plates :

Tunnel restriction code : D/E
Limited quantities (ADR) : 1L
EAC : 3YE
Excepted quantities (ADR) : E2

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
MFAG-No : 130

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Dangerous for the environment :

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE UNLABELED (108-88-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 311/312 Hazard Classes

Fire hazard
Immediate (acute) health hazard
Delayed (chronic) health hazard

15.2. International regulations

CANADA

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE

Listed on the Canadian DSL (Domestic Substances List) inventory.

TOLUENE UNLABELED (108-88-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2.1. National regulations

No additional information available

15.3. US State regulations

1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE()

State or local regulations

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List
WARNING! This product contains a chemical known by the state of California to cause birth defects or other reproductive harm.

TOLUENE UNLABELED (108-88-3)

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List
WARNING! This product contains a chemical known by the state of California to cause birth defects or other reproductive harm.

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases::

Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 2	Specific target organ toxicity (single exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation


1,2-BIS(PENTABROMOPHENYL)ETHANE UNLABELED 25 UG/ML IN TOLUENE ULM-7375-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H361d	Suspected of damaging the unborn child
H371	May cause damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
R11	Highly flammable
R20	Harmful by inhalation
R22	Harmful if swallowed
R36/38	Irritating to eyes and skin
R40	Limited evidence of a carcinogenic effect
R41	Risk of serious damage to eyes
R51	Toxic to aquatic organisms
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 3 Serious Hazard
- Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product