

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date:

Date of issue: 24/06/2015

ULM-8807-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Product name. : SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE

Product code : ULM-8807-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Dermal) H312
Acute Tox. 4 (Inhalation:dust,mist) H332
Eye Irrit. 2 H319
Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F- R11

Full text of R-phrases: see section 16

Classification (GHS-US)

Flam. Liq. 2 H225 Acute Tox. 4 (Oral) H302 Acute Tox. 4 (Dermal) H312 Acute Tox. 4 (Inhalation:dust,mist) H332 Eye Irrit. 2A H319

Adverse physicochemical, human health and environmental effects

Lungs, Blood, Kidney, Liver, Central nervous system.

23/07/2015 EN (English US) 1/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





Signal word (CLP) : Danger

: ACETONITRILE UNLABELED Hazardous ingredients

H225 - Highly flammable liquid and vapor Hazard statements (CLP)

H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

H319 - Causes serious eye irritation

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P261 - Avoid breathing dust, fume, gas, mist, spray, vapors P264 - Wash Both hands thoroughly after handling P270 - Do no eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H225 - Highly flammable liquid and vapor

H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, ventilating, lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P261 - Avoid breathing dust, fume, gas, mist, spray, vapors P264 - Wash Both hands thoroughly after handling P270 - Do no eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area P280 - Wear eye protection, face protection, protective clothing, protective gloves

P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER/doctor/physician if you feel unwell

P321 - Specific treatment (see Hazard pictograms (CLP) on this label)

P330 - If swallowed, rinse mouth

P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use Alcohol resistant foam., Carbon dioxide., Dry chemical., Water

spray for extinction

P403+P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/container to Comply with applicable regulations.

Other hazards

No additional information available

23/07/2015 EN (English US) 2/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

Substances

Not applicable

iot applicable			
.2. Mixtures			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
ACETONITRILE UNLABELED	(CAS No) 75-05-8 (EC no) 200-835-2 (EC index no) 608-001-00-3	99.9873	F; R11
SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED	(CAS No) 577-11-7 (EC no) 209-406-4	0.0127	Xn; R22 Xi; R41 Xi; R38
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETONITRILE UNLABELED	(CAS No) 75-05-8 (EC no) 200-835-2 (EC index no) 608-001-00-3	99.9873	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED	(CAS No) 577-11-7 (EC no) 209-406-4	0.0127	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318
Name	Product identifier	%	Classification (GHS-US)
ACETONITRILE UNLABELED	(CAS No) 75-05-8	99.9873	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

First-aid measures after eye contact

4.1. Description of first aid measures
--

First-aid measures general : Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of

dangerous area.

First-aid measures after inhalation Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER/doctor/physician if you feel unwell.

Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash First-aid measures after skin contact

with plenty of soap and water. Wash contaminated clothing before reuse. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

First-aid measures after ingestion : Rinse mouth. Call a POISON CENTER/doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

inhaled.

Symptoms/injuries after skin contact Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Harmful in contact with skin.

Symptoms/injuries after eye contact Causes eye irritation.

Symptoms/injuries after ingestion Swallowing a small quantity of this material will result in serious health hazard.

Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

Extinguishing media

suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

: May form flammable/explosive vapor-air mixture. Explosion hazard Reactivity : Vapors may form explosive mixture with air.

Advice for firefighters

Firefighting instructions : Use water spray to cool unopened containers.

23/07/2015 EN (English US) 3/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures

: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No

smoking.

6.1.1. For non-emergency personnel

Emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.1.2. For emergency responders

No additional information available

Environmental precautions

Avoid release to the environment.

Methods and material for containment and cleaning up

For containment

: Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations.

Reference to other sections

No additional information available

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

No naked lights. No smoking. Use only non-sparking tools. Use only outdoors or in a well-

ventilated area.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.

Storage conditions

Store at room temperature away from light and moisture.

Incompatible materials Heat sources.

Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE				
Italy - Portugal - USA ACGIHACGIH TWA (ppm)20.0000000000 ppm Lower Respiratory TractNot classifiable as a human carcinogen.				
ACETONITRILE UNLABELED (75-05-8)				
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.0000000000 ppm Lower Respiratory Tract irritation. Not classifiable as a human carcinogen.		
USA OSHA	OSHA PEL (TWA) (ppm)	40.0000000000 ppm		
USA OSHA	OSHA PEL (STEL) (ppm)	60.000000000 ppm		

Exposure controls

: Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus. Personal protective equipment



Hand protection Wear suitable protective clothing and gloves.

Wear safety glasses with side shields (or goggles) and a face shield. Eye protection

Skin and body protection Wear suitable protective clothing.

Respiratory protection : Wear appropriate NIOSH/MSHA approved respirator.

23/07/2015 EN (English US) 4/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

Appearance : Liquid, clear.

Molecular mass : 41.05

Color : Colourless.

Odor : ether-like.

Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : -48 °C (-54°F)
Freezing point : No data available
Boiling point : 81 - 82 °C (178 - 180 °F)

Self ignition temperature : 523 °C (973 °F)

Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapor

Vapor pressure : 73.18 hPa (54.89 mmHg) at 15°C (59 °F), 119.81 hPa (89.86 mmHg) at 25°C(77 °F)

Relative vapor density at 20 °C : 1.42 - (Air = 1.0)
Relative density : No data available
Solubility : Water: 100 %

Log Pow : -0.34

Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : 4.4 - 16 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

Acids, Bases, Oxidizing agents, Reducing agents, Alkali metals.

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE		
LD50 oral rat	2460 mg/kg	
LD50 dermal rabbit	2000 mg/kg	
LC50 inhalation rat (mg/l)	≥ 26.8 mg/l	
LC50 inhalation rat (ppm)	7551 ppm - 8h	
ATE (oral)	500.000 mg/kg body weight	

23/07/2015 EN (English US) 5/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Regulation (EC) No. 453/2010 and accordin	g to Federal Register / Vol. 77, No. 56 / Monday, March 26, 2012 / Rules and Regulations	
SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCI	NATE UNLABELED 100UG/ML ACETONITRILE	
ATE (dermal)	1100.000 mg/kg body weight	
ATE (gases)	4500.000 ppmV/4h	
ATE (vapors)	11.000 mg/l/4h	
ATE (dust, mist)	1.500 mg/l/4h	
ACETONITRILE UNLABELED (75-05-8)		
LD50 oral rat	2460 mg/kg	
LD50 dermal rabbit	2000 mg/kg	
LC50 inhalation rat (mg/l)	≥ 26.8 mg/l	
LC50 inhalation rat (ppm)	7551 ppm - 8h	
ATE (oral)	500.000 mg/kg body weight	
ATE (dermal)	2000.000 mg/kg body weight	
ATE (gases)	4500.000 ppmV/4h	
ATE (vapors)	11.000 mg/l/4h	
ATE (dust, mist)	1.500 mg/l/4h	
SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCI	NATE UNLABELED (577-11-7)	
LD50 oral rat	1900 mg/kg	
LD50 dermal rabbit	> 10000 mg/kg	
LC50 inhalation rat (mg/l)	> 2000 mg/m³	
ATE (oral)	1900.000 mg/kg body weight	
Skin corrosion/irritation	: Not classified	
	Skin - rabbit - No skin irritation	
Serious eye damage/irritation	: Causes serious eye irritation.	
	Eyes - Rabbit - Irritating to eyes	
Respiratory or skin sensitization	: Did not cause sensitization on laboratory animals.	
	Buehler Test - guinea pig - Did not cause sensitisation on laboratory animals.	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: No evidence of carcinogenicity in animal studies (when indicated).	
Reproductive toxicity	: Animal testing did not show any effects on fertility.	
Specific target organ toxicity (single exposure)	: Not classified	
	The substance or mixture is not classified as specific target organ toxicant.	
Specific target organ toxicity (repeated	: Not classified	
exposure)	The substance or mixture is not classified as specific target organ toxicant.	
Aspiration hazard	: Not classified	

Aspiration hazard : Not classified

Potential Adverse human health effects and

Symptoms/injuries after skin contact

symptoms

: Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

Repeated exposure to this material can result in absorption through skin causing significant

Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

inhaled.

health hazard. Harmful in contact with skin.

Symptoms/injuries after eye contact

: Causes eye irritation.

Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE		
LC50 fish 1 1640.00 mg/l Pimephales promelas (fathead minnow) - 96h		
EC50 Daphnia 1 3600 mg/l Daphnia magna (Water flea) - 48h		
NOEC (chronic) 640 mg/l Daphnia magna (Water flea) - 14d		
ACETONITRILE UNLABELED (75-05-8)		
ACETONITRILE UNLABELED (75-05-8		
ACETONITRILE UNLABELED (75-05-8 LC50 fish 1	1640.00 mg/l Pimephales promelas (fathead minnow) - 96h	

23/07/2015 EN (English US) 6/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED (577-11-7)			
LC50 fish 1 28 mg/l Oncorhynchus mykiss (rainbow trout) - 96 h			

12.2. Persistence and degradability

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE				
Persistence and degradability	Biodegradability	Result: - Readily biodegradable.		

ACETONITRILE UNLABELED (75-05-8)

Persistence and degradability Biodegradability Result: - Readily biodegradable

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED (577-11-7)

Persistence and degradability Not available.

12.3. Bioaccumulative potential

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE			
Log Pow -0.34			
Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).		

ACETONITRILE UNLABELED (75-05-8)

Log Pow	-0.34
Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).

12.4. Mobility in soil

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE		
Ecology - soil	Not expected to absorb on soil.	

ACETONITRILE UNLABELED (75-05-8)

Ecology - soil Not expected to absorb on soil.

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED (577-11-7)

Ecology - soil Not available.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local

environmental control regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

UN-No.(DOT) : 1648 DOT NA no. UN1648

14.2. UN proper shipping name

DOT Proper Shipping Name : Acetonitrile

Department of Transportation (DOT) Hazard : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Classes

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

23/07/2015 EN (English US) 7/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal................. 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 33 Classification code (ADR) : F1

Danger labels (ADR) : 3 - Flammable liquids



Orange plates

33 1648

Tunnel restriction code : D/E
Limited quantities (ADR) 1L
EAC : •2YE
Excepted quantities (ADR) : E2

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

MFAG-No : 127

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

23/07/2015 EN (English US) 8/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION	15: Regul	latory inf	formation

15.1. US Federal regulations

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 311/312 Hazard Classes Fire hazard

Immediate (acute) health hazard Delayed (chronic) health hazard

ACETONITRILE UNLABELED (75-05-8)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 311/312 Hazard Classes Fire hazard

Immediate (acute) health hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE

Listed on the Canadian DSL (Domestic Substances List) inventory.

ACETONITRILE UNLABELED (75-05-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2.1. National regulations

No additional information available

15.3. US State regulations

SODIUM BIS(2-ETHYLHEXYL)SULFOSUCCINATE UNLABELED 100UG/ML ACETONITRILE()	
State or local regulations	U.S Massachusetts - Right To Know List
	U.S Pennsylvania - RTK (Right to Know) List
	U.S New Jersey - Right to Know Hazardous Substance List
	This product does not contain any chemicals known to State of California to cause cancer,
	birth defects, or any other reproductive harm.

ACETONITRILE UNLABELED (75-05-8)

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Other information

This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases::

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	skin corrosion/irritation Category 2
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin

23/07/2015 EN (English US) 9/10

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
R11	Highly flammable
R22	Harmful if swallowed
R38	Irritating to skin
R41	Risk of serious damage to eyes
F	Highly flammable
Xi	Irritant
Xn	Harmful

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt


medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

23/07/2015 EN (English US) 10/10