

OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 19/12/2018 Revision date: 25/03/21 Supersedes: 19/12/2018 Version: 2.0

ULM-9441-MT-S

aduct name : boduct code : coduct code : code <th>Mixtures OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE ULM-9441-MT-S nce or mixture and uses advised against Professional use For professional use only ta sheet</th>	Mixtures OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE ULM-9441-MT-S nce or mixture and uses advised against Professional use For professional use only ta sheet		
aduct name : boduct code : coduct code : code <td>OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE ULM-9441-MT-S nce or mixture and uses advised against Professional use For professional use only</td>	OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE ULM-9441-MT-S nce or mixture and uses advised against Professional use For professional use only		
adduct code : Relevant identified uses of the substar additional information available adover, MA 01810 adation available.	ULM-9441-MT-S nce or mixture and uses advised against Professional use For professional use only		
Relevant identified uses of the substant Relevant identified uses in use category in use	nce or mixture and uses advised against Professional use For professional use only		
2.1. Relevant identified uses iin use category : lustrial/Professional use spec : 2.2. Uses advised against additional information available 3. Details of the supplier of the safety dat mbridge Isotope Laboratories, Inc. Frontage Road dover, MA 01810 SA SA: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number nergency numbers: emtrec: 1-800-424-9300 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.	Professional use For professional use only		
in use category : : lustrial/Professional use spec : : 2.2. Uses advised against additional information available 3. Details of the supplier of the safety dat mbridge Isotope Laboratories, Inc. Frontage Road dover, MA 01810 3A 3A: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number nergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.	For professional use only		
Instrial/Professional use spec : Instrial/Professional use spec : Instrinct	For professional use only		
 2.2. Uses advised against additional information available Details of the supplier of the safety date mbridge Isotope Laboratories, Inc. Frontage Road dover, MA 01810 GA: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number nergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification Classification of the substance or mixt assification according to Regulation (EC) No.			
additional information available Details of the supplier of the safety dat mbridge Isotope Laboratories, Inc. Frontage Road dover, MA 01810 A SA: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number nergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.	ta sheet		
additional information available Details of the supplier of the safety dat mbridge Isotope Laboratories, Inc. Frontage Road dover, MA 01810 A SA: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number nergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.	ta sheet		
mbridge Isotope Laboratories, Inc. Frontage Road dover, MA 01810 GA GA: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number hergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.	ta sheet		
mbridge Isotope Laboratories, Inc. Frontage Road dover, MA 01810 GA GA: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number hergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.			
Frontage Road dover, MA 01810 SA: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number hergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.			
A A: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number hergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.			
A: 1-800-322-1174 Int: 1-978-749-8000 sales@isotope.com www.isotope.com Emergency telephone number nergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.			
sales@isotope.com www.isotope.com Emergency telephone number hergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.			
hergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification Classification of the substance or mixt assification according to Regulation (EC) No.			
hergency numbers: emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification Classification of the substance or mixt assification according to Regulation (EC) No.			
emtrec: 1-800-424-9300 (24 hours) ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification Classification of the substance or mixt assification according to Regulation (EC) No.			
ernational: 1-703-741-5970 (24 hours) ECTION 2: Hazards identification . Classification of the substance or mixt assification according to Regulation (EC) No.			
. Classification of the substance or mixt assification according to Regulation (EC) No.			
assification according to Regulation (EC) No.			
	ture		
	1272/2008 [CLP]		
•	Flam. Liq. 2 H225		
in Irrit. 2 H315			
II text of hazard classes and H-statements : see s	section 16		
assification according to Directive 67/548/EEC	C [DSD] or 1999/45/EC [DPD]		
R11 R38			
ا text of R-phrases: see section 16			
IS-US classification			
Im. Liq. 2 H225			
in Irrit. 2 H315			
Il text of H statements : see section 16			
verse physicochemical, human health and en	nvironmental effects		
Adverse physicochemical, human health and environmental effects central nervous system. kidneys.			
. Label elements			
beling according to Regulation (EC) No. 1272/	/2008 [CLP]		
zard pictograms (CLP) :			

GHS07

UG/ML IN MTBE ULM-9441-MT-S

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Signal word (CLP)	: Danger
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapor H315 - Causes skin irritation
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective clothing, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of water. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
GHS-US labeling	
Hazard pictograms (GHS-US)	
	GHS02 GHS07
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H225 - Highly flammable liquid and vapor H315 - Causes skin irritation
Precautionary statements (GHS-US)	 P210 - Keep away from heat, hot surfaces, open flames, sparks No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical equipment P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear eye protection, face protection, protective clothing, protective gloves. P302+P352 - If on skin: Wash with plenty of water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P321 - Specific treatment (see Hazardous component(s) for labeling on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use Water spray, Alcohol resistant foam, Dry chemical, Carbon dioxide. to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. **Other hazards**

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. **Substances**

- Not applicable
- 3.2. **Mixtures Product identifier** Classification according to Name % Directive 67/548/EEC METHYL TERT-BUTYL ETHER UNLABELED (CAS-No.) 1634-04-4 99.99 F; R11 (EC-No.) 216-653-1 Xi; R38 (EC Index-No.) 603-181-00-X (REACH-no) 01-2119452786-27 (CAS-No.) 556-67-2 (EC-No.) 209-136-7 (EC Index-No.) 014-018-00-1 OCTAMETHYLCYCLOTETRASILOXANE UNLABELED 0.01 R53

UG/ML IN MTBE ULM-9441-MT-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
METHYL TERT-BUTYL ETHER UNLABELED	(CAS-No.) 1634-04-4 (EC-No.) 216-653-1 (EC Index-No.) 603-181-00-X (REACH-no) 01-2119452786-27	99.99	Flam. Liq. 2, H225 Skin Irrit. 2, H315
OCTAMETHYLCYCLOTETRASILOXANE UNLABELED	(CAS-No.) 556-67-2 (EC-No.) 209-136-7 (EC Index-No.) 014-018-00-1	0.01	Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 4, H413
Name	Product identifier	%	GHS-US classification
METHYL TERT-BUTYL ETHER UNLABELED	(CAS-No.) 1634-04-4	99.99	Flam. Liq. 2, H225 Skin Irrit. 2, H315
OCTAMETHYLCYCLOTETRASILOXANE UNLABELED	(CAS-No.) 556-67-2	0.01	Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Chronic 4, H413

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). Evacuate danger area.
First-aid measures after inhalation	: When symptoms occur: go into open air and ventilate suspected area. If not breathing give artificial respiration. Get medical advice/attention.
First-aid measures after skin contact	: Wash with plenty of soap and water. and soap. Get immediate medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.
4.2. Most important symptoms and e	fects, both acute and delayed
Symptoms/effects after inhalation	: May be harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
4.3. Indication of any immediate med	ical attention and special treatment needed
No additional information available	
SECTION 5: Firefighting measures	5
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).
5.2. Special hazards arising from the	substance or mixture
Fire hazard	: Highly flammable liquid and vapor.
5.3. Advice for firefighters	
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Wear a self contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear recommended personal protective equipment.
SECTION 6: Accidental release me	easures
6.1. Personal precautions, protective	equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Avoid breathing vapors, mist, gas. Avoid dust formation.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Avoid release to the environment.

UG/ML IN MTBE ULM-9441-MT-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and materia	I for containment and cleanin	a up	
For containment	: Collect spill it. Small qu container fo earth for su safe way, a	age. Clean up any spills as soon as possible, using an absorbent material to collect antities of liquid spill: take up in non-combustible absorbent material and shovel into r disposal. For large spills, confine the spill in a dike and charge it with wet sand or bsequent safe disposal. This material and its container must be disposed of in a nd as per local legislation.	
Other information	: Dispose of	materials or solid residues at an authorized site.	
6.4. Reference to other sections			
For further information refer to section 13.			
SECTION 7: Handling an	id storage		
7.1. Precautions for safe	handling		
Precautions for safe handling	: Provide ade	equate ventilation to minimize dust and/or vapor concentrations.	
Hygiene measures		s and other exposed areas with mild soap and water before eating, drinking or d when leaving work. Handle in accordance with good industrial hygiene and safety	
7.2. Conditions for safe s	torage, including any incomp	atibilities	
Technical measures	: Store in a v	ell-ventilated place. Keep container tightly closed.	
Storage conditions	: Store at roo	m temperature away from light and moisture.	
7.3. Specific end use(s)			
No additional information availab	ble		
SECTION 8: Exposure c	ontrols/personal protect	ion	
8.1. Control parameters			
	SILOXANE "D4" UNLABELE	100 UG/ML IN MTBE	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV) Remarks: Upper Respiratory Tract irritation. Kidney damage. Confirmed animal carcinogen with unknown relevance to humans.	
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	144 mg/m ³ Basis: California permissible exposure limits for chemical contaminants. (Title 8, Article 107).	
USA OSHA	OSHA PEL (Ceiling) (ppm)	40 ppm Basis: California permissible exposure limits for chemical contaminants. (Title 8, Article 107).	
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)			
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV) Remarks: Upper Respiratory Tract irritation. Kidney damage. Confirmed animal carcinogen with unknown relevance to humans.	
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	144 mg/m ³ Basis: California permissible exposure limits for chemical contaminants. (Title 8, Article 107).	
USA OSHA	OSHA PEL (Ceiling) (ppm)	40 ppm Basis: California permissible exposure limits for chemical contaminants. (Title 8, Article 107).	
OCTAMETHYLCYCLOTETRASILOXANE UNLABELED (556-67-2)			
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm USA. Workplace Environmental Exposure Levels (WEEL)	
8.2. Exposure controls			

Appropriate engineering controls

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.

Personal protective equipment

smoking and when leaving work.Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Wear eye protection. Chemical goggles or face shield with safety glasses.Wear suitable protective clothing, gloves and eye/face protection.

: Wear suitable protective clothing and gloves.

: Wear suitable protective clothing and gloves.

Materials for protective clothing Hand protection Eye protection Skin and body protection Respiratory protection

UG/ML IN MTBE ULM-9441-MT-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls

: Avoid release to the environment.

Environmental exposure controls	: Avoid release to the environment.	
SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
The properties listed below are for the solvent, the main compone		
Physical state	: Liquid	
Appearance	: Liquid	
Molecular mass	: 88.15 g/mol	
Color	: Colorless	
Odor	: No data available	
Odor threshold	: No data available	
рН	: No data available	
Relative evaporation rate (butyl acetate=1)	: No data available	
Melting point	: -108.6 °C (-163.5 °F)	
Freezing point	: No data available	
Boiling point	: 55 - 56 °C (131 - 133 °F) - lit.	
Flash point	: -33 °C (- 27.4 °F) - closed cup	
Auto-ignition temperature	: 374 °C (705.2 °F)	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapor pressure	: 1018.7 hPa (764.1 mmHg) at 55°C (131°F), 279.2 hPa (209.4 mmHg) at 20 °C (68°F)	
Relative vapor density at 20 °C	: No data available	
Relative density	: No data available	
Specific gravity / density	: 0.74 g/ml at 25 °C (77 °F)	
Solubility	: Water: 42 g/l at 20 °C (68 °F) - OECD Test Guideline 105	
Log Pow	: 1.06	
Log Kow	: No data available	
Viscosity, kinematic	: 0.464 mm ² /s at 20 °C (68 °F) - 0.409 mm2/s at 40 °C (104 °F)	
Viscosity, dynamic	: No data available	
Explosive properties	: No data available	
Oxidizing properties	: No data available	
Explosion limits	: 1.6 - 15.1 % (V)	
9.2. Other information		
No additional information available		
SECTION 10: Stability and reactivity		
10.1. Reactivity		
No additional information available		
10.2. Chemical stability		
See storage and expiration date on CoA.		
10.3. Possibility of hazardous reactions		
No additional information available		
10.4. Conditions to avoid		
Heat. Open flame. Sparks.		
10.5. Incompatible materials		
Oxidizing agent. Strong acids.		
10.6. Hazardous decomposition products		
Carbon oxides (CO, CO2).		
SECTION 11: Toxicological informati	on	
11.1. Information on toxicological effects		
Acute toxicity	: Not classified	
OCTAMETHYLCYCLOTETRASILOXANE "D4	UNLABELED 100 UG/ML IN MTBE	
LD50 oral rat	4000 mg/kg	

UG/ML IN MTBE ULM-9441-MT-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

OCTAMETHYLCYCLOTETRASILOXANE "D4	" UNLABELED 100 UG/ML IN MTBE	
LC50 inhalation rat (ppm)	23576 ppm/4h	
ATE CLP (oral)	4000.000 mg/kg body weight	
ATE CLP (gases)	23576.000 ppmV/4h	
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)		
LD50 oral rat	4000 mg/kg	
LC50 inhalation rat (ppm)	23576 ppm/4h	
OCTAMETHYLCYCLOTETRASILOXANE UNL	ABELED (556-67-2)	
LD50 oral rat	> 2000 mg/kg Remarks: Behavioral:Excitment. Lungs, Thorax, or Respiration: Dyspnea (IUCLID)	
LD50 dermal rabbit	4640 mg/kg	
LC50 inhalation rat (mg/l)	36000 mg/m ³ 4h	
ATE CLP (dermal)	4640.000 mg/kg body weight	
ATE CLP (vapors)	36.000 mg/l/4h	
ATE CLP (dust, mist)	36.000 mg/l/4h	
Additional information	LD50 Oral - Rat - male - > 4,800 mg/kg (OECD Test Guideline 401). LD50 Dermal - Rat - male and female - > 2,400 mg/kg (OECD Test Guideline 402) Remarks: (IUCLID)	
Skin corrosion/irritation	: Causes skin irritation.	
	Skin – Rabbit - Causes skin irritation	
Serious eye damage/irritation	: Eyes – Rabbit - No eye irritation	
Respiratory or skin sensitization	: Will not occur	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
Specific target organ toxicity – single exposure	: Not classified	
Specific target organ toxicity – repeated exposure	: Not classified	
OCTAMETHYLCYCLOTETRASILOXANE UNLABELED (556-67-2)		
NOAEL (dermal,rat/rabbit,90 days)	>= 960 mg/kg bodyweight/day Rabbit - male and female -21d OECD Test Guideline 410	
Aspiration hazard	: Not classified	
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. central nervous system. Dizziness. Nausea. Vomiting. IF INHALED: Risk of pneumonia.	

IARC group

Symptoms/effects after inhalation

Symptoms/effects after eye contact

EC50 other aquatic organisms 1

- : May be harmful if inhaled. May cause respiratory irritation.
- Symptoms/effects after skin contact : Causes skin irritation.
 - : May cause eye irritation.
- Symptoms/effects after ingestion : May be harmful if swallowed.

: 2B

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.	
OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE		
LC50 fish 1	672 mg/l Pimephales promelas (fathead minnow) - 96 h	
EC50 Daphnia 1	472 mg/l Daphnia magna (Water flea) - 48 h	
EC50 other aquatic organisms 1	491 mg/l Pseudokirchneriella subcapitata (green algae) - 96 h	
LC50 fish 2	> 1000 mg/l other fish - 96 h	
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)		
LC50 fish 1	672 mg/l Pimephales promelas (fathead minnow) - 96 h	
EC50 Daphnia 1	472 mg/l Daphnia magna (Water flea) - 48 h	

491 mg/l Pseudokirchneriella subcapitata (green algae) - 96 h

LC50 fish 2

> 1000 mg/l other fish - 96 h

UG/ML IN MTBE ULM-9441-MT-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

-, -	
OCTAMETHYLCYCLOTETRASILOXANE UNL	ABELED (556-67-2)
LC50 fish 1	200 mg/l Leusicus idue (Golden orfe) - 96h
EC50 Daphnia 1	0.015 mg/l Daphnia magna (Water flea) - 48h
ErC50 (algae)	0.022 mg/l Selenastrum capricornutum (green algae) - 96h
12.2. Persistence and degradability	
OCTAMETHYLCYCLOTETRASILOXANE "D4"	UNLABELED 100 UG/ML IN MTBE
Persistence and degradability	Not readily biodegradable. (OECD 301D method).
Biodegradation	0 %
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)
Persistence and degradability	Not readily biodegradable. (OECD 301D method).
Biodegradation	0 %
OCTAMETHYLCYCLOTETRASILOXANE UNL	ABELED (556-67-2)
Persistence and degradability	aerobic - Exposure time 10 d (OECD Test Guideline 310) Remarks: Not readily biodegradable.
12.3. Bioaccumulative potential	
OCTAMETHYLCYCLOTETRASILOXANE "D4"	UNLABELED 100 UG/ML IN MTBE
Log Pow	1.06
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)
Log Pow	1.06
OCTAMETHYLCYCLOTETRASILOXANE UNL	
Bioconcentration factor (BCF REACH)	14261
Bioaccumulative potential	Biocibcebtratuib factor: 12,400. Pimephales promelas (fathead minnow) - 0.160g/l. Pimephales promelas (fathead minnow) - 28d.
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessmen	t
No additional information available	
12.6. Other adverse effects	
No additional information available	
SECTION 12: Disposal consideration	
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	Weste materiale should be disposed of under conditions which must Enderst. Otate and there is
	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.
SECTION 14: Transport information	
In accordance with ADR / RID / IMDG / IATA / AD	N
14.1. UN number	
UN-No.(DOT)	: 2398
DOT NA no.	UN2398
14.2. UN proper shipping name	
	: Methyl tert-butyl ether
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
	: 3 - Flammable liquid
	FLAMMABLE LIQUID
Packing group (DOT)	: II - Medium Danger

UG/ML IN MTBE ULM-9441-MT-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT RQ	: 1000 lbs
Marine pollutant	: No

14.3. Additional information	
Emergency Response Guide (ERG) Number	: 127
Other information	: No supplementary information available.
Special transport precautions	: Not classified as dangerous in the meaning of transport regulations.
Overland transport	
Packing group (ADR)	: 11
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 33
Classification code (ADR)	: F1
Hazard labels (ADR)	: 3 - Flammable liquids
	3
Orange plates	33 2398
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
EAC	: •3YE
Excepted quantities (ADR)	: E2
Transport by sea	
DOT Vessel Stowage Location	: E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.
MFAG-No	: 127
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
Civil Aeronautics Law	: Flammable liquids
14.4. Environmental hazards	
Other information	: No supplementary information available.
14.5. Special precautions for user	
Special transport precautions	: Not classified as dangerous in the meaning of transport regulations.

UG/ML IN MTBE ULM-9441-MT-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information		
15.1. US Federal regulations		
OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313	
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)		
Subject to reporting requirements of United States SARA Section 313		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
OCTAMETHYLCYCLOTETRASILOXANE UNLABELED (556-67-2)		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.	

15.2. International regulations

CANADA

OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE	
Listed on the Canadian DSL (Domestic Substances List)	
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)	
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)	

15.2.1. National regulations

No additional information available

15.3. US State regulations

OCTAMETHYLCYCLOTETRASILOXANE "D4" UNLABELED 100 UG/ML IN MTBE()					
U.S California - Proposition 65 - Carcinogens List		No			
U.S California - Proposition 65 - Developmental Toxicity		No			
U.S California - Proposition 65 - Reproductive Toxicity - Female		No			
U.S California - Proposition 65 - Reproductive Toxicity - Male		No			
State or local regulations		U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List			
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity -	U.S California - Proposition 65 - Reproductive Toxicity -	No significant risk level (NSRL)	

Male

No

No

No

Female

No

UG/ML IN MTBE ULM-9441-MT-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

OCTAMETHYLCYCLOTETRASILOXANE UNLABELED (556-67-2)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
METHYL TERT-BUTYL ETHER UNLABELED (1634-04-4) State or local regulations					
U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List					
OCTAMETHYLCYCLOTETRASILOXANE UNLABELED (556-67-2)					
State or local regulations					
U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List					

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

,	•
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H315	Causes skin irritation
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H413	May cause long lasting harmful effects to aquatic life
R11	Highly flammable
R38	Irritating to skin
R53	May cause long-term adverse effects in the aquatic environment
F	Highly flammable
Xi	Irritant

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product