

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rules and Regulations

Date of issue: 25/09/2014 Revision date: 29/10/2014

Supersedes: 25/09/2014

Version: 1.1

ULM-9622-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Product name. : DECHLORANE 604 (COMPONENT A) 95% CHEMICAL PURITY UNLABELED 100 UG/ML IN

NONANE

Product code : ULM-9622-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-202-483-7616 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

 Flam. Liq. 3
 H226

 Acute Tox. 4 (Inhalation)
 H332

 Skin Irrit. 2
 H315

 Eye Irrit. 2
 H319

 STOT SE 3
 H336

 Asp. Tox. 1
 H304

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

Xn; R20 Xn; R65 R10

Full text of R-phrases: see section 16

Classification (GHS-US)

 Flam. Liq. 3
 H226

 Acute Tox. 4 (Inhalation)
 H332

 Skin Irrit. 2
 H315

 Eye Irrit. 2A
 H319

 STOT SE 3
 H336

 Asp. Tox. 1
 H304

Adverse physicochemical, human health and environmental effects

Central Nervous System.

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. **Label elements**

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







Signal word (CLP) : Danger

H226 - Flammable liquid and vapor Hazard statements (CLP)

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P261 - Avoid breathing dust, fume, gas, mist, spray, vapors P264 - Wash Both hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, face protection, protective clothing, protective gloves

GHS-US labeling

Hazard pictograms (GHS-US)







Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P261 - Avoid breathing dust, fume, gas, mist, spray, vapors P264 - Wash Both hands thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, face protection, protective clothing, protective gloves

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER/doctor/physician if you feel unwell

P331 - If swallowed, do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362 - Take off contaminated clothing and wash before reuse

P370+P378 - In case of fire: Use Alcohol resistant foam., Carbon dioxide., Dry chemical., Water

spray for extinction

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up

P501 - Dispose of contents/container to Comply with applicable regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS No)111-84-2 (EC no)203-913-4	99.9861	R10 Xn; R20 Xn; R65 R67
DECHLORANE 604 (COMPONENT A) UNLABELED	(CAS No)34571-16-9 (Unlabeled)	0.0139	R52/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS No)111-84-2 (EC no)203-913-4	99.9861	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
DECHLORANE 604 (COMPONENT A) UNLABELED	(CAS No)34571-16-9 (Unlabeled)	0.0139	Aquatic Chronic 4, H413

Name	Product identifier	%	Classification (GHS-US)
N-NONANE UNLABELED	(CAS No)111-84-2	99.9861	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Move out of dangerous area. Consult a physician and show this safety data sheet.

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER/doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.

Wash contaminated clothing before reuse.

First-aid measures after eye contact : Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical

attention

First-aid measures after ingestion : Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

suitable extinguishing media

: For small fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

Reactivity : Vapors may form explosive mixture with air.

5.3. Advice for firefighters

Firefighting instructions : Use water spray to cool unopened containers.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No

smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain spillage, then collect with non-combustible absorbent material. Disposal should be in

accordance with applicable Federal, State and local regulations.

vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : No naked lights. No smoking. Take precautionary measures against static discharge. Use only

non-sparking tools. Use only outdoors or in a well-ventilated area.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Use explosion-proof electrical equipment.

Storage conditions : Store refrigerated (-5 C to 5 C). Protect from light.

Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DECHLORANE 604 (COMPONENT A) 95% CHEMICAL PURITY UNLABELED 100 UG/ML IN NONANE		
Italy - Portugal- USA ACGIH	ACGIH TWA (ppm)	200.0000000000 ppm Central Nervous System
		impairment.

N-NONANE UNLABELED (111-84-2)

Italy - Portugal- USA ACGIH	ACGIH TWA (ppm)	200.0000000000 ppm Central Nervous System
		impairment.

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Personal protective equipment : Protective clothing. Protective goggles. Self-contained breathing apparatus. Gloves.



Hand protection : protective gloves.

Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

Appearance : Liquid.

Molecular mass : 692.5

Color : No data available. Odor : No data available : No data available Odor threshold pΗ No data available Relative evaporation rate (butyl acetate=1) : No data available : -53 °C (- 63 °F) - lit Melting point Freezing point : No data available Boiling point : 151 °C (304 °F) - lit

Flash point : $31.0 \, ^{\circ}\text{C} \, (87.8 \, ^{\circ}\text{F})$ - closed cup

Self ignition temperature : 205 °C (401 °F)

Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapor

Vapor pressure : 12.4 hPa (9.3 mmHg) at 37.7 °C (99.9 °F)

Relative vapor density at 20 °C : No data available Relative density : No data available Solubility : Water: 0 % Log Pow : 5.65

Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : 0.87 - 2.9 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

10.5. Incompatible materials

Strong oxidizing agents.

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

DECHLORANE 604 (COMPONENT A) 95% CHEMICAL PURITY UNLABELED 100 UG/ML IN NONANE	
LC50 inhalation rat (ppm)	3200 ppm/4h
ATE (gases)	4500.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
ATE (dust, mist)	1.500 mg/l/4h

N-NONANE UNLABELED (111-84-2)		
LC50 inhalation rat (ppm)	3200 ppm/4h	
ATE (dust, mist)	1.500 mg/l/4h	

Skin corrosion/irritation : Causes skin irritation.

Skin - rat - Skin irritation - Draize test

Serious eye damage/irritation : Causes serious eye irritation.

No data available

Respiratory or skin sensitization : Not available

No data available

Germ cell mutagenicity : Not available
Carcinogenicity : Not classified
Reproductive toxicity : Not available

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

May cause drowsiness or dizziness.

Specific target organ toxicity (repeated

exposure)

Aspiration hazard

Not classifiedNo data available

: May be fatal if swallowed and enters airways.

Potential Adverse human health effects and

symptoms

: The chemical, physical, and toxicological properties have not been thoroughly investigated.

: May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : Causes eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

DECHLORANE 604 (COMPONENT A) 95% CHEMICAL PURITY UNLABELED 100 UG/ML IN NONANE

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

Symptoms/injuries after inhalation

12.2. Persistence and degradability

Persistence and degradability	Not available.
DECHLORANE 604 (COMPONENT A) UNLABELED (34571-16-9 (Unlabeled))	
Persistence and degradability	Not available.

N-NONANE UNLABELED (111-84-2)

Persistence and degradability Not available.

12.3. Bioaccumulative potential

DECHLORANE 604 (COMPONENT A) 95% CHEMICAL PURITY UNLABELED 100 UG/ML IN NONANE	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

DECHLORANE 604 (COMPONENT A) UNLABELED (34571-16-9 (Unlabeled))

Bioaccumulative potential Not available.

N-NONANE UNLABELED (111-84-2)

29/10/2014 EN (English US)

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

12.4. Mobility in soil

DECHLORANE 604 (COMPONENT A) 95% CHEMICAL PURITY UNLABELED 100 UG/ML IN NONANE	
Ecology - soil	Not available.

DECHLORANE 604 (COMPONENT A) UNLABELED (34571-16-9 (Unlabeled))

Ecology - soil Not available.

N-NONANE UNLABELED (111-84-2)

Not available. Ecology - soil

Results of PBT and vPvB assessment 12.5.

No additional information available

Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

SECTION 13: Disposal considerations

Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local

environmental control regulations.

Waste disposal recommendations : Dispose of contents/container to Comply with applicable regulations.

: Handle empty containers with care because residual vapors are flammable. Additional information

Ecology - waste materials Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

UN number

UN-No.(DOT) : 1920 DOT NA no. UN1920

UN proper shipping name

DOT Proper Shipping Name : Nonanes

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a

flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this

subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

7/10

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. **Additional information**

: No supplementary information available. Other information

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Overland transport

Packing group (ADR) : III

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 30
Classification code (ADR) : F1

Danger labels (ADR) : 3 - Flammable liquids



Orange plates

30 1920

Tunnel restriction code : D/E
Limited quantities (ADR) 5L
EAC : 3Y
Excepted quantities (ADR) : E1

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

MFAG-No : 128

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

DECHLORANE 604 (COMPONENT A) 95% CHEMICAL PURITY UNLABELED 100 UG/ML IN NONANE	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
N-NONANE UNI ARELED (111-84-2)	

N-NONANE UNLABELED (111-04-2)
CADA Costion 244/242 Horord Classes

SARA Section 311/312 Hazard Classes Fire hazard Immediate (acute) health hazard

15.2. International regulations

CANADA

DECHLORANE 604 (COMPONENT A) 95% CHEMICAL PURITY UNLABELED 100 UG/ML IN NONANE

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2.1. National regulations

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

DECHLORANE 604	COMPONENT A	95% CHEMICAL	PURITY UNLABELED	100 UG/ML IN NONANE()
DECLIECTALITE OUT	COMIN CHERT A		I OKII I ONLABELED	100 00/ME III IIOIAAIIE()

State or local regulations U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List

This product does not contain any chemicals known to State of California to cause cancer,

birth defects, or any other reproductive harm.

N-NONANE UNLABELED (111-84-2)

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R- H- and FUH-phrases**

ext of R-, H- and EUH-phrases::		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4	
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4	
Asp. Tox. 1	Aspiration hazard Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation Category 2	
Flam. Liq. 3	Flammable liquids Category 3	
Skin Irrit. 2	skin corrosion/irritation Category 2	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H226	Flammable liquid and vapor	
H304	May be fatal if swallowed and enters airways	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H332 Harmful if inhaled		
H336	May cause drowsiness or dizziness	
H413	May cause long lasting harmful effects to aquatic life	
R10 Flammable		
R20	Harmful by inhalation	
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects	
	in the aquatic environment	
R65	Harmful: may cause lung damage if swallowed	
R67	Vapors may cause drowsiness and dizziness	
Xn	Harmful	

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.


NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard Physical : 0 Minimal Hazard

CIL Mixture SDS

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product