

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 11/18/2015 Revision date: 3/15/2024 Supersedes: 11/18/2015 Version: 2.0

## **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture

Product name : 4,4'-DDT (ring-13C<sub>12</sub>, 99%) 100 µg/mL in nonane

Product code : CLM-1281-S

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Cambridge Isotope Laboratories, Inc.

50 Frontage Rd 01810

ANDOVER, MA, 01810

USA

T 1-800-322-1174

cilsales@isotope.com - www.isotope.com

#### 1.4. Emergency telephone number

Emergency number : 1-703-741-5970

Chemtrec 1-800-424-9300 24 hours

## **SECTION 2: Hazard(s) identification**

## 2.1. Classification of the substance or mixture

#### **GHS US classification**

H226 Flammable liquids Category 3 Flammable liquid and vapor Acute toxicity (inhalation:dust,mist) Category 4 H332 Harmful if inhaled Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation Specific target organ toxicity – Single exposure, Category 3, Narcosis H336 May cause drowsiness or dizziness Aspiration hazard Category 1 May be fatal if swallowed and enters airways H304 Hazardous to the aquatic environment - Chronic Hazard Category 3 H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

H412 - Harmful to aquatic life with long lasting effects

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)

 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.

P264 - Wash Both hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a poison center or doctor if you feel unwell.

P321 - Specific treatment (see Hazard pictograms (CLP) on this label).

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to Comply with applicable regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/Information on ingredients**

## 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
N-NONANE UNLABELED	CAS-No.: 111-84-2	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
4,4'-DDT (RING-13C12, 99%)	CAS-No.: 50-29-3		Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Carc. 2, H351 STOT RE 1, H372 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

## **SECTION 4: First-aid measures**

## 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash

with plenty of soap and water. Wash contaminated clothing before reuse. Get medical

advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be

construed as guaranteeing any specific property of the product.

Symptoms/effects after inhalation : Harmful if inhaled. Danger of serious damage to health by prolonged exposure through

inhalation. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

#### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

## 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

3/15/2024 (Revision date) US - en 3/14

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment

: Dike and contain spill. Dispose as hazardous waste. Comply with local regulations for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information

: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Additional hazards when processed

: Avoid all contact with skin, eyes, or clothing. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the

manufacturer). Take precautionary measures against static discharges.

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

Hygiene measures

Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Store in a well-ventilated place. Keep container tightly closed. Keep dry. Ground/bond container and receiving equipment.

Storage conditions

: Store at room temperature away from light and moisture.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

3/15/2024 (Revision date) US - en 4/14

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4,4′-DDT (ring-¹³C <sub>12</sub> , 99%) 100 μg/mL in nonane			
USA - ACGIH - Occupational Exposure Limits			
Local name	Nonane		
ACGIH OEL TWA [ppm]	200 ppm USA. ACGIH Threshold Limit Values (TLV)		
Remark (ACGIH)	CNS impair		
ACGIH chemical category	No component of this product present at levels greater than or equal to 0.1% is identifiable as a carcinogen or potential carcinogen by ACGIH.		
N-NONANE UNLABELED (111-84-2)			
USA - ACGIH - Occupational Exposure Limits			
Local name	Nonane		
ACGIH OEL TWA [ppm]	200 ppm USA. ACGIH Threshold Limit Values (TLV)		
Remark (ACGIH)	CNS impair		
ACGIH chemical category	No component of this product present at levels greater than or equal to 0.1% is identifiable as a carcinogen or potential carcinogen by ACGIH.		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL TWA [1]	1050 mg/m³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000		
OSHA PEL TWA [2]	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000		
OSHA PEL C	1050 California permissible exposure limits for chemical contaminants.		
OSHA PEL C [ppm]	200 ppm California permissible exposure limits for chemical contaminants.		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL TWA	1050 mg/m³ USA. NIOSH Recommended Exposure Limits		
NIOSH REL TWA [ppm]	200 ppm USA. NIOSH Recommended Exposure Limits		
Remark (NIOSH)	Central Nervous System impairment		
4,4'-DDT (RING-13C12, 99%) (50-29-3)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	1 mg/m³ Liver damage. Confirmed animal carcinogen with unknown relevance to humans.		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL TWA [1]	1 mg/m³ Skin designation		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL TWA	0.5 mg/m³ Potential Occupational Carcinogen		

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

## 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.

#### Materials for protective clothing:

Wear suitable protective clothing and gloves

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Hand protection:

protective gloves

## Eye protection:

Chemical goggles or face shield. Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing, gloves and eye/face protection

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator

#### Personal protective equipment symbol(s):











## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : Colorless

Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : -53 °C (-63 °F) - lit
Boiling point : 151 °C (304 °F) - lit
Flash point : 31 °C (87.8 °F) - closed cup

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable.

Vapor pressure : 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)

Relative vapor density at 20°C : No data available Relative density : No data available

Density : 0.718 g/ml at 25 °C (77 °F)

Molecular mass : 128.3 g/mol Solubility : Water: 0.0002 %

Partition coefficient n-octanol/water (Log Pow) : 5.65

Auto-ignition temperature : 205 °C (401 °F)

Decomposition temperature : No data available

Viscosity, kinematic : ≤ 1.008 mm²/s at 20 °C (68 °F)

Viscosity, dynamic : No data available Explosion limits : 0.87 – 2.9 % (V) Explosive properties : No data available Oxidizing properties : No data available

## 9.2. Other information

No additional information available

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Flammable liquid and vapor. Vapors may form flammable mixture with air.

#### 10.2. Chemical stability

See storage and expiration date on CoA.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

## 10.5. Incompatible materials

No additional information available

## 10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

4,4'-DDT (ring- <sup>13</sup> C <sub>12</sub> , 99%) 100 μg/mL in	n nonane
LC50 Inhalation - Rat	23760 mg/m³ male - 4 h
ATE US (dust, mist)	1.5 mg/l/4h
Additional data	Skin corrosion/irritation, Dermal, rat: Result: Skin Irritation (Draize Test) S. Typhimurium Result negative
N-NONANE UNLABELED (111-84-2)	
LC50 Inhalation - Rat	23760 mg/m³ male - 4 h
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative
4,4'-DDT (RING-13C12, 99%) (50-29-3)	
LD50 oral rat	87 mg/kg
LD50 dermal rabbit	300 mg/kg Remarks: Behavioral:Tremor. Behavioral:Muscle weakness. Behavioral:Ataxia.
ATE US (oral)	87 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.

3/15/2024 (Revision date) US - en 7/14

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

 IARC group
 2A - Probably carcinogenic to humans

 National Toxicology Program (NTP) Status
 Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

## **N-NONANE UNLABELED (111-84-2)**

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

### 4,4'-DDT (RING-13C12, 99%) (50-29-3)

STOT-repeated exposure Causes damage to organs (liver, pancreas) through prolonged or repeated exposure (Dermal, Inhalation, oral).

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : ≤ 1.008 mm²/s at 20 °C (68 °F)

#### **N-NONANE UNLABELED (111-84-2)**

Viscosity, kinematic ≤ 1.008 mm²/s at 20 °C (68 °F)

Potential Adverse human health effects and

symptoms

: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Symptoms/effects after inhalation

Harmful if inhaled. Danger of serious damage to health by prolonged exposure through inhalation. May cause drowsiness or dizziness.

Symptoms/effects after skin contact

Symptoms/effects after eye contact

Symptoms/effects after ingestion

: Causes skin irritation.: Causes serious eye irritation.

: May be fatal if swallowed and enters airways.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

4,4'-DDT (RING-13C12, 99%) (50-29-3)		
LC50 - Fish [1]	0.01 mg/l Pimephales promelas (fathead minnow) - 96 h	
LC50 - Other aquatic organisms [1]	0.01 mg/l Lepomis macrochirus (Bluegill) - 96.0 h	
EC50 - Crustacea [1]	0.00108 mg/l Daphnia magna (Water flea) - 48 h	
LC50 - Fish [2]	0.0034 mg/l Oncorhynchus mykiss (rainbow trout) - 96 h	
ErC50 other aquatic plants	> 20 mg/l Scenedesmus quadricauda (Green algae) - 7 d	
LOEC (chronic)	150 mg/l Oncorhynchus mykiss (rainbow trout) - 96 h	
NOEC (chronic)	113 mg/l Oncorhynchus mykiss (rainbow trout) - 3 d	

#### 12.2. Persistence and degradability

4,4'-DDT (ring-¹³C <sub>12</sub> , 99%) 100 μg/mL in nonane		
Persistence and degradability	May cause long-term adverse effects in the environment.	

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 12.3. Bioaccumulative potential

4,4'-DDT (ring-¹³C <sub>12</sub> , 99%) 100 μg/mL in nonane			
Partition coefficient n-octanol/water (Log Pow)	5.65		
Bioaccumulative potential	Not established.		
N-NONANE UNLABELED (111-84-2)			
Partition coefficient n-octanol/water (Log Pow)	5.65		
Bioaccumulative potential	Indication of bioaccumulation.		
4,4'-DDT (RING-13C12, 99%) (50-29-3)			
BCF - Fish [1]	0.001 mg/l Oncorhynchus mykiss (rainbow trout) - 20 d		
Bioconcentration factor (BCF REACH)	46,670		
Partition coefficient n-octanol/water (Log Pow)	6.91		

#### 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

Other information : Avoid release to the environment. Disposal must be done according to official regulations.

## **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local

environmental control regulations.

Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed

professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

## **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

DOT NA No : UN1920 UN-No. (TDG) : UN1920 UN-No. (IMDG) : 1920 UN-No. (IATA) : 1920

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Nonanes
Proper Shipping Name (TDG) : NONANES
Proper Shipping Name (IMDG) : NONANES
Proper Shipping Name (IATA) : Nonanes

## 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 3 Hazard labels (DOT) : 3

3/15/2024 (Revision date) US - en 9/14

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



#### **TDG**

Transport hazard class(es) (TDG) : 3
Hazard labels (TDG) : 3



#### **IMDG**

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



## 14.4. Packing group

Packing group (DOT) : III
Packing group (TDG) : III
Packing group (IMDG) : III
Packing group (IATA) : III

## 14.5. Environmental hazards

Marine pollutant : Yes (IMDG only)



Other information : No supplementary information available.

## 14.6. Special precautions for user

#### DOT

UN-No.(DOT) : UN1920

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

**TDG** 

UN-No. (TDG) : UN1920
Explosive Limit and Limited Quantity Index : 5 L
Excepted quantities (TDG) : E1
Passenger Carrying Road Vehicle or Passenger : 60 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 128

**IMDG** 

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T2

Tank special provisions (IMDG) : TP1

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : A Flash point (IMDG) : '

Properties and observations (IMDG) : Colourless liquids. Explosive limits: 0.8% to 2.9% normal-NONANE: flashpoint 31°C c.c.

Immiscible with water. Irritating to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) Y344 PCA limited quantity max net quantity (IATA) 10L PCA packing instructions (IATA) 355 60L PCA max net quantity (IATA) 366 CAO packing instructions (IATA) CAO max net quantity (IATA) 220L : 3L ERG code (IATA)

3/15/2024 (Revision date) US - en 11/14

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
N-NONANE UNLABELED	111-84-2	Present	Active	Т
4,4'-DDT (RING-13C12, 99%)	50-29-3	Present	Active	S

N-NONANE UNLABELED (111-84-2)		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	

4,4'-DDT (RING-13C12, 99%) (50-29-3)			
Not subject to reporting requirements of the United States SARA Section 313			
CERCLA RQ	1 lb		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard		

#### 15.2. International regulations

### **CANADA**

## 4,4'-DDT (ring-13C<sub>12</sub>, 99%) 100 μg/mL in nonane

Listed on the Canadian DSL (Domestic Substances List)

#### **N-NONANE UNLABELED (111-84-2)**

Listed on the Canadian DSL (Domestic Substances List)

#### 4,4'-DDT (RING-13C12, 99%) (50-29-3)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

#### **EU-Regulations**

No additional information available

### **National regulations**

## 4,4'-DDT (ring-13C<sub>12</sub>, 99%) 100 μg/mL in nonane

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### **N-NONANE UNLABELED (111-84-2)**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 4,4'-DDT (RING-13C12, 99%) (50-29-3)

Listed on IARC (International Agency for Research on Cancer)

Listed as carcinogen on NTP (National Toxicology Program)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

#### 15.3. US State regulations

4,4'-DDT (RING-13C12, 99%) (50-29-3)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	Yes	Yes	Yes	2 μg/day (DDT. DDE. DDD in combination)	

Component	State or local regulations
N-NONANE UNLABELED(111-84-2)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
4,4'-DDT (RING-13C12, 99%)(50-29-3)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

## **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 03/15/2024

Other information : This product is not radioactive. The data given for this product are those of the corresponding

unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the

corresponding unlabeled compound.

Full text of H-phrases	
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.