

Safety Data Sheet

 according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
 Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 Date of issue: 27/02/2015
 Revision date: 18/11/2020
 Supersedes: 09/10/2019
 Version: 2.0

 CLM-4516-S
 CLM-4516-S
 Supersedes: 09/10/2019
 Version: 2.0

	of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixtures
Product name	: P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%) 100 UG/ML IN NONANE
Product code	: CLM-4516-S
1.2. Relevant identified use	es of the substance or mixture and uses advised against
1.2.1. Relevant identified use	es
Main use category	: Professional use
Industrial/Professional use spec	: For professional use only
1.2.2. Uses advised against	
No additional information available	
	of the safety data sheet
Cambridge Isotope Laboratories,	-
50 Frontage Road	
Andover, MA 01810 USA	
USA: 1-800-322-1174 Int: 1-97	8-749-8000
<u>cilsales@isotope.com</u> www.iso	
Emergency telephone	number
Emergency numbers:	
Chemtrec: 1-800-424-9300 (24 h	
International: 1-703-741-5970 (2	•
SECTION 2: Hazards iden	tification
2.1. Classification of the s	ubstance or mixture
Classification according to Reg	ulation (EC) No. 1272/2008 [CLP]
Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
	H336
Asp. Tox. 1	H304
Full text of hazard classes and H-	statements : see section 16
Classification according to Dire	ctive 67/548/EEC [DSD] or 1999/45/EC [DPD]
R10	
Xn; R20 Xn; R65	
Xi; R36/38	
R67	
Full text of R-phrases: see section	16

GHS-US classification

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of H statements : see section 16

IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Central Nervous System. Flammable liquid and vapor. May cause drowsiness or dizziness. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.



IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to Comply with applicable regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.986	R10 Xn; R20 Xn; R65 Xi; R36/38 R67
P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%)	(CAS-No.) 27176-95-0 (unlabeled)	0.014	Xi; R36/37/38
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%)	(CAS-No.) 27176-95-0 (unlabeled)	0.014	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS-No.) 111-84-2	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%)	(CAS-No.) 27176-95-0 (unlabeled)	0.014	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of R- and H- phrases: see section 16

48/44/2020	EN (Explicit UD) 2/44
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects	: May cause drowsiness or dizziness.
4.2. Most important symptoms and effect	cts, both acute and delayed
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures general	: Call a physician immediately.
4.1. Description of first aid measures	
SECTION 4: First aid measures	

IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

26, 2012 / Rules and Regulations	
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.
4.3. Indication of any immediate media	cal attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. Alcohol resistant foam.
5.2. Special hazards arising from the s	substance or mixture
Fire hazard	: Flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Flammable liquid and vapor. Vapors may form flammable mixture with air.
5.3. Advice for firefighters	
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release me	asures
6.1. Personal precautions, protective	equipment and emergency procedures
General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
6.1.1. For non-emergency personnel	
Emergency procedures	: Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Prevent entry to sewers and public waters. Ave	oid release to the environment.
6.3. Methods and material for contain	ment and cleaning up
For containment	: For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Dike and contain spill. Dispose as hazardous waste. Comply with local regulations for disposal.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13.	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, inclu	ding any incompatibilities
Storage conditions	: Store at room temperature away from light and moisture.
Incompatible materials	: Heat sources.
7.3. Specific end use(s)	
No additional information available	
SECTION 8: Exposure controls/per	rsonal protection
8.1. Control parameters	
P-N-NONYLPHENOL TRIETHOXYLATE (R	ING-13C6, 99%) 100 UG/ML IN NONANE
Italy - Portugal - USA ACGIH ACGIH TWA	
40/44/0000	

IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P-N-NONYLPHENOL TRIETH	IOXYLATE (RING-13C6, 99%) 100 UG/ML IN NONANI	E
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1050 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m³)	1050 mg/m ³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.
N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1050 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m³)	1050 mg/m ³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.

8.2. Exposure controls

Appropriate engineering controls Personal protective equipment

- : Ensure good ventilation of the work station.
- : Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.



Materials for protective clothing	: Wear suitable protective clothing and gloves.
Hand protection	: protective gloves.
Eye protection	: Chemical goggles or face shield. Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing, gloves and eye/face protection.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator.

Environmental exposure controls

: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties The properties listed below are for the solvent, the main component of this mixture.

Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 128.3 g/mol
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available

IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31 °C (87.8 °F) - closed cup
Auto-ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapor
Vapor pressure	: 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.718 g/ml at 25 °C (77 °F)
Solubility	: Water: 0.0002 % at 25 °C (77 °F) - slightly soluble
Log Pow	: 5.65
Log Kow	: No data available
Viscosity, kinematic	: <= 1.008 mm ² /s at 20 °C (68 °F)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 0.87 - 2.9 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity		
10.1. Reactivity		
Flammable liquid and vapor. Vapors may form flammable mixture with air.		
10.2. Chemical stability		
See storage and expiration date on CoA.		
10.3. Possibility of hazardous reactions		
No dangerous reactions known under normal cond	litions of use.	
10.4. Conditions to avoid		
Open flame. Overheating. Direct sunlight. Heat. Sp	parks.	
10.5. Incompatible materials		
No additional information available		
10.6. Hazardous decomposition products		
May release flammable gases.		
SECTION 11: Toxicological information	on	
11.1. Information on toxicological effects		
Acute toxicity	Inhalation:vapour: Harmful if inhaled.	
P-N-NONYLPHENOL TRIETHOXYLATE (RING-	-13C6, 99%) 100 UG/ML IN NONANE	
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h	
ATE CLP (gases)	4500.000 ppmV/4h	
ATE CLP (vapors)	11.000 mg/l/4h	
ATE CLP (dust, mist)	1.500 mg/l/4h	
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)	
Additional information	: S. Typhimurium Result: negative	
N-NONANE UNLABELED (111-84-2)		
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h	
ATE CLP (vapors)	11.000 mg/l/4h	
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)	
Additional information	: S. Typhimurium Result: negative	
Skin corrosion/irritation : Causes skin irritation.		

IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential	
P-N-NONYLPHENOL TRIETHOXYLATE (RING	-13C6, 99%) 100 UG/ML IN NONANE
Log Pow	5.65
Bioaccumulative potential Indication of bioaccumulation.	
N-NONANE UNLABELED (111-84-2)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessment	t
No additional information available	
12.6. Other adverse effects	
Other adverse effects	: Disposal must be done according to official regulations.
SECTION 13: Disposal considerations	3
13.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Hazardous waste due to toxicity.
SECTION 14: Transport information	
In accordance with ADR / RID / IMDG / IATA / AD	Ν
14.1. UN number	
UN-No.(DOT)	: 1920
DOT NA no.	UN1920
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Nonanes
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
18/11/2020	EN (English US) 7/11

IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	: 3 - Flammable liquid
	FLAMMABLE LIQUID
Packing group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table
	2 for UN2672). T2 - 1.5 178.274(d)(2) Normal 178.275(d)(3)
	TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
14.3. Additional information	
Other information	: No supplementary information available.
Overland transport	
Packing group (ADR)	
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 30
Classification code (ADR)	: F1
Hazard labels (ADR)	: 3 - Flammable liquids
Orange plates	30 1920
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	51
EAC	: 3Y
Excepted quantities (ADR)	: E1
Transport by sea	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
MFAG-No	: 128
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
Civil Aeronautics Law	: Flammable liquids

IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.4.	Environmental hazards	
Other in	formation	: No supplementary information available.
14.5.	Special precautions for user	
14.6.	6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
Not applicable		

SECTION 15: Regulatory information

15.1. US Federal regulations

P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%) 100 UG/ML IN NONANE

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the onited otales 100A (Tokie oubs		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.	
N-NONANE UNLABELED (111-84-2)		
Listed on the United States TSCA (Toxic Subs	stances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.	
P-N-NONYLPHENOL TRIETHOXYLATE (RIN	IG-13C6, 99%) (27176-95-0 (unlabeled))	
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313	
15.2. International regulations		

CANADA

P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%) 100 UG/ML IN NONANE	
Listed on the Canadian DSL (Domestic Substances List)	
N-NONANE UNLABELED (111-84-2)	
Listed on the Canadian DSL (Domestic Substances List)	

15.2.1. National regulations

No additional information available

15.3. US State regulations

·····				
P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%) 100 UG/ML IN NONANE()				
U.S California - Proposition 65 - Carcinogens List				
U.S California - Proposition 65 - Developmental Toxicity		No		
U.S California - Proposition 65 - Reproductive Toxicity - Female				
U.S California - Proposition 65 - Reproductive Toxicity - Male		No		
State or local regulations		U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S New Jersey - Right to Know Hazardous Substance List U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances		
N-NONANE UNLABELED (111-84-2)				
U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
	65 - Carcinogens List 65 - Developmental 65 - Reproductive 65 - Reproductive 65 - Reproductive U.S California - Proposition 65 -	n 65 - Carcinogens List No n 65 - Developmental No n 65 - Reproductive No u 65 - Reproductive No U.S Idaho - Non-Carcinogo U.S New Jersey - Right to U.S New Jersey - Right to U.S Massachusetts - Right U.S Pennsylvania - RTK (f U.S Pennsylvania - RTK (f U.S California - Proposition 65 - Developmental Toxicity U.S California - Proposition 65 - Reproductive Toxicity -	n 65 - Carcinogens List No n 65 - Developmental No n 65 - Reproductive No n 65 - Reproductive No n 65 - Reproductive No u 65 - Reproductive No u 65 - Reproductive No U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Accept U.S New Jersey - Right to Know Hazardous Substance List U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S Pennsylvania - RTK (Right to Know) List U.S New York - Reporting of Releases Part 597 - List of Ha 111-84-2) U.S California - Proposition 65 - Reproductive Toxicity - V.S California - Proposition 65 - Reproductive Toxicity - New York - Reproductive To	

No

No

No

No

IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%) (27176-95-0 (unlabeled))				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
N-NONANE UNLABELED (111-84-2)			
State or local regulations				
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S New Jersey - Right to Know Hazardous Substance List U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances				
P-N-NONYLPHENOL TRIETHOXYLATE (RING-13C6, 99%) (27176-95-0 (unlabeled))				
State or local regulations				
U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List				

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:


Acute toxicity (inhalation:vapour) Category 4
Aspiration hazard Category 1
Serious eye damage/eye irritation Category 2
Flammable liquids Category 3
Skin corrosion/irritation Category 2
Specific target organ toxicity (single exposure) Category 3
Specific target organ toxicity (single exposure) Category 3
Flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
Harmful if inhaled
May cause respiratory irritation
May cause drowsiness or dizziness
Flammable
Harmful by inhalation
Irritating to eyes, respiratory system and skin
Irritating to eyes and skin
Harmful: may cause lung damage if swallowed
Vapors may cause drowsiness and dizziness
Irritant
Harmful

NFPA health hazard

NFPA fire hazard

NFPA reactivity

- : 2 Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- : 3 Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- : 0 Material that in themselves are normally stable, even under fire conditions.



IN NONANE CLM-4516-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product