



ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/01/2022

Revision date:

Version: 1.0

DLM-271-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name : ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE
Product code : DLM-271-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Dermal) H312
Skin Irrit. 2 H315
Eye Irrit. 2 H319
Carc. 2 H351
STOT SE 3 H335
STOT SE 3 H336
STOT RE 2 H373

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc. Cat. 3; R40
Xn; R21/22
Xi; R36/37/38
R67
T; R48

Full text of R-phrases: see section 16

GHS-US classification

Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Dermal) H312
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Carc. 2 H351
STOT SE 3 H335

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT SE 3 H336
STOT RE 2 H373

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Liver, Pancreas, Blood, Central nervous system, Heart, Kidney. Inhalation: anesthetic effects, nausea and drunkenness. Suspected of causing cancer (in contact with skin, if swallowed, if inhaled). May cause damage to organs (liver, blood, central nervous system) through prolonged or repeated exposure (if swallowed, if inhaled). May cause drowsiness or dizziness. Harmful in contact with skin. Harmful if swallowed. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

GHS07

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H302+H312 - Harmful if swallowed or in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer (in contact with skin, if inhaled, if swallowed)
H373 - May cause damage to organs (liver, pancreas, blood, central nervous system, heart, kidneys) through prolonged or repeated exposure (in contact with skin, if inhaled, if swallowed)

Precautionary statements (CLP) :

P260 - Do not breathe dust, mist, spray, vapors.
P264 - Wash both hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H302+H312 - Harmful if swallowed or in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer (Dermal, Inhalation, oral)
H373 - May cause damage to organs (liver, pancreas, blood, central nervous system, heart, kidneys) through prolonged or repeated exposure (Dermal, Inhalation, oral)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe fume, mist, spray, vapors.
P261 - Avoid breathing fume, mist, spray, vapors.
P264 - Wash Both hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell
P302+P352 - If on skin: Wash with plenty of water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention.
 P312 - Call a poison center or doctor if you feel unwell
 P314 - Get medical advice/attention if you feel unwell.
 P321 - Specific treatment (see Hazard pictograms (CLP) on this label)
 P330 - Rinse mouth.
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P362 - Take off contaminated clothing and wash before reuse.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P405 - Store locked up.
 P501 - Dispose of contents/container to Comply with applicable regulations

2.3. Other hazards

PBT: not relevant – no registration required

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
METHYLENE CHLORIDE UNLABELED	(CAS-No.) 75-09-2 (EC-No.) 200-838-9 (EC Index-No.) 602-004-00-3 (REACH-no) 01-2119480404-41	99.924869	Xi; R36/37/38 Carc.Cat.3; R40 T; R48/25 R67 Xn; R21/22
ETHYLENE OXIDE (D4, 98%)	(CAS-No.) 6552-57-4 (EC-No.) 200-849-9 (Unlabeled) (EC Index-No.) 603-023-00-X (Unlabeled) (REACH-no) 01-2119432402-53	0.075131	F+; R12 R5 Xi; R36/37/38 T; R23 Carc.Cat.2; R45 Carc.Cat.2; R49 Muta.Cat.2; R46 R52/53
HYDROQUINONE UNLABELED	(CAS-No.) 123-31-9 (EC-No.) 204-617-8 (EC Index-No.) 604-005-00-4	0.000075	Muta.Cat.1; R46 T+; R26 T; R24/25 Xn; R22 Xi; R36 Xi; R37 Xi; R39 N; R50

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
METHYLENE CHLORIDE UNLABELED	(CAS-No.) 75-09-2 (EC-No.) 200-838-9 (EC Index-No.) 602-004-00-3 (REACH-no) 01-2119480404-41	99.924869	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 STOT SE 3, H335 STOT RE 2, H373
ETHYLENE OXIDE (D4, 98%)	(CAS-No.) 6552-57-4 (EC-No.) 200-849-9 (Unlabeled) (EC Index-No.) 603-023-00-X (Unlabeled) (REACH-no) 01-2119432402-53	0.075131	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT SE 3, H335 Aquatic Chronic 3, H412

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
HYDROQUINONE UNLABELED	(CAS-No.) 123-31-9 (EC-No.) 204-617-8 (EC Index-No.) 604-005-00-4	0.000075	Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Inhalation:dust,mist), H330 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 2, H351 STOT SE 3, H335 Aquatic Acute 1, H400
Name	Product identifier	%	GHS-US classification
METHYLENE CHLORIDE UNLABELED	(CAS-No.) 75-09-2	99.924869	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H336 STOT SE 3, H335 STOT RE 2, H373
ETHYLENE OXIDE (D4, 98%)	(CAS-No.) 6552-57-4	0.075131	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 1A, H340 Carc. 1A, H350 STOT SE 3, H335 Aquatic Chronic 3, H412
HYDROQUINONE UNLABELED	(CAS-No.) 123-31-9	0.000075	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness. Suspected of causing cancer (in contact with skin, if inhaled, if swallowed). May cause damage to organs (central nervous system, kidneys, liver) through prolonged or repeated exposure (in contact with skin, if inhaled, if swallowed).
Symptoms/effects after inhalation	: May be harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Harmful in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Use personal protective equipment as required. Ventilate spillage area. Do not breathe dust, fume, gas, mist, spray, vapors. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For containment : Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store refrigerated (-5 °C to 5 °C). Protect from light.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Central Nervous system impairment. Carboxyhemoglobinemia. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Confirmed animal carcinogen with unknown relevance to humans. Potential Occupational Carcinogen See Appendix A.
USA OSHA	OSHA PEL (STEL) (mg/m ³)	435 mg/m ³ Basis: California permissible exposure limits for chemical contaminants (Title 8, Article 107) see section 5202
USA OSHA	OSHA PEL (STEL) (ppm)	125 ppm Basis: OSHA Specially Regulated Chemicals/Carcinogens California permissible exposure limits for chemical contaminants (Title 8, Article 107) see section 5202
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	87 mg/m ³ Basis: California permissible exposure limits for chemical contaminants (Title 8, Article 107) see section 5202

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE		
USA OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm Basis: OSHA Specifically Regulated Chemicals/Carcinogens California permissible exposure limits for chemical contaminants (Title 8, Article 107) see section 5202
USA OSHA	Remark (OSHA)	Substance listed; for mor information see OSHA document 1910.1052. See Table Z-2. This section applies to all occupational exposures to methylene chloride (MC). Chemical Abstracts Service Registry Number 75-09-2, in general industry, construction and shipyard employment. Methylene chloride (MC) means an organic compound with chemical formula CH ₂ Cl ₂ . Its Chemical Abstracts Service Registry Number is 75-09-2. Its molecular weight is 8.9 g/mole. OSHA Specifically regulated carcinogen.
METHYLENE CHLORIDE UNLABELED (75-09-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Central Nervous system impairment. Carboxyhemoglobinemia. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Confirmed animal carcinogen with unknown relevance to humans. Potential Occupational Carcinogen See Appendix A.
USA OSHA	OSHA PEL (STEL) (mg/m ³)	435 mg/m ³ Basis: California permissible exposure limits for chemical contaminants (Title 8, Article 107) see section 5202
USA OSHA	OSHA PEL (STEL) (ppm)	125 ppm Basis: OSHA Specially Regulated Chemicals/Carcinogens California permissible exposure limits for chemical contaminants (Title 8, Article 107) see section 5202
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	87 mg/m ³ Basis: California permissible exposure limits for chemical contaminants (Title 8, Article 107) see section 5202
USA OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm Basis: OSHA Specifically Regulated Chemicals/Carcinogens California permissible exposure limits for chemical contaminants (Title 8, Article 107) see section 5202
USA OSHA	Remark (OSHA)	Substance listed; for mor information see OSHA document 1910.1052. See Table Z-2. This section applies to all occupational exposures to methylene chloride (MC). Chemical Abstracts Service Registry Number 75-09-2, in general industry, construction and shipyard employment. Methylene chloride (MC) means an organic compound with chemical formula CH ₂ Cl ₂ . Its Chemical Abstracts Service Registry Number is 75-09-2. Its molecular weight is 8.9 g/mole. OSHA Specifically regulated carcinogen.
HYDROQUINONE UNLABELED (123-31-9)		
Italy - Portugal - USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ Eye irritation. Eye damage 2008 Adoption . Sensitizer.
ETHYLENE OXIDE (D4, 98%) (6552-57-4)		
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	9 mg/m ³ Potential Occupational Carcinogen. 10 minute per day ceiling value.
USA NIOSH	NIOSH REL (ceiling) (ppm)	5 ppm Potential Occupational Carcinogen. 10 minute per day ceiling value.
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm Central Nervous System impairment. Cancer. Suspected human carcinogen.
USA OSHA	OSHA PEL (STEL) (ppm)	5 ppm Central Nervous System impairment. Cancer. Suspected human carcinogen.
ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	706 mg/m ³	

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE	
Acute - local effects, inhalation	353 mg/m ³
Long-term - systemic effects, dermal	4750 mg/kg bodyweight/day
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	353 mg/m ³
Acute - local effects, inhalation	88.3 mg/m ³
Long-term - systemic effects, oral	0.06 mg/kg bodyweight/day
Long-term - systemic effects, dermal	2395 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.54 mg/l
PNEC aqua (marine water)	0.194 mg/l
PNEC aqua (intermittent, freshwater)	0.27 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	4.47 mg/kg dwt
PNEC sediment (marine water)	1.61 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.583 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	26 mg/l

8.2. Exposure controls

- Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



- Materials for protective clothing : Wear suitable protective clothing and gloves.
- Hand protection : Wear suitable protective clothing and gloves.
- Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses. Safety glasses.
- Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
- Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

- Physical state : Liquid
- Appearance : Liquid
- Molecular mass : 84.93 g/mol
- Color : Colorless
- Odor : Sweet, penetrating, ether-like odor
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Relative evaporation rate (ether=1) : 0.71
- Melting point : -97 °C (-143 °F)
- Freezing point : No data available
- Boiling point : 39.8 - 40 °C (103.6 - 104 °F)
- Flash point : No data available
- Auto-ignition temperature : 556.1 °C (1,033.0 °F); 622.0 °C (1,223.6 °F)
- Decomposition temperature : No data available
- Flammability (solid, gas) : Not applicable
- Vapor pressure : 470.9 hPa (353.2 mmHg) at 20 °C (68 °F)
- Relative vapor density at 20 °C : 2.93 - (Air = 1.0)
- Relative density : No data available

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific gravity / density	: 1.325 g/ml at 25 °C (77 °F)
Solubility	: Water: Slightly soluble
Log Pow	: 1.25
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 12 - 19 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Protect from sunlight.

10.5. Incompatible materials

Alkali metals. Aluminum. Strong oxidizing agents. Bases. Magnesium. Strong acids. Strong bases. Vinyl.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Hydrogen chloride.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin.

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg (OECD Test Guideline 402)
LC50 inhalation rat (mg/l)	52000 mg/m ³
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight

METHYLENE CHLORIDE UNLABELED (75-09-2)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg (OECD Test Guideline 402)
LC50 inhalation rat (mg/l)	52000 mg/m ³
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (vapors)	52.000 mg/l/4h
ATE CLP (dust, mist)	52.000 mg/l/4h

HYDROQUINONE UNLABELED (123-31-9)	
LD50 oral rat	367.3 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

ETHYLENE OXIDE (D4, 98%) (6552-57-4)	
LC50 inhalation rat (ppm)	800 ppm/4h Remarks: Lungs, Thorax, or Respiration: Other changes. Liver: Other changes. Kidney, Ureter, Bladder: Other changes.
ATE CLP (gases)	700.000 ppmV/4h

Skin corrosion/irritation	: Skin – Rabbit - Irritating to skin - Result: 24 Hours
Serious eye damage/irritation	: Eyes – Rabbit - Result: Irritating to eyes - 24 Hours. (Draize Test)
Respiratory or skin sensitization	: Not available
Germ cell mutagenicity	: Rat.- DNA Damage

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Carcinogenicity. rat. Inhalation. Tumorigenic: Carcinogenic by RTECS criteria. endocrine system. Tumors. Limited evidence of a carcinogenic effect. Suspected human carcinogens

ETHYLENE OXIDE (D4, 98%) (6552-57-4)	
Additional information	OSHA specifically regulated carcinogen.
Reproductive toxicity	: Not available
Specific target organ toxicity – single exposure	: May cause respiratory irritation. May cause drowsiness or dizziness
Specific target organ toxicity – repeated exposure	: Inhalation. May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation). Oral
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Harmful if swallowed. Harmful in contact with skin. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: May be harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Harmful in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE	
LC50 fish 1	193 mg/l Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	1682 mg/l Daphnia magna (Water flea) - 48 h
NOEC (chronic)	130 mg/l Cyprinodon variegatus (sheepshead minnow) - 96 h
METHYLENE CHLORIDE UNLABELED (75-09-2)	
LC50 fish 1	193 mg/l Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	1682 mg/l Daphnia magna (Water flea) - 48 h
NOEC (chronic)	130 mg/l Cyprinodon variegatus (sheepshead minnow) - 96 h
HYDROQUINONE UNLABELED (123-31-9)	
LC50 fish 1	0.04 - 0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 96 h
EC50 Daphnia 1	0.13 mg/l Daphnia magna (Water flea) - 48 h
ErC50 (algae)	0.335 mg/l Pseudokirchneriella subcapitata (green algae) - 72 h
ETHYLENE OXIDE (D4, 98%) (6552-57-4)	
LC50 fish 1	84 mg/l Pimephales promelas (fathead minnow) - 96 h

12.2. Persistence and degradability

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE	
Biodegradation	< 26 % - Not readily biodegradable. (OECD Test Guideline 301C)
METHYLENE CHLORIDE UNLABELED (75-09-2)	
Biodegradation	< 26 % - Not readily biodegradable. (OECD Test Guideline 301C)
HYDROQUINONE UNLABELED (123-31-9)	
Persistence and degradability	Biotic/Aerobic. Biodegradability: Result - Readily biodegradable.

12.3. Bioaccumulative potential

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE	
Log Pow	1.25
Bioaccumulative potential	Does not accumulate in organisms.
METHYLENE CHLORIDE UNLABELED (75-09-2)	
Log Pow	1.25
Bioaccumulative potential	Does not accumulate in organisms.
HYDROQUINONE UNLABELED (123-31-9)	
BCF fish 1	0.05 mg/l Leuciscus idus (Golden orfe) - 3d
Bioconcentration factor (BCF REACH)	40

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HYDROQUINONE UNLABELED (123-31-9)	
Log Pow	0.59

ETHYLENE OXIDE (D4, 98%) (6552-57-4)	
Log Pow	0.3

12.4. Mobility in soil

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE	
---	--

12.5. Results of PBT and vPvB assessment

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE	
PBT: not relevant – no registration required	

METHYLENE CHLORIDE UNLABELED (75-09-2)	
PBT: not relevant – no registration required	

12.6. Other adverse effects

Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Dispose of as unused product.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT) : 1593
DOT NA no. UN1593

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Dichloromethane
Class (DOT) : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132
Hazard labels (DOT) : 6.1 - Poison



Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
IP8 - Ammonia solutions may be transported in rigid or composite plastic IBCs (31H1, 31H2 and 31HZ1) that have successfully passed, without leakage or permanent deformation, the hydrostatic test specified in 178.814 of this subchapter at a test pressure that is not less than 1.5 times the vapor pressure of the contents at 55 C (131 F).
N36 - Aluminum or aluminum alloy construction materials are permitted only for halogenated hydrocarbons that will not react with aluminum.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 153
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Additional information


Other information : No supplementary information available.

Overland transport

Packing group (ADR) : III
Class (ADR) : 6.1 - Toxic substances
Hazard identification number (Kemler No.) : 60
Classification code (ADR) : T1
Hazard labels (ADR) : 6.1 - Toxic substances



Orange plates :



Tunnel restriction code (ADR) : E
Limited quantities (ADR) : 5l
EAC : 2Z
Excepted quantities (ADR) : E1

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
MFAG-No : 160

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)
Civil Aeronautics Law : Toxic and infectious substances/Toxic substances

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313
METHYLENE CHLORIDE UNLABELED (75-09-2)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HYDROQUINONE UNLABELED (123-31-9)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Listed on the United States SARA Section 302
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313;

ETHYLENE OXIDE (D4, 98%) (6552-57-4)	
Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Fire hazard Sudden release of pressure hazard Immediate (acute) health hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE
Listed on the Canadian DSL (Domestic Substances List)

ETHYLENE OXIDE (D4, 98%) (6552-57-4)
Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE ()	
U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List

METHYLENE CHLORIDE UNLABELED (75-09-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

HYDROQUINONE UNLABELED (123-31-9)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

ETHYLENE OXIDE (D4, 98%) (6552-57-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

METHYLENE CHLORIDE UNLABELED (75-09-2)	
State or local regulations	
U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List	

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HYDROQUINONE UNLABELED (123-31-9)
State or local regulations
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
ETHYLENE OXIDE (D4, 98%) (6552-57-4)
State or local regulations
U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Gas 1	Flammable gases Category 1
Muta. 1B	Germ cell mutagenicity Category 1B
Muta. 2	Germ cell mutagenicity Category 2
Press. Gas (Comp.)	Gases under pressure Compressed gas
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects
R12	Extremely flammable
R21/22	Harmful in contact with skin and if swallowed
R22	Harmful if swallowed

ETHYLENE OXIDE (STABILIZED W/ 0.1% HYDROQUINONE) (D4, 98%) 1000 UG/ML IN METHYLENE CHLORIDE

DLM-271-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

R23	Toxic by inhalation
R24/25	Toxic in contact with skin and if swallowed
R26	Very toxic by inhalation
R36	Irritating to eyes
R36/37/38	Irritating to eyes, respiratory system and skin
R37	Irritating to respiratory system
R39	Danger of very serious irreversible effects
R40	Limited evidence of a carcinogenic effect
R45	May cause cancer
R46	May cause heritable genetic damage
R48/23	Toxic: danger of serious damage to health by prolonged exposure through inhalation
R48/25	Toxic: danger of serious damage to health by prolonged exposure if swallowed
R49	May cause cancer by inhalation
R5	Heating may cause an explosion
R50	Very toxic to aquatic organisms
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R67	Vapors may cause drowsiness and dizziness
F+	Extremely flammable
N	Dangerous for the environment
T	Toxic
T+	Very toxic
Xi	Irritant
Xn	Harmful

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 0 Minimal Hazard

Physical

: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product