

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 24/08/2015

Revision date:

Version: 1.0

ULM-2425-S

SECTION 1: Identification	of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixture
Product name.	: CIS-HEPTACHLOR EPOXIDE UNLABELED 100 UG/ML IN NONANE
Product code	: ULM-2425-S
1.2. Relevant identified use	s of the substance or mixture and uses advised against
1.2.1. Relevant identified use	S
Industrial/Professional use spec	: For professional use only.
1.2.2. Uses advised against	
No additional information available	
1.3. Details of the supplier of	of the safety data sheet
Cambridge Isotope Laboratories, Ir 50 Frontage Road Andover, MA 01810 USA	IC.
USA: 1-800-322-1174 Int: 1-978 cilsales@isotope.com www.isoto	
Emergency telephone r	number
Emergency numbers:	
Chemtrec: 1-800-424-9300 (24 ho International: 1-703-741-5970 (24	
SECTION 2: Hazards ident	ification
2.1. Classification of the su	bstance or mixture
Classification according to Regu	Ilation (EC) No. 1272/2008 [CLP]
Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Full text of H-phrases: see section	16
Classification according to Direc	tive 67/548/EEC or 1999/45/EC
Xn; R20 Xn; R65 R10	
Full text of R-phrases: see section	16
GHS-US classification	
Flam. Liq. 3 Acute Tox. 4 (Inhalation:dust,mist) Skin Irrit. 2 Eye Irrit. 2A	H226 H332 H315 H319

Adverse physicochemical, human health and environmental effects Central Nervous System.

H336 H304

STOT SE 3

Asp. Tox. 1


ULM-2425-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Label elements 2.2.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]



Signal word (CLP)		
Hazardous ingredients		
Hazard statements (CLP)		

Precautionary statements (CLP)

: Danger

- : N-NONANE UNLABELED

GHS02

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways

GHS08

- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H336 May cause drowsiness or dizziness
- : P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

GHS07

- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical, lighting, ventilating equipment
- P261 Avoid breathing dust, fume, gas, mist, spray, vapours
- P264 Wash Both hands thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear eye protection, face protection, protective clothing, protective gloves

GHS-US labelling

Hazard pictograms (G	HS-US)
----------------------	--------

Signal word (GHS-US)
Hazard statements (GHS-US)

Precautionary statements (GHS-US)

GHS08 GHS07

: Danger

GHS02

- : H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H319 Causes serious eve irritation
- H332 Harmful if inhaled
- H336 May cause drowsiness or dizziness
- P210 Keep away from heat, hot surfaces, open flames, sparks. No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical, lighting, ventilating equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing dust, fume, gas, mist, spray, vapours
- P264 Wash Both hands thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear eye protection, face protection, protective clothing, protective gloves
- P301+P310 IF SWALLOWED: immediately call a POISON CENTER or doctor/physician
 - P302+P352 IF ON SKIN: Wash with plenty of soap and water
 - P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 - P304+P340 IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
 - P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P312 Call a POISON CENTER/doctor/physician if you feel unwell
- P321 Specific treatment (see Hazard pictograms (CLP) on this label)
- P331 If swallowed, do NOT induce vomiting
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P337+P313 If eye irritation persists: Get medical advice/attention
- P362 Take off contaminated clothing and wash before reuse
- P370+P378 In case of fire: Use Alcohol resistant foam, Carbon dioxide., Dry chemical, Water spray for extinction
- P403+P233 Store in a well-ventilated place. Keep container tightly closed
 - P403+P235 Store in a well-ventilated place. Keep cool

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up

P501 - Dispose of contents/container to Comply with applicable regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	99.986	R10 Xn; R20 Xn; R65 R67 Xi; R38
CIS-HEPTACHLOR EPOXIDE UNLABELED	(CAS No) 1024-57-3 (EC no) 213-831-0 (EC index no) 602-063-00-5	0.014	T+; R28 N; R50/53
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
CIS-HEPTACHLOR EPOXIDE UNLABELED	(CAS No) 1024-57-3 (EC no) 213-831-0 (EC index no) 602-063-00-5	0.014	Acute Tox. 2 (Oral), H300 Carc. 2, H351 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410
Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS No) 111-84-2	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general	: Move out of dangerous area. Consult a physician and show this safety data sheet.			
First-aid measures after inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.			
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Wash with plenty of soap and water. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).			
First-aid measures after eye contact	: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.			
First-aid measures after ingestion	: Immediately call a POISON CENTER or doctor/physician.			
4.2. Most important symptoms and effects, both acute and delayed				
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.			
Symptoms/injuries after skin contact	: Causes skin irritation.			
Symptoms/injuries after eye contact	: Causes eye irritation.			
Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.				
4.3. Indication of any immediate medical attention and special treatment needed				
No additional information available				

ULM-2425-S

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	nd according to Federal Register / Vol. 77, No. 58		
SECTION 5: Firefighting mea	sures		
5.1. Extinguishing media			
Suitable extinguishing media	: Use water spray, alcohol-resi	stant foam, dry chemical, or carbon dioxide.	
5.2. Special hazards arising from	om the substance or mixture		
Fire hazard	: Flammable liquid and vapour		
Explosion hazard	: May form flammable/explosiv		
Reactivity	: Vapors may form explosive m	nixture with air.	
5.3. Advice for firefighters			
Firefighting instructions	: Use water spray to cool unop	ened containers.	
Protection during firefighting	: Do not enter fire area without	proper protective equipment, including respiratory protection.	
SECTION 6: Accidental relea	se measures		
	tective equipment and emergency proce	dures	
General measures		e special care to avoid static electric charges. No naked lights. No	
	smoking.		
6.1.1. For non-emergency perso	nnel		
6.1.1. For non-emergency perso Emergency procedures		oment. Avoid breathing vapors, mist or gas. Ensure adequate	
Emergency procedures	ventilation. Remove all source	es of ignition. Evacuate personnel to safe areas. Beware of vapours ve concentrations. Vapours can accumulate in low areas.	
6.1.2. For emergency responder	s		
Protective equipment	: Avoid breathing dust, mist or	spray.	
6.2. Environmental precaution	S		
		s. Discharge into the environment must be avoided.	
	containment and cleaning up	°	
For containment		with non-combustible absorbent material. Disposal should be in	
For containment		ederal, State and local regulations.	
6.4. Reference to other section	IS		
No additional information available			
SECTION 7: Handling and st	orage		
7.1. Precautions for safe hand	ling		
Additional hazards when processed	: Handle empty containers with	n care because residual vapours are flammable.	
Precautions for safe handling	non-sparking tools. Use only	: No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust, mist or	
	spray.		
Hygiene measures	: Wash Both hands thoroughly	after handling.	
7.2. Conditions for safe storag	e, including any incompatibilities		
Technical measures		to avoid static electricity should be followed. Ground/bond oment. Use explosion-proof electrical equipment.	
Storage conditions	: Store at room temperature av	vay from light and moisture.	
Incompatible materials	: Heat sources.		
7.3. Specific end use(s)	7.3. Specific end use(s)		
No additional information available			
SECTION 8: Exposure control	bls/personal protection		
8.1. Control parameters			
CIS-HEPTACHLOR EPOXIDE UNLABELED 100 UG/ML IN NONANE			
	BIH TWA (ppm)	200.000000000 ppm Central Nervous System impairment.	
N-NONANE UNLABELED (111-84-2 Italy - Portugal - USA ACGIH ACG	2) GIH TWA (ppm)	200.000000000 ppm Central Nervous System	
ACC	(וויאן) איזי דווי	impairment.	

ULIVI-2423-3

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls Personal protective equipment

: Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Hand protection	:	We
Eye protection	:	We
Skin and body protection	:	We
Respiratory protection	:	Wł
		roo

- Wear suitable protective clothing and gloves.
- : Wear safety glasses with side shields (or goggles) and a face shield.
- : Wear suitable protective clothing.
- : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and c	hemical properties		
The properties listed below are for the solvent, the main component of this mixture.			
Physical state	: Liquid		
Appearance	: Liquid.		
Molecular mass	: 128.3 g/mol		
Colour	: Colourless.		
Odour	: No data available		
Odour threshold	: No data available		
рН	: No data available		
Relative evaporation rate (butylacetate=1)	: No data available		
Melting point	: No data available		
Freezing point	: -53 °C (- 63 °F) - lit		
Boiling point	: 151 °C (304 °F) - lit		
Flash point	: 31.0 °C (87.8 °F) - closed cup		
Self ignition temperature	: 205 °C (401 °F)		
Decomposition temperature	: No data available		
Flammability (solid, gas)	: Flammable liquid and vapour		
Vapour pressure	: 12.4 hPa (9.3 mmHg) at 37.7 °C (99.9 °F)		
Relative vapour density at 20 °C	: No data available		
Relative density	: No data available		
Density	: 0.718 g/ml at 25 °C (77 °F)		
Solubility	: Water: 0 %		
Log Pow	: 5.65		
Log Kow	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
Explosive properties	: No data available		
Oxidising properties	: No data available		
Explosive limits	: 0.87 - 2.9 % (V)		
0.2 Other information			

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity					
10.1.	Reactivity				
Vapors	Vapors may form explosive mixture with air.				
10.2.	Chemical stability				
See sto	See storage and expiration date on CoA.				
10.3.	Possibility of hazardous reactions				
No additional information available					
10.4.	Conditions to avoid				
Open fla	Open flame. Overheating. Direct sunlight. Heat. Sparks.				

ULM-2425-S

Safety Data Sheet

3/2010 and according to Federal Register / Vol. 77. No. 58 / Monday, March 26, 2012 / Rules and Regulation a

according to Regulation (EC) No. 453/2010 and accordin	g to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
10.5. Incompatible materials	
Strong oxidizing agents.	
10.6. Hazardous decomposition products	
May release flammable gases.	
SECTION 11: Toxicological informat	ion
11.1. Information on toxicological effects	
Acute toxicity	: Harmful if inhaled.
CIS-HEPTACHLOR EPOXIDE UNLABELED	100 UG/ML IN NONANE
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h
LC50 inhalation rat (ppm)	3200 ppm/4h
ATE (gases)	3200.000 ppmV/4h
ATE (vapours)	11.000 mg/l/4h
ATE (dust,mist)	1.500 mg/l/4h
N-NONANE UNLABELED (111-84-2)	22760 ma/m3 mala 4 h
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h
LC50 inhalation rat (ppm)	3200 ppm/4h
ATE (gases)	3200.000 ppmV/4h
ATE (vapours)	11.000 mg/l/4h
ATE (dust,mist)	23.760 mg/l/4h
CIS-HEPTACHLOR EPOXIDE UNLABELED (1024-57-3)
LD50 oral rat	15 mg/kg
ATE (oral)	15.000 mg/kg bodyweight
	LD50 Oral Mouse 39 mg/kg
	LD50 Oral Rabbit 144 mg/kg
Skin corrosion/irritation	: Causes skin irritation.
	Skin - rat - Skin irritation - Draize test
Serious eye damage/irritation	: Causes serious eve irritation.
conous eye damage/imation	No data available
Respiratory or skin sensitisation	: Not available
Respiratory of skin sensitisation	No data available
Germ cell mutagenicity	: Not available
Carcinogenicity	: Not classified
Reproductive toxicity	: Not available
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
	May cause drowsiness or dizziness.
Specific target organ toxicity (repeated	: Not classified
exposure)	No data available
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Harmful if inhaled.
Symptoms/injuries after inhalation	 Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
cymptomo/injunes alter ingestion	. May be talar ii Swanowea ana enters an ways.

SECTION 12: Ecological information			
12.1. Tox	xicity		
-			
CIS-HEPTA	CIS-HEPTACHLOR EPOXIDE UNLABELED (1024-57-3)		
LC50 fishes	s 1	0.02 mg/l Oncorhynchus mykiss (rainbow trout) -96h	

LC50 fishes 1	0.02 mg/l Oncorhynchus mykiss (rainbow trout) -96h
EC50 Daphnia 1	0.24 mg/l Daphnia magna (Water flea) -48h

ULM-2425-S

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Regulation (EC) No. 453/2010 and according	to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
CIS-HEPTACHLOR EPOXIDE UNLABELED 1	100 UG/ML IN NONANE
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
N-NONANE UNLABELED (111-84-2)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
CIS-HEPTACHLOR EPOXIDE UNLABELED (1	1024-57-3)
Bioconcentration factor (BCF REACH)	14400
Log Pow	5.40
Bioaccumulative potential	Bioaccumulative potential: Pimephales promelas (fathead minnow)- 32d.
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessme	né
No additional information available	n.
12.6. Other adverse effects	
Other adverse effects	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposa Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SECTION 13: Disposal consideration	S
13.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Hazardous waste due to toxicity.
SECTION 14: Transport information	
In accordance with ADR / RID / ADNR / IMDG / I	CAO / IATA
14.1. UN number	
UN-No.(DOT)	: 1920
DOT NA no.	UN1920
14.2. UN proper shipping name	
DOT Proper Shipping Name	: Nonanes
Department of Transportation (DOT) Hazard	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Classes	
Hazard labels (DOT)	: 3 - Flammable liquid
	3
Packing group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
	TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
04/05/2016	EN (English) 7/10

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203	
DOT Packaging Bulk (49 CFR 173.xxx)	: 242	
14.3. Additional information		
Other information	: No supplementary information available.	
Overland transport		
Packing group (ADR)	: III	
Class (ADR)	: 3 - Flammable liquids	
Hazard identification number (Kemler No.)	: 30	
Classification code (ADR)	: F1	
Danger labels (ADR)	: 3 - Flammable liquids	
Orange plates		
	30 1920	
Tunnel restriction code	: D/E	
Limited quantities (ADR)	5L	
EAC code	: 3Y	
Excepted quantities (ADR)	: E1	
Transport by sea		
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.	
MFAG-No	: 128	
Air transport		
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L	
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L	
Civil Aeronautics Law	: Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)	
14.4. Environmental hazards		
Other information	: No supplementary information available.	
14.5. Special precautions for user		
· · · ·	x II of MARPOL 73/78 and the IBC Code	
Not applicable		
SECTION 15: Regulatory information		
15.1. US Federal regulations		
CIS-HEPTACHLOR EPOXIDE UNLABELED 100 UG/ML IN NONANE		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	
N-NONANE UNLABELED (111-84-2)		

ULM-2425-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

Listed on the Canadian DSL (Domestic Sustances List) inventory.

15.2.1. National regulations

No additional information available

15.3. US State regulations		
CIS-HEPTACHLOR EPOXIDE UNLABELED 100 UG/ML IN NONANE()		
State or local regulations	U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.	

N-NONANE UNLABELED (111-84-2)

U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases::

te toxicity (oral), Category 2 te toxicity (inhalation:dust,mist) Category 4 te toxicity (inhalation:vapour) Category 4 ardous to the aquatic environment — AcuteHazard, Category 1 ardous to the aquatic environment — Chronic Hazard, Category 1 iration hazard, Category 1 cinogenicity, Category 2 ious eye damage/eye irritation, Category 2
te toxicity (inhalation:vapour) Category 4 aardous to the aquatic environment — AcuteHazard, Category 1 aardous to the aquatic environment — Chronic Hazard, Category 1 iration hazard, Category 1 cinogenicity, Category 2 ious eye damage/eye irritation, Category 2
ardous to the aquatic environment — AcuteHazard, Category 1 ardous to the aquatic environment — Chronic Hazard, Category 1 iration hazard, Category 1 cinogenicity, Category 2 ious eye damage/eye irritation, Category 2
ardous to the aquatic environment — Chronic Hazard, Category 1 iration hazard, Category 1 cinogenicity, Category 2 ious eye damage/eye irritation, Category 2
iration hazard, Category 1 cinogenicity, Category 2 ious eye damage/eye irritation, Category 2
cinogenicity, Category 2 ious eye damage/eye irritation, Category 2
ious eye damage/eye irritation, Category 2
nmable liquids, Category 3
n corrosion/irritation, Category 2
cific target organ toxicity — Single exposure, Category 3, Narcosis
nmable liquid and vapour
al if swallowed
be fatal if swallowed and enters airways
ises skin irritation
ises serious eye irritation
mful if inhaled
r cause drowsiness or dizziness
pected of causing cancer
y toxic to aquatic life
y toxic to aquatic life with long lasting effects
nmable
mful by inhalation
y toxic if swallowed
ating to skin
y toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
mful: may cause lung damage if swallowed
ours may cause drowsiness and dizziness
ours may cause drowsiness and dizziness gerous for the environment

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	Xi	Irritant
	Xn	Harmful
NFP	A health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFP	A fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFP	A reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
нміз	S III Rating	
Heal	th	: 2 Moderate Hazard - Temporary or minor injury may occur
Flam	mability	: 3 Serious Hazard
Phys	ical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product