



BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 22/05/2014

Revision date: 02/05/2019

Supersedes: 22/05/2014

Version: 2.0

ULM-4835-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name : BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE
Product code : ULM-4835-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304
Aquatic Acute 1 H400

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11
Xn; R65
Xi; R38
R67
R48
N; R50
Repr.Cat.3; R62
Repr.Cat.3; R63

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304
Aquatic Acute 1 H400

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Brain. Kidneys. Liver. Urinary bladder. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs (brain, kidneys, liver, urinary bladder) (if inhaled, if swallowed, in contact with skin). May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



- Signal word (CLP) : Danger
- Hazardous ingredients : TOLUENE UNLABELED
- Hazard statements (CLP) : H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility. Suspected of damaging the unborn child. (if inhaled, if swallowed, in contact with skin)
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
- Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.

GHS-US labeling

Hazard pictograms (GHS-US)



- Signal word (GHS-US) : Danger
- Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
- Precautionary statements (GHS-US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label)
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

PBT: not relevant – no registration required

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
TOLUENE UNLABELED	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	99.9942	F; R11 Xi; R38 Xn; R65 Repr.Cat.3; R62 Repr.Cat.3; R63 R67 N; R51/53 Xn; R48/20
BETA-HEXABROMOCYCLODODECANE UNLABELED substance listed as REACH Candidate (Hexabromocyclododecane (HBCDD) and all major diastereoisomers identified) substance listed in REACH Annex XIV (Hexabromocyclododecane (HBCDD) (alpha-, beta-, gamma-))	(CAS-No.) 134237-51-7 (Unlabeled) (EC-No.) 247-148-4	0.0058	N; R50/53 Repr.Cat.3; R62 Repr.Cat.3; R63
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
TOLUENE UNLABELED	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	99.9942	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
BETA-HEXABROMOCYCLODODECANE UNLABELED substance listed as REACH Candidate (Hexabromocyclododecane (HBCDD) and all major diastereoisomers identified) substance listed in REACH Annex XIV (Hexabromocyclododecane (HBCDD) (alpha-, beta-, gamma-))	(CAS-No.) 134237-51-7 (Unlabeled) (EC-No.) 247-148-4	0.0058	Repr. 2, H361fd Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Name	Product identifier	%	GHS-US classification
TOLUENE UNLABELED	(CAS-No.) 108-88-3	99.9942	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Wash with plenty of soap and water. Get immediate medical advice/attention. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Suspected of damaging fertility. Suspected of damaging the unborn child. (in contact with skin, if inhaled, if swallowed). Causes damage to organs (brain, kidneys, liver, urinary bladder) (in contact with skin, if inhaled, if swallowed).
Symptoms/effects after inhalation	: Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Harmful in contact with skin. Causes skin irritation. Repeated exposure to this material can result in absorption through skin causing significant health hazard.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry powder. Dry sand. Dry chemical. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

5.3. Advice for firefighters

Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.
Other information	: Use water spray to cool exposed surfaces.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Flammable liquids. No open flames. No smoking. Eliminate every possible source of ignition. Use special care to avoid static electric charges.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Use personal protective equipment as required. Ensure adequate air ventilation. Avoid breathing vapors, mist, gas. Eliminate all ignition sources if safe to do so. Evacuate unnecessary personnel. Special attention should be given to low areas/pits where flammable vapors can accumulate.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Prevent liquid from entering sewers, watercourses, underground or low areas. Do not allow to enter drains or water courses. Do not discharge the product into the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Dike and contain spill.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Avoid all eye and skin contact and do not breathe vapor and mist. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust, fume, gas, spray, vapors, mist. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. No open flames. No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust, fume, gas, mist, spray, vapors.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof Lighting equipment, ventilating equipment.
- Storage conditions : Store refrigerated (-5 °C to 5 °C). Protect from light.
- Incompatible materials : Heat sources.
- Storage area : Under inert gas.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Visual impairment. Female reproductive. Pregnancy loss. 2015 Adoption. Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen.; Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0300 mg/l Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0200 mg/l Biological specimen: In blood Remarks: Prior to last shift of workweek Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: o-Cresol Value: 0.3000 mg/g Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	375 mg/m³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m³)	560 mg/m³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm USA. NIOSH Recommended Exposure Limits
USA OSHA	OSHA PEL (TWA) (mg/m³)	375 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (mg/m³)	560 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE		
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-2
USA OSHA	Remark (OSHA)	OSHA PEL (TWA) - 200 ppm - USA. Occupational Exposure Limits (OSHA) - Table Z-2. Remarks: Z37.12-1967
TOLUENE UNLABELED (108-88-3)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Visual impairment. Female reproductive. Pregnancy loss. 2015 Adoption. Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen.; Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0300 mg/l Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0200 mg/l Biological specimen: In blood Remarks: Prior to last shift of workweek Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: o-Cresol Value: 0.3000 mg/g Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	375 mg/m³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m³)	560 mg/m³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm USA. NIOSH Recommended Exposure Limits
USA OSHA	OSHA PEL (TWA) (mg/m³)	375 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (mg/m³)	560 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-2
USA OSHA	Remark (OSHA)	OSHA PEL (TWA) - 200 ppm - USA. Occupational Exposure Limits (OSHA) - Table Z-2. Remarks: Z37.12-1967

8.2. Exposure controls

Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing : Wear suitable protective clothing and gloves.

Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses.

Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection. Wear suitable protective clothing.

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 92.14 g/mol
Color	: Colorless
Odor	: Aromatic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -93 °C (-135 °F)
Freezing point	: No data available
Boiling point	: 110 - 111 °C (230 - 232 °F)
Flash point	: 4 °C (39.2 °F) - closed cup
Auto-ignition temperature	: 535 °C (995 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: 29.1 hPa (21.8 mmHg) at 20.0 °C (68.0 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.865 g/ml at 25 °C (77 °F)
Solubility	: Water: 0.5 g/l at 15 °C (59 °F)
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 1.2 - 7 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

LD50 oral rat	> 5580 mg/kg
LD50 dermal rabbit	12196 mg/kg
LC50 inhalation rat (mg/l)	12,500 - 28,800 mg/m3 - 4 h
ATE CLP (dermal)	12196.000 mg/kg body weight
ATE CLP (vapors)	12.500 mg/l/4h
ATE CLP (dust, mist)	12.500 mg/l/4h

TOLUENE UNLABELED (108-88-3)

LD50 oral rat	> 5580 mg/kg
LD50 dermal rabbit	12196 mg/kg
LC50 inhalation rat (mg/l)	12,500 - 28,800 mg/m3 - 4 h
ATE CLP (dermal)	12196.000 mg/kg body weight
ATE CLP (vapors)	12.500 mg/l/4h
ATE CLP (dust, mist)	12.500 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. Skin – Rabbit - Causes skin irritation - 24 Hours
Serious eye damage/irritation	: Not classified Eyes – Rabbit - No eye irritation - (OECD 405 method)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Rat - Liver - DNA Damage
Carcinogenicity	: Not classified
Reproductive toxicity	: Damage to fetus possible. Suspected human reproductive toxicant. Reproductive toxicity - Rat - Inhalation. Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count). Experiments have shown reproductive toxicity effects in male and female laboratory animals. Developmental Toxicity - Rat - Oral. Effects on Embryo or Fetus: Fetotoxicity (except death, e.g. stunted fetus).
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Symptoms/effects. IF INHALED: lungs. Pulmonary irritation. Pulmonary edema. Chest pain. central nervous system. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Stomach - Irregularities - Based on Human Evidence. Lung irritation, chest pain, pulmonary edema, Inhalation studies have shown the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals.
IARC group	: 3
Symptoms/effects after inhalation	: Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Harmful in contact with skin. Causes skin irritation. Repeated exposure to this material can result in absorption through skin causing significant health hazard.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to bees.
Ecology - water	: Very toxic to aquatic life.

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

EC50 Daphnia 1	8 mg/l Daphnia magna (Water flea) - 24h
LC50 fish 2	7.63 mg/l Oncorhynchus mykiss (Rainbow trout) - 96 h
EC50 Daphnia 2	6 mg/l Daphnia magna (Water flea) - Immobilization - 48 h
ErC50 (algae)	245 mg/l Chlorella vulgaris (Fresh water algae) - 24 h
ErC50 (other aquatic plants)	10 mg/l Pseudokirchneriella subcapitata (Green algae) - 24 h
NOEC (chronic)	5.44 mg/l Pimephales promelas (fathead minnow) - 7 d

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE UNLABELED (108-88-3)	
EC50 Daphnia 1	8 mg/l Daphnia magna (Water flea) - 24h
LC50 fish 2	7.63 mg/l Oncorhynchus mykiss (Rainbow trout) - 96 h
EC50 Daphnia 2	6 mg/l Daphnia magna (Water flea) - Immobilization - 48 h
ErC50 (algae)	245 mg/l Chlorella vulgaris (Fresh water algae) - 24 h
ErC50 (other aquatic plants)	10 mg/l Pseudokirchneriella subcapitata (Green algae) - 24 h
NOEC (chronic)	5.44 mg/l Pimephales promelas (fathead minnow) - 7 d

12.2. Persistence and degradability

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE	
Persistence and degradability	Readily biodegradable.

TOLUENE UNLABELED (108-88-3)	
Persistence and degradability	Readily biodegradable.

BETA-HEXABROMOCYCLODODECANE UNLABELED (134237-51-7 (Unlabeled))	
Persistence and degradability	Not available.

12.3. Bioaccumulative potential

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE	
BCF fish 1	0.05 mg/l Leuciscus idus (Golden orfe) - 3 d
Bioconcentration factor (BCF REACH)	90

TOLUENE UNLABELED (108-88-3)	
BCF fish 1	0.05 mg/l Leuciscus idus (Golden orfe) - 3 d
Bioconcentration factor (BCF REACH)	90

BETA-HEXABROMOCYCLODODECANE UNLABELED (134237-51-7 (Unlabeled))	
Bioaccumulative potential	Not available.

12.4. Mobility in soil

BETA-HEXABROMOCYCLODODECANE UNLABELED (134237-51-7 (Unlabeled))	
Ecology - soil	Not available.

12.5. Results of PBT and vPvB assessment

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE	
PBT: not relevant – no registration required	

TOLUENE UNLABELED (108-88-3)	
PBT: not relevant – no registration required	

BETA-HEXABROMOCYCLODODECANE UNLABELED (134237-51-7 (Unlabeled))	
This substance/mixture meets the PBT criteria of REACH, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH, annex XIII	

12.6. Other adverse effects

Other adverse effects : Disposal must be done according to official regulations. Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Dispose of as unused product. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT)	: 1294
DOT NA no.	UN1294

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Toluene
----------------------------	-----------

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
Marine pollutant : No

14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II
Class (ADR) : 3 - Flammable liquid
Hazard identification number (Kemler No.) : 33
Classification code (ADR) : F1
Hazard labels (ADR) : 3 - Flammable liquids



Orange plates : 

Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) : 11
EAC : 3YE
Excepted quantities (ADR) : E2

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
MFAG-No : 130

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)
Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313

TOLUENE UNLABELED (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

Listed on the Canadian DSL (Domestic Substances List)

TOLUENE UNLABELED (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
No significant risk level (NSRL)	7000 µg/day
State or local regulations	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List

TOLUENE UNLABELED (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	7000 µg/day

TOLUENE UNLABELED (108-88-3)

State or local regulations

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

BETA-HEXABROMOCYCLODODECANE UNLABELED 50 UG/ML IN TOLUENE

ULM-4835-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE UNLABELED (108-88-3)

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R11	Highly flammable
R38	Irritating to skin
R48	Danger of serious damage to health by prolonged exposure
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R50	Very toxic to aquatic organisms
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product