

4,4'-DDD UNLABELED 100 UG/ML IN NONANE

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Version: 1.0 :

Date of issue: 03/11/2016

Revision date:

ULM-7216-S

SECT	ION 1: Identification	of the substance/mixture and of the company/undertaking
1.1.	Product identifier	
Produc	t form	: Mixture
Produc	t name	: 4,4'-DDD UNLABELED 100 UG/ML IN NONANE
Produc	t code	: ULM-7216-S
1.2.	Relevant identified use	s of the substance or mixture and uses advised against
1.2.1.	Relevant identified use	S
vlain us	se category	: Professional use
ndustri	al/Professional use spec	: For professional use only
1.2.2.	Uses advised against	
No add	itional information available	
1.3.	Details of the supplier of	of the safety data sheet
Cambri	idge Isotope Laboratories, Ir	
50 Fror	ntage Road	
Andove JSA	er, MA 01810	
	1-800-322-1174 Int: 1-978	-749-8000
<u>cilsales@isotope.com</u> www.isotope.com		
	Emergency telephone r	number
Emerge	ency numbers:	
Chemtr	rec: 1-800-424-9300 (24 ho	ours)
Interna	tional: 1-703-741-5970 (24	hours)
SECT	ION 2: Hazards ident	tification
2.1.	Classification of the su	bstance or mixture
Classif	ication according to Regu	Ilation (EC) No. 1272/2008 [CLP]
-lam. L	.iq. 3	H226
Acute 7	<pre>Fox. 4 (Inhalation:dust,mist)</pre>	H332
Skin Irr	it. 2	H315
Eye Irri	t. 2	H319
STOT S	SE 3	H336
Asp. To	ox. 1	H304
Full tex	t of H-statements: see secti	on 16
Classif	ication according to Direc	ctive 67/548/EEC [DSD] or 1999/45/EC [DPD]
R10		na na na na na kao kao kao kao kao kao kao kao kao ka
Yn P2	0	

Xn; R20 Xi; R36/37/38 Xn; R65 Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Adverse physicochemical, human health and environmental effects Central Nervous System.

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Label elements 2.2

- Labelling according to Regulation (EC) No. 1272/2008 [CLP]
- Hazard pictograms (CLP)



GHS07 GHS08

Signal word (CLP) Hazardous ingredients Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger : N-NONANE UNLABELED
- : H226 Flammable liquid and vapour
 - H304 May be fatal if swallowed and enters airways
 - H315 Causes skin irritation
 - H319 Causes serious eye irritation
 - H332 Harmful if inhaled
 - H336 May cause drowsiness or dizziness
- : P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 - P233 Keep container tightly closed
 - P240 Ground/bond container and receiving equipment
 - P241 Use explosion-proof electrical, lighting, ventilating equipment
 - P261 Avoid breathing dust, fume, gas, mist, spray, vapours
 - P264 Wash Both hands thoroughly after handling
 - P271 Use only outdoors or in a well-ventilated area
 - P280 Wear eye protection, face protection, protective clothing, protective gloves

GHS-US labelling

Signal word (GHS-US)

Hazard pictograms (GHS-US)

Hazard statements (GHS-US)

Precautionary statements (GHS-US)

:	X	\wedge
	\checkmark	\mathbf{V}

GHS02

- : Danger
- : H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways

GHS08

- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H336 May cause drowsiness or dizziness
- P210 Keep away from heat, hot surfaces, open flames, sparks. No smoking

GHS07

- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof lighting, ventilating, electrical equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing dust, fume, gas, mist, spray, vapours
- P264 Wash Both hands thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P273 Avoid release to the environment
- P280 Wear eye protection, face protection, protective clothing, protective gloves
- P301+P310 IF SWALLOWED: immediately call a POISON CENTER or doctor/physician
- P302+P352 IF ON SKIN: Wash with plenty of soap and water
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

- P312 Call a POISON CENTER or doctor/physician if you feel unwell
- P321 Specific treatment (see Hazard pictograms (CLP) on this label)
- P331 Do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention

- P337+P313 If eye irritation persists: Get medical advice/attention
- P362 Take off contaminated clothing and wash before reuse

P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide., Dry chemical, Water sprav for extinction

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up

P501 - Dispose of contents/container to Comply with applicable regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	99.986	R10 Xn; R20 Xn; R65 R67 Xi; R38
4,4'-DDD UNLABELED	(CAS No) 72-54-8 (EC no) 200-783-0	0.014	Carc.Cat.3; R40 Xn; R21 T; R25 N; R50/53
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
4,4'-DDD UNLABELED	(CAS No) 72-54-8 (EC no) 200-783-0	0.014	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 Carc. 2, H351 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410
Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS No) 111-84-2	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304

Full text of R- and H-statements: see section 16

4.1. Description of first aid n	easures
First-aid measures after inhalation	 Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contac	 Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occur Wash with plenty of soap and water. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).
First-aid measures after eye contact	: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
First-aid measures after ingestion	: Immediately call a POISON CENTER or doctor/physician.
4.2. Most important symptom	is and effects, both acute and delayed
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.		
5.2. Special hazards arising from the s	ubstance or mixture	
Fire hazard	: Flammable liquid and vapour.	
Explosion hazard	: May form flammable/explosive vapour-air mixture.	
5.3. Advice for firefighters		
Firefighting instructions	: Wear self contained breathing apparatus for fire fighting if necessary.	
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.		
SECTION 6: Accidental release mea		
6.1. Personal precautions, protective e	equipment and emergency procedures	
General measures	 Remove ignition sources. Use special care to avoid static electric charges. No open flames. N smoking. 	
6.1.1. For non-emergency personnel No additional information available		
6.1.2. For emergency responders		
Protective equipment	: Avoid breathing dust, mist or spray.	
6.2. Environmental precautions		
	so. Do not let product enter drains. Discharge into the environment must be avoided.	
.3. Methods and material for containm	nent and cleaning up	
For containment	: Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet- brushing and place in container for disposal according to local regulations.	
6.4. Reference to other sections		
lo additional information available		
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.	
Precautions for safe handling	 No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust, mist or spray. 	
Hygiene measures	: Wash Both hands thoroughly after handling.	
7.2. Conditions for safe storage, includ		
Fechnical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.	
Storage conditions	: Store at room temperature away from light and moisture.	
ncompatible materials	: Heat sources.	
7.3. Specific end use(s)		
No additional information available		
SECTION 8: Exposure controls/per	sonal protection	
3.1. Control parameters		
4,4'-DDD UNLABELED 100 UG/ML IN NON	ANE	
Italy - Portugal - USA ACGIH ACGIH TWA	(ppm) 200.00000000 ppm Central Nervous System impairment.	
N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH ACGIH TWA	(ppm) 200.00000000 ppm Central Nervous System impairment.	
8.2. Exposure controls		
Personal protective equipment	: Gloves. Protective goggles. Protective clothing. Self-contained breathing apparatus.	

Hand protection

EN (English)

 \bigcirc

: Wear suitable protective clothing and gloves.

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection	: Wear safety glasses with side shields (or goggles) and a face shield.	
Skin and body protection	: Wear suitable protective clothing.	
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipmen	nt is
	recommended. Wear respiratory protection.	

SECTION 9: Phy	sical and chemical	properties

9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Appearance	: Liquid.	
Molecular mass	: 128.3 g/mol	
Colour	: Colourless.	
Odour	: No data available	
Odour threshold	: No data available	
рН	: No data available	
Relative evaporation rate (butylacetate=1)	: No data available	
Melting point	: No data available	
Freezing point	: -53 °C (- 63 °F) - lit	
Boiling point	: 151 °C (304 °F) - lit	
Flash point	: 31.0 °C (87.8 °F) - closed cup	
Auto-ignition temperature	: 205 °C (401 °F)	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: Flammable liquid and vapour	
Vapour pressure	: 12.4 hPa (9.3 mmHg) at 37.7 °C (99.9 °F)	
Relative vapour density at 20 °C	: No data available	
Relative density	: No data available	
Density	: 0.718 g/ml at 25 °C (77 °F)	
Solubility	: Water: 0 %	
Log Pow	: 5.65	
Log Kow	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
Explosive properties	: No data available	
Oxidising properties	: No data available	
Explosive limits	: 0.87 - 2.9 % (V)	
9.2. Other information		

No additional information available

SECT	SECTION 10: Stability and reactivity		
10.1.	Reactivity		
	tional information available		
10.2.	Chemical stability		
	rage and expiration date on CoA.		
	5		
10.3.	Possibility of hazardous reactions		
No addi	tional information available		
10.4.	Conditions to avoid		
Open fla	ame. Overheating. Direct sunlight. Heat. Sp	parks.	
10.5.	Incompatible materials		
No addi	tional information available		
10.6.	Hazardous decomposition products		
May rel	May release flammable gases.		
SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Acute to	Acute toxicity : Harmful if inhaled.		
4,4'-DDD UNLABELED 100 UG/ML IN NONANE			
LC50	nhalation rat (mg/l)	23760 mg/m ³ male - 4 h	
LC50	nhalation rat (ppm)	3200 ppm/4h	

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4,4'-DDD UNLABELED 100 UG/ML IN NONANE				
ATE CLP (gases)	3200.000 ppmv/4h			
ATE CLP (vapours)	11.000 mg/l/4h			
ATE CLP (dust,mist)	1.500 mg/l/4h			
N-NONANE UNLABELED (111-84-2)				
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h			
LC50 inhalation rat (ppm)	3200 ppm/4h			
ATE CLP (gases)	3200.000 ppmv/4h			
ATE CLP (vapours)	11.000 mg/l/4h			
ATE CLP (dust,mist)	23.760 mg/l/4h			
4,4'-DDD UNLABELED (72-54-8)				
LD50 oral	> 5,000 mg/kg - Hamster			
LD50 dermal	1200 mg/kg - Rabbit. Remarks: Behavioral:Excitement. Behavioral:Convulsions or effect on seizure threshold. Skin irritation			
ATE CLP (oral)	100.000 mg/kg bodyweight			
ATE CLP (dermal)	1100.000 mg/kg bodyweight			
TDLo Oral - Human - 428.5 mg/kg Remarks	Endocrine:Adrenal cortex hypoplasia.			
TDLo Oral - Rat - 6,000 mg/kg; Remarks	Cardiac:Cardiac:Other changes. Gastrointestinal:Other changes. Kidney, Ureter, Bladder:Changes in both tubules and glomeruli.			
TDLo Oral - Rat - 14 mg/kg; Remarks	Liver: Changes in liver weight. Endocrine: Estrogenic. Musculoskeletal: Other changes.			
TDLo Oral - Rat - 2,100 mg/kg; Remarks	Behavioral:Altered sleep time (including change in righting reflex).			
Skin corrosion/irritation	: Causes skin irritation.			
Serious eye damage/irritation	: Causes serious eye irritation.			
Respiratory or skin sensitisation	: Not classified			
Germ cell mutagenicity	: Not classified			
Carcinogenicity	: Not classified			
Reproductive toxicity	: Not classified			
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.			
Specific target organ toxicity (repeated exposure)	: Not classified			
Aspiration hazard	: May be fatal if swallowed and enters airways.			
Potential adverse human health effects and symptoms	: Harmful if inhaled. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.			
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.			
Symptoms/injuries after skin contact	: Causes skin irritation.			
Symptoms/injuries after eye contact	: Causes serious eye irritation.			
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.			

SECTION 12: Ecological information			
12.1. Toxicity	12.1. Toxicity		
4,4'-DDD UNLABELED (72-54-8)			
LC50 fish 1	0.04 - 0.05 mg/l Lepomis macrochirus (Bluegill) - 96.0 h		
LC50 other aquatic organisms 1	0.06 - 0.09 mg/l - Oncorhynchus mykiss (rainbow trout) - 96.0 h		
EC50 Daphnia 1	0.01 mg/l Daphnia pulex (Water flea) - 48 h		
LC50 fish 2	1.18 - 9 mg/l - other fish - 96.0 h		
LC50 other aquatic organisms 2	3.47 - 5.58 mg/l - Pimephales promelas (fathead minnow) - 96.0 h		

12.2. Persistence and degradability

No additional information available

12.3	Bioaco	umulative	e notentia

12.3. Bloaccumulative potential	
4,4'-DDD UNLABELED 100 UG/ML IN NONANE	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
N-NONANE UNLABELED (111-84-2)	
Log Pow	5.65

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Bioaccumulative potential	Indication of bioaccumulation.
4,4'-DDD UNLABELED (72-54-8)	
Log Pow	6.02
Bioaccumulative potential	Indication of bioaccumulation.
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessme	nt
No additional information available	
12.6. Other adverse effects	
Other adverse effects	: An environmental hazard cannot be excluded in the event of unprofessional handling or dispos Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environmen
SECTION 13: Disposal consideration	IS
13.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
Waste disposal recommendations	: Dispose of contents/container to Comply with applicable regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Hazardous waste due to toxicity.
	·
SECTION 14: Transport information	
In accordance with ADR / RID / IMDG / IATA / A	DN
14.1. UN number	
UN-No.(DOT)	: 1920
DOT NA no.	UN1920
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Nonanes
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
Packing group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquid: with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
Marine pollutant	: No
14.3. Additional information	
Other information	: No supplementary information available.
Overland transport	
Packing group (ADR)	: 111
	: III : 3 - Flammable liquids

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification code (ADR) : F1 Danger labels (ADR) : 3 - Flammable liquids Image labels (ADR) : 3 - Flammable liquids Image labels (ADR) : 3 - Flammable liquids Orange plates : 3 0 1920 1920 Tunnel restriction code : D/E Limited quantities (ADR) : 5 EAC code : 3 Y Excepted quantities (ADR) : E1 Transport by sea . . DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. MFAG-No : 128 Air transport U . . DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27) . . . DOT Quantity Limitations Cargo aircraft only (49 : 220 L CFR 175.75 . . Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations) Cher information : No supplementary information available. <	Hazard identification number (Kemler No.)	: 30
Orange plates 30 Tunnel restriction code : 30 Imited quantities (ADR) : 5 EAC code : 3Y Excepted quantities (ADR) : 1 DT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a massenger vessel. MFAG-No : 128 Air transport : 60 L QOT Quantity Limitations Passenger aircraft/mil : 60 L (49 CFR 173.27) : 220 L OT Quantity Limitations Cargo aircraft on y(4) : 220 L Civil Aeronautics Law : Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations) THAL Environmental hazards : Dary materials notice appended Table 1 Article 194 of the Enforcement Regulations)	Classification code (ADR)	: F1
30 1920 Tunnel restriction code : D/E Limited quantities (ADR) :5 EAC code : 3Y Excepted quantities (ADR) : E1 Transport by sea	Danger labels (ADR)	: 3 - Flammable liquids
30 1920 Tunnel restriction code : D/E Limited quantities (ADR) :5 EAC code : 3Y Excepted quantities (ADR) : E1 Transport by sea		
Limited quantities (ADR) 5I EAC code : 3Y Excepted quantities (ADR) : E1 Transport by sea	Orange plates	
EAC code: 3YExcepted quantities (ADR): E1Transport by sea DOT Vessel Stowage Location: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.MFAG-No: 128Air transport DOT Quantity Limitations Passenger aircraft/rail: 60 L 200 L CFR 173.27)DOT Quantity Limitations Cargo aircraft only (49): 220 LCivil Aeronautics Law: Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)THAL Environmental hazardsOther information: No supplementary information available.	Tunnel restriction code	: D/E
Excepted quantities (ADR) : E1 Transport by sea DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. MFAG-No : 128 Air transport DOT Quantity Limitations Passenger aircraft/rail : 60 L DOT Quantity Limitations Cargo aircraft only (49) : 220 L CFR 175.75) Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations) 14.4. Environmental hazards Other information : No supplementary information available.	Limited quantities (ADR)	51
Transport by sea : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. MFAG-No : 128 Air transport DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27) : 220 L CFR 175.75) : Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations) 14.4 Environmental hazards Other information : No supplementary information available.	EAC code	: 3Y
DOT Vessel Stowage Location: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.MFAG-No: 128Air transportDOT Quantity Limitations Passenger aircraft/rail: 60 LDOT Quantity Limitations Cargo aircraft only (49: 200 LCFR 175.75): Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)14.4Environmental hazardsOther information: No supplementary information available.	Excepted quantities (ADR)	: E1
DOT Vessel Stowage Location: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.MFAG-No: 128Air transportDOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27): 60 L 20 LDOT Quantity Limitations Cargo aircraft only (49 CFR 175.75): Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)14.4Environmental hazards: No supplementary information available.		
MFAG-No : 128 Air transport DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 ; 200 L CFR 175.75) Civil Aeronautics Law the transport Regulations) 1 Nother information the transport Regulation available.	Transport by sea	
Air transport DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 220 L CFR 175.75) Civil Aeronautics Law : Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations) 14.4. Environmental hazards Other information : No supplementary information available.	DOT Vessel Stowage Location	,
DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 ; 20 L CFR 175.75) : Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations) 14.4. Environmental hazards Other information : No supplementary information available.	MFAG-No	: 128
DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 ; 20 L CFR 175.75) : Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations) 14.4. Environmental hazards Other information : No supplementary information available.	Air transport	
CFR 175.75) Civil Aeronautics Law : Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations) 14.4. Environmental hazards Other information : No supplementary information available.	DOT Quantity Limitations Passenger aircraft/rail	: 60 L
Image: Addition of the second seco		9 : 220 L
Other information : No supplementary information available.	Civil Aeronautics Law	: Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)
	14.4. Environmental hazards	
14.5. Special precautions for user	Other information	: No supplementary information available.
	14.5. Special precautions for user	

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

SECTION 15: Regulatory information	
15.1. US Federal regulations	
4,4'-DDD UNLABELED 100 UG/ML IN NONANE	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
N-NONANE UNLABELED (111-84-2)	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard

15.2. International regulations

	CANADA	
4,4'-DDD UNLABELED 100 UG/ML IN NONANE		
	Listed on the Canadian DSL (Domestic Substances List)	

15.2.1. National regulations

No additional information available

15.3. US State regulations

4,4'-DDD UNLABELED 100 UG/ML IN NONANE()	
State or local regulations	U.S Massachusetts - Right To Know List
	U.S Pennsylvania - RTK (Right to Know) List

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

w Jersey - Right to Know Hazardous Substance List
uct does not contain any chemicals known to State of California to cause cancer, cts, or any other reproductive harm.

N-NONANE UNLABELED (111-84-2)

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-statements:

,	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R10	Flammable
R20	Harmful by inhalation
R21	Harmful in contact with skin
R25	Toxic if swallowed
R36/37/38	Irritating to eyes, respiratory system and skin
R38	Irritating to skin
R40	Limited evidence of a carcinogenic effect
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapours may cause drowsiness and dizziness
N	Dangerous for the environment
Т	Toxic
Xi	Irritant
Xn	Harmful
	•

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

st all

NFPA fire hazard

3 - Liquids and solids that can be ignited under almost all ambient conditions.

:

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

HMIS III Rating

Physical

- Health: 2 Moderate Hazard Temporary or minor injury may occurFlammability: 3 Serious Hazard
 - : 0 Minimal Hazard

CIL Multi-Solvent Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product