

ENDRIN UNLABELED 100 UG/ML IN NONANE

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations :

Date of issue: 25/10/2016

Revision date:

Version: 1.0

ULM-7444-S

SECTION 1: Identification of the	e substance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixture
Product name	: ENDRIN UNLABELED 100 UG/ML IN NONANE
Product code	: ULM-7444-S
1.2. Relevant identified uses of the	e substance or mixture and uses advised against
1.2.1. Relevant identified uses	
Main use category	: Professional use
Industrial/Professional use spec	: For professional use only.
1.2.2. Uses advised against	
No additional information available	
1.3. Details of the supplier of the s	afety data sheet
Cambridge Isotope Laboratories, Inc. 50 Frontage Road Andover, MA 01810 USA USA: 1-800-322-1174 Int: 1-978-749-80	900
cilsales@isotope.com www.isotope.com	
Emergency telephone number	
Emergency numbers:	
Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)	
SECTION 2: Hazards identificati	ion
2.1. Classification of the substance	e or mixture
Classification according to Regulation ((EC) No. 1272/2008 [CLP]
Flam. Liq. 3 H226	
Acute Tox. 4 (Inhalation:dust,mist) H332	
Skin Irrit. 2 H315	
Eye Irrit. 2 H319	
STOT SE 3 H336	
Asp. Tox. 1 H304	
Full text of H-phrases: see section 16	
Classification according to Directive 67	/548/EEC [DSD] or 1999/45/EC [DPD]
Xn; R20 Xn; R65 Xi; R38 N; R51/53 R10	
Full text of R-phrases: see section 16	
Classification (GHS-US)	
Flam. Liq. 3H226Acute Tox. 4 (Inhalation:dust,mist)H332	

Acute Tox. 4 (Inhalation:d st.mist Skin Irrit. 2 H315 Eye Irrit. 2A STOT SE 3 H319 H336 H304 Asp. Tox. 1

Adverse physicochemical, human health and environmental effects

Central Nervous System.

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2 Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) Hazardous ingredients Hazard statements (CLP)

Precautionary statements (CLP)

: Danger

- : N-NONANE UNLABELED
- : H226 Flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H336 May cause drowsiness or dizziness
- : P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 - P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical, ventilating, lighting equipment
- P261 Avoid breathing dust, gas, fume, mist, spray, vapors
- P264 Wash Both hands thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear eye protection, face protection, protective clothing, protective gloves

GHS-US labeling

Hazard pictograms	(GHS-US)
-------------------	----------



GHS08

: Danger

- : H226 Flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H336 May cause drowsiness or dizziness
- : P210 Keep away from heat, open flames, hot surfaces, sparks. No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical, lighting, ventilating equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing gas, dust, fume, mist, spray, vapors
- P264 Wash Both hands thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear eye protection, face protection, protective clothing, protective gloves

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

- P312 Call a POISON CENTER or doctor/physician if you feel unwell
- P321 Specific treatment (see Hazard pictograms (CLP) on this label)
- P331 Do NOT induce vomiting
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P337+P313 If eye irritation persists: Get medical advice/attention
- P362 Take off contaminated clothing and wash it before reuse
- P370+P378 In case of fire: Use Alcohol resistant foam., Carbon dioxide., Dry chemical., Water spray to extinguish
- P403+P233 Store in a well-ventilated place. Keep container tightly closed
- P403+P235 Store in a well-ventilated place. Keep cool

EN (English US)

Precautionary statements (GHS-US)

Signal word (GHS-US) Hazard statements (GHS-US)

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container to Comply with applicable regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	99.986	R10 Xn; R20 Xn; R65 R67 Xi; R38
ENDRIN UNLABELED	(CAS No) 72-20-8 (EC no) 200-775-7 (EC index no) 602-051-00-X	0.014	T+; R28 T; R24 N; R50/53
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
ENDRIN UNLABELED	(CAS No) 72-20-8 (EC no) 200-775-7 (EC index no) 602-051-00-X	0.014	Acute Tox. 1 (Oral), H300 Acute Tox. 2 (Dermal), H310 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410
Name	Product identifier	%	Classification (GHS-US)
N-NONANE UNLABELED	(CAS No) 111-84-2	99.986	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measur	es
First-aid measures after inhalation	 Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	 Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs Wash with plenty of soap and water. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).
First-aid measures after eye contact	: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
First-aid measures after ingestion	: Immediately call a poison center or doctor/physician.
4.2. Most important symptoms and	effects, both acute and delayed
Symptoms/injuries after inhalation	 Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
4.3. Indication of any immediate m	edical attention and special treatment needed

No additional information available

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

, or carbon dioxide.
ng if necessary.
nent, including respiratory protection.
atic electric charges. No naked lights. No
vironment must be avoided.
sorbent material. Disposal should be in egulations.
vapors are flammable.
asures against static discharge. Use only tilated area. Avoid breathing dust, mist o
entilated place.
ire.
00 ppm Central Nervous System
mg/m ³ Central Nervous System eadache, Liver damage
mg/m ³ Danger of cutaneous absorption a a human carcinogen
He 000

iygi ty p breaks and at the end of workday.

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment	: Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.
Materials for protective clothing	: Wear suitable protective clothing and gloves.
Hand protection	: Wear suitable protective clothing and gloves.
Eye protection	: Wear safety glasses with side shields (or goggles) and a face shield.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	 Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.
Environmental experience controls	· Provent further leakage or chillage if safe to do so. Do not let product onter drains

Environmental exposure controls	: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
SECTION 9: Physical and chemical	properties
9.1. Information on basic physical and o	chemical properties
The properties listed below are for the solvent, the main compo	nent of this mixture.
Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 128.3 g/mol
Color	: Colorless.
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31.0 °C (87.8 °F) - closed cup
Auto-ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapor
Vapor pressure	: 12.4 hPa (9.3 mmHg) at 37.7 °C (99.9 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.718 g/ml at 25 °C (77 °F)
Solubility	: Water: 0 %
Log Pow	: 5.65
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 0.87 - 2.9 % (V)
9.2. Other information	
No odditional information ovallable	

No additional information available

SECT	TON 10: Stability and reactivity	
10.1.	Reactivity	
No add	itional information available	
10.2.	Chemical stability	
See sto	prage and expiration date on CoA.	
10.3.	Possibility of hazardous reactions	
No add	itional information available	
10.4.	Conditions to avoid	
Open f	ame. Overheating. Direct sunlight. Heat. Sparks.	
10.5.	Incompatible materials	
No add	itional information available	
00/40/0/		E/10

26/10/2016

EN (English US)

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products	
May release flammable gases.	
	0 1
SECTION 11: Toxicological informati	on
11.1. Information on toxicological effects	
Acute toxicity	: Harmful if inhaled.
ENDRIN UNLABELED 100 UG/ML IN NONANI	
ATE CLP (dust, mist)	1.500 mg/l/4h
N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h
LC50 inhalation rat (ppm)	3200 ppm/4h
ATE CLP (gases)	3200.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	23.760 mg/l/4h
ENDRIN UNLABELED (72-20-8)	
LD50 oral rat	3.0 mg/kg
LD50 dermal rabbit	60.0 mg/kg
ATE CLP (oral)	3.000 mg/kg body weight
ATE CLP (dermal)	60.000 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Harmful if inhaled.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information	
12.1. Toxicity	
ENDRIN UNLABELED (72-20-8)	
LC50 fish 1	< 0.001 mg/l Oncorhynchus mykiss (rainbow trout) -96h
EC50 Daphnia 1	0.02 mg/l Daphnia pulex (Water flea) -48h

Immobilization EC50- Daphnia magna (water flea)-0.0042 mg/l-48h

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential	
ENDRIN UNLABELED 100 UG/ML IN NONA	NE
Log Pow	5.65
N-NONANE UNLABELED (111-84-2)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
ENDRIN UNLABELED (72-20-8)	
Bioconcentration factor (BCF REACH)	13000
Log Pow	5.20
26/10/2016	EN (English US) 6/1

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ENDRIN UNLABELED (72-20-8)	
Bioaccumulative potential	Pimephales promela (fathead minnow)-56d-0.63 mg/l.
12.4. Mobility in soil	
No additional information available	
2.5. Results of PBT and vPvB assessm	nent
No additional information available	
2.6. Other adverse effects	
No additional information available	
SECTION 13: Disposal consideratio	ons
13.1. Waste treatment methods	
Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and Loca environmental control regulations.
Naste disposal recommendations	: Dispose of contents/container to Comply with applicable regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Hazardous waste due to toxicity.
SECTION 14: Transport information]
n accordance with ADR / RID / IMDG / IATA / A	
14.1. UN number	
JN-No.(DOT)	: 1920
DOT NA no.	UN1920
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Nonanes
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
/=	: III - Minor Danger
Packing group (DOT)	
DOT Special Provisions (49 CFR 172.102)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then th bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liqui with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tat 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) 14.3. Additional information Dther information Dther information	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 52 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) 14.3. Additional information Dther information Dverland transport Packing group (ADR)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 2 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) 14.3. Additional information Dther information Dther information	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 52 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5 5 ()	
Hazard labels (ADR)	: 3 - Flammable liquids
Orange plates	30 1920
Tunnel restriction code	: D/E
Limited quantities (ADR)	51
EAC	: 3Y
Excepted quantities (ADR)	: E1
Transport by sea	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
MFAG-No	: 128
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
Civil Aeronautics Law	: Flammable liquids
14.4. Environmental hazards	
Dangerous for the environment	₹ ₩2
Other information	: No supplementary information available.

Special precautions for user 14.5.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code 14.6.

Not applicable

SECTION 15: Regulatory information		
15.1. US Federal regulations		
ENDRIN UNLABELED 100 UG/ML IN NONANE		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	
N-NONANE UNLABELED (111-84-2)		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard	

15.2. International regulations

CANADA

ENDRIN UNLABELED 100 UG/ML IN NONANE	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

15.2.1. National regulations

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations		
ENDRIN UNLABELED 100 UG/ML IN NONANE()		
State or local regulations	U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.	

N-NONANE UNLABELED (111-84-2)

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

```
Other information
```

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 1 (Oral)	Acute toxicity (oral) Category 1
Acute Tox. 2 (Dermal)	Acute toxicity (dermal) Category 2
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H300	Fatal if swallowed
H304	May be fatal if swallowed and enters airways
H310	Fatal in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R10	Flammable
R20	Harmful by inhalation
R24	Toxic in contact with skin
R28	Very toxic if swallowed
R38	Irritating to skin
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
Ν	Dangerous for the environment
Т	Toxic
T+	Very toxic
Xi	Irritant

Safety Data Sheet according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product