



EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/03/2019

Revision date:

Version: 1.0

EC-7438

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name : EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE
Product code : EC-7438

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Skin Irrit. 2 H315
STOT SE 3 H336
Asp. Tox. 1 H304
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xi; R38
N; R50/53
R67
F; R11
Xn; R65

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 H225
Skin Irrit. 2 H315
STOT SE 3 H336
Asp. Tox. 1 H304
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Full text of H statements : see section 16

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Liver, Kidney. Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: ISOCTANE UNLABELED

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.

GHS-US labelling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P312 - Call a doctor, a POISON CENTER if you feel unwell
P321 - Specific treatment (see Hazardous component(s) for labelling on this label)
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO₂), dry

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

extinguishing powder to extinguish.

P391 - Collect spillage.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ISOCTANE UNLABELED	(CAS-No.) 540-84-1 (EC-No.) 208-759-1 (EC Index-No.) 601-009-00-8 (REACH-no) 01-2119457965-22	99.9942	Xi; R38 N; R50/53 R67 F; R11 Xn; R65
3,3',4,4'-TETRACB UNLABELED	(CAS-No.) 32598-13-3 (EC Index-No.) 602-039-00-4	0.0014	R33 N; R50/53
2,2',4,5,5'-PENTACB UNLABELED	(CAS-No.) 37680-73-2	0.0014	R33
2,2',3,4,5,5'-HEXACB UNLABELED	(CAS-No.) 52712-04-6	0.0014	N; R50/53 R33 R48
2,2',3,3',5,5',6-HEPTACB UNLABELED	(CAS-No.) 52663-67-9	0.0014	N; R50/53 R33 R48

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ISOCTANE UNLABELED	(CAS-No.) 540-84-1 (EC-No.) 208-759-1 (EC Index-No.) 601-009-00-8 (REACH-no) 01-2119457965-22	99.9942	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4'-TETRACB UNLABELED	(CAS-No.) 32598-13-3 (EC Index-No.) 602-039-00-4	0.0014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',4,5,5'-PENTACB UNLABELED	(CAS-No.) 37680-73-2	0.0014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,5,5'-HEXACB UNLABELED	(CAS-No.) 52712-04-6	0.0014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,3',5,5',6-HEPTACB UNLABELED	(CAS-No.) 52663-67-9	0.0014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
ISOCTANE UNLABELED	(CAS-No.) 540-84-1	99.9942	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4'-TETRACB UNLABELED	(CAS-No.) 32598-13-3	0.0014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',4,5,5'-PENTACB UNLABELED	(CAS-No.) 37680-73-2	0.0014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
2,2',3,4,5,5'-HEXACB UNLABELED	(CAS-No.) 52712-04-6	0.0014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,3',5,5',6-HEPTACB UNLABELED	(CAS-No.) 52663-67-9	0.0014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Take immediately victim to hospital. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May be harmful in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Flood fire area with water from a distance. Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: Flash back over considerable distance.
Reactivity	: Vapours may form flammable mixture with air. Highly flammable liquid and vapour.

5.3. Advice for firefighters

Firefighting instructions	: Wear a self contained breathing apparatus.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Use water spray to cool exposed surfaces.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Use personal protective equipment as required. Remove all sources of ignition. Ensure adequate air ventilation. Provide adequate ventilation to minimize dust and/or vapour concentrations. No open flames, no sparks, and no smoking. Avoid breathing gas, mist, vapours. Avoid contact with skin and eyes. Evacuate danger area. Special attention should be given to low areas/pits where flammable vapours can accumulate.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Stop leak without risks if possible. Prevent entry to sewers and public waters. Avoid release to the environment.

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Vacuum with an equipment that avoids ignition risk. This material and its container must be disposed of in a safe way, and as per local legislation. Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Avoid all contact with skin, eyes, or clothing.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, mist. Avoid contact with skin and eyes.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep dry. Store in tightly closed, leak-proof containers. Containers which are opened should be properly resealed and kept upright to prevent leakage. Ground/bond container and receiving equipment.
- Storage conditions : Store at room temperature away from light and moisture.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	300.0000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract irritation
ISOCTANE UNLABELED (540-84-1)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	300.0000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract irritation

8.2. Exposure controls

- Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



- Materials for protective clothing : Wear suitable protective clothing and gloves.
- Hand protection : Wear suitable protective clothing and gloves.
- Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses. Safety glasses.
- Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
- Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

- Physical state : Liquid

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appearance	: Liquid.
Molecular mass	: 114.23 g/mol
Colour	: Colourless.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -107 °C (-161 °F)
Freezing point	: No data available
Boiling point	: 98 - 99 °C (208 - 210 °F) at 1,013 hPa (760 mmHg)
Flash point	: -12 °C (10 °F) - closed cup
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 55 hPa (41 mmHg) at 21 °C (70 °F); 117 hPa (88 mmHg) at 37.8 °C (100.04 °F)
Relative vapour density at 20 °C	: 3.94 - (Air = 1.0)
Relative density	: No data available
Density	: 0.69 g/ml at 20 °C (68 °F)
Solubility	: Water: insoluble
Log Pow	: 4.6
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1 - 6 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form flammable mixture with air. Highly flammable liquid and vapour.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE	
LD50 oral rat	> 5000 mg/kg (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg (OECD Test Guideline 402)
LC50 inhalation rat (mg/l)	> 33.52 mg/l/4h (OECD Test Guideline 403)
ISOCTANE UNLABELED (540-84-1)	
LD50 oral rat	> 5000 mg/kg (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg (OECD Test Guideline 402)
LC50 inhalation rat (mg/l)	> 33.52 mg/l/4h (OECD Test Guideline 403)

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Skin. rabbit. Result: Irritating to skin. (OECD 404 method)
Serious eye damage/irritation	: Eyes. rabbit. Result: No eye irritation. (OECD 405 method)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: rat - Unscheduled DNA synthesis
Carcinogenicity	: Not classified
Reproductive toxicity	: Not available
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Health hazard - Aspiration hazard No data available
Aspiration hazard	: Aspiration hazard
Potential adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Affects the liver.
Symptoms/effects after inhalation	: May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May be harmful in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. Risk of lung oedema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

3,3',4,4'-TETRACB UNLABELED (32598-13-3)	
LC50 fish 1	> 0.002 mg/l Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	> 0.002 mg/l Daphnia magna (Water flea) - 48 h
NOEC (chronic)	0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 7 d

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE	
Log Pow	4.6
3,3',4,4'-TETRACB UNLABELED (32598-13-3)	
Bioconcentration factor (BCF REACH)	81.5
Bioaccumulative potential	Bioaccumulation: Oryzias latipes - 20 d Bioconcentration factor (BCF): 81.5.
ISOCTANE UNLABELED (540-84-1)	
Log Pow	4.6

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : Very toxic to aquatic life with long lasting effects. Avoid release to the environment. Disposal must be done according to official regulations.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
Product/Packaging disposal recommendations:	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT) : 1262
DOT NA no. UN1262

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Octanes
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT RQ : 1000 lbs
Marine pollutant : No



14.3. Additional information

Emergency Response Guide (ERG) Number : 128
Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II
Class (ADR) : 3 - Flammable liquid
Hazard identification number (Kemler No.) : 33
Classification code (ADR) : F1
Danger labels (ADR) : 3 - Flammable liquids



Orange plates : An orange rectangular label with a black border. It is divided into two horizontal sections. The top section contains the number "33" and the bottom section contains the number "1262".

Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) : 1l
EAC code : 3YE
Excepted quantities (ADR) : E2

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

MFAG-No : 128

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Dangerous for the environment :



Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
--	--

SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard
-------------------------------------	--

SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
---------------------------------------	--

3,3',4,4'-TETRACB UNLABELED (32598-13-3)

SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
--	--

SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
---------------------------------------	--

2,2',4,5,5'-PENTACB UNLABELED (37680-73-2)

SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
--	--

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
-------------------------------------	---------------------------------

SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
---------------------------------------	--

2,2',3,3',5,5',6-HEPTACB UNLABELED (52663-67-9)

SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
--	--

SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
---------------------------------------	--

ISOCTANE UNLABELED (540-84-1)

SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
--	--

SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard
-------------------------------------	--

SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
---------------------------------------	--

15.2. International regulations

CANADA

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

Listed on the Canadian DSL (Domestic Substances List)

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2.1. National regulations

No additional information available

15.3. US State regulations

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE()				
U.S. - California - Proposition 65 - Carcinogens List	No			
U.S. - California - Proposition 65 - Developmental Toxicity	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No			
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List			
3,3',4,4'-TETRACB UNLABELED (32598-13-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	Yes	
2,2',4,5,5'-PENTACB UNLABELED (37680-73-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	Yes	
2,2',3,4,5,5'-HEXACB UNLABELED (52712-04-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
2,2',3,3',5,5',6-HEPTACB UNLABELED (52663-67-9)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	Yes	
ISOCTANE UNLABELED (540-84-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
3,3',4,4'-TETRACB UNLABELED (32598-13-3)				
State or local regulations				
U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List				
2,2',4,5,5'-PENTACB UNLABELED (37680-73-2)				
State or local regulations				
U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List				

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,2',3,3',5,5',6-HEPTACB UNLABELED (52663-67-9)

State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List

ISOCTANE UNLABELED (540-84-1)

State or local regulations

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
R11	Highly flammable
R33	Danger of cumulative effects
R38	Irritating to skin
R48	Danger of serious damage to health by prolonged exposure
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

CIL Mixture SDS

EC-4060 UNLABELED STANDARD PCBS-77/101/141/178 10 UG/ML IN ISOCTANE

EC-7438

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product